SWAT

Generated by Doxygen 1.8.16

| 2 Modules Index 7 2.1 Modules List 7 3 Data Type Index 9 3.1 Data Types List 9 4 File Index 11 4.1 File List 11 5 Module Documentation 13 5.1 parm Module Reference 13 5.1.2 Variable Documentation 68 5.1.2 Variable Documentation 68 6.1 parm:asscrv Interface Reference 69 6.2 parm:astr Interface Reference 69 6.3 parm:assrv Interface Reference 69 6.3 parm:astr Interface Reference 69 6.3 parm:astr Interface Reference 69 6.4 parm:distr Interface Reference 70 6.5 parm:de Interface Reference 70 6.5 parm:de Interface Reference 70 6.5 parm:de Interface Reference 71 6.7 parm:regol Interface Reference 71 6.8 parm:dQDAV Interface Reference 71 6.10 parm:apara Interface Reference 71 6.10 parm:apara Interface Reference 71 6.12 parm:regora Interface Reference 72 6.13 parm:reddaa Interface Reference 72 | 1 SWAT | 1 |
|--|--|----|
| 3 Data Type Index 9 3.1 Data Types List 9 4 File Index 11 4.1 File List 11 5 Module Documentation 13 5.1 parm Module Reference 13 5.1.1 Detailed Description 68 5.1.2 Variable Documentation 68 5.1.2 Type Documentation 68 6.1 parm:ascriv Interface Reference 69 6.2 parm:ascri Interface Reference 69 6.3 parm:asunif Interface Reference 69 6.4 parm:dstn1 Interface Reference 70 6.5 parm:ese Interface Reference 70 6.5 parm:ese Interface Reference 70 6.7 parm:dgd Interface Reference 70 6.7 parm:dgd Interface Reference 71 6.10 parm:aperspiit Interface Reference 71 6.10 parm:aperspiit Interface Reference 71 6.12 parm:regers Interface Reference 72 6.13 parm:redaa Interface Reference 72 6.14 parm:regers Interface Reference 72 6.15 parm:that Interface Reference 72 6.16 parm:xbt Interface Reference 72 6.15 parm:that Interface Reference | 2 Modules Index | 7 |
| 3.1 Data Types List 9 4 File Index 11 4.1 File List 11 5 Module Documentation 13 5.1 parm Module Reference 13 5.1 parm Module Reference 13 5.1.1 Detailed Description 68 5.1.2 Variable Documentation 68 5.1.2.1 igropt 68 6 Data Type Documentation 69 6.1 parm:assrv Interface Reference 69 6.2 parm:astri Interface Reference 69 6.3 parm:aunif Interface Reference 69 6.4 parm:dstrl Interface Reference 70 6.5 parm:expo Interface Reference 70 6.6 parm:expo Interface Reference 70 6.7 parm:idqd Interface Reference 70 6.8 parm:tlqdq Interface Reference 70 6.9 parm:idqd Interface Reference 71 6.10 parm:indenit Interface Reference 71 6.11 parm:qman Interface Reference 71 6.12 parm:regres Interface Reference 72 6.13 parm:tlqder Reference 72 6.14 parm:tlater Reference 72 6.15 parm:tedaa Interface Reference 72 6.16 parm:tedaa Interface Reference 72 6.17 parm:tregres Interface Reference 72 6.18 parm:tlater Interface Reference 72 6.19 parm:tlater Interface Reference 72 6.19 parm:tlater Interface Reference 72 6.10 parm:tlater Interface Reference 72 6.11 parm:tlater Interface Reference 72 6.12 parm:tlater Interface Reference 72 6.13 parm:tlater Interface Reference 72 6.14 parm:tlater Interface Reference 72 6.15 parm:theta Interface Reference 72 6.16 parm:vbl Interface Reference 72 7.1 allocate_parms.f90 File Reference 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Eunction/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunit.f90 File Reference 74 | 2.1 Modules List | 7 |
| 4 File Index 11 4.1 File List 11 5 Module Documentation 13 5.1 parm Module Reference 13 5.1.1 Detailed Description 68 5.1.2 Variable Documentation 68 5.1.2.1 igropt 68 6 Data Type Documentation 69 6.1 parm::ascrv Interface Reference 69 6.2 parm::astr Interface Reference 69 6.3 parm::ascrv Interface Reference 69 6.4 parm::distr1 Interface Reference 70 6.5 parm::ele Interface Reference 70 6.5 parm::dep Interface Reference 70 6.6 parm::dxpo Interface Reference 70 6.7 parm::dxpo Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.10 parm::dxportil Interface Reference 71 6.10 parm::dxportil Interface Reference 71 6.11 parm::gxps Interface Reference 72 6.12 parm::regres Interface Reference 72 6.13 parm::regres Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm:: | 3 Data Type Index | 9 |
| 4.1 File List 11 5 Module Documentation 13 5.1 parm Module Reference 13 5.1.1 Detailed Description 68 5.1.2 Variable Documentation 68 5.1.2.1 igropt 68 6 Data Type Documentation 69 6.1 parm::ascrv Interface Reference 69 6.2 parm::atri Interface Reference 69 6.3 parm::aunif Interface Reference 69 6.4 parm::dstn1 Interface Reference 70 6.5 parm::el Interface Reference 70 6.5 parm::expc Interface Reference 70 6.7 parm::dcgd Interface Reference 70 6.8 parm::AUDAV Interface Reference 71 6.10 parm::dcpd Interface Reference 71 6.10 parm::dcpd Interface Reference 71 6.11 parm::regres Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::regres Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7.1 allocate parms::f90 File Reference 73 | 3.1 Data Types List | 9 |
| 4.1 File List 11 5 Module Documentation 13 5.1 parm Module Reference 13 5.1.1 Detailed Description 68 5.1.2 Variable Documentation 68 5.1.2.1 igropt 68 6 Data Type Documentation 69 6.1 parm::ascrv Interface Reference 69 6.2 parm::atri Interface Reference 69 6.3 parm::aunif Interface Reference 69 6.4 parm::dstn1 Interface Reference 70 6.5 parm::el Interface Reference 70 6.5 parm::expc Interface Reference 70 6.7 parm::dcgd Interface Reference 70 6.8 parm::AUDAV Interface Reference 71 6.10 parm::dcpd Interface Reference 71 6.10 parm::dcpd Interface Reference 71 6.11 parm::regres Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::regres Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7.1 allocate parms::f90 File Reference 73 | 4 File Index | 11 |
| 5.1 parm Module Reference 13 5.1.1 Detailed Description 68 5.1.2 Variable Documentation 68 5.1.2.1 igropt 68 6 Data Type Documentation 69 6.1 parm::ascrv Interface Reference 69 6.2 parm::atri Interface Reference 69 6.3 parm::aunif Interface Reference 69 6.4 parm::dstn1 Interface Reference 70 6.5 parm::e Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::fcgd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.10 parm::denit Interface Reference 71 6.11 parm::regres Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::regres Interface Reference 72 6.15 parm::rheta Interface Reference 72 6.16 parm::rbeta Interface Reference 72 6.17 parm::rbeta Interface Reference 72 6.16 parm::rbeta Interface Reference 72 6.17 parm::rbeta Interface Reference 73 7.1 a Detailed Description <td< td=""><td></td><td>11</td></td<> | | 11 |
| 5.1 parm Module Reference 13 5.1.1 Detailed Description 68 5.1.2 Variable Documentation 68 5.1.2.1 igropt 68 6 Data Type Documentation 69 6.1 parm::ascrv Interface Reference 69 6.2 parm::atri Interface Reference 69 6.3 parm::aunif Interface Reference 69 6.4 parm::dstn1 Interface Reference 70 6.5 parm::e Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::fcgd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.10 parm::denit Interface Reference 71 6.11 parm::regres Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::regres Interface Reference 72 6.15 parm::rheta Interface Reference 72 6.16 parm::rbeta Interface Reference 72 6.17 parm::rbeta Interface Reference 72 6.16 parm::rbeta Interface Reference 72 6.17 parm::rbeta Interface Reference 73 7.1 a Detailed Description <td< td=""><td>5 Module Documentation</td><td>12</td></td<> | 5 Module Documentation | 12 |
| 5.1.1 Detailed Description 68 5.1.2 Variable Documentation 68 5.1.2.1 igropt 68 6 Data Type Documentation 69 6.1 parm::ascrv Interface Reference 69 6.2 parm::atri Interface Reference 69 6.3 parm::aunif Interface Reference 69 6.4 parm::dstr1 Interface Reference 70 6.5 parm::en Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::fogd Interface Reference 70 6.8 parm::hQDAV Interface Reference 71 6.10 parm::hqprsplit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7.1i Bocumentation 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.3 aunif.f90 File Reference 74 | | _ |
| 5.1.2 Variable Documentation 68 5.1.2.1 igropt 68 6 Data Type Documentation 69 6.1 parm::ascrv Interface Reference 69 6.2 parm::atri Interface Reference 69 6.3 parm::aunif Interface Reference 69 6.4 parm::dstn1 Interface Reference 70 6.5 parm::ee Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::doll Interface Reference 70 6.9 parm::doll Interface Reference 71 6.10 parm::deprisit Interface Reference 71 6.10 parm::deprisit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::readaa Interface Reference 72 6.14 parm::talir Interface Reference 72 6.15 parm::tbla Interface Reference 72 6.16 parm::vbl Interface Reference 72 7.1.1 Detailed Description 73 7.2 ascrv.!90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.3. aunif.!90 File Reference | • | _ |
| 5.1.2.1 igropt 68 6 Data Type Documentation 69 6.1 parm::ascrv Interface Reference 69 6.2 parm::atri Interface Reference 69 6.3 parm::aunif Interface Reference 69 6.4 parm::distri Interface Reference 70 6.5 parm::expo Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::fcgd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.9 parm::layersplit Interface Reference 71 6.10 parm::layersplit Interface Reference 71 6.11 parm::gramal Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::regres Interface Reference 72 6.14 parm::theta Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.3.3 aunif.f90 File Reference 74 7.3.4 aunif.f90 File Reference | · | |
| 6 Data Type Documentation 69 6.1 parm::ascrv Interface Reference 69 6.2 parm::atri Interface Reference 69 6.3 parm::aunif Interface Reference 69 6.4 parm::dstn1 Interface Reference 70 6.5 parm::ele Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::fogd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.9 parm::layersplit Interface Reference 71 6.19 parm::layersplit Interface Reference 71 6.10 parm::layersplit Interface Reference 71 6.12 parm::regres Interface Reference 71 6.12 parm::regres Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2 I ascrv() 74 7.3 aunif.f90 File Reference 74 | | |
| 6.1 parm::ascrv Interface Reference 69 6.2 parm::atri Interface Reference 69 6.3 parm::aunif Interface Reference 69 6.4 parm::dstn1 Interface Reference 70 6.5 parm::el Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::flogd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.9 parm::layersplit Interface Reference 71 6.10 parm::ndenit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::theta Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.3 aunif.f90 File Reference 74 7.3 aunif.f90 File Reference 74 | 5.1.2.1 igropt | 00 |
| 6.2 parm::aunif Interface Reference 69 6.3 parm::aunif Interface Reference 69 6.4 parm::dstn1 Interface Reference 70 6.5 parm::ee Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::fcgd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.9 parm::layersplit Interface Reference 71 6.10 parm::ndenit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms:f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 scrv/f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.3 aunif.f90 File Reference 74 | 6 Data Type Documentation | 69 |
| 6.3 parm::aunif Interface Reference 69 6.4 parm::dstn1 Interface Reference 70 6.5 parm::ee Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::fcgd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.9 parm::layersplit Interface Reference 71 6.10 parm::ndenit Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::regres Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 7.3 aunif.f90 File Reference 74 | 6.1 parm::ascrv Interface Reference | 69 |
| 6.4 parm::dstn1 Interface Reference 70 6.5 parm::ee Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::fcgd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.9 parm::layersplit Interface Reference 71 6.10 parm::ndenit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.15 parm::theta Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.3 aunif.f90 File Reference 74 7.3 aunif.f90 File Reference 74 | 6.2 parm::atri Interface Reference | 69 |
| 6.5 parm::ee Interface Reference 70 6.6 parm::expo Interface Reference 70 6.7 parm::fcgd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.9 parm::layersplit Interface Reference 71 6.10 parm::ndenit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::resedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7.1 allocate_parms.f90 File Reference 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.3 parm::aunif Interface Reference | 69 |
| 6.6 parm::expo Interface Reference 70 6.7 parm::fogd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.9 parm::layersplit Interface Reference 71 6.10 parm::ndenit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.4 parm::dstn1 Interface Reference | 70 |
| 6.7 parm::fcgd Interface Reference 70 6.8 parm::HQDAV Interface Reference 71 6.9 parm::layersplit Interface Reference 71 6.10 parm::ndenit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::resedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.5 parm::ee Interface Reference | 70 |
| 6.8 parm::HQDAV Interface Reference 71 6.9 parm::layersplit Interface Reference 71 6.10 parm::ndenit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.3 aunif.f90 File Reference 74 | 6.6 parm::expo Interface Reference | 70 |
| 6.9 parm::layersplit Interface Reference 71 6.10 parm::ndenit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.7 parm::fcgd Interface Reference | 70 |
| 6.10 parm::ndenit Interface Reference 71 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.8 parm::HQDAV Interface Reference | 71 |
| 6.11 parm::qman Interface Reference 71 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.9 parm::layersplit Interface Reference | 71 |
| 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.10 parm::ndenit Interface Reference | 71 |
| 6.12 parm::regres Interface Reference 72 6.13 parm::rsedaa Interface Reference 72 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.11 parm::qman Interface Reference | 71 |
| 6.14 parm::tair Interface Reference 72 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | | 72 |
| 6.15 parm::theta Interface Reference 72 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.13 parm::rsedaa Interface Reference | 72 |
| 6.16 parm::vbl Interface Reference 72 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.14 parm::tair Interface Reference | 72 |
| 7 File Documentation 73 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.15 parm::theta Interface Reference | 72 |
| 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 6.16 parm::vbl Interface Reference | 72 |
| 7.1 allocate_parms.f90 File Reference 73 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | 7 File Documentation | 73 |
| 7.1.1 Detailed Description 73 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | | 73 |
| 7.2 ascrv.f90 File Reference 73 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | _ | 73 |
| 7.2.1 Detailed Description 73 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | | _ |
| 7.2.2 Function/Subroutine Documentation 74 7.2.2.1 ascrv() 74 7.3 aunif.f90 File Reference 74 | | 73 |
| 7.2.2.1 ascrv() | • | 74 |
| 7.3 aunif.f90 File Reference | | |
| | | |
| 7.5.1 Detailed Description | 7.3.1 Detailed Description | 74 |

| 7.3.2 Function/Subroutine Documentation |
|---|
| 7.3.2.1 aunif() |
| 7.4 caps.f90 File Reference |
| 7.4.1 Detailed Description |
| 7.4.2 Function/Subroutine Documentation |
| 7.4.2.1 caps() |
| 7.5 gcycl.f90 File Reference |
| 7.5.1 Detailed Description |
| 7.6 getallo.f90 File Reference |
| 7.6.1 Detailed Description |
| 7.7 jdt.f90 File Reference |
| 7.7.1 Detailed Description |
| 7.7.2 Function/Subroutine Documentation |
| 7.7.2.1 jdt() |
| 7.8 main.f90 File Reference |
| 7.8.1 Detailed Description |
| 7.9 modparm.f90 File Reference |
| 7.9.1 Detailed Description |
| 7.10 readbsn.f90 File Reference |
| 7.10.1 Detailed Description |
| 7.11 readchm.f90 File Reference |
| 7.11.1 Detailed Description |
| 7.12 readfcst.f90 File Reference |
| 7.12.1 Detailed Description |
| 7.13 readfert.f90 File Reference |
| 7.13.1 Detailed Description |
| 7.14 readfig.f90 File Reference |
| 7.14.1 Detailed Description |
| 7.15 readfile.f90 File Reference |
| 7.15.1 Detailed Description |
| 7.16 readhru.f90 File Reference |
| 7.16.1 Detailed Description |
| 7.17 readlup.f90 File Reference |
| 7.17.1 Detailed Description |
| 7.18 readpest.f90 File Reference |
| 7.18.1 Detailed Description |
| 7.19 readplant.f90 File Reference |
| 7.19.1 Detailed Description |
| 7.20 readsdr.f90 File Reference |
| 7.20.1 Detailed Description |
| 7.21 readsepticbz.f90 File Reference |
| 7 21 1 Detailed Description |

| Index | | 141 |
|-----------------------------------|------|-----|
| Bibliography | | 139 |
| 7.26.1 Detailed Description | | 138 |
| 7.26 simulate.f90 File Reference | | 138 |
| 7.25.1 Detailed Description | | 138 |
| 7.25 readwwq.f90 File Reference | | 138 |
| 7.24.1 Detailed Description | | 138 |
| 7.24 readurban.f90 File Reference | | 138 |
| 7.23.1 Detailed Description | | 138 |
| 7.23 readtill.f90 File Reference | | 137 |
| 7.22.1 Detailed Description | | 137 |
| 7.22 readsno.f90 File Reference | | 137 |
| | | |

Chapter 1

SWAT

An updated SWAT 2012 revision 670 code

Objectives

- Standard indentation and translation to Fortran 90 by using findent. See the translate-fortran90.pl perl script file (:heavy_check_mark:)
- Exhaustive use of the "implicit none" directive to detect bad variable usage (:heavy_check_mark:)
- Generate a GNU Make makefile and compile with GNU GFortran. See the gernerate-makefile.pl perl script file (:heavy_check_mark:)
- Remove non-used variables and format labels (:heavy_check_mark:)
- Detect and solve all uninitialized variables (:heavy_check_mark: :construction:, some proposed solutions could be incorrect)
- Remove unneeded variable initializations (:heavy check mark:) as:

```
j=0 ! this line is not necessary j=ihru
```

- · Remove redundant code (:heavy_check_mark:)
- Exhaustive use of the "parameter" directive on constants (:heavy_check_mark:)
- Generate a detailed list of issues detected in the original code (:heavy_check_mark:, see at the end of this README)
- Remove obsolete commented code (:x:)
- Update variable descriptions in comments (:construction:, a lot of work)
- Standardize comments by using Doxygen style in order to generate documentation. See at latex/refman.pdf (:construction:, a lot of work)

2 SWAT

Required tools

- GFortran (to compile the source code)
- · Make (to build the executable file)
- Perl (optional: to execute the perl scripts to update the makefile or to translate original files to Fortran 90)
- Findent (optional: to translate original files to Fortran 90 with a standard indentation)
- Doxygen (optional: to generate a reference programming manual from source code)
- Tex Live or MikTex (optional: to generate a reference programming manual from source code)
- On Microsoft Windows systems you have to install MSYS2 and the required utilities (GFortran and Make). You can follow detailed instructions in install-unix

Instructions to generate Fortran 90 style code from original code

In order to generate Fortran 90 style code with standard indentation from original code you have to type on a UNIX type terminal (you need Perl and Findent):

\$ perl translate-fortran90.pl

Instructions to generate an initial GNU make Makefile

Type on the UNIX type terminal, when translated the original code to Fortran 90 style (you need Perl):

\$ perl generate-makefile.pl

Instructions to generate an executable to test

Type on the UNIX type terminal (you need GFortran and Make)

· In UNIX type operative systems:

\$ make

• In a MSYS2 terminal in Microsoft Windows:

\$ EXE=".exe" LDFLAGS="-static" make

• Cross-compiling a 32 bits Microsoft Windows executable in a UNIX type operative system:

\$ prefix="i686-w64-mingw32-" EXE=".exe" LDFLAGS="-static" make

· Cross-compiling a 64 bits Microsoft Windows executable in a UNIX type operative system:

\$ prefix="x86_64-w64-mingw32-" EXE=".exe" LDFLAGS="-static" make

Instructions to generate an optimized executable file

Type on the UNIX type terminal (you need GFortran and Make)

· In UNIX type operative systems:

```
$ CFLAGS="-march=native -flto" LDFLAGS="-flto" make strip
```

In a MSYS2 terminal in Microsoft Windows:

```
$ EXE=".exe" CFLAGS="-flto" LDFLAGS="-flto -static" make strip
```

· Cross-compiling a 32 bits Microsoft Windows executable in a UNIX type operative system:

```
$ prefix="i686-w64-mingw32-" EXE=".exe" CFLAGS="-flto" LDFLAGS="-flto -static" make strip
```

Cross-compiling a 64 bits Microsoft Windows executable in a UNIX type operative system:

```
$ prefix="x86\ 64-w64-mingw32-" EXE=".exe" CFLAGS="-flto" LDFLAGS="-flto -static" make strip
```

Instructions to generate a reference programming manual from source code

Type on the UNIX type terminal (you need Doxygen and TeX Live or MiKTeX):

- \$ doxygen
- \$ cd latex
- \$ make

The reference programming manual file latex/refman.pdf is generated from source code in PDF format

Issues in the original source code

This is a list of possible issues detected in the original source code. These issues have been mostly detected by the GFortran compiler warnings. Some of them could not arise because the logic of the variables is not possible.

- · In biofilm.f:
 - "dcoef" is used but not initialized. dcoef=3 as in watqual.f? Then, I propose at beginning: real*8, parameter :: dcoef = 3.
- · In bmp_ri_pond.f:
 - "qseep" and "qet" could be used not initialized at lines 133 and 134. However the problem only arises for nstep<1
- In bmp_sand_filter.f:
 - "sed\ removed" at line 342 could be used not initialized if sfsedstdev<=0
- In bpm_sed_pond.f:
 - bmp_sed _pond seems to be bmp_sed_pond at line 186

4 SWAT

- In bmp_wet_pond.f:
 - "hvol" could be used not initialized in "ext\ dpth" subroutine at line 267 in first bucle iteration
- · In clicon.f:
 - "tmxbsb", "tmnbsb", "rbsb", "rstpbsb", "rhdbsb", "rabsb", "rmxbsb", "daylbsb", "fradbsb" and "u10bsb" could be used not initialized at 186-207 lines
- · In conapply.f:
 - "k" and "kk" could be used not initialized at 121-122 lines if iday_pest(j) /=ipst_freq(j) and curyr>nyskip
- · In confert.f:
 - "ifrt" seems to be "it" at line 214
- · In curno.f:
 - "smxold" could be used not initialized if cn1 (h) <=1.e−6 and curyr/=0 at line 96
- · In drains.f:
 - "nlayer" could be used not initialized at line 23. However, the problem only arises if it is not set in the previous bucle (mlyr <= 1 or $sol_z(j1, j) <= 0$)
- · In etact.f:
 - "sev" could be used not initialized at line 286 if dep>=esd and ly==2
- · In filter.f:
 - "remove21" seems to be "remove2" at line 316
- · In grass wway.f:
 - "sf_depth" and "sf_sed" could be used not initialized at lines 133 and 137 if $sf_area>0$ and $sf_\leftrightarrow area<=1.e-6$
- · In hhnoqual.f:
 - "algon" seems to be "algcon" at line 190
- · In hhwatqual.f
 - "orgnpin" seems to be "orgpin" at line 278
 - thour=1.0 at line 377 overwrites previous "thour" calculation. It is wrong
- · In hmeas.f:
 - "rhdbsb" could be used not initialized at line 84
- In killop.f:
 - "ff1" and "ff2" are used but not initialized at lines 167 and 267. They are set in harvkillop.f file (lines 257-258). They have to be included in modparm.f to share harvkillop.f values? or they have to be redefined as in harvkillop.f?
- In NCsed leach.f90:
 - "perc\ clyr" could be used not initialized at line 221 if sol nly (j) <2
- In nrain.f:
 - "no2pcp" seems to be "no3pcp" at line 72
- In pmeas.f:

- "rbsb" could be used not initialized at line 143
- "flag" could be used not initialized if 'a==' 'at line 210
- "rainsb" could be used not initialized, however only ifnstep<=0`
- In pminrl2.f:
 - at line 95 a comma is necessary between "base" and "vara"
 - "ssp" could be used not initialized at line 196 if $xx \le 1.e-6$
- · In pothole.f:
 - "solp_tileo" could be used not initialized at line 593 if $pot_vol(j) \le 1.e-6$ or $potvol_{\leftarrow} tile \le 1.e-6$
- · In potholehr.f:
 - "potflow" seems to be "potflwo" at line 447
- · In readatmodep.f:
 - momax=12*nbyr is defined at line 65 but not used. It has to be "mo_max"? but then, it overwrites the file read
- In readops.f:
 - year = 0. seems to be iyear = 0 at line 98
 - "mg13" seems to be "mgt13" at line 206
- In readpnd.f:
 - "vselsetlpnd" seems to be "velsetlpnd" at line 279
- · In readru.f:
 - "tck" is used but not initialized at line 79
- · In readsepticbz.f:
 - **–** at line 135 4. e-8 seems to be 4.e-8
- In rewind_init.f:
 - "orig_tnylda" is used but not initialized at line 174
- · In routels.f:
 - "dstor" is used but not initialized at line 134. It has to be calculated as in watbal.f? or as in the commented line 109?
 - "latgout" and "gwgout" could be used not initialized at lines 142-143
- In rtbact.f:
 - "netwtr" could be used not initialized at line 124, however only if nstep<1
- In rthpest.f:
 - thour=1.0 at line 183 overwrites previous "thour" calculation. It is wrong
 - "frsol" and "frsrb" could be used not initialized at lines 289-290 if hrtwtr(ii) > 0.001 and hrtwtr(ii) / (idt*60) <= 0.01
- In rtpest.f:
 - tday=1.0 at line 180 overwrites previous "tday" calculation. It is wrong
- In sched_mgt.f:
 - < = seems to be <= at 202 line

6 SWAT

- "husc" and "igrow" at lines 264-265 are used but not initialized. "husc" has to be phu_op (iop, ihru) has in readmgt.f? "igrow" has to be igro (ihru) has in readmgt.f?

- · In smeas.f:
 - "rabsb" could be used not initialized at line 86
- · In sweep.f:
 - "fr_curb" is used but not initialized at line 56. It has to be added to modparm.f to share result with sched_mgt.f? or it has to be mgt5op (nop (ihru), ihru) as in sched_mgt.f?
- · In tmeas.f:
 - "tmxbsb" and "tmnbsb" could be used not initialized at lines 109-110
- · In transfer.f:
 - "ratio", "xx" and "ratio1" could be used not initialized at lines 236, 239 and 241 if ihout==2
- · In wmeas.f:
 - "u10bsb" could be used not initialized at line 85
- In zero0.f:
 - "sol_sumn03" seems to be "sol_sumno3" at line 508
- In zero_urbn.f:
 - "stp_stagdis" seems to be "dtp_stagdis" at line 84
 - "subdr_kg" seems to be "subdr_km" at line 149
 - "spl_eros" is not defined at line 21, it could be "eros_spl"?

Chapter 2

Modules Index

2.1 Modules List

| Here is a lis | t of all documented modules with brief descript | ions: | |
|---------------|---|-------|--------|
| parm | | | |
| • | Main module containing the global variables | | 13 |

8 Modules Index

Chapter 3

Data Type Index

3.1 Data Types List

Here are the data types with brief descriptions:

| parm::ascrv | 69 |
|------------------|----|
| parm::atri | 69 |
| parm::aunif | 69 |
| parm::dstn1 | 70 |
| parm::ee | 70 |
| parm::expo | 70 |
| parm::fcgd | 70 |
| parm::HQDAV | 71 |
| parm::layersplit | |
| parm::ndenit | 71 |
| parm::qman | 71 |
| parm::regres | 72 |
| parm::rsedaa | 72 |
| parm::tair | 72 |
| parm::theta | 72 |
| narmovhl | 72 |

10 Data Type Index

Chapter 4

File Index

4.1 File List

Here is a list of all documented files with brief descriptions:

| allocate_parms.f90 | . 73 |
|--------------------|------|
| ascrv.f90 | . 73 |
| aunif.f90 | . 74 |
| caps.f90 | . 75 |
| gcycl.f90 | . 76 |
| getallo.f90 | . 76 |
| jdt.f90 | . 76 |
| main.f90 | |
| modparm.f90 | |
| readbsn.f90 | |
| readchm.f90 | |
| readfcst.f90 | |
| readfert.f90 | |
| readfig.f90 | |
| readfile.f90 | |
| readhru.f90 | |
| readlup.f90 | |
| readpest.f90 | |
| readplant.f90 | |
| readsdr.f90 | |
| readsepticbz.f90 | |
| readsno.f90 | |
| readtill.f90 | |
| readurban.f90 | |
| readwwq.f90 | |
| simulate f00 | 120 |

12 File Index

Chapter 5

Module Documentation

5.1 parm Module Reference

main module containing the global variables

Data Types

- · interface ascrv
- interface atri
- interface aunif
- interface dstn1
- interface ee
- interface expo
- interface fcgd
- interface HQDAV
- · interface layersplit
- interface ndenit
- interface qman
- interface regres
- · interface rsedaa
- interface tair
- · interface theta
- interface vbl

Variables

- integer, parameter mvaro = 33

 max number of variables routed through the reach
- integer, parameter mhruo = 79

max number of variables in output.hru

- integer, parameter mrcho = 62
 - max number of variables in reach file
- integer, parameter msubo = 24
 - max number of variables in output.sub
- integer, parameter mstdo = 113

max number of variables summarized in output.std

- integer, parameter motot = 600
- · integer icalen
- real *8 prf bsn

Basinwide peak rate adjustment factor for sediment routing in the channel. Allows impact of peak flow rate on sediment routing and channel reshaping to be taken into account.

- real *8 co2 x2
- real *8 co2 x
- real *8, dimension(:), allocatable alph_e
- real *8, dimension(:), allocatable cdn

denitrification exponential rate coefficient

real *8, dimension(:), allocatable nperco

nitrate percolation coefficient (0-1)

0:concentration of nitrate in surface runoff is zero

1:percolate has same concentration of nitrate as surface runoff

real *8, dimension(:), allocatable surlag

Surface runoff lag time. This parameter is needed in subbasins where the time of concentration is greater than 1 day. SURLAG is used to create a "storage" for surface runoff to allow the runoff to take longer than 1 day to reach the subbasin outlet (days)

- real *8, dimension(:), allocatable co_p
- real *8, dimension(:), allocatable cmn

rate factor for humus mineralization on active organic N

real *8, dimension(:), allocatable phoskd

Phosphorus soil partitioning coefficient. Ratio of soluble phosphorus in surface layer to soluble phosphorus in runoff.

real *8, dimension(:), allocatable psp

Phosphorus availibility index. The fraction of fertilizer P remaining in labile pool after initial rapid phase of P sorption.

real *8, dimension(:), allocatable sdnco

denitrification threshold: fraction of field capacity triggering denitrification

real *8 r2adj bsn

basinwide retention parameter adjustment factor (greater than 1)

- real *8 yield
- real *8 burn_frlb
- real *8 pst_kg
- real *8 vieldgrn
- real *8 yieldbms
- real *8 yieldtbr
- real *8 yieldn
- real *8 yieldp
- real *8 hi bms
- real *8 hi_rsd
- real *8 yieldrsd
- real *8, dimension(:), allocatable I_k1
- real *8, dimension(:), allocatable I_k2
- real *8, dimension(:), allocatable I_lambda
- real *8, dimension(:), allocatable I beta
- real *8, dimension(:), allocatable I gama
- real *8, dimension(:), allocatable I_harea
- real *8, dimension(:), allocatable I_vleng
- real *8, dimension(:), allocatable I_vslope
- real *8, dimension(:), allocatable I_ktc
- real *8, dimension(:), allocatable biofilm_mumax
- real *8, dimension(:), allocatable biofilm_kinv
- real *8, dimension(:), allocatable biofilm klw
- real *8, dimension(:), allocatable biofilm_kla

- real *8, dimension(:), allocatable biofilm_cdet
- real *8, dimension(:), allocatable biofilm_bm
- real *8, dimension(:,:), allocatable hru_rufr
- real *8, dimension(:,:), allocatable daru_km
- real *8, dimension(:,:), allocatable ru_k
- real *8, dimension(:,:), allocatable ru_c
- real *8, dimension(:,:), allocatable ru_eiq
- real *8, dimension(:,:), allocatable ru_ovsl
- real *8, dimension(:,:), allocatable ru_a
- real *8, dimension(:,:), allocatable ru_ovs
- real *8, dimension(:,:), allocatable ru_ktc
- real *8, dimension(:), allocatable gwq_ru
- real *8, dimension(:), allocatable qdayout
- integer, dimension(:), allocatable ils2
- integer, dimension(:), allocatable ils2flag
- · integer iru
- · integer mru
- · integer irch
- · integer isub
- · integer idum
- integer mhyd_bsn
- · integer ipest
- · integer ils_nofig
- · integer mhru1
- integer, dimension(:), allocatable mhyd1
- · integer, dimension(:), allocatable irtun
- real *8 wshd_sepno3
- real *8 wshd sepnh3
- real *8 wshd_seporgn
- real *8 wshd_sepfon
- real *8 wshd_seporgp
- real *8 wshd_sepfop
- real *8 wshd_sepsolp
- real *8 wshd_sepbod
- real *8 wshd_sepmm
- integer, dimension(:), allocatable isep_hru
- real *8 fixco

nitrogen fixation coefficient

real *8 nfixmx

maximum daily n-fixation (kg/ha)

real *8 res_stlr_co

reservoir sediment settling coefficient

real *8 rsd_covco

residue cover factor for computing frac of cover

real *8 vcrit

critical velocity

- real *8 wshd sw
- real *8 wshd_snob
- real *8 wshd_pndfr
- real *8 wshd pndv
- real *8 wshd_pndsed
- real *8 percop

pesticide percolation coefficient (0-1)

0: concentration of pesticide in surface runoff is zero

1: percolate has same concentration of pesticide as surface runoff

- real *8 wshd_wetfr
- real *8 wshd_resfr
- real *8 wshd_resha
- real *8 wshd pndha
- real *8 wshd_fminp
- real *8 wshd_ftotn
- real *8 wshd_fnh3
- real *8 wshd_fno3
- real *8 wshd_forgn
- real *8 wshd_forgp
- real *8 wshd_ftotp
- real *8 wshd_yldn
- real *8 wshd_yldp
- real *8 wshd fixn
- real *8 wshd_pup
- real *8 wshd wstrs
- real *8 wshd_nstrs
- real *8 wshd_pstrs
- real *8 wshd_tstrs
- real *8 wshd_astrs
- real *8 ffcb

initial soil water content expressed as a fraction of field capacity

- real *8 wshd hmn
- real *8 wshd rwn
- real *8 wshd_hmp
- real *8 wshd_rmn
- real *8 wshd_dnit
- real *8 wdpq

die-off factor for persistent bacteria in soil solution (1/day)

- real *8 wshd rmp
- real *8 wshd_voln
- real *8 wshd nitn
- real *8 wshd_pas
- real *8 wshd_pal
- real *8 wof_p

wash off fraction for persistent bacteria on foliage during a rainfall event

- real *8 wshd_plch
- real *8 wshd_raino3
- real *8 ressedc
- real *8 basno3f
- · real *8 basorgnf
- real *8 wshd_pinlet
- real *8 wshd_ptile
- real *8 sftmp

Snowfall temperature (deg C)

real *8 smfmn

Minimum melt rate for snow during year (Dec. 21) where deg C refers to the air temperature. (mm/deg C/day)

real *8 smfmx

Maximum melt rate for snow during year (June 21) where deg C refers to the air temperature. SMFMX and SM FMN allow the rate of snow melt to vary through the year. These parameters are accounting for the impact of soil temperature on snow melt. (mm/deg C/day)

real *8 smtmp

Snow melt base temperature. Mean air temperature at which snow melt will occur. (deg C)

real *8 wgpq

growth factor for persistent bacteria in soil solution (1/day)

- real *8 basminpf
- real *8 basorgpf
- real *8 wdlpq

die-off factor for less persistent bacteria in soil solution (1/day)

- real *8 wshd_resv
- real *8 wshd_ressed
- · real *8 basno3i
- · real *8 basorgni
- real *8 basminpi
- real *8 wdps

die-off factor for persistent bacteria adsorbed to soil particles (1/day)

real *8 wglpq

growth factor for less persistent bacteria in soil solution (1/day)

- real *8 basorgpi
- · real *8 peakr
- real *8 pndsedin
- real *8 sw excess
- · real *8 albday
- real *8 timp

Snow pack temperature lag factor (0-1)

1 = no lag (snow pack temp=current day air temp) as the lag factor goes to zero, the snow pack's temperature will be less influenced by the current day's air temperature.

- real *8 wtabelo
- real *8 tilep
- real *8 wt_shall
- real *8 sq_rto
- real *8 tloss
- real *8 inflpcp
- real *8 snomlt
- real *8 snofall
- real *8 fixn
- · real *8 qtile
- real *8 crk
- real *8 latlyr
- real *8 pndloss
- real *8 wetloss
- real *8 potloss
- real *8 Ipndloss
- real *8 lwetloss
- real *8 sedrch
- real *8 fertn
- · real *8 sol rd
- real *8 cfertn
- real *8 cfertp
- real *8 sepday
- real *8 bioday
- real *8 sepcrk
- real *8 sepcrktot
- real *8 fertno3
- · real *8 fertnh3

- · real *8 fertorgn
- real *8 fertsolp
- real *8 fertorgp
- real *8 wgps

growth factor for persistent bacteria adsorbed to soil particles (1/day)

- real *8 fertp
- real *8 grazn
- real *8 grazp
- real *8 soxy
- real *8 qdfr
- real *8 sdti
- real *8 rtwtr
- real *8 ressa
- real *8 wdlps

die-off factor for less persistent bacteria absorbed to soil particles (1/day)

real *8 wglps

growth factor for less persistent bacteria adsorbed to soil particles (1/day)

real *8 da km

area of the watershed in square kilometers (km²)

- real *8 rttime
- real *8 rchdep
- real *8 rtevp
- real *8 rttlc
- real *8 resflwi
- real *8 wdprch

die-off factor for persistent bacteria in streams (1/day)

- real *8 resflwo
- real *8 respcp
- real *8 resev
- real *8 ressep
- real *8 ressedi
- · real *8 ressedo
- real *8 dtot
- real *8 pperco_bsn

phosphorus percolation coefficient. Ratio of soluble phosphorus in surface to soluble phosphorus in percolate

• real *8 nperco_bsn

basin nitrate percolation coefficient (0-1)

0:concentration of nitrate in surface runoff is zero

1:percolate has same concentration of nitrate as surface runoff

real *8 rsdco

residue decomposition coefficient. The fraction of residue which will decompose in a day assuming optimal moisture, temperature, C:N ratio, and C:P ratio

- real *8 phoskd_bsn
- real *8 voltot
- real *8 msk_x

weighting factor controling relative importance of inflow rate and outflow rate in determining storage on reach

- real *8 volcrmin
- real *8 bactkdq

bacteria soil partitioning coefficient. Ratio of solution bacteria in surface layer to solution bacteria in runoff soluble and sorbed phase in surface runoff.

real *8 wdpf

die-off factor for persistent bacteria on foliage (1/day)

real *8 uno3d

- · real *8 canev
- real *8 usle
- real *8 rcn
- real *8 surlag_bsn
- real *8 precipday
- real *8 thbact

temperature adjustment factor for bacteria die-off/growth

real *8 wlpq20

overall rate change for less persistent bacteria in soil solution (1/day)

real *8 wlps20

overall rate change for less persistent bacteria adsorbed to soil particles (1/day)

real *8 wpq20

overall rate change for persistent bacteria in soil solution (1/day)

real *8 wps20

overall rate change for persistent bacteria adsorbed to soil particles (1/day)

- real *8 bactrop
- real *8 bactsedp
- real *8 wgpf

growth factor for persistent bacteria on foliage (1/day)

- real *8 bactlchp
- real *8 bactlchlp
- real *8 enratio
- real *8 wetpcp
- real *8 pndpcp
- real *8 wetsep
- real *8 pndsep
- real *8 wetev
- real *8 pndev
- real *8 pndsedo
- real *8 wetsedo
- real *8 pndflwi
- real *8 wetflwi
- real *8 pndflwo
- real *8 wetflwo
- real *8 wetsedi
- real *8 da_ha
- real *8 vpd
- real *8 evlai

leaf area index at which no evaporation occurs. This variable is used in ponded HRUs where evaporation from the water surface is restricted by the plant canopy cover. Evaporation from the water surface equals potential ET when LAI = 0 and decreased linearly to O when LAI = EVLAI

· real *8 evrch

Reach evaporation adjustment factor. Evaporation from the reach is multiplied by EVRCH. This variable was created to limit the evaporation predicted in arid regions.

real *8 wdlpf

die-off factor for less persistent bacteria on foliage (1/day)

- real *8 bactrolp
- real *8 bactsedlp
- real *8 pet_day
- real *8 ep_day
- real *8 adj pkr

peak rate adjustment factor in the subbasin. Used in the MUSLE equation to account for impact of peak flow on erosion.

real *8 n_updis

nitrogen uptake distribution parameter. This parameter controls the amount of nitrogen removed from the different soil layer layers by the plant. In particular, this parameter allows the amount of nitrogen removed from the surface layer via plant uptake to be controlled. While the relationship between UBN and N removed from the surface layer is affected by the depth of the soil profile, in general, as UBN increases the amount of N removed from the surface layer relative to the amount removed from the entire profile increases

real *8 nactfr

nitrogen active pool fraction. The fraction of organic nitrogen in the active pool.

real *8 p_updis

phosphorus uptake distribution parameter This parameter controls the amount of phosphorus removed from the different soil layers by the plant. In particular, this parameter allows the amount of phosphorus removed from the surface layer via plant uptake to be controlled. While the relationship between UBP and P uptake from the surface layer is affected by the depth of the soil profile, in general, as UBP increases the amount of P removed from the surface layer relative to the amount removed from the entire profile increases

- real *8 snoev
- real *8 sno3up
- real *8 reactw
- real *8 sdiegropq
- real *8 sdiegrolpq
- real *8 sdiegrops
- real *8 sdiegrolps
- real *8 es_day
- real *8 wof lp

wash off fraction for less persistent bacteria on foliage during a rainfall event

- real *8 sbactrop
- real *8 sbactrolp
- real *8 sbactsedp
- real *8 sbactsedlp
- real *8 ep_max
- real *8 sbactlchp
- real *8 sbactlchlp
- real *8 psp_bsn
- real *8 rchwtr
- real *8 resuspst
- real *8 setIpst
- real *8 bsprev
- real *8 bssprev
- real *8 spadyo
- real *8 spadyev
- real *8 spadysp
- real *8 spadyrfv
- real *8 spadyosp
- real *8 qday
- real *8 usle_ei
- real *8 al5
- real *8 pndsedc
- real *8 no3pcp
- real *8 rcharea
- real *8 volatpst
- real *8 ubw

water uptake distribution parameter. This parameter controls the amount of water removed from the different soil layers by the plant. In particular, this parameter allows the amount of water removed from the surface layer via plant uptake to be controlled. While the relationship between UBW and H2O removed from the surface layer is affected by the depth of the soil profile, in general, as UBW increases the amount of water removed from the surface layer relative to the amount removed from the entire profile increases

real *8 uobn

nitrogen uptake normalization parameter. This variable normalizes the nitrogen uptake so that the model can easily verify that upake from the different soil layers sums to 1.0

real *8 uobp

phosphorus uptake normalization parameter. This variable normalizes the phosphorus uptake so that the model can easily verify that uptake from the different soil layers sums to 1.0

real *8 uobw

water uptake normalization parameter. This variable normalizes the water uptake so that the model can easily verify that uptake from the different soil layers sums to 1.0

real *8 wglpf

growth factor for less persistent bacteria on foliage (1/day)

- real *8 wetsedc
- real *8 respesti
- real *8 rcor

correction coefficient for generated rainfall to ensure that the annual means for generated and observed values are comparable (needed only if IDIST=1)

real *8 rexp

value of exponent for mixed exponential rainfall distribution (needed only if IDIST=1)

real *8 snocov1

1st shape parameter for snow cover equation. This parameter is determined by solving the equation for 50% snow cover

real *8 snocov2

2nd shape parameter for snow cover equation. This parameter is determined by solving the equation for 95% snow cover

real *8 snocovmx

Minimum snow water content that corresponds to 100% snow cover. If the snow water content is less than SNOC← OVMX, then a certain percentage of the ground will be bare (mm H2O)

- real *8 lyrtile
- real *8 lyrtilex
- real *8 sno50cov

Fraction of SNOCOVMX that corresponds to 50% snow cover. SWAT assumes a nonlinear relationship between snow water and snow cover.

real *8 ai0

ratio of chlorophyll-a to algal biomass (ug chla/mg alg)

real *8 ai1

fraction of algal biomass that is nitrogen (mg N/mg alg)

real *8 ai2

fraction of algal biomass that is phosphorus (mg P/mg alg)

real *8 ai3

the rate of oxygen production per unit of algal photosynthesis (mg O2/mg alg)

real *8 ai4

the rate of oxygen uptake per unit of algae respiration (mg O2/mg alg)

real *8 ai5

the rate of oxygen uptake per unit of NH3 nitrogen oxidation (mg O2/mg N)

real *8 ai6

the rate of oxygen uptake per unit of NO2 nitrogen oxidation (mg O2/mg N)

real *8 rhoq

algal respiration rate (1/day or 1/hr)

real *8 tfact

fraction of solar radiation computed in the temperature heat balance that is photosynthetically active

real *8 k_l

half-saturation coefficient for light (MJ/(m2*hr))

real *8 k n

michaelis-menton half-saturation constant for nitrogen (mg N/L)

real *8 k_p

michaelis-menton half saturation constant for phosphorus (mg P/L)

· real *8 lambda0

non-algal portion of the light extinction coefficient (1/m)

real *8 lambda1

linear algal self-shading coefficient (1/(m*ug chla/L))

· real *8 lambda2

nonlinear algal self-shading coefficient ((1/m)(ug chla/L)**(-2/3))

real *8 mumax

maximum specific algal growth rate (1/day or 1/hr)

real *8 p_n

algal preference factor for ammonia

- real *8 rnum1
- real *8 autop
- real *8 auton
- real *8 etday
- · real *8 hmntl
- real *8 rwntl
- real *8 hmptl
- real *8 rmn2tl
- real *8 rmptl
- real *8 wdntl
- real *8 cmn bsn
- real *8 rmp1tl
- real *8 roctl
- real *8 gwseep
- real *8 revapday
- real *8 reswtr
- real *8 wdlprch

die-off factor for less persistent bacteria in streams (1/day)

real *8 wdpres

die-off factor for persistent bacteria in reservoirs (1/day)

- real *8 bury
- real *8 difus
- real *8 reactb
- real *8 solpesto
- · real *8 petmeas
- real *8 wdlpres

die-off factor for less persistent bacteria in reservoirs (1/day)

- · real *8 sorpesto
- real *8 spcon_bsn
- real *8 spexp bsn
- · real *8 solpesti
- real *8 sorpesti
- real *8 msk co1

calibration coefficient to control impact of the storage time constant for the reach at bankfull depth (phi(10,:) upon the storage time constant for the reach used in the Muskingum flow method

real *8 msk_co2

calibration coefficient to control impact of the storage time constant for the reach at 0.1 bankfull depth (phi(13,:) upon the storage time constant for the reach used in the Muskingum flow method

- real *8 snoprev
- real *8 swprev
- real *8 shallstp

- · real *8 deepstp
- real *8 ressolpo
- · real *8 resorgno
- real *8 resorgpo
- real *8 resno3o
- real *8 reschlao
- real *8 resno2o
- real *8 resnh3o
- real *8 qdbank
- real *8 potpcpmm
- real *8 potevmm
- real *8 potsepmm
- real *8 potflwo
- · real *8 bactminlp

Threshold detection level for less persistent bacteria. When bacteria levels drop to this amount the model considers bacteria in the soil to be insignificant and sets the levels to zero (cfu/m^2 2)

real *8 bactminp

Threshold detection level for persistent bacteria. When bacteria levels drop to this amount the model considers bacteria in the soil to be insignificant and sets the levels to zero (cfu/m^2)

real *8 trnsrch

fraction of transmission losses from main channel that enter deep aquifer

real *8 wp20p_plt

overall rate change for persistent bacteria on foliage (1/day)

- real *8 potsedo
- real *8 pest_sol
- real *8 bact_swf

fraction of manure containing active colony forming units (cfu)

real *8 bactmx

bacteria percolation coefficient. Ratio of solution bacteria in surface layer to solution bacteria in percolate

· real *8 cncoef

plant ET curve number coefficient

real *8 wp20lp_plt

overall rate change for less persistent bacteria on foliage (1/day)

- real *8 cdn bsn
- real *8 sdnco_bsn
- · real *8 bactmin
- real *8 cn froz

drainge coefficient (mm day -1)

real *8 dorm_hr

time threshold used to define dormant (hours)

real *8 smxco

adjustment factor for max curve number s factor (0-1)

real *8 tb_adj

adjustment factor for subdaily unit hydrograph basetime

real *8 chla_subco

regional adjustment on sub chla_a loading (fraction)

real *8 depimp bsn

depth to impervious layer. Used to model perched water tables in all HRUs in watershed (mm)

real *8 ddrain_bsn

depth to the sub-surface drain (mm)

real *8 tdrain_bsn

time to drain soil to field capacity (hours)

```
    real *8 gdrain_bsn

real *8 rch_san
· real *8 rch_sil
• real *8 rch cla

    real *8 rch sag

 real *8 rch_lag

 real *8 rch_gra

real *8 hlife_ngw_bsn
     Half-life of nitrogen in groundwater? (days)

    real *8 ch opco bsn

• real *8 ch onco bsn

    real *8 decr_min

     Minimum daily residue decay.

 real *8 rcn sub bsn

     Concentration of nitrogen in the rainfall (mg/kg)
real *8 bc1_bsn
real *8 bc2_bsn

    real *8 bc3_bsn

 real *8 bc4 bsn

real *8 anion_excl_bsn
• real *8, dimension(:), allocatable wat_tbl

    real *8, dimension(:), allocatable sol_swpwt

• real *8, dimension(:,:), allocatable vwt
• real *8 re bsn
     Effective radius of drains (range 3.0 - 40.0) (mm)

    real *8 sdrain bsn

     Distance bewtween two drain or tile tubes (range 7600.0 - 30000.0) (mm)

    real *8 sstmaxd bsn

 real *8 drain co bsn
     Drainage coeffcient (range 10.0 - 51.0) (mm-day-1)

    real *8 latksatf bsn

     Multiplication factor to determine lateral ksat from SWAT ksat input value for HRU (range 0.01 - 4.0)
real *8 pc bsn
     Pump capacity (def val = 1.042 mm h-1 or 25 mm day-1) (mm h-1)
· integer i_subhw
· integer imgt
· integer idlast
· integer iwtr
· integer ifrttyp

    integer mo_atmo

· integer mo atmo1
· integer ifirstatmo
· integer iyr_atmo
integer iyr_atmo1
· integer matmo

    integer mch

     maximum number of channels
· integer mcr
     maximum number of crops grown per year
```

· integer mfcst

· integer mcrdb

maximum number of forecast stations

maximum number of crops/landcover in database file (crop.dat)

integer mfdb

max number of fertilizers in fert.dat

· integer mhru

maximum number of HRUs in watershed

integer mhyd

maximum number of hydrograph nodes

· integer mpdb

max number of pesticides in pest.dat

integer mrg

max number of rainfall/temp gages

· integer mcut

maximum number of cuttings per year

· integer mgr

maximum number of grazings per year

· integer mnr

max number of years of rotation

· integer myr

max number of years of simulation

integer isubwq

subbasin water quality code

0 do not calculate algae/CBOD 1 calculate algae/CBOD drainmod tile equations

- · integer ffcst
- · integer isproj

special project code: 1 test rewind (run simulation twice)

integer nbyr

number of calendar years simulated

· integer irte

water routing method: 0 variable storage method 1 Muskingum method

integer nrch

number of reaches in watershed (none)

· integer nres

number of reservoirs in watershed (none)

- integer nhru
- integer mo
- · integer immo
- · integer i_mo
- · integer wndsim

wind speed input code
1 measured data read for each subbasin

2 data simulated for each subbasin

· integer ihru

HRU number (none)

- integer icode
- · integer ihout
- integer inum1
- integer inum2
- integer inum3
- integer inum4
- integer icfac

icfac = 0 for C-factor calculation using Cmin (as described in manual) = 1 for new C-factor calculation from RUSLE (no minimum needed)

- · integer inum5
- · integer inum6
- · integer inum7
- · integer inum8
- · integer mrech

maximum number of rechour files

integer nrgage

number of raingage files

· integer nrgfil

number of rain gages per file

· integer nrtot

total number of rain gages

integer ntgage

number of temperature gage files

· integer ntgfil

number of temperature gages per file

· integer nttot

total number of temperature gages

· integer tmpsim

temperature input code

1 measured data read for each subbasin

2 data simulated for each subbasin

integer icrk

crack flow code

1: compute flow in cracks

· integer irtpest

number of pesticide to be routed through the watershed

· integer igropt

Qual2E option for calculating the local specific growth rate of algae

1: multiplicative.

· integer lao

Qual2E light averaging option. Qual2E defines four light averaging options. The only option currently available in SWAT is #2.

integer npmx

number of different pesticides used in the simulation (none)

- · integer curyr
- · integer iihru
- integer itdrn

tile drainage equations flag/code

1 simulate tile flow using subroutine drains(wt_shall)

0 simulate tile flow using subroutine origtile(wt_shall,d)

· integer iwtdn

water table depth algorithms flag/code

1 simulate wt_shall using subroutine new water table depth routine

0 simulate wt_shall using subroutine original water table depth routine

integer ismax

maximum depressional storage selection flag/code

0 = static depressional storage

1 = dynamic storage based on tillage and cumulative rainfall

· integer iroutunit

not being implemented in this version drainmod tile equations

• integer ires_nut

· integer iclb

auto-calibration flag

integer mrecc

maximum number of recenst files

integer mrecd

maximum number of recday files

integer mrecm

maximum number of recmon files

· integer mtil

max number of tillage types in till.dat

· integer mudb

maximum number of urban land types in urban.dat

· integer idist

rainfall distribution code

0 for skewed normal dist

1 for mixed exponential distribution

· integer mrecy

maximum number of recyear files

integer nyskip

number of years to not print output

· integer slrsim

solar radiation input code

1 measured data read for each subbasin

2 data simulated for each subbasin

· integer ideg

channel degredation code

1: compute channel degredation (downcutting and widening)

· integer ievent

rainfall/runoff code

0 daily rainfall/curve number technique 1 sub-daily rainfall/Green&Ampt/hourly routing 3 sub-daily rainfall/ \leftarrow Green&Ampt/hourly routing

integer ipet

code for potential ET method

0 Priestley-Taylor method

1 Penman/Monteith method

2 Hargreaves method

3 read in daily potential ET data

- integer iopera
- · integer idaf

beginning day of simulation (julian date)

integer idal

ending day of simulation (julian date)

· integer rhsim

relative humidity input code

1 measured data read for each subbasin

2 data simulated for each subbasin

- · integer id1
- · integer leapyr
- · integer mo_chk
- integer nhtot

number of relative humidity records in file

· integer nstot

number of solar radiation records in file

· integer nwtot

number of wind speed records in file

- · integer ifirsts
- · integer ifirsth
- integer ifirstw
- integer icst
- integer ilog

streamflow print code

· integer itotr

number of output variables printed (output.rch)

· integer iyr

beginning year of simulation (year)

· integer iwq

stream water quality code

0 do not model stream water quality

1 model stream water quality (QUAL2E & pesticide transformations)

· integer i

forecast region number or subbasin number (none)

- integer iskip
- · integer ifirstpet
- integer iprp

print code for output.pst file

0 do not print pesticide output

1 print pesticide output

· integer itotb

number of output variables printed (output.sub)

· integer itots

number of output variables printed (output.hru)

· integer itoth

number of HRUs printed (output.hru/output.wtr)

• integer pcpsim

rainfall input code

1 measured data read for each subbasin

2 data simulated for each subbasin

- integer nd_30
- integer iops
- integer iphr
- integer isto
- integer isol
- integer fcstcycles

number of times forecast period is simulated (using different weather generator seeds each time)

· integer fcstday

beginning date of forecast period (julian date)

· integer fcstyr

beginning year of forecast period

integer iscen

scenarios counter

· integer subtot

number of subbasins in watershed (none)

- · integer ogen
- · integer mapp

maximum number of applications

integer mlyr

maximum number of soil layers

integer mpst

max number of pesticides used in wshed

integer mres

maximum number of reservoirs

· integer msub

maximum number of subbasins

· integer igen

random number generator code:

0: use default numbers

1: generate new numbers in every simulation

integer iprint

print code: 0=monthly, 1=daily, 2=annual

- · integer iida
- · integer icn

CN method flag (for testing alternative method):

0 use traditional SWAT method which bases CN on soil moisture

1 use alternative method which bases CN on plant ET.

· integer ised det

max half-hour rainfall fraction calc option:

0 generate max half-hour rainfall fraction from triangular distribution

1 use monthly mean max half-hour rainfall fraction

- · integer fcstcnt
- · integer mtran
- · integer idtill
- integer, dimension(100) ida lup
- integer, dimension(100) iyr_lup
- integer no_lup
- integer no_up
- · integer nostep
- character(len=8) date

date simulation is performed where leftmost eight characters are set to a value of yyyymmdd, where yyyy is the year, mm is the month and dd is the day

• character(len=10) time

time simulation is performed where leftmost ten characters are set to a value of hhmmss.sss, where hh is the hour, mm is the minutes and ss.sss is the seconds and milliseconds

• character(len=5) zone

time difference with respect to Coordinated Universal Time (ie Greenwich Mean Time)

character(len=80) prog

SWAT program header string.

• character(len=13) calfile

name of file containing calibration parameters

• character(len=13) rhfile

relative humidity file name (.hmd)

• character(len=13) slrfile

solar radiation file name (.slr)

character(len=13) wndfile

wind speed file name (.wnd)

• character(len=13) petfile

potential ET file name (.pet)

- character(len=13) atmofile
- character(len=13) lucfile
- character(len=13) septdb

name of septic tank database file (septwq1.dat)

- character(len=13) dpd file
- character(len=13) wpd_file
- · character(len=13) rib_file
- · character(len=13) sfb file
- character(len=13) lid_file
- integer, dimension(9) idg

array location of random number seed used for a given process

- · integer, dimension(:), allocatable ifirstr
- · integer, dimension(:), allocatable ifirsthr
- · integer, dimension(8) values

values(1): year simulation is performed

values(2): month simulation is performed

values(3): day in month simulation is performed

values(4): time difference with respect to Coordinated Universal Time (ie Greenwich Mean Time)

values(5): hour simulation is performed

values(6): minute simulation is performed

values(7): second simulation is performed

values(8): millisecond simulation is performed

• integer, dimension(13) ndays

julian date for last day of preceding month (where the array location is the number of the month) The dates are for leap years (julian date)

- integer, dimension(13) ndays noleap
- integer, dimension(13) ndays_leap
- integer mapex
- real *8, dimension(:), allocatable flodaya
- real *8, dimension(:), allocatable seddaya
- real *8, dimension(:), allocatable orgndaya
- real *8, dimension(:), allocatable orgpdaya
- real *8, dimension(:), allocatable no3daya
- real *8, dimension(:), allocatable minpdaya
- real *8, dimension(:), allocatable hi_targ

index target of cover defined at planting

- real *8, dimension(:), allocatable bio_targ
- real *8, dimension(:), allocatable tnyld
- · integer, dimension(:), allocatable idapa
- integer, dimension(:), allocatable iypa
- · integer, dimension(:), allocatable ifirsta
- integer, dimension(100) mo_transb
- integer, dimension(100) mo_transe
- integer, dimension(100) ih_tran
- integer msdb
- integer iseptic
- real *8, dimension(:), allocatable sptqs
- real *8, dimension(:), allocatable percp
- real *8, dimension(:), allocatable sptbodconcs
- real *8, dimension(:), allocatable spttssconcs
- real *8, dimension(:), allocatable spttnconcs
- real *8, dimension(:), allocatable sptnh4concs
- real *8, dimension(:), allocatable sptno3concs
- real *8, dimension(:), allocatable sptno2concs
- real *8, dimension(:), allocatable sptorgnconcs
- real *8, dimension(:), allocatable spttpconcs
- real *8, dimension(:), allocatable **sptminps**
- real *8, dimension(:), allocatable sptorgps
- real *8, dimension(:), allocatable sptfcolis

```
    real *8, dimension(:), allocatable failyr

• real *8, dimension(:), allocatable qstemm

    real *8, dimension(:), allocatable bio_amn

• real *8, dimension(:), allocatable bio bod

    real *8, dimension(:), allocatable biom

    real *8, dimension(:), allocatable rbiom

• real *8, dimension(:), allocatable fcoli

    real *8, dimension(:), allocatable bio_ntr

    real *8, dimension(:), allocatable bz_perc

    real *8, dimension(:), allocatable sep_cap

      number of permanent residents in the hourse (none)

    real *8, dimension(:), allocatable plqm

  real *8, dimension(:), allocatable bz_area
  real *8, dimension(:), allocatable bz z
      Depth of biozone layer(mm)

    real *8, dimension(:), allocatable bz thk

      thickness of biozone (mm)
  real *8, dimension(:), allocatable bio bd
      density of biomass (kg/m<sup>\(^{\)</sup>3) carbon outputs for .hru file
  real *8, dimension(:), allocatable cmup_kgh
  real *8, dimension(:), allocatable cmtot_kgh
  real *8, dimension(:), allocatable coeff_denitr
      denitrification rate coefficient (none)

    real *8, dimension(:), allocatable coeff_bod_dc

      BOD decay rate coefficient (m^3/day)

    real *8, dimension(:), allocatable coeff_bod_conv

      BOD to live bacteria biomass conversion factor (none)

    real *8, dimension(:), allocatable coeff_fc1

      field capacity calibration parameter 1 (none)

    real *8, dimension(:), allocatable coeff_fc2

      field capacity calibration parameter 2 (none)
• real *8, dimension(:), allocatable coeff_fecal
      fecal coliform bacteria decay rate coefficient (m<sup>\(\circ\)</sup> 3/day)

    real *8, dimension(:), allocatable coeff mrt

      mortality rate coefficient (none)

    real *8, dimension(:), allocatable coeff_nitr

      nitrification rate coefficient (none)

    real *8, dimension(:), allocatable coeff_plg

      conversion factor for plaque from TDS (none)

    real *8, dimension(:), allocatable coeff_rsp

      respiration rate coefficient (none)

    real *8, dimension(:), allocatable coeff_slg1

      slough-off calibration parameter (none)

    real *8, dimension(:), allocatable coeff_slg2

      slough-off calibration parameter (none)

    real *8, dimension(:), allocatable coeff_pdistrb

  real *8, dimension(:), allocatable coeff solpslp
  real *8, dimension(:), allocatable coeff_solpintc
• real *8, dimension(:), allocatable coeff_psorpmax
  integer, dimension(:), allocatable isep typ
      septic system type (none)

    integer, dimension(:), allocatable i_sep
```

- integer, dimension(:), allocatable isep_opt
 septic system operation flag (1=active, 2=failing, 3=not operated) (none)
- integer, dimension(:), allocatable sep tsincefail
- · integer, dimension(:), allocatable isep_tfail
- · integer, dimension(:), allocatable isep_iyr
- integer, dimension(:), allocatable sep_strm_dist
- integer, dimension(:), allocatable sep_den
- real *8, dimension(:), allocatable sol_sumno3
- real *8, dimension(:), allocatable sol sumsolp
- real *8, dimension(:), allocatable strsw_sum
- real *8, dimension(:), allocatable strstmp sum
- real *8, dimension(:), allocatable strsn_sum
- real *8, dimension(:), allocatable strsp_sum
- real *8, dimension(:), allocatable strsa_sum
- real *8, dimension(:), allocatable spill hru
- real *8, dimension(:), allocatable tile_out
- real *8, dimension(:), allocatable hru_in
- real *8, dimension(:), allocatable spill_precip
- real *8, dimension(:), allocatable pot_seep
- real *8, dimension(:), allocatable pot evap
- real *8, dimension(:), allocatable pot_sedin
- real *8, dimension(:), allocatable pot_solp
- real *8, dimension(:), allocatable pot solpi
- real *8, dimension(:), allocatable pot_orgp
- real *8, dimension(:), allocatable pot_orgpi
- real *8, dimension(:), allocatable pot_orgn
- real *8, dimension(:), allocatable pot orgni
- real *8, dimension(:), allocatable pot_mps
- real *8, dimension(:), allocatable pot_mpsi
- real *8, dimension(:), allocatable pot mpa
- real *8, dimension(:), allocatable pot_mpai
- real *8, dimension(:), allocatable pot_no3i
- real *8, dimension(:), allocatable precip_in
- real *8, dimension(:), allocatable tile_sedo
- real *8, dimension(:), allocatable tile_no3o
- real *8, dimension(:), allocatable tile_solpo
- real *8, dimension(:), allocatable tile_orgno
- real *8, dimension(:), allocatable tile_orgpo
- real *8, dimension(:), allocatable tile_minpso
- real *8, dimension(:), allocatable tile_minpao
- integer ia b
- · integer ihumus
- · integer itemp
- integer isnow
- integer, dimension(41) icolrsv
- · integer, dimension(mhruo) icols
- integer, dimension(mrcho) icolr
- integer, dimension(msubo) icolb
- integer, dimension(46) ipdvar
 - output variable codes for output.rch file
- integer, dimension(mhruo) ipdvas
 - output varaible codes for output.hru file
- integer, dimension(msubo) ipdvab
 - output variable codes for output.sub file

- integer, dimension(:), allocatable ipdhru
 - HRUs whose output information will be printed to the output.hru and output.wtr files.
- real *8, dimension(mstdo) wshddayo
- real *8, dimension(mstdo) wshdmono
- real *8, dimension(mstdo) wshdyro
- real *8, dimension(16) fcstaao
- real *8, dimension(mstdo) wshdaao
- real *8, dimension(:,:), allocatable wpstdayo
- real *8, dimension(:,:), allocatable wpstmono
- real *8, dimension(:,:), allocatable wpstyro
- real *8, dimension(:,:), allocatable yldkg
- real *8, dimension(:,:), allocatable bio_hv
- real *8, dimension(:,:), allocatable wpstaao
- real *8, dimension(:,:), allocatable rchmono
- real *8, dimension(:,:), allocatable rchyro
- real *8, dimension(:,:), allocatable rchaao
- real *8, dimension(:,:), allocatable rchdy
- real *8, dimension(:,:), allocatable hrumono
- real *8, dimension(:,:), allocatable hruyro
- real *8, dimension(:,:), allocatable hruaao
- real *8, dimension(:,:), allocatable submono
- real *8, dimension(:,:), allocatable subyro
- real *8, dimension(:,:), allocatable subaao
- real *8, dimension(:,:), allocatable resoutm
- real *8, dimension(:,:), allocatable resouty
- real *8, dimension(:,:), allocatable resouta
- real *8, dimension(12, 8) wshd_aamon
- real *8, dimension(:,:), allocatable wtrmon
- real *8, dimension(:,:), allocatable wtryr
- real *8, dimension(:,:), allocatable wtraa
- real *8, dimension(:,:), allocatable sub_smfmx

max melt rate for snow during year (June 21) for subbasin(:) where deg C refers to the air temperature. SUB_SMFMX and SMFMN allow the rate of snow melt to vary through the year. These parameters are accounting for the impact of soil temperature on snow melt (range: -5.0/5.0) (mm/deg C/day)

real *8, dimension(:,:), allocatable sub_smfmn

min melt rate for snow during year (Dec 21) for subbasin(:) (range: -5.0/5.0) where deg C refers to the air temperature (mm/deg C/day)

- real *8, dimension(:,:,:), allocatable hrupstd
- real *8, dimension(:,:,:), allocatable hrupsta
- real *8, dimension(:,:,:), allocatable hrupstm
- real *8, dimension(:,:,:), allocatable hrupsty
- · integer, dimension(:), allocatable ifirstt
- integer, dimension(:), allocatable ifirstpcp
- integer, dimension(:), allocatable elevp
- · integer, dimension(:), allocatable elevt
- real *8, dimension(:,:), allocatable ftmpmn

avg monthly minimum air temperature (deg C)

real *8, dimension(:,:), allocatable ftmpmx

avg monthly maximum air temperature (deg C)

real *8, dimension(:,:), allocatable ftmpstdmn

standard deviation for avg monthly minimum air temperature (deg C)

real *8, dimension(:,:), allocatable ftmpstdmx

standard deviation for avg monthly maximum air temperature (deg C)

real *8, dimension(:,:,:), allocatable fpcp_stat

```
fpcp_stat(:,1,:): average amount of precipitation falling in one day for the month (mm/day)
     fpcp_stat(:,2,:): standard deviation for the average daily precipitation (mm/day)
     fpcp_stat(:,3,:): skew coefficient for the average daily precipitationa (none)
 real *8, dimension(:,:), allocatable fpr w1
     probability of wet day after dry day in month (none)

    real *8, dimension(:,:), allocatable fpr w2

     probability of wet day after wet day in month (none)
  real *8, dimension(:,:), allocatable fpr w3
     proportion of wet days in the month (none)
  real *8, dimension(:), allocatable flwin
  real *8, dimension(:), allocatable flwout
  real *8, dimension(:), allocatable bankst
  real *8, dimension(:), allocatable ch_wi
  real *8, dimension(:), allocatable ch d
  real *8, dimension(:), allocatable ch onco
     channel organic n concentration (ppm)
  real *8, dimension(:), allocatable ch_opco
     channel organic p concentration (ppm)
  real *8, dimension(:), allocatable ch orgn
  real *8, dimension(:), allocatable ch orgp
  real *8, dimension(:), allocatable drift
  real *8, dimension(:), allocatable rch_dox
  real *8, dimension(:), allocatable rch bactp
  real *8, dimension(:), allocatable alpha bnk
  real *8, dimension(:), allocatable alpha bnke
  real *8, dimension(:), allocatable disolvp
  real *8, dimension(:), allocatable algae
  real *8, dimension(:), allocatable sedst
  real *8, dimension(:), allocatable rchstor
  real *8, dimension(:), allocatable organicn
  real *8, dimension(:), allocatable organicp
  real *8, dimension(:), allocatable chlora
  real *8, dimension(:), allocatable nitraten
  real *8, dimension(:), allocatable nitriten
  real *8, dimension(:), allocatable ch_li
  real *8, dimension(:), allocatable ch_si
  real *8, dimension(:), allocatable ch_bnk_san
  real *8, dimension(:), allocatable ch_bnk_sil
  real *8, dimension(:), allocatable ch_bnk_cla
  real *8, dimension(:), allocatable ch bnk gra
  real *8, dimension(:), allocatable ch bed san
  real *8, dimension(:), allocatable ch_bed_sil
  real *8, dimension(:), allocatable ch bed cla
  real *8, dimension(:), allocatable ch_bed_gra
  real *8, dimension(:), allocatable depfp
  real *8, dimension(:), allocatable depsanfp
  real *8, dimension(:), allocatable depsilfp
  real *8, dimension(:), allocatable depclafp
  real *8, dimension(:), allocatable depsagfp
  real *8, dimension(:), allocatable deplagfp
  real *8, dimension(:), allocatable depch
  real *8, dimension(:), allocatable depsanch
  real *8, dimension(:), allocatable depsilch
```

real *8, dimension(:), allocatable depclach

- real *8, dimension(:), allocatable depsagch
- real *8, dimension(:), allocatable deplagch
- real *8, dimension(:), allocatable depgrach
- real *8, dimension(:), allocatable depgrafp
- real *8, dimension(:), allocatable grast
- real *8, dimension(:), allocatable depprch
- real *8, dimension(:), allocatable depprfp
- real *8, dimension(:), allocatable prf
- real *8, dimension(:), allocatable r2adi
- real *8, dimension(:), allocatable spcon

linear parameter for calculating sediment reentrained in channel sediment routing

real *8, dimension(:), allocatable spexp

exponent parameter for calculating sediment reentrained in channel sediment routing

- real *8, dimension(:), allocatable sanst
- real *8, dimension(:), allocatable silst
- real *8, dimension(:), allocatable clast
- real *8, dimension(:), allocatable sagst
- real *8, dimension(:), allocatable lagst
- real *8, dimension(:), allocatable pot_san
- real *8, dimension(:), allocatable pot_sil
- real *8, dimension(:), allocatable pot_cla
- real *8, dimension(:), allocatable pot_sag
- real *8, dimension(:), allocatable pot_lag
- real *8, dimension(:), allocatable potsani
- real *8, dimension(:), allocatable potsali
- real *8, dimension(:), allocatable potclai
- real *8, dimension(:), allocatable potsagi
- real *8, dimension(:), allocatable **potlagi**
- real *8, dimension(:), allocatable sanyld
- real *8, dimension(:), allocatable silyld
- real *8, dimension(:), allocatable clayId
- real *8, dimension(:), allocatable sagyld
- real *8, dimension(:), allocatable lagyld
- real *8, dimension(:), allocatable grayId
- real *8, dimension(:), allocatable res_san
- real *8, dimension(:), allocatable res_sil
- real *8, dimension(:), allocatable res_cla
- real *8, dimension(:), allocatable res_sag
- real *8, dimension(:), allocatable res_lag
- real *8, dimension(:), allocatable res_gra
- real *8, dimension(:), allocatable pnd_san
- real *8, dimension(:), allocatable pnd_sil
- real *8, dimension(:), allocatable pnd_cla
- real *8, dimension(:), allocatable pnd_sag
- real *8, dimension(:), allocatable pnd_lag
- real *8, dimension(:), allocatable wet_san
- real *8, dimension(:), allocatable wet_sil
- real *8, dimension(:), allocatable wet_cla
- real *8, dimension(:), allocatable wet_lag
- real *8, dimension(:), allocatable wet_sag
- real *8 ressano
- real *8 ressilo
- real *8 resclao
- real *8 ressago

- · real *8 reslago
- real *8 resgrao
- real *8 ressani
- real *8 ressili
- · real *8 resclai
- real *8 ressagi
- real *8 reslagi
- real *8 resgrai
- real *8 potsano
- real *8 potsilo
- real *8 potclao
- real *8 potsago
- real *8 potlago
- real *8 pndsanin
- real *8 pndsilin
- real *8 pndclain
- real *8 pndsagin
- real *8 pndlagin
- real *8 pndsano
- real *8 pndsilo
- · real *8 pndclao
- real *8 pndsago
- real *8 pndlago
- real *8, dimension(:), allocatable ch_di
- real *8, dimension(:), allocatable ch_erod
- real *8, dimension(:), allocatable ch_l2
- real *8, dimension(:), allocatable ch_cov
- real *8, dimension(:), allocatable ch_cov1
- real *8, dimension(:), allocatable ch_cov2
- real *8, dimension(:), allocatable ch_bnk_bd
- real *8, dimension(:), allocatable ch bed bd
- real *8, dimension(:), allocatable ch_bnk_kd
- real *8, dimension(:), allocatable ch_bed_kd
- real *8, dimension(:), allocatable **ch_bnk_d50**
- real *8, dimension(:), allocatable ch_bed_d50
- real *8, dimension(:), allocatable tc_bed
- real *8, dimension(:), allocatable tc_bnk
- integer, dimension(:), allocatable ch_eqn
- real *8, dimension(:), allocatable chpst_conc
- real *8, dimension(:), allocatable chpst_rea
- real *8, dimension(:), allocatable chpst vol
- real *8, dimension(:), allocatable chpst_koc
- real *8, dimension(:), allocatable chpst_stl
- real *8, dimension(:), allocatable chpst_rsp
- real *8, dimension(:), allocatable chpst_mix
- real *8, dimension(:), allocatable sedpst_conc
- real *8, dimension(:), allocatable ch wdr
- real *8, dimension(:), allocatable sedpst_rea
- real *8, dimension(:), allocatable sedpst_bry
- real *8, dimension(:), allocatable sedpst_act
- real *8, dimension(:), allocatable rch_cbod
- real *8, dimension(:), allocatable rch_bactlp
- real *8, dimension(:), allocatable chside
- real *8, dimension(:), allocatable rs1
- real *8, dimension(:), allocatable rs2

```
    real *8, dimension(:), allocatable rs3

• real *8, dimension(:), allocatable rs4
• real *8, dimension(:), allocatable rs5
• real *8, dimension(:), allocatable rs6

    real *8, dimension(:), allocatable rs7

    real *8, dimension(:), allocatable rk1

    real *8, dimension(:), allocatable rk2

• real *8, dimension(:), allocatable rk3
• real *8, dimension(:), allocatable rk4
• real *8, dimension(:), allocatable rk5

    real *8, dimension(:), allocatable bc1

      rate constant for biological oxidation of NH3 to NO2 in reach at 20 deg C (1/hr)
• real *8, dimension(:), allocatable bc2
      rate constant for biological oxidation of NO2 to NO3 in reach at 20 deg C (1/hr)

    real *8, dimension(:), allocatable bc3

      rate constant for hydrolysis of organic N to ammonia in reach at 20 deg C (1/hr)

    real *8, dimension(:), allocatable bc4

      rate constant for the decay of organic P to dissolved P in reach at 20 deg C (1/hr)

    real *8, dimension(:), allocatable rk6

    real *8, dimension(:), allocatable ammonian

  real *8, dimension(:), allocatable orig_sedpstconc

    real *8, dimension(:,:), allocatable wurch

• integer, dimension(:), allocatable icanal

    integer, dimension(:), allocatable itb

    real *8, dimension(:), allocatable ch_revap

    real *8, dimension(:), allocatable dep_chan

    real *8, dimension(:), allocatable harg_petco

      coefficient related to radiation used in hargreaves eq (range: 0.0019 - 0.0032)

    real *8, dimension(:), allocatable subfr_nowtr

  real *8, dimension(:), allocatable cncoef sub
      soil water depletion coefficient used in the new (modified curve number method) same as soil index coeff used in
      APEX range: 0.5 - 2.0
real *8, dimension(:), allocatable dr_sub
• real *8, dimension(:), allocatable wcklsp

    real *8, dimension(:), allocatable sub_fr

    real *8, dimension(:), allocatable sub_minp

    real *8, dimension(:), allocatable sub sw

• real *8, dimension(:), allocatable sub_sumfc

    real *8, dimension(:), allocatable sub gwno3

    real *8, dimension(:), allocatable sub_gwsolp

• real *8, dimension(:), allocatable co2
      CO2 concentration (ppmv)

    real *8, dimension(:), allocatable sub km

      area of subbasin in square kilometers (km^{\wedge}2)

    real *8, dimension(:), allocatable sub_tc

• real *8, dimension(:), allocatable wlat
• real *8, dimension(:), allocatable sub_pet

    real *8, dimension(:), allocatable welev

    real *8, dimension(:), allocatable sub_orgn

    real *8, dimension(:), allocatable sub_orgp
```

real *8, dimension(:), allocatable sub_bd

```
    real *8, dimension(:), allocatable sub wtmp

    real *8, dimension(:), allocatable sub sedpa

real *8, dimension(:), allocatable sub_sedps
• real *8, dimension(:), allocatable sub minpa

    real *8, dimension(:), allocatable sub minps

    real *8, dimension(:), allocatable daylmn

    real *8, dimension(:), allocatable latcos

    real *8, dimension(:), allocatable latsin

  real *8, dimension(:), allocatable phutot
 real *8, dimension(:), allocatable plaps
     precipitation lapse rate: precipitation change due to change in elevation (mm H2O/km)

    real *8, dimension(:), allocatable tlaps

      temperature lapse rate: temperature change due to change in elevation (deg C/km)

    real *8, dimension(:), allocatable tmp_an

    real *8, dimension(:), allocatable sub precip

  real *8, dimension(:), allocatable pcpdays

    real *8, dimension(:), allocatable rcn sub

    real *8, dimension(:), allocatable rammo_sub

    real *8, dimension(:), allocatable atmo day

    real *8, dimension(:), allocatable sub snom

    real *8, dimension(:), allocatable sub_qd

    real *8, dimension(:), allocatable sub sedy

    real *8, dimension(:), allocatable sub_tran

• real *8, dimension(:), allocatable sub_no3
  real *8, dimension(:), allocatable sub latno3

    real *8, dimension(:,:), allocatable sub_sftmp

      snowfall temperature for subbasin(:). Mean air temperature at which precip is equally likely to be rain as snow/freezing
     rain (range: -5.0/5.0) (deg C)

    real *8, dimension(:,:), allocatable sub_smtmp

      snow melt base temperature for subbasin(:) mean air temperature at which snow melt will occur (range: -5.0/5.0)
      (dea C)

    real *8, dimension(:,:), allocatable sub_timp

      snow pack temperature lag factor (0-1) (none)

    real *8, dimension(:), allocatable sub_tileno3

    real *8, dimension(:), allocatable sub_solp

    real *8, dimension(:), allocatable sub subp

    real *8, dimension(:), allocatable sub_etday

    real *8, dimension(:), allocatable sub_elev

      average elevation of subbasin (m)

    real *8, dimension(:), allocatable sub wyld

    real *8, dimension(:), allocatable sub_surfq

  real *8, dimension(:), allocatable gird

    real *8, dimension(:), allocatable sub_gwq

    real *8, dimension(:), allocatable sub_sep

    real *8, dimension(:), allocatable sub_chl

• real *8, dimension(:), allocatable sub cbod

    real *8, dimension(:), allocatable sub dox

    real *8, dimension(:), allocatable sub_solpst

    real *8, dimension(:), allocatable sub sorpst

    real *8, dimension(:), allocatable sub_yorgn

    real *8, dimension(:), allocatable sub_yorgp

  real *8, dimension(:), allocatable sub_lat
      latitude of subbasin (degrees)
```

real *8, dimension(:), allocatable sub_bactp

- real *8, dimension(:), allocatable sub_bactlp
- real *8, dimension(:), allocatable sub_latq
- real *8, dimension(:), allocatable sub_gwq_d
- real *8, dimension(:), allocatable sub_tileq
- real *8, dimension(:), allocatable sub_vaptile
- real *8, dimension(:), allocatable sub_dsan
- real *8, dimension(:), allocatable sub dsil
- real *8, dimension(:), allocatable sub_dcla
- real *8, dimension(:), allocatable sub_dsag
- real *8, dimension(:), allocatable sub dlag
- real *8 vap tile
- real *8, dimension(:), allocatable wnan
- real *8, dimension(:,:), allocatable sol_stpwt
- real *8, dimension(:,:), allocatable sub_pst
- real *8, dimension(:,:), allocatable sub_hhqd
- real *8, dimension(:,:), allocatable sub_hhwtmp
- real *8, dimension(:,:), allocatable huminc

monthly humidity adjustment. Daily values for relative humidity within the month are rasied or lowered by the specified amount (used in climate change studies) (none)

• real *8, dimension(:,:), allocatable radinc

monthly solar radiation adjustment. Daily radiation within the month is raised or lowered by the specified amount. (used in climate change studies) (MJ/m^2)

real *8, dimension(:,:), allocatable rfinc

monthly rainfall adjustment. Daily rainfall within the month is adjusted to the specified percentage of the original value (used in climate change studies)(%)

• real *8, dimension(:,:), allocatable tmpinc

monthly temperature adjustment. Daily maximum and minimum temperatures within the month are raised or lowered by the specified amount (used in climate change studies) (deg C)

real *8, dimension(:), allocatable ch_k1

effective hydraulic conductivity of tributary channel alluvium (mm/hr)

- real *8, dimension(:), allocatable ch_k2
- real *8, dimension(:,:), allocatable elevb

elevation at the center of the band (m)

real *8, dimension(:,:), allocatable elevb_fr

fraction of subbasin area within elevation band (the same fractions should be listed for all HRUs within the subbasin) (none)

- real *8, dimension(:,:), allocatable wndav
- real *8, dimension(:), allocatable ch_n1

Manning's "n" value for the tributary channels (none)

- real *8, dimension(:), allocatable ch_n2
- real *8, dimension(:), allocatable ch_s1

average slope of tributary channels (m/m)

- real *8, dimension(:), allocatable ch_s2
- real *8, dimension(:), allocatable ch_w1

average width of tributary channels (m)

- real *8, dimension(:), allocatable ch_w2
- real *8, dimension(:,:), allocatable dewpt
- real *8, dimension(:,:), allocatable amp_r
- real *8, dimension(:,:), allocatable solarav
- real *8, dimension(:,:), allocatable tmpstdmx
- real *8, dimension(:,:), allocatable tmpstdmn
- real *8, dimension(:,:), allocatable pcf
- real *8, dimension(:,:), allocatable tmpmn
- real *8, dimension(:,:), allocatable tmpmx

```
• real *8, dimension(:,:), allocatable otmpstdmn
```

- real *8, dimension(:,:), allocatable otmpmn
- real *8, dimension(:,:), allocatable otmpmx
- real *8, dimension(:,:), allocatable otmpstdmx
- real *8, dimension(:,:), allocatable ch_erodmo
- real *8, dimension(:,:), allocatable uh
- real *8, dimension(:,:), allocatable hqdsave
- real *8, dimension(:,:), allocatable hsdsave
- real *8, dimension(:,:), allocatable pr_w1
- real *8, dimension(:,:), allocatable pr_w2
- real *8, dimension(:,:), allocatable pr w3
- real *8, dimension(:,:,:), allocatable pcp_stat
- real *8, dimension(:,:), allocatable opr_w1
- real *8, dimension(:,:), allocatable opr_w2
- real *8, dimension(:,:), allocatable opr_w3
- real *8, dimension(:,:,:), allocatable opcp_stat
- integer, dimension(:), allocatable hrutot
- · integer, dimension(:), allocatable hru1
- · integer, dimension(:), allocatable ireg
- integer, dimension(:), allocatable ihgage

subbasin relative humidity data code (none)

• integer, dimension(:), allocatable isgage

subbasin radiation gage data code (none)

• integer, dimension(:), allocatable iwgage

subbasin wind speed gage data code (none)

• integer, dimension(:), allocatable subgis

GIS code printed to output files (output.sub) (none.

integer, dimension(:), allocatable irgage

subbasin rain gage data code (none)

• integer, dimension(:), allocatable itgage

subbasin temp gage data code (none)

- integer, dimension(:), allocatable fcst_reg
- integer, dimension(:), allocatable irelh
- real *8, dimension(:,:), allocatable sol_aorgn
- real *8, dimension(:,:), allocatable sol_tmp
- real *8, dimension(:,:), allocatable sol_fon
- real *8, dimension(:,:), allocatable sol_awc
- real *8, dimension(:,:), allocatable sol_prk
- real *8, dimension(:,:), allocatable volcr
- real *8, dimension(:,:), allocatable pperco_sub

subbasin phosphorus percolation coefficient. Ratio of soluble phosphorus in surface to soluble phosphorus in percolate

- real *8, dimension(:,:), allocatable sol_actp
- real *8, dimension(:,:), allocatable sol_stap
- real *8, dimension(:,:), allocatable conv_wt
- real *8, dimension(:,:), allocatable sol_solp

soluble P concentration in top soil layer (mg P/kg soil)

- real *8, dimension(:,:), allocatable sol_ul
- real *8, dimension(:,:), allocatable sol fc
- real *8, dimension(:,:), allocatable crdep
- real *8, dimension(:,:), allocatable sol z
- real *8, dimension(:,:), allocatable sol up
- real *8, dimension(:,:), allocatable sol_bd

 real *8, dimension(:,:), allocatable sol_st • real *8, dimension(:,:), allocatable flat real *8, dimension(:,:), allocatable sol_nh3 real *8, dimension(:,:), allocatable sol_hk real *8, dimension(:,:), allocatable sol clay real *8, dimension(:,:), allocatable sol_ec real *8, dimension(:,:), allocatable sol_orgn organic N concentration in top soil layer (mg N/kg soil) real *8. dimension(:::), allocatable sol por real *8, dimension(:,:), allocatable sol wp real *8, dimension(:,:), allocatable sol_orgp organic P concentration in top soil layer (mg P/kg soil) real *8, dimension(:,:), allocatable sol hum real *8, dimension(:,:), allocatable sol_wpmm real *8, dimension(:,:), allocatable sol no3 concentration of nitrate in soil layer (mg N/kg) real *8, dimension(:,:), allocatable sol k real *8, dimension(:,:), allocatable sol_cbn real *8, dimension(:,:), allocatable sol rsd real *8, dimension(:,:), allocatable sol fop real *8, dimension(:,:), allocatable sol_silt real *8, dimension(:,:), allocatable sol_sand real *8, dimension(:,:), allocatable sol_rock real *8, dimension(:,:), allocatable orig solno3 real *8, dimension(:,:), allocatable orig solorgn real *8, dimension(:,:), allocatable orig_solsolp real *8, dimension(:,:), allocatable orig solorgp real *8, dimension(:,:), allocatable orig soltmp real *8, dimension(:,:), allocatable orig solrsd real *8, dimension(:,:), allocatable orig solfop real *8, dimension(:,:), allocatable orig_solfon real *8, dimension(:,:), allocatable orig solaorgn real *8, dimension(:,:), allocatable orig_solst real *8, dimension(:,:), allocatable orig solactp real *8, dimension(:,:), allocatable orig solstap real *8, dimension(:,:), allocatable orig_volcr real *8, dimension(:,:), allocatable conk real *8, dimension(:,:,:), allocatable sol_pst sol pst(:,:,1) pesticide concentration in soil (mg/kg) real *8, dimension(:,:,:), allocatable sol_kp real *8, dimension(:,:,:), allocatable orig_solpst real *8, dimension(:), allocatable velsetlr real *8, dimension(:), allocatable velsetlp real *8, dimension(:), allocatable br1 real *8, dimension(:), allocatable res k real *8, dimension(:), allocatable Ikpst conc real *8, dimension(:), allocatable evrsv real *8, dimension(:), allocatable res_evol real *8, dimension(:), allocatable res_pvol • real *8, dimension(:), allocatable res_vol real *8, dimension(:), allocatable res psa real *8, dimension(:), allocatable lkpst_rea real *8, dimension(:), allocatable lkpst vol

real *8, dimension(:), allocatable br2

- real *8, dimension(:), allocatable res_rr
- real *8, dimension(:), allocatable res sed
- real *8, dimension(:), allocatable lkpst_koc
- real *8, dimension(:), allocatable lkpst stl
- real *8, dimension(:), allocatable lkpst_rsp
- real *8, dimension(:), allocatable lkpst_mix
- real *8, dimension(:), allocatable lkspst conc
- real *8, dimension(:), allocatable lkspst_rea
- real *8, dimension(:), allocatable theta_n
- real *8, dimension(:), allocatable theta p
- real *8, dimension(:), allocatable con_nirr
- real *8, dimension(:), allocatable con_pirr
- real *8, dimension(:), allocatable lkspst_bry
- real *8, dimension(:), allocatable lkspst_act
- real *8, dimension(:), allocatable sed_stlr
- real *8, dimension(7) resdata
- real *8, dimension(:), allocatable wurtnf
- real *8, dimension(:), allocatable res nsed
- real *8, dimension(:), allocatable chlar
- real *8, dimension(:), allocatable res_orgn
- real *8, dimension(:), allocatable res_orgp
- real *8, dimension(:), allocatable res no3
- real *8, dimension(:), allocatable res solp
- real *8, dimension(:), allocatable res_chla
- real *8, dimension(:), allocatable res_seci
- real *8, dimension(:), allocatable res_esa
- real *8, dimension(:), allocatable seccir
- real *8, dimension(:), allocatable res_no2
- real *8, dimension(:), allocatable res_nh3
- real *8, dimension(:), allocatable res_bactp
- real *8, dimension(:), allocatable res_bactlp
- real *8, dimension(:), allocatable oflowmn_fps
- real *8, dimension(:), allocatable starg_fps
- real *8, dimension(:), allocatable weirc
- real *8, dimension(:), allocatable weirk
- real *8, dimension(:), allocatable weirw
- real *8, dimension(:), allocatable acoef
- real *8, dimension(:), allocatable bcoef
- · real *8, dimension(:), allocatable ccoef
- real *8, dimension(:), allocatable orig_resvol
- real *8, dimension(:), allocatable orig ressed
- real *8, dimension(:), allocatable orig_lkpstconc
- real *8, dimension(:), allocatable orig lkspstconc
- real *8, dimension(:), allocatable orig_ressolp
- real *8, dimension(:), allocatable orig_resorgp
- real *8, dimension(:), allocatable orig resno3
- real *8, dimension(:), allocatable orig resno2
- real *8, dimension(:), allocatable orig_resnh3
- real *8, dimension(:), allocatable orig_resorgn
- real *8, dimension(:,:), allocatable starg
- real *8, dimension(:,:), allocatable oflowmx
- real *8, dimension(:,:), allocatable oflowmn
- real *8, dimension(:,:), allocatable psetIr
- real *8, dimension(:,:), allocatable nsetlr
- real *8, dimension(:,:), allocatable wuresn

```
real *8, dimension(:,:,:), allocatable res_out
· integer, dimension(:), allocatable ires1
• integer, dimension(:), allocatable ires2

    integer, dimension(:), allocatable res_sub

· integer, dimension(:), allocatable iresco
• integer, dimension(:), allocatable mores

    integer, dimension(:), allocatable iyres

    integer, dimension(:), allocatable iflod1r

    integer, dimension(:), allocatable iflod2r

• integer, dimension(:), allocatable ndtargr

    real *8, dimension(:), allocatable ap ef

      application efficiency (0-1) (none)

    real *8, dimension(:), allocatable decay_f

      exponential of the rate constant for degradation of the pesticide on foliage (none)
  real *8, dimension(:), allocatable skoc
      soil adsorption coefficient normalized for soil organic carbon content ((mg/kg)/(mg/L))
  real *8, dimension(:), allocatable decay s
      exponential of the rate constant for degradation of the pesticide in soil (none)

    real *8, dimension(:), allocatable hlife_f

      half-life of pesticide on foliage (days)

    real *8, dimension(:), allocatable hlife s

      half-life of pesticide in soil (days)

    real *8, dimension(:), allocatable pst_wof

      fraction of pesticide on foliage which is washed-off by a rainfall event (none)

    real *8, dimension(:), allocatable pst wsol

      solubility of chemical in water (mg/L (ppm))
• real *8, dimension(:), allocatable irramt
  real *8, dimension(:), allocatable phusw
  real *8, dimension(:), allocatable phusw_nocrop

    integer, dimension(:), allocatable pstflg

      flag for types of pesticide used in watershed array location is pesticide ID number
      0: pesticide not used
      1: pesticide used
• integer, dimension(:), allocatable nope
      sequence number of pesticide in NPNO(:) (none)

    integer, dimension(:), allocatable nop

    integer, dimension(:), allocatable yr_skip

• integer, dimension(:), allocatable isweep
• integer, dimension(:), allocatable icrmx

    integer, dimension(:), allocatable nopmx

• integer, dimension(:,:), allocatable mgtop

    integer, dimension(:,:), allocatable idop

• integer, dimension(:,:), allocatable mgt1iop
• integer, dimension(:,:), allocatable mgt2iop

    integer, dimension(:,:), allocatable mgt3iop

• real *8, dimension(:,:), allocatable mgt4op

    real *8, dimension(:,:), allocatable mgt5op

    real *8, dimension(:,:), allocatable mgt6op

    real *8, dimension(:,:), allocatable mgt7op

    real *8, dimension(:,:), allocatable mgt8op

    real *8, dimension(:,:), allocatable mgt9op

 real *8, dimension(:,:), allocatable mgt10iop
```

real *8, dimension(:,:), allocatable phu_op

```
    real *8, dimension(:), allocatable cnyld

      fraction of nitrogen in yield (kg N/kg yield)

    real *8, dimension(:), allocatable rsdco pl

      plant residue decomposition coefficient. The fraction of residue which will decompose in a day assuming optimal
      moisture, temperature, C:N ratio, and C:P ratio (none)
• real *8, dimension(:), allocatable wac21
      1st shape parameter for radiation use efficiency equation (none)
• real *8, dimension(:), allocatable wac22
      2nd shape parameter for radiation use efficiency equation (none)

    real *8, dimension(:), allocatable alai_min

      minimum LAI during winter dormant period (m^2/m^2)

    real *8, dimension(:), allocatable leaf1

      1st shape parameter for leaf area development equation (none)
• real *8, dimension(:), allocatable leaf2
     2nd shape parameter for leaf area development equation (none)

    real *8, dimension(:), allocatable wsyf

      Value of harvest index between 0 and HVSTI which represents the lowest value expected due to water stress
      ((kg/ha)/(kg/ha))
• real *8, dimension(:), allocatable bio e
     biomass-energy ratio. The potential (unstressed) growth rate per unit of intercepted photosynthetically active
     radiation.((kg/ha)/(MJ/m**2))

    real *8, dimension(:), allocatable hvsti

     harvest index: crop yield/aboveground biomass ((kg/ha)/(kg/ha))

    real *8, dimension(:), allocatable t_base

      minimum temperature for plant growth (deg C)

    real *8, dimension(:), allocatable t opt

      optimal temperature for plant growth (deg C)

    real *8, dimension(:), allocatable chtmx

      maximum canopy height (m)

    real *8, dimension(:), allocatable cvm

      natural log of USLE_C (none)
• real *8, dimension(:), allocatable gsi
      maximum stomatal conductance (m/s)

    real *8, dimension(:), allocatable vpd2

      rate of decline in stomatal conductance per unit increase in vapor pressure deficit ((m/s)*(1/kPa))

    real *8, dimension(:), allocatable wavp

      rate of decline in radiation use efficiency as a function of vapor pressure deficit (none)
• real *8, dimension(:), allocatable bio_leaf
      fraction of leaf/needle biomass that drops during dormancy (for trees only) (none)

    real *8, dimension(:), allocatable blai

      maximum (potential) leaf area index (none)

    real *8, dimension(:), allocatable cpyld

      fraction of phosphorus in yield (kg P/kg yield)

    real *8, dimension(:), allocatable dlai

      fraction of growing season when leaf area declines (none)

    real *8, dimension(:), allocatable rdmx

     maximum root depth (m)

    real *8, dimension(:), allocatable bio_n1

      1st shape parameter for plant N uptake equation (none)

 real *8, dimension(:), allocatable bio n2

     2nd shape parameter for plant N uptake equation (none)
```

```
    real *8, dimension(:), allocatable bio_p1

      1st shape parameter for plant P uptake equation (none)

    real *8, dimension(:), allocatable bio p2

      2st shape parameter for plant P uptake equation (none)

    real *8, dimension(:), allocatable bm_dieoff

      fraction above ground biomass that dies off at dormancy (fraction)

    real *8, dimension(:), allocatable bmx_trees

  real *8, dimension(:), allocatable ext_coef

    real *8, dimension(:), allocatable rsr1

      initial root to shoot ratio at the beg of growing season
• real *8, dimension(:), allocatable rsr2
      root to shoot ratio at the end of the growing season

    real *8, dimension(:), allocatable pltnfr1

      nitrogen uptake parameter #1: normal fraction of N in crop biomass at emergence (kg N/kg biomass)

    real *8, dimension(:), allocatable pltnfr2

      nitrogen uptake parameter #2: normal fraction of N in crop biomass at 0.5 maturity (kg N/kg biomass)

    real *8, dimension(:), allocatable pltnfr3

      nitrogen uptake parameter #3: normal fraction of N in crop biomass at maturity (kg N/kg biomass)

    real *8, dimension(:), allocatable pltpfr1

      phosphorus uptake parameter #1: normal fraction of P in crop biomass at emergence (kg P/kg biomass)

    real *8, dimension(:), allocatable pltpfr2

      phosphorus uptake parameter #2: normal fraction of P in crop biomass at 0.5 maturity (kg P/kg biomass)

    real *8, dimension(:), allocatable pltpfr3

      phosphorus uptake parameter #3: normal fraction of P in crop biomass at maturity (kg P/kg biomass)

    integer, dimension(:), allocatable idc

      crop/landcover category:
      1 warm season annual legume
      2 cold season annual legume
      3 perennial legume
      4 warm season annual
      5 cold season annual
      6 perennial
      7 trees

    integer, dimension(:), allocatable mat yrs

  real *8, dimension(:), allocatable bactpdb
      concentration of persistent bacteria in manure (fertilizer) (cfu/g manure)

    real *8, dimension(:), allocatable fminn

      fraction of mineral N (NO3 + NH3) (kg minN/kg fert)

    real *8, dimension(:), allocatable forgn

      fraction of organic N (kg orgN/kg fert)

    real *8, dimension(:), allocatable forgp

      fraction of organic P (kg orgP/kg fert)

    real *8, dimension(:), allocatable bactkddb

      bacteria partition coefficient (none):
      1: all bacteria in solution
      0: all bacteria sorbed to soil particles

    real *8, dimension(:), allocatable bactlpdb

      concentration of less persistent bacteria in manure (fertilizer) (cfu/g manure)

    real *8, dimension(:), allocatable fminp

      fraction of mineral P (kg minP/kg fert)
  real *8, dimension(:), allocatable fnh3n
      fraction of NH3-N in mineral N (kg NH3-N/kg minN)
```

character(len=8), dimension(200) fertnm
 name of fertilizer

real *8, dimension(:), allocatable curbden

curb length density in HRU (km/ha)

• real *8, dimension(:), allocatable dirtmx

maximum amount of solids allowed to build up on impervious surfaces (kg/curb km)

• real *8, dimension(:), allocatable fimp

fraction of HRU area that is impervious (both directly and indirectly connected)(fraction)

• real *8, dimension(:), allocatable urbcoef

wash-off coefficient for removal of constituents from an impervious surface (1/mm)

real *8, dimension(:), allocatable thalf

time for the amount of solids on impervious areas to build up to 1/2 the maximum level (days)

real *8, dimension(:), allocatable tnconc

concentration of total nitrogen in suspended solid load from impervious areas (mg N/kg sed)

real *8, dimension(:), allocatable tno3conc

concentration of NO3-N in suspended solid load from impervious areas (mg NO3-N/kg sed)

real *8, dimension(:), allocatable tpconc

concentration of total phosphorus in suspended solid load from impervious areas (mg P/kg sed)

• real *8, dimension(:), allocatable fcimp

fraction of HRU area that is classified as directly connected impervious (fraction)

• real *8, dimension(:), allocatable urbcn2

SCS curve number for moisture condition II in impervious areas (none)

- real *8 sweepeff
- real *8 frt kg
- real *8 pst_dep
- real *8 fr_curb
- real *8, dimension(:), allocatable ranrns hru
- · integer, dimension(:), allocatable itill
- real *8, dimension(:), allocatable deptil

depth of mixing caused by operation (mm)

• real *8, dimension(:), allocatable effmix

mixing efficiency of operation (none)

real *8, dimension(:), allocatable ranrns

random roughness of a given tillage operation (mm)

character(len=8), dimension(550) tillnm

8-character name for the tillage operation

• real *8, dimension(:), allocatable rnum1s

For ICODES equal to (none)

0.1.3.5.9: not used

2: Fraction of flow in channel

4: amount of water transferred (as defined by INUM4S)

7,8,10,11: drainage area in square kilometers associated with the record file.

- real *8, dimension(:), allocatable hyd_dakm
- real *8, dimension(:,:), allocatable varoute
- real *8, dimension(:,:), allocatable shyd
- real *8, dimension(:,:), allocatable vartran
- real *8, dimension(:,:,:), allocatable hhvaroute
- integer, dimension(:), allocatable icodes

```
routing command code (none):
     0 = finish
      1 = subbasin
     2 = route
     3 = routres
      4 = transfer
      5 = add
      6 = rechour
      7 = recmon
     8 = recyear
      9 = save
      10 = recday
      11 = reccnst
      12 = structure
      13 = apex
      14 = saveconc
      15 =
· integer, dimension(:), allocatable ihouts
      For ICODES equal to (none)
      0: not used
      1,2,3,5,7,8,10,11: hydrograph storage location number
      4: departure type (1=reach, 2=reservoir)
     9: hydrograph storage location of data to be printed to event file
      14:hydrograph storage location of data to be printed to saveconc file.
· integer, dimension(:), allocatable inum1s
     For ICODES equal to (none)
     0: not used
      1: subbasin number
     2: reach number
     3: reservoir number
      4: reach or res # flow is diverted from
     5: hydrograph storage location of 1st dataset to be added
      7,8,9,10,11,14: file number.
• integer, dimension(:), allocatable inum2s
     For ICODES equal to (none)
     0,1,7,8,10,11: not used
     2,3: inflow hydrograph storage location
      4: destination type (1=reach, 2=reservoir)
      5: hydrograph storage location of 2nd dataset to be added
      9,14:print frequency (0=daily, 1=hourly)
• integer, dimension(:), allocatable inum3s
      For ICODES equal to (none)
      0,1,2,3,5,7,8,10,11: not used
     4: destination number. Reach or reservoir receiving water
      9: print format (0=normal, fixed format; 1=txt format for AV interface, recday)
· integer, dimension(:), allocatable inum4s
     For ICODES equal to (none)
     0.2.3.5.7.8.9.10.11: not used
      1: GIS code printed to output file (optional)
      4: rule code governing transfer of water (1=fraction transferred out, 2=min volume or flow left, 3=exact amount trans-
      ferred)
• integer, dimension(:), allocatable inum5s

    integer, dimension(:), allocatable inum6s

• integer, dimension(:), allocatable inum7s
· integer, dimension(:), allocatable inum8s
· integer, dimension(:), allocatable subed
• character(len=10), dimension(:), allocatable recmonps

    character(len=10), dimension(:), allocatable recenstps

    character(len=5), dimension(:), allocatable subnum
```

character(len=4), dimension(:), allocatable hruno

- real *8, dimension(:), allocatable grwat_n
- real *8, dimension(:), allocatable grwat_i
- real *8, dimension(:), allocatable grwat_l
- real *8, dimension(:), allocatable grwat_w
- real *8, dimension(:), allocatable grwat d
- real *8, dimension(:), allocatable grwat_s
- real *8, dimension(:), allocatable grwat_spcon
- real *8, dimension(:), allocatable tc_gwat
- real *8, dimension(:), allocatable pot_volmm
- real *8, dimension(:), allocatable pot tilemm
- real *8, dimension(:), allocatable pot_volxmm
- real *8, dimension(:), allocatable pot_fr
- real *8, dimension(:), allocatable pot_tile
- real *8, dimension(:), allocatable pot vol
- real *8, dimension(:), allocatable potsa
- real *8, dimension(:), allocatable pot volx
- real *8, dimension(:), allocatable potflwi
- real *8, dimension(:), allocatable potsedi
- real *8, dimension(:), allocatable wfsh
- real *8, dimension(:), allocatable pot_nsed
- real *8, dimension(:), allocatable pot no3l
- real *8, dimension(:), allocatable newrti
- real *8, dimension(:), allocatable gwno3
- real *8, dimension(:), allocatable pot_sed
- real *8, dimension(:), allocatable pot_no3
- real *8, dimension(:), allocatable fsred
- real *8, dimension(:), allocatable tmpavp
- real *8, dimension(:), allocatable evpot
- real *8, dimension(:), allocatable dis_stream
- real *8, dimension(:), allocatable pot_solpl
- real *8, dimension(:), allocatable **sed_con**
- real *8, dimension(:), allocatable orgn_con
- real *8, dimension(:), allocatable orgp_con
- real *8, dimension(:), allocatable soln_con
- real *8, dimension(:), allocatable solp_con
- real *8, dimension(:), allocatable pot k
- real *8, dimension(:), allocatable n_reduc
- real *8, dimension(:), allocatable n_lag
- real *8, dimension(:), allocatable n In
- real *8, dimension(:), allocatable n_Inco
- · integer, dimension(:), allocatable ioper
- · integer, dimension(:), allocatable ngrwat
- real *8, dimension(:), allocatable filterw
- real *8, dimension(:), allocatable sumix
- real *8, dimension(:), allocatable usle_ls
- real *8, dimension(:), allocatable phuacc
- real *8, dimension(:), allocatable epco
 - plant water uptake compensation factor (0-1)
- real *8, dimension(:), allocatable esco
 - soil evaporation compensation factor (0-1)
- real *8, dimension(:), allocatable slsubbsn
- real *8, dimension(:), allocatable hru_slp
- real *8, dimension(:), allocatable erorgn
- real *8, dimension(:), allocatable erorgp

- real *8, dimension(:), allocatable biomix
- real *8, dimension(:), allocatable pnd_seci
- · real *8, dimension(:), allocatable flowmin
- real *8, dimension(:), allocatable divmax
- real *8, dimension(:), allocatable canmx
- real *8, dimension(:), allocatable usle_p
- real *8, dimension(:), allocatable lat_sed
- real *8, dimension(:), allocatable rch_dakm
- real *8, dimension(:), allocatable pnd_no3s
- real *8, dimension(:), allocatable cn1
- real *8, dimension(:), allocatable cn2
- real *8, dimension(:), allocatable lat_ttime
- real *8, dimension(:), allocatable flowfr
- real *8, dimension(:), allocatable sol_zmx
- · real *8, dimension(:), allocatable tile ttime
- real *8, dimension(:), allocatable slsoil
- real *8, dimension(:), allocatable sed_stl
- real *8, dimension(:), allocatable gwminp
- real *8, dimension(:), allocatable sol_cov
- real *8, dimension(:), allocatable yldanu
- real *8, dimension(:), allocatable pnd solp
- real *8, dimension(:), allocatable pnd_no3
- real *8, dimension(:), allocatable ov_n
- · real *8, dimension(:), allocatable driftco

coefficient for pesticide drift directly onto stream (none)

- real *8, dimension(:), allocatable pnd_orgp
- real *8, dimension(:), allocatable pnd_orgn
- real *8, dimension(:), allocatable cn3
- real *8, dimension(:), allocatable twlpnd
- real *8, dimension(:), allocatable twlwet
- real *8, dimension(:), allocatable sol_sumul
- real *8, dimension(:), allocatable pnd_chla
- real *8, dimension(:), allocatable hru_fr
- real *8, dimension(:), allocatable hru_km

area of HRU in square kilometers (km²)

- real *8, dimension(:), allocatable bio_ms
- real *8, dimension(:), allocatable sol_alb
- real *8, dimension(:), allocatable strsw
- real *8, dimension(:), allocatable pnd_fr
- real *8, dimension(:), allocatable pnd_psa
- real *8, dimension(:), allocatable pnd_pvol
- real *8, dimension(:), allocatable pnd_k
- real *8, dimension(:), allocatable pnd_esa
- · real *8, dimension(:), allocatable pnd_evol
- real *8, dimension(:), allocatable pnd_vol
- real *8, dimension(:), allocatable yldaa
- real *8, dimension(:), allocatable pnd_sed
- real *8, dimension(:), allocatable pnd_nsed
- real *8, dimension(:), allocatable strsa
- real *8, dimension(:), allocatable dep_imp
- real *8, dimension(:), allocatable evpnd
- real *8, dimension(:), allocatable evwet
- real *8, dimension(:), allocatable wet_fr
- real *8, dimension(:), allocatable wet_nsa

- real *8, dimension(:), allocatable wet_nvol
- real *8, dimension(:), allocatable wet_k
- integer, dimension(:), allocatable iwetgw
- integer, dimension(:), allocatable iwetile
- real *8, dimension(:), allocatable wet_mxsa
- real *8, dimension(:), allocatable wet_mxvol
- real *8, dimension(:), allocatable wet_vol
- real *8, dimension(:), allocatable wet_sed
- real *8, dimension(:), allocatable wet_nsed
- real *8, dimension(:), allocatable smx
- real *8, dimension(:), allocatable sci
- real *8, dimension(:), allocatable bp1
- real *8, dimension(:), allocatable bp2
- real *8, dimension(:), allocatable bw1
- real *8, dimension(:), allocatable bw2
- real *8, dimension(:), allocatable bactpg
- real *8, dimension(:), allocatable bactp_plt
- real *8, dimension(:), allocatable bactlp_plt
- real *8, dimension(:), allocatable cnday
- real *8, dimension(:), allocatable bactlpq
- real *8, dimension(:), allocatable auto eff
- real *8, dimension(:), allocatable sol_sw
- real *8, dimension(:), allocatable secciw
- real *8, dimension(:), allocatable bactps
- real *8, dimension(:), allocatable bactlps
- real *8, dimension(:), allocatable tmpav
- real *8, dimension(:), allocatable chlaw
- real *8, dimension(:), allocatable sno_hru
 - amount of water stored as snow (mm H2O)
- real *8, dimension(:), allocatable subp
- real *8, dimension(:), allocatable hru_ra
- real *8, dimension(:), allocatable wet_orgn
- real *8, dimension(:), allocatable tmx
- real *8, dimension(:), allocatable tmn
- real *8, dimension(:), allocatable rsdin
- real *8, dimension(:), allocatable tmp_hi
- real *8, dimension(:), allocatable tmp_lo
- real *8, dimension(:), allocatable rwt
- real *8, dimension(:), allocatable olai
- real *8, dimension(:), allocatable usle k
- real *8, dimension(:), allocatable tconc
- real *8, dimension(:), allocatable hru_rmx
- real *8, dimension(:), allocatable usle_cfac
- real *8, dimension(:), allocatable usle_eifac
- real *8, dimension(:), allocatable anano3
- real *8, dimension(:), allocatable aird
- real *8, dimension(:), allocatable t_ov
- real *8, dimension(:), allocatable sol_sumfc
- real *8, dimension(:), allocatable sol_avpor
- real *8, dimension(:), allocatable usle_mult
- real *8, dimension(:), allocatable wet_orgp
- real *8, dimension(:), allocatable aairr
- real *8, dimension(:), allocatable cht
- real *8, dimension(:), allocatable u10

- real *8, dimension(:), allocatable rhd
- · real *8, dimension(:), allocatable shallirr
- real *8, dimension(:), allocatable deepirr
- real *8, dimension(:), allocatable lai_aamx
- real *8, dimension(:), allocatable ch_l1

longest tributary channel length in subbasin (km)

- real *8, dimension(:), allocatable canstor
- real *8, dimension(:), allocatable ovrlnd
- real *8, dimension(:), allocatable wet_no3
- real *8, dimension(:), allocatable irr_mx
- real *8, dimension(:), allocatable auto_wstr
- real *8, dimension(:), allocatable cfrt_id
- real *8, dimension(:), allocatable cfrt_kg
- real *8, dimension(:), allocatable cpst_id
- real *8, dimension(:), allocatable cpst_kg
- real *8, dimension(:), allocatable irr_asq
- real *8, dimension(:), allocatable irr_eff
- real *8, dimension(:), allocatable irrsq
- real *8, dimension(:), allocatable irrefm
- real *8, dimension(:), allocatable irrsalt
- real *8, dimension(:), allocatable bio eat
- real *8, dimension(:), allocatable bio_trmp
- · integer, dimension(:), allocatable ifrt_freq
- integer, dimension(:), allocatable ipst freq
- integer, dimension(:), allocatable irr_noa
- · integer, dimension(:), allocatable irr_sc
- integer, dimension(:), allocatable irr_no
- integer, dimension(:), allocatable imp_trig
- integer, dimension(:), allocatable fert_days
- integer, dimension(:), allocatable irr_sca
- integer, dimension(:), allocatable pest_days
- integer, dimension(:), allocatable idplt
- integer, dimension(:), allocatable wstrs_id
- real *8, dimension(:,:), allocatable bio_aahv
- real *8, dimension(:), allocatable cumei
- real *8, dimension(:), allocatable cumeira
- real *8, dimension(:), allocatable cumrt
- real *8, dimension(:), allocatable cumrai
- real *8, dimension(:), allocatable wet_solp
- real *8, dimension(:), allocatable wet_no3s
- real *8, dimension(:), allocatable wet_chla
- real *8, dimension(:), allocatable wet_seci
- real *8, dimension(:), allocatable pnd_no3g
- real *8, dimension(:), allocatable pstsol
- real *8, dimension(:), allocatable gwht
- real *8, dimension(:), allocatable delay
- real *8, dimension(:), allocatable gw_q
- real *8, dimension(:), allocatable pnd_solpg
- real *8, dimension(:), allocatable alpha_bf
- real *8, dimension(:), allocatable alpha_bfe
- real *8, dimension(:), allocatable gw_spyld
- real *8, dimension(:), allocatable alpha_bf_d
- real *8, dimension(:), allocatable alpha_bfe_d
- real *8, dimension(:), allocatable gw_qdeep

real *8, dimension(:), allocatable gw_delaye

```
    real *8, dimension(:), allocatable gw_revap

 real *8, dimension(:), allocatable rchrg_dp
• real *8, dimension(:), allocatable anion excl
     fraction of porosity from which anions are excluded

    real *8, dimension(:), allocatable revapmn

  real *8, dimension(:), allocatable rchrg
  real *8, dimension(:), allocatable ffc

    real *8, dimension(:), allocatable bio min

  real *8, dimension(:), allocatable surgsolp
  real *8, dimension(:), allocatable cklsp

    real *8, dimension(:), allocatable deepst

  real *8, dimension(:), allocatable shallst
  real *8, dimension(:), allocatable wet_solpg
 real *8, dimension(:), allocatable rchrq src

    real *8, dimension(:), allocatable wet_no3g

real *8, dimension(:), allocatable sol_avbd
• real *8, dimension(:), allocatable trapeff

    real *8, dimension(:), allocatable gwgmn

• real *8, dimension(:), allocatable tdrain
  real *8, dimension(:), allocatable ppInt

    real *8, dimension(:), allocatable snotmp

• real *8, dimension(:), allocatable gdrain
     drain tile lag time (hours)
• real *8, dimension(:), allocatable ddrain
 real *8, dimension(:), allocatable sol_crk

    real *8, dimension(:), allocatable dayl

  real *8, dimension(:), allocatable brt
• real *8, dimension(:), allocatable sstmaxd
     static maximum depressional storage; read from .sdr (mm)

 real *8, dimension(:), allocatable re

     effective radius of drains (mm)

    real *8, dimension(:), allocatable sdrain

     distance between two drain tubes or tiles (mm)
• real *8, dimension(:), allocatable ddrain_hru
  real *8, dimension(:), allocatable drain co
     drainage coefficient (mm/day)

    real *8, dimension(:), allocatable latksatf

     multiplication factor to determine conk(j1,j) from sol_k(j1,j) for HRU (none)

    real *8, dimension(:), allocatable pc

     pump capacity (default pump capacity = 1.042mm/hr or 25mm/day) (mm/hr)

    real *8, dimension(:), allocatable stmaxd

· real *8, dimension(:), allocatable twash
  real *8, dimension(:), allocatable rnd2
• real *8, dimension(:), allocatable rnd3

    real *8, dimension(:), allocatable sol_cnsw

  real *8, dimension(:), allocatable doxq

    real *8, dimension(:), allocatable rnd8

• real *8, dimension(:), allocatable rnd9
  real *8, dimension(:), allocatable percn

    real *8, dimension(:), allocatable sol_sumwp

 real *8, dimension(:), allocatable tauton

    real *8, dimension(:), allocatable tautop
```

- real *8, dimension(:), allocatable cbodu
- real *8, dimension(:), allocatable chl_a
- · real *8, dimension(:), allocatable qdr
- real *8, dimension(:), allocatable tfertn
- real *8, dimension(:), allocatable tfertp
- real *8, dimension(:), allocatable tgrazn
- real *8, dimension(:), allocatable tgrazp
- real *8, dimension(:), allocatable latno3
- real *8, dimension(:), allocatable latq
- real *8, dimension(:), allocatable minpgw
- real *8, dimension(:), allocatable no3gw
- real *8, dimension(:), allocatable npInt
- real *8, dimension(:), allocatable tileq
- real *8, dimension(:), allocatable tileno3
- real *8, dimension(:), allocatable sedminpa
- real *8, dimension(:), allocatable sedminps
- real *8, dimension(:), allocatable sedorgn
- real *8, dimension(:), allocatable sedorgp
- real *8, dimension(:), allocatable sedyld
- real *8, dimension(:), allocatable sepbtm
- real *8, dimension(:), allocatable strsn
- real *8, dimension(:), allocatable strsp
- real *8, dimension(:), allocatable strstmp
- real *8, dimension(:), allocatable surfq
- real *8, dimension(:), allocatable surqno3
- real *8, dimension(:), allocatable tcfrtn
- real *8, dimension(:), allocatable tcfrtp
- real *8, dimension(:), allocatable hru_ha
- real *8, dimension(:), allocatable hru_dafr
- real *8, dimension(:), allocatable drydep_no3
- real *8, dimension(:), allocatable drydep_nh4
- real *8, dimension(:), allocatable phubase
- real *8, dimension(:), allocatable bio_yrms
- real *8, dimension(:), allocatable hvstiadj
- real *8, dimension(:), allocatable laimxfr
- real *8, dimension(:), allocatable laiday
- real *8, dimension(:), allocatable chlap
- real *8, dimension(:), allocatable pnd_psed
- real *8, dimension(:), allocatable wet_psed
- real *8, dimension(:), allocatable seccip
- real *8, dimension(:), allocatable plantn
- real *8, dimension(:), allocatable plt_et
- real *8, dimension(:), allocatable plt_pet
- real *8, dimension(:), allocatable plantp
- real *8, dimension(:), allocatable bio_aams
- real *8, dimension(:), allocatable bio_aamx
- real *8, dimension(:), allocatable lai_yrmx
- real *8, dimension(:), allocatable dormhr
- real *8, dimension(:), allocatable lat_pst
- real *8, dimension(:), allocatable orig_snohru
- real *8, dimension(:), allocatable orig potvol
- real *8, dimension(:), allocatable fld_fr
- real *8, dimension(:), allocatable orig_alai
- real *8, dimension(:), allocatable orig_bioms
- real *8, dimension(:), allocatable pltfr_n

- real *8, dimension(:), allocatable orig phuacc
- real *8, dimension(:), allocatable orig sumix
- real *8, dimension(:), allocatable pltfr_p
- real *8, dimension(:), allocatable orig phu
- real *8, dimension(:), allocatable phu_plt
- real *8, dimension(:), allocatable orig_shallst
- real *8, dimension(:), allocatable orig deepst
- real *8, dimension(:), allocatable orig_pndvol
- real *8, dimension(:), allocatable orig pndsed
- real *8, dimension(:), allocatable rip_fr
- real *8, dimension(:), allocatable orig_pndno3
- real *8, dimension(:), allocatable orig_pndsolp
- real *8, dimension(:), allocatable orig_pndorgn
- real *8, dimension(:), allocatable orig_pndorgp
- real *8, dimension(:), allocatable orig_wetvol
- real *8, dimension(:), allocatable orig_wetsed
- real *8, dimension(:), allocatable orig_wetno3
- real *8, dimension(:), allocatable orig wetsolp
- real *8, dimension(:), allocatable orig wetorgn
- real *8, dimension(:), allocatable orig wetorgp
- real *8, dimension(:), allocatable orig_solcov
- real *8, dimension(:), allocatable **orig solsw**
- real *8, dimension(:), allocatable orig potno3
- real *8, dimension(:), allocatable orig_potsed
- real *8, dimension(:), allocatable wtab
- real *8, dimension(:), allocatable wtab_mn
- real *8, dimension(:), allocatable wtab mx
- real *8, dimension(:), allocatable shallst n
- real *8, dimension(:), allocatable gw nloss
- real *8, dimension(:), allocatable rchrg n
- real *8, dimension(:), allocatable det_san
- real *8, dimension(:), allocatable det_sil
- real *8, dimension(:), allocatable det_cla
- real *8, dimension(:), allocatable det_sag
- real *8, dimension(:), allocatable det_lag
- real *8, dimension(:), allocatable tnylda
- real *8, dimension(:), allocatable afrt_surface
- real *8 frt surface
- real *8, dimension(:), allocatable auto_nyr
- real *8, dimension(:), allocatable auto napp
- real *8, dimension(:), allocatable manure kg
- real *8, dimension(:), allocatable auto_nstrs
- real *8, dimension(:,:), allocatable rcn_mo
- real *8, dimension(:,:), allocatable rammo_mo
- real *8, dimension(:,:), allocatable drydep no3 mo
- real *8, dimension(:,:), allocatable drydep nh4 mo
- real *8, dimension(:), allocatable rcn d
- real *8, dimension(:), allocatable rammo d
- real *8, dimension(:), allocatable drydep_no3_d
- real *8, dimension(:), allocatable drydep_nh4_d
- real *8, dimension(:,:), allocatable yldn
- real *8, dimension(:,:), allocatable gwati
- real *8, dimension(:,:), allocatable gwatn
- real *8, dimension(:.:), allocatable qwatl
- real *8, dimension(:,:), allocatable gwatw

 real *8, dimension(:,:), allocatable gwatd real *8, dimension(:,:), allocatable gwatveg real *8, dimension(:,:), allocatable gwata real *8, dimension(:,:), allocatable gwats real *8, dimension(:,:), allocatable qwatspcon real *8, dimension(:,:), allocatable rfqeo_30d real *8, dimension(:,:), allocatable eo_30d real *8, dimension(:,:), allocatable wgncur real *8, dimension(:,:), allocatable wgnold real *8. dimension(:::), allocatable wrt real *8, dimension(:,:), allocatable **psetlp** real *8, dimension(:,:), allocatable pst_enr pesticide enrichment ratio (none) • real *8, dimension(:,:), allocatable zdb real *8, dimension(:,:), allocatable pst_surq real *8, dimension(:,:), allocatable plt_pst pesticide on plant foliage (kg/ha) • real *8, dimension(:,:), allocatable pst_sed real *8, dimension(:,:), allocatable psetlw real *8, dimension(:,:), allocatable pcpband real *8, dimension(:,:), allocatable wupnd real *8, dimension(:,:), allocatable tavband real *8, dimension(:,:), allocatable phi real *8, dimension(:,:), allocatable wat phi • real *8, dimension(:,:), allocatable snoeb initial snow water content in elevation band (mm H2O) real *8, dimension(:,:), allocatable wushal real *8, dimension(:,:), allocatable wudeep real *8, dimension(:,:), allocatable tmnband real *8, dimension(:,:), allocatable nsetlw real *8, dimension(:,:), allocatable snotmpeb real *8, dimension(:,:), allocatable bss real *8, dimension(:,:), allocatable surf bs real *8, dimension(:,:), allocatable tmxband • real *8, dimension(:,:), allocatable nsetlp real *8, dimension(:,:), allocatable rainsub real *8, dimension(:,:), allocatable frad real *8, dimension(:), allocatable rstpbsb real *8, dimension(:,:), allocatable orig_snoeb real *8, dimension(:,:), allocatable orig pltpst real *8, dimension(:,:), allocatable terr_p real *8, dimension(:,:), allocatable terr_cn real *8, dimension(:,:), allocatable terr sl real *8, dimension(:,:), allocatable drain_d real *8, dimension(:,:), allocatable drain_t real *8, dimension(:,:), allocatable drain_g real *8, dimension(:,:), allocatable drain_idep

real *8, dimension(:,:), allocatable cont cn real *8, dimension(:,:), allocatable cont_p • real *8, dimension(:,:), allocatable filt_w real *8, dimension(:,:), allocatable strip n real *8, dimension(:,:), allocatable strip_cn real *8, dimension(:,:), allocatable strip_c real *8, dimension(:,:), allocatable strip_p

- real *8, dimension(:,:), allocatable fire_cn
- real *8, dimension(:,:), allocatable cropno_upd
- real *8, dimension(:,:), allocatable hi_upd
- real *8, dimension(:,:), allocatable laimx_upd
- real *8, dimension(:,:,:), allocatable pst_lag
- real *8, dimension(:,:,:), allocatable phug
- integer, dimension(:), allocatable hrupest

pesticide use flag (none)

0: no pesticides used in HRU

1: pesticides used in HRU

- integer, dimension(:), allocatable nrelease
- integer, dimension(:), allocatable swtrg
- · integer, dimension(:), allocatable nro
- integer, dimension(:), allocatable nrot
- integer, dimension(:), allocatable nfert
- integer, dimension(:), allocatable igro
- integer, dimension(:), allocatable nair
- · integer, dimension(:), allocatable ipnd1
- integer, dimension(:), allocatable ipnd2
- · integer, dimension(:), allocatable nirr
- · integer, dimension(:), allocatable iflod1
- integer, dimension(:), allocatable iflod2
- · integer, dimension(:), allocatable ndtarg
- integer, dimension(:), allocatable iafrttyp
- integer, dimension(:), allocatable nstress
- integer, dimension(:), allocatable igrotree
- · integer, dimension(:), allocatable grz days
- integer, dimension(:), allocatable nmgt
- integer, dimension(:), allocatable icr
- integer, dimension(:), allocatable ncut
- integer, dimension(:), allocatable **nsweep**
- · integer, dimension(:), allocatable nafert
- integer, dimension(:), allocatable irn
- integer, dimension(:), allocatable irrno
- integer, dimension(:), allocatable sol_nly
- integer, dimension(:), allocatable npcp
- integer, dimension(:), allocatable igrz
- integer, dimension(:), allocatable **ndeat**
- integer, dimension(:), allocatable ngr
- integer, dimension(:), allocatable ncf
- integer, dimension(:), allocatable hru_sub

subbasin in which HRU is located (none)

- integer, dimension(:), allocatable idorm
- integer, dimension(:), allocatable urblu
- · integer, dimension(:), allocatable Idrain
- · integer, dimension(:), allocatable hru_seq
- integer, dimension(:), allocatable iurban
- integer, dimension(:), allocatable iday_fert
- integer, dimension(:), allocatable icfrt
 integer, dimension(:), allocatable ifld
 - number of HRU (in subbasin) that is a floodplain (none)

integer, dimension(:), allocatable irip

number of HRU (in subbasin) that is a riparian zone (none)

• integer, dimension(:), allocatable ndcfrt

- · integer, dimension(:), allocatable hrugis
- integer, dimension(:), allocatable orig_igro
- integer, dimension(:), allocatable ntil
- integer, dimension(:), allocatable irrsc
- integer, dimension(:), allocatable iwatable
- integer, dimension(:), allocatable curyr_mat
- integer, dimension(:), allocatable ncpest
- integer, dimension(:), allocatable icpst
- integer, dimension(:), allocatable ndcpst
- integer, dimension(:), allocatable iday_pest
- integer, dimension(:), allocatable irr_flag
- integer, dimension(:), allocatable irra_flag
- integer, dimension(:,:), allocatable rndseed

random number generator seed. The seeds in the array are used to generate random numbers for the following purposes:

- (1) wet/dry day probability
- (2) solar radiation
- (3) precipitation
- (4) USLE rainfall erosion index
- (5) wind speed
- (6) 0.5 hr rainfall fraction
- (7) relative humidity
- (8) maximum temperature
- (9) minimum temperature
- (10) generate new random numbers
- integer, dimension(:,:), allocatable iterr
- integer, dimension(:,:), allocatable iyterr
- integer, dimension(:,:), allocatable itdrain
- integer, dimension(:,:), allocatable iydrain
- integer, dimension(:,:), allocatable ncrops
- · integer, dimension(:), allocatable manure_id
- integer, dimension(:,:), allocatable mgt_sdr
- integer, dimension(:,:), allocatable idplrot
 integer, dimension(:,:), allocatable icont
- integer, dimension(:,:), allocatable iycont
- integer, dimension(:,:), allocatable ifilt
- integer, dimension(:,:), allocatable iyfilt
- integer, dimension(:,:), allocatable istrip
- integer, dimension(:,:), allocatable iystrip
- integer, dimension(:,:), allocatable iopday
- integer, dimension(:,:), allocatable iopyr
- integer, dimension(:,:), allocatable mgt_ops
- real *8, dimension(:), allocatable wshd_pstap
- real *8, dimension(:), allocatable wshd_pstdg
- integer, dimension(12) ndmo
- integer, dimension(:), allocatable npno

array of unique pesticides used in watershed (none)

- integer, dimension(:), allocatable mcrhru
- character(len=13), dimension(18) rfile

rainfall file names (.pcp)

• character(len=13), dimension(18) tfile

temperature file names (.tmp)

• character(len=4), dimension(1000) urbname

name of urban land use

• character(len=1), dimension(:), allocatable hydgrp

- character(len=1), dimension(:), allocatable kirr
- character(len=16), dimension(:), allocatable snam
- character(len=17), dimension(300) pname

name of pesticide/toxin adding gtile to output.hru write 3/2/2010 gsm increased heds(70) to heds(71)

- character(len=13), dimension(79) heds
- character(len=13), dimension(24) hedb
- character(len=13), dimension(46) hedr
- character(len=13), dimension(41) hedrsv
- character(len=13), dimension(40) hedwtr
- character(len=4), dimension(60) title

description lines in file.cio (1st 3 lines)

character(len=4), dimension(5000) cpnm

four character code to represent crop name

- character(len=17), dimension(50) fname
- real *8, dimension(:,:,:), allocatable flomon
- real *8, dimension(:,:,:), allocatable solpstmon
- real *8, dimension(:,:,:), allocatable srbpstmon
- real *8, dimension(:,:,:), allocatable sedmon
- real *8, dimension(:,:,:), allocatable orgnmon
- real *8, dimension(:,:,:), allocatable orgpmon
- real *8, dimension(:,:,:), allocatable no3mon
- real *8, dimension(:,:,:), allocatable minpmon
- real *8, dimension(:,:,:), allocatable nh3mon
- real *8, dimension(:,:,:), allocatable no2mon
- real *8, dimension(:,:,:), allocatable bactpmon
- real *8, dimension(:,:,:), allocatable bactlpmon
- real *8, dimension(:,:,:), allocatable cmtl1mon
- real *8, dimension(:,:,:), allocatable cmtl2mon
- real *8, dimension(:,:,:), allocatable cmtl3mon
- real *8, dimension(:,::), allocatable chlamon
- real *8, dimension(:,:,:), allocatable disoxmon
- real *8, dimension(:,:,:), allocatable cbodmon
- real *8, dimension(:,:), allocatable floyr
- real *8, dimension(:,:), allocatable sedyr
- real *8, dimension(:,:), allocatable orgnyr
- real *8, dimension(:,:), allocatable orgpyr
- real *8, dimension(:,:), allocatable no3yr
- real *8, dimension(:,:), allocatable minpyr
- real *8, dimension(:,:), allocatable nh3yr
- real *8, dimension(:,:), allocatable no2yr
- real *8, dimension(:,:), allocatable bactpyr
- real *8, dimension(:,:), allocatable bactlpyr
- real *8, dimension(:,:), allocatable cmtl1yr
- real *8, dimension(:,:), allocatable cmtl2yr
- real *8, dimension(:,:), allocatable cmtl3yr
- real *8, dimension(:,:), allocatable chlayr
- real *8, dimension(:,:), allocatable disoxyr
- real *8, dimension(:,:), allocatable cbodyr
- real *8, dimension(:,:), allocatable solpstyr
- real *8, dimension(:,:), allocatable srbpstyr
- real *8, dimension(:,:), allocatable sol_mc
- real *8, dimension(:,:), allocatable sol_mn
- real *8, dimension(:,:), allocatable sol_mp
- real *8, dimension(:), allocatable flocnst

- real *8, dimension(:), allocatable sedcnst
- real *8, dimension(:), allocatable orgncnst
- real *8, dimension(:), allocatable orgpcnst
- real *8, dimension(:), allocatable no3cnst
- real *8, dimension(:), allocatable minpcnst
- real *8, dimension(:), allocatable nh3cnst
- real *8, dimension(:), allocatable no2cnst
- real *8, dimension(:), allocatable bactpcnst
- real *8, dimension(:), allocatable cmtl1cnst
- real *8, dimension(:), allocatable cmtl2cnst
- real *8, dimension(:), allocatable bactlpcnst
- real *8, dimension(:), allocatable cmtl3cnst
- real *8, dimension(:), allocatable chlacnst
- real *8, dimension(:), allocatable disoxcnst
- real *8, dimension(:), allocatable cbodcnst
- real *8, dimension(:), allocatable solpstcnst
- real *8, dimension(:), allocatable srbpstcnst
- integer nstep

max number of time steps per day

integer idt

length of time step used to report precipitation data for sub-daily modeling (minutes)

- real *8, dimension(:), allocatable hrtwtr
- real *8, dimension(:), allocatable hhstor
- real *8, dimension(:), allocatable hdepth
- real *8, dimension(:), allocatable hsdti
- real *8, dimension(:), allocatable hrchwtr
- real *8, dimension(:), allocatable halgae
- real *8, dimension(:), allocatable horgn
- real *8, dimension(:), allocatable hnh4
- real *8, dimension(:), allocatable hno2
 real *8, dimension(:), allocatable hno3
- real *8, dimension(:), allocatable horgp
- real *8, dimension(:), allocatable hsolp
- real *8, dimension(:), allocatable hbod
- real *8, dimension(:), allocatable hdisox
- real *8, dimension(:), allocatable hchla
- · real *8, dimension(:), allocatable hsedyld
- real *8, dimension(:), allocatable hsedst
- real *8, dimension(:), allocatable **hharea**
- real *8, dimension(:), allocatable hsolpst
- real *8, dimension(:), allocatable hsorpst
- real *8, dimension(:), allocatable hhqday
 real *8, dimension(:), allocatable precipdt
- wast (0, dimension(t), allocately betimes
- real *8, dimension(:), allocatable hhtime
- real *8, dimension(:), allocatable hbactp
- real *8, dimension(:), allocatable hbactlp
- integer, dimension(10) ivar_orig
- real *8, dimension(10) rvar_orig
- integer nsave

number of save commands in .fig file

- · integer nauto
- integer iatmodep
- real *8, dimension(:), allocatable wattemp
- real *8, dimension(:), allocatable lkpst_mass

```
    real *8, dimension(:), allocatable lkspst_mass
    real *8, dimension(:), allocatable vel_chan
    real *8, dimension(:), allocatable vfscon
    real *8, dimension(:), allocatable vfsratio
```

- real +8, dimension(:), allocatable **vfsch**
- real *8, dimension(:), allocatable vfsi
- real *8, dimension(:,:), allocatable filter i
- real *8, dimension(:,:), allocatable filter_ratio
- real *8, dimension(:,:), allocatable filter con
- real *8, dimension(:,:), allocatable filter_ch
- real *8, dimension(:,:), allocatable sol_n
- · integer cswat
 - = 0 Static soil carbon (old mineralization routines)
 - = 1 C-FARM one carbon pool model
 - = 2 Century model
- real *8, dimension(:,:), allocatable sol_bdp
- real *8, dimension(:,:), allocatable tillagef
- real *8, dimension(:), allocatable rtfr
- real *8, dimension(:), allocatable stsol_rd
- integer urban_flag
- · integer dorm flag
- real *8 bf_flg
- real *8 iabstr
- real *8, dimension(:), allocatable ubnrunoff
- real *8, dimension(:), allocatable ubntss
- real *8, dimension(:,:), allocatable sub_ubnrunoff
- real *8, dimension(:,:), allocatable sub_ubntss
- real *8, dimension(:,:), allocatable ovrlnd_dt
- real *8, dimension(:,:,:), allocatable hhsurf_bs
- integer iuh

unit hydrograph method: 1=triangular UH; 2=gamma funtion UH;

integer sed_ch

channel routing for HOURLY; 0=Bagnold; 2=Brownlie; 3=Yang;

real *8 eros_expo

an exponent in the overland flow erosion equation ranges 1.5-3.0

real *8 eros_spl

coefficient of splash erosion varing 0.9-3.1

real *8 rill_mult

Multiplier to USLE_K for soil susceptible to rill erosion, range 0.5-2.0.

- real *8 sedprev
- real *8 c_factor
- real *8 ch_d50

median particle diameter of channel bed (mm)

real *8 sig_g

geometric standard deviation of particle sizes for the main channel. Mean air temperature at which precipitation is equally likely to be rain as snow/freezing rain.

real *8 uhalpha

alpha coefficient for estimating unit hydrograph using a gamma function (*.bsn)

- real *8 abstinit
- real *8 abstmax
- real *8, dimension(:,:), allocatable hhsedy
- real *8, dimension(:,:), allocatable sub_subp_dt
- real *8, dimension(:,:), allocatable sub hhsedy
- real *8, dimension(:,:), allocatable sub_atmp

- real *8, dimension(:), allocatable rhy
- real *8, dimension(:), allocatable init abstrc
- real *8, dimension(:), allocatable dratio
- real *8, dimension(:), allocatable hrtevp
- real *8, dimension(:), allocatable hrttlc
- real *8, dimension(:,:,:), allocatable rchhr
- real *8, dimension(:), allocatable hhresflwi
- real *8, dimension(:), allocatable hhresflwo
- real *8, dimension(:), allocatable hhressedi
- real *8, dimension(:), allocatable hhressedo
- character(len=4), dimension(:), allocatable lu_nodrain
- · integer, dimension(:), allocatable bmpdrain
- real *8, dimension(:), allocatable sub_cn2
- real *8, dimension(:), allocatable sub ha urb
- real *8, dimension(:), allocatable bmp_recharge
- real *8, dimension(:), allocatable sub_ha_imp
- real *8, dimension(:), allocatable subdr_km
- real *8, dimension(:), allocatable subdr_ickm
- real *8, dimension(:,:), allocatable sf_im
- real *8, dimension(:,:), allocatable sf_iy
- real *8, dimension(:,:), allocatable sp_sa
- real *8, dimension(:,:), allocatable sp pvol
- real *8, dimension(:,:), allocatable sp pd
- real *8, dimension(:,:), allocatable sp_sedi
- roal to, aminoriolom(1,1), anobatable op_coal
- real *8, dimension(:,:), allocatable sp_sede
- real *8, dimension(:,:), allocatable ft_sa
- real *8, dimension(:,:), allocatable ft_fsa
- real *8, dimension(:,:), allocatable ft_dep
- real *8, dimension(:,:), allocatable **ft_h**
- real *8, dimension(:,:), allocatable ft_pd
- real *8, dimension(:,:), allocatable ft_k
- real *8, dimension(:,:), allocatable ft_dp
 real *8, dimension(:,:), allocatable ft_dc
- real *8, dimension(:,:), allocatable ft por
- real *8, dimension(:,:), allocatable tss_den
- real *8, dimension(:,:), allocatable ft alp
- real *8, dimension(:,:), allocatable sf_fr
- real *8, dimension(:,:), allocatable sp_qi
- real *8, dimension(:,:), allocatable sp_k
- real *8, dimension(:,:), allocatable ft_qpnd
- real *8, dimension(:,:), allocatable sp dp
- real *8, dimension(:,:), allocatable ft_qsw
- real *8, dimension(:,:), allocatable ft_qin
- real *8, dimension(:,:), allocatable ft_qout
- real *8, dimension(:,:), allocatable ft_sedpnd
- real *8, dimension(:,:), allocatable sp_bpw
- real *8, dimension(:,:), allocatable ft_bpw
- real *8, dimension(:,:), allocatable ft_sed_cumul
- real *8, dimension(:,:), allocatable sp_sed_cumul
- · integer, dimension(:), allocatable num_sf
- integer, dimension(:,:), allocatable sf_typ
- integer, dimension(:,:), allocatable sf_dim
- integer, dimension(:,:), allocatable ft_qfg
- integer, dimension(:,:), allocatable sp_qfg
- integer, dimension(:,:), allocatable sf_ptp

- integer, dimension(:,:), allocatable ft_fc
- real *8 sfsedmean
- real *8 sfsedstdev
- · integer, dimension(:), allocatable dtp subnum
- integer, dimension(:), allocatable dtp_imo
- integer, dimension(:), allocatable dtp_iyr
- integer, dimension(:), allocatable dtp numweir
- integer, dimension(:), allocatable dtp_numstage
- · integer, dimension(:), allocatable dtp stagdis
- integer, dimension(:), allocatable dtp_reltype
- integer, dimension(:), allocatable dtp onoff
- real *8, dimension(:), allocatable cf
- real *8, dimension(:), allocatable cfh
- real *8, dimension(:), allocatable cfdec
- real *8, dimension(:), allocatable lat_orgn
- real *8, dimension(:), allocatable lat_orgp
- integer, dimension(:,:), allocatable dtp_weirtype
- integer, dimension(:,:), allocatable dtp weirdim
- real *8, dimension(:), allocatable dtp_evrsv
- real *8, dimension(:), allocatable dtp inflvol
- real *8, dimension(:), allocatable dtp_totwrwid
- real *8, dimension(:), allocatable dtp lwratio
- real *8, dimension(:), allocatable dtp wdep
- real *8, dimension(:), allocatable dtp_totdep
- real *8, dimension(:), allocatable dtp watdepact
- real *8, dimension(:), allocatable dtp_outflow
- real *8, dimension(:), allocatable dtp totrel
- real *8, dimension(:), allocatable dtp backoff
- real *8, dimension(:), allocatable dtp seep sa
- real *8, dimension(:), allocatable dtp_evap_sa
- real *8, dimension(:), allocatable dtp_pet_day
- real *8, dimension(:), allocatable dtp_pcpvol
- real *8, dimension(:), allocatable **dtp_seepvol**
- real *8, dimension(:), allocatable dtp_evapvol
- real *8, dimension(:), allocatable dtp_flowin
- real *8, dimension(:), allocatable dtp_backup_length
- real *8, dimension(:), allocatable dtp_intcept
- real *8, dimension(:), allocatable dtp_expont
- real *8, dimension(:), allocatable dtp_coef1
- real *8, dimension(:), allocatable dtp_coef2
- real *8, dimension(:), allocatable dtp coef3
- real *8, dimension(:), allocatable dtp_dummy1
- real *8, dimension(:), allocatable dtp_dummy2
- real *8, dimension(:), allocatable dtp_dummy3
- real *8, dimension(:), allocatable dtp ivol
- real *8, dimension(:), allocatable dtp ised
- integer, dimension(:,:), allocatable so res flag
- integer, dimension(:,:), allocatable ro bmp flag
- real *8, dimension(:,:), allocatable sol_watp
- real *8, dimension(:,:), allocatable sol_solp_pre
- real *8, dimension(:,:), allocatable psp store
- real *8, dimension(:,:), allocatable ssp store
- real *8, dimension(:,:), allocatable so_res
- real *8, dimension(:,:), allocatable sol cal
- real *8, dimension(:,:), allocatable sol_ph

- integer sol_p_model
- integer, dimension(:,:), allocatable a_days
- integer, dimension(:,:), allocatable b_days
- real *8, dimension(:), allocatable harv_min
- real *8, dimension(:), allocatable fstap
- real *8, dimension(:), allocatable min_res
- real *8, dimension(:,:), allocatable ro_bmp_flo
- real *8, dimension(:,:), allocatable ro_bmp_sed
- real *8, dimension(:,:), allocatable ro_bmp_bac
- real *8, dimension(:,:), allocatable ro_bmp_pp
- real *8, dimension(:,:), allocatable ro_bmp_sp
- real *8, dimension(:,:), allocatable ro bmp pn
- real *8, dimension(:,:), allocatable ro_bmp_sn
- real *8, dimension(:,:), allocatable ro bmp flos
- real *8, dimension(:,:), allocatable ro_bmp_seds
- real *8, dimension(:,:), allocatable ro bmp bacs
- real *8, dimension(:,:), allocatable ro_bmp_pps
- real *8, dimension(:,:), allocatable ro bmp sps
- real *8, dimension(:,:), allocatable ro bmp pns
- real *8, dimension(:,:), allocatable ro_bmp_sns
- real *8, dimension(:,:), allocatable ro_bmp_flot
- real *8, dimension(:,:), allocatable ro bmp sedt
- real *8, dimension(:,:), allocatable ro bmp bact
- real *8, dimension(:,:), allocatable ro_bmp_ppt
- real *8, dimension(:,:), allocatable ro_bmp_spt
- real *8, dimension(:,:), allocatable ro_bmp_pnt
- real *8, dimension(:,:), allocatable ro_bmp_snt
- real *8, dimension(:), allocatable bmp_flo
- real *8, dimension(:), allocatable bmp sed
- real *8, dimension(:), allocatable bmp_bac
- real *8, dimension(:), allocatable bmp_pp
- real *8, dimension(:), allocatable bmp_sp
- real *8, dimension(:), allocatable bmp_pn
- real *8, dimension(:), allocatable bmp_sn
- real *8, dimension(:), allocatable bmp_flag
- real *8, dimension(:), allocatable bmp_flos
- real *8, dimension(:), allocatable bmp_seds
- real *8, dimension(:), allocatable bmp_bacs
- real *8, dimension(:), allocatable bmp_pps
- real *8, dimension(:), allocatable bmp_sps
- real *8, dimension(:), allocatable bmp pns
- real *8, dimension(:), allocatable bmp_sns
- real *8, dimension(:), allocatable bmp flot
- real *8, dimension(:), allocatable bmp_sedt
- real *8, dimension(:), allocatable bmp bact
- real *8, dimension(:), allocatable bmp ppt
- real *8, dimension(:), allocatable bmp_spt
- real *8, dimension(:), allocatable bmp_pnt
- real *8, dimension(:), allocatable bmp_snt
- real *8, dimension(:,:), allocatable dtp_wdratio
- real *8, dimension(:,:), allocatable dtp_depweir
- real *8, dimension(:,:), allocatable dtp_diaweir
- real *8, dimension(:,:), allocatable dtp_retperd
- real *8, dimension(:,:), allocatable dtp_pcpret
- real *8, dimension(:,:), allocatable dtp_cdis

- real *8, dimension(:,:), allocatable dtp_flowrate
- real *8, dimension(:,:), allocatable dtp wrwid
- real *8, dimension(:,:), allocatable dtp_addon
- real *8, dimension(:), allocatable ri subkm
- real *8, dimension(:), allocatable ri_totpvol
- real *8, dimension(:), allocatable irmmdt
- real *8, dimension(:,:), allocatable ri_sed
- real *8, dimension(:,:), allocatable ri_fr
- real *8, dimension(:,:), allocatable ri dim
- real *8, dimension(:,:), allocatable ri_im
- real *8, dimension(:,:), allocatable ri_iy
- real *8, dimension(:,:), allocatable ri_sa
- real *8, dimension(:,:), allocatable ri_vol
- real *8, dimension(:,:), allocatable ri_qi
- real *8, dimension(:,:), allocatable ri_k
- real *8, dimension(:,:), allocatable ri_dd
- real *8, dimension(:,:), allocatable ri_evrsv
- real *8, dimension(:,:), allocatable ri dep
- real *8, dimension(:,:), allocatable ri_ndt
- real *8, dimension(:,:), allocatable ri_pmpvol
- real *8, dimension(:,:), allocatable ri_sed_cumul
- real *8, dimension(:,:), allocatable hrnopcp
- real *8, dimension(:,:), allocatable ri_qloss
- real *8, dimension(:,:), allocatable ri_pumpv
- real *8, dimension(:,:), allocatable ri_sedi
- character(len=4), dimension(:,:), allocatable ri_nirr
- integer, dimension(:), allocatable num ri
- integer, dimension(:), allocatable ri_luflg
- integer, dimension(:), allocatable num_noirr
- integer, dimension(:), allocatable wtp_subnum
- · integer, dimension(:), allocatable wtp_onoff
- integer, dimension(:), allocatable wtp_imo
- integer, dimension(:), allocatable wtp_iyr
- integer, dimension(:), allocatable **wtp_dim**
- integer, dimension(:), allocatable wtp_stagdis
- integer, dimension(:), allocatable wtp_sdtype
- real *8, dimension(:), allocatable wtp_pvol
- real *8, dimension(:), allocatable wtp_pdepth
- real *8, dimension(:), allocatable wtp_sdslope
- real *8, dimension(:), allocatable wtp lenwdth
- real *8, dimension(:), allocatable wtp extdepth
- real *8, dimension(:), allocatable wtp_hydeff
- real *8, dimension(:), allocatable wtp_evrsv
- real *8, dimension(:), allocatable wtp_sdintc
- real *8, dimension(:), allocatable wtp sdexp
- real *8, dimension(:), allocatable wtp sdc1
- real *8, dimension(:), allocatable wtp_sdc2
- real *8, dimension(:), allocatable wtp_sdc3
- real *8, dimension(:), allocatable wtp_pdia
- real *8, dimension(:), allocatable wtp_plen
- real *8, dimension(:), allocatable wtp_pmann
- real *8, dimension(:), allocatable wtp_ploss
- real *8, dimension(:), allocatable wtp_k
- real *8, dimension(:), allocatable wtp_dp
- real *8, dimension(:), allocatable wtp_sedi

- real *8, dimension(:), allocatable wtp_sede
- real *8, dimension(:), allocatable wtp_qi
- real *8 bio init
- real *8 lai_init
- real *8 cnop
- real *8 hi ovr
- · real *8 harveff
- real *8 frac_harvk
- real *8 lid_vgcl
- real *8 lid_vgcm
- · real *8 lid qsurf total
- real *8 lid farea sum
- real *8, dimension(:,:), allocatable lid_cuminf_last
- real *8, dimension(:,:), allocatable lid sw last
- real *8, dimension(:,:), allocatable interval_last
- real *8, dimension(:.:), allocatable lid f last
- real *8, dimension(:,:), allocatable lid_cumr_last
- real *8, dimension(:,:), allocatable lid str_last
- real *8, dimension(:,:), allocatable lid_farea
- real *8, dimension(:,:), allocatable lid_qsurf
- real *8, dimension(:,:), allocatable lid_sw_add
- real *8, dimension(:,:), allocatable lid cumpperc last
- real *8, dimension(:,:), allocatable lid cumirr last
- real *8, dimension(:,:), allocatable lid_excum_last
- integer, dimension(:,:), allocatable gr_onoff
- integer, dimension(:,:), allocatable gr_imo
- integer, dimension(:,:), allocatable gr_iyr
- real *8, dimension(:,:), allocatable gr_farea
- real *8, dimension(:,:), allocatable gr_solop
- real *8, dimension(:,:), allocatable gr_etcoef
- real *8, dimension(:,:), allocatable gr_fc
- real *8, dimension(:,:), allocatable gr_wp
- real *8, dimension(:,:), allocatable gr_ksat
- real *8, dimension(:,:), allocatable gr_por
- real *8, dimension(:,:), allocatable gr_hydeff
- real *8, dimension(:,:), allocatable gr_soldpt
- real *8, dimension(:,:), allocatable gr_dummy1
- real *8, dimension(:,:), allocatable gr_dummy2
- real *8, dimension(:,:), allocatable gr_dummy3
- real *8, dimension(:,:), allocatable **gr_dummy4**
- real *8, dimension(:,:), allocatable gr_dummy5
- integer, dimension(:,:), allocatable rg_onoff
- integer, dimension(:,:), allocatable rg_imo
- integer, dimension(:,:), allocatable rg_iyr
- real *8, dimension(:,:), allocatable rg_farea
- real *8, dimension(:,:), allocatable rg_solop
- real *8, dimension(:,:), allocatable rg etcoef
- real *8, dimension(:,:), allocatable rg_fc
- real *8, dimension(:,:), allocatable rg_wp
- real *8, dimension(:,:), allocatable rg_ksat
- real *8, dimension(:,:), allocatable rg_por
- real *8, dimension(:,:), allocatable rg_hydeff
- real *8, dimension(:,:), allocatable rg soldpt
- real *8, dimension(:,:), allocatable rg_dimop
- real *8, dimension(:,:), allocatable rg_sarea

- real *8, dimension(:,:), allocatable rg_vol
- real *8, dimension(:,:), allocatable rg sth
- real *8, dimension(:,:), allocatable rg_sdia
- real *8, dimension(:,:), allocatable rg bdia
- real *8, dimension(:,:), allocatable rg_sts
- real *8, dimension(:,:), allocatable rg_orifice
- real *8, dimension(:,:), allocatable rg_oheight
- real *8, dimension(:,:), allocatable rg_odia
- real *8, dimension(:,:), allocatable rg dummy1
- real *8, dimension(:,:), allocatable rg_dummy2
- real *8, dimension(:,:), allocatable rg_dummy3
- real *8, dimension(:,:), allocatable rg dummy4
- real *8, dimension(:,:), allocatable rg_dummy5
- integer, dimension(:,:), allocatable cs onoff
- integer, dimension(:,:), allocatable cs_imo
- integer, dimension(:,:), allocatable cs_iyr
- integer, dimension(:,:), allocatable cs grcon
- real *8, dimension(:,:), allocatable cs farea
- real *8, dimension(:,:), allocatable cs_vol
- real *8, dimension(:,:), allocatable cs rdepth
- real *8, dimension(:,:), allocatable cs_dummy1
- real *8, dimension(:,:), allocatable cs dummy2
- real *8, dimension(:,:), allocatable cs dummy3
- real *8, dimension(:,:), allocatable cs_dummy4
- real *8, dimension(:,:), allocatable cs_dummy5
- integer, dimension(:,:), allocatable pv_onoff
- integer, dimension(:,:), allocatable pv imo
- integer, dimension(:,:), allocatable pv_iyr
- integer, dimension(:,:), allocatable pv_solop
- real *8, dimension(:,:), allocatable pv grvdep
- real *8, dimension(:,:), allocatable pv_grvpor
- real *8, dimension(:,:), allocatable pv_farea
- real *8, dimension(:,:), allocatable pv_drcoef
- real *8, dimension(:,:), allocatable pv_fc
- real *8, dimension(:,:), allocatable pv_wp
- real *8, dimension(:,:), allocatable pv_ksat
- real *8, dimension(:,:), allocatable pv_por
- real *8, dimension(:,:), allocatable pv_hydeff
- real *8, dimension(:,:), allocatable pv_soldpt
- real *8, dimension(:,:), allocatable pv_dummy1
- real *8, dimension(:,:), allocatable pv_dummy2
- real *8, dimension(:,:), allocatable pv_dummy3
- real *8, dimension(:,:), allocatable pv_dummy4
- real *8, dimension(:,:), allocatable pv_dummy5
- integer, dimension(:,:), allocatable lid_onoff
- real *8, dimension(:,:), allocatable sol_bmc
- real *8, dimension(:,:), allocatable sol_bmn
- real *8, dimension(:,:), allocatable sol_hsc
- real *8, dimension(:,:), allocatable sol_hsn
- real *8, dimension(:,:), allocatable sol_hpc
- real *8, dimension(:,:), allocatable sol_hpn
- real *8, dimension(:,:), allocatable sol_lm
- real *8, dimension(:,:), allocatable sol_lmc
- real *8, dimension(:,:), allocatable sol_lmn
- real *8, dimension(:,:), allocatable sol_ls

- real *8, dimension(:,:), allocatable sol_lsl
- real *8, dimension(:,:), allocatable sol_lsc
- real *8, dimension(:,:), allocatable sol_lsn
- real *8, dimension(:,:), allocatable sol_rnmn
- real *8, dimension(:,:), allocatable sol Islc
- real *8, dimension(:,:), allocatable sol_lslnc
- real *8, dimension(:,:), allocatable sol rspc
- real *8, dimension(:,:), allocatable sol_woc
- real *8, dimension(:,:), allocatable sol_won
- real *8, dimension(:,:), allocatable sol_hp
- real *8, dimension(:,:), allocatable sol_hs
- real *8, dimension(:,:), allocatable sol bm
- real *8, dimension(:,:), allocatable sol_cac
- real *8, dimension(:,:), allocatable sol_cec
- real *8, dimension(:,:), allocatable sol_percc
- roar ro, amonorom,,,,, amooatable col_poro
- real *8, dimension(:,:), allocatable sol_latc
- real *8, dimension(:), allocatable sedc_d
- real *8, dimension(:), allocatable surfqc_d
 real *8, dimension(:), allocatable latc d
- real *8, dimension(:), allocatable percc_d
- real *8, dimension(:), allocatable foc_d
- real *8, dimension(:), allocatable nppc d
- real *8, dimension(:), allocatable rsdc d
- real *8, dimension(:), allocatable grainc_d
- real *8, dimension(:), allocatable stoverc d
- real *8, dimension(:), allocatable soc_d
- real *8, dimension(:), allocatable rspc_d
- real *8, dimension(:), allocatable emitc_d
- real *8, dimension(:), allocatable sub sedc d
- real *8, dimension(:), allocatable sub_surfqc_d
- real *8, dimension(:), allocatable sub_latc_d
- real *8, dimension(:), allocatable sub percc d
- real *8, dimension(:), allocatable sub_foc_d
- real *8, dimension(:), allocatable sub_nppc_d
- real *8, dimension(:), allocatable sub_rsdc_d
- real *8, dimension(:), allocatable sub_grainc_d
- real *8, dimension(:), allocatable sub_stoverc_d
- real *8, dimension(:), allocatable sub_emitc_d
- real *8, dimension(:), allocatable sub_soc_d
- real *8, dimension(:), allocatable sub_rspc_d
- real *8, dimension(:), allocatable **sedc m**
- real *8, dimension(:), allocatable surfqc_m
- real *8, dimension(:), allocatable latc_m
- real *8, dimension(:), allocatable percc_m
 real *8, dimension(:), allocatable foc_m
- real *8, dimension(:), allocatable nppc m
- real *8, dimension(:), allocatable rsdc m
- real *8, dimension(:), allocatable grainc_m
- real *8, dimension(:), allocatable stoverc_m
- real *8, dimension(:), allocatable emitc_m
- real *8, dimension(:), allocatable soc_m
- real *8, dimension(:), allocatable rspc m
- real *8, dimension(:), allocatable sedc_a
- real *8, dimension(:), allocatable surfqc_a
- real *8, dimension(:), allocatable latc_a

68 Module Documentation

- real *8, dimension(:), allocatable percc_a
- real *8, dimension(:), allocatable foc_a
- real *8, dimension(:), allocatable nppc a
- real *8, dimension(:), allocatable rsdc_a
- real *8, dimension(:), allocatable grainc_a
- real *8, dimension(:), allocatable stoverc_a
- real *8, dimension(:), allocatable emitc_a
- real *8, dimension(:), allocatable soc a
- real *8, dimension(:), allocatable rspc_a
- integer, dimension(:), allocatable tillage switch
- real *8, dimension(:), allocatable tillage_depth
- integer, dimension(:), allocatable tillage_days
- real *8, dimension(:), allocatable tillage_factor
- real *8 dthy

time interval for subdaily routing

- integer, dimension(4) ihx
- · integer, dimension(:), allocatable nhy
- real *8, dimension(:), allocatable rchx
- real *8, dimension(:), allocatable rcss
- real *8, dimension(:), allocatable qcap
- real *8, dimension(:), allocatable chxa
- real *8, dimension(:), allocatable chxp
- real *8, dimension(:,:,:), allocatable qhy
- real *8 ff1
- real *8 ff2

5.1.1 Detailed Description

main module containing the global variables

5.1.2 Variable Documentation

5.1.2.1 igropt

integer parm::igropt

Qual2E option for calculating the local specific growth rate of algae 1: multiplicative.

u = mumax fll fnn fpp

2: limiting nutrient

 $u = mumax fll \min(fnn, fpp)$

3: harmonic mean

$$u = mumax \, fll \, \frac{2}{\frac{1}{fnn} + \frac{1}{fpp}}$$

Chapter 6

Data Type Documentation

6.1 parm::ascrv Interface Reference

Public Member Functions

• subroutine **ascrv** (x1, x2, x3, x4, x5, x6)

The documentation for this interface was generated from the following file:

• modparm.f90

6.2 parm::atri Interface Reference

Public Member Functions

• real *8 function atri (at1, at2, at3, at4i)

The documentation for this interface was generated from the following file:

· modparm.f90

6.3 parm::aunif Interface Reference

Public Member Functions

• real *8 function aunif (x1)

The documentation for this interface was generated from the following file:

modparm.f90

6.4 parm::dstn1 Interface Reference

Public Member Functions

• real *8 function dstn1 (rn1, rn2)

The documentation for this interface was generated from the following file:

· modparm.f90

6.5 parm::ee Interface Reference

Public Member Functions

• real *8 function ee (tk)

The documentation for this interface was generated from the following file:

• modparm.f90

6.6 parm::expo Interface Reference

Public Member Functions

• real *8 function expo (xx)

The documentation for this interface was generated from the following file:

• modparm.f90

6.7 parm::fcgd Interface Reference

Public Member Functions

• real *8 function fcgd (xx)

The documentation for this interface was generated from the following file:

modparm.f90

6.8 parm::HQDAV Interface Reference

Public Member Functions

• subroutine hqdav (A, CBW, QQ, SSS, ZCH, ZX, CHW, FPW, jrch)

The documentation for this interface was generated from the following file:

· modparm.f90

6.9 parm::layersplit Interface Reference

Public Member Functions

subroutine layersplit (dep_new)

The documentation for this interface was generated from the following file:

• modparm.f90

6.10 parm::ndenit Interface Reference

Public Member Functions

• subroutine **ndenit** (k, j, cdg, wdn, void)

The documentation for this interface was generated from the following file:

· modparm.f90

6.11 parm::qman Interface Reference

Public Member Functions

real *8 function qman (x1, x2, x3, x4)

The documentation for this interface was generated from the following file:

modparm.f90

6.12 parm::regres Interface Reference

Public Member Functions

• real *8 function regres (k)

The documentation for this interface was generated from the following file:

· modparm.f90

6.13 parm::rsedaa Interface Reference

Public Member Functions

· subroutine rsedaa (years)

The documentation for this interface was generated from the following file:

· modparm.f90

6.14 parm::tair Interface Reference

Public Member Functions

• real *8 function tair (hr, jj)

The documentation for this interface was generated from the following file:

· modparm.f90

6.15 parm::theta Interface Reference

Public Member Functions

• real *8 function theta (r20, thk, tmp)

The documentation for this interface was generated from the following file:

• modparm.f90

6.16 parm::vbl Interface Reference

Public Member Functions

• subroutine vbl (evx, spx, pp, qin, ox, vx1, vy, yi, yo, ysx, vf, vyf, aha)

The documentation for this interface was generated from the following file:

• modparm.f90

Chapter 7

File Documentation

7.1 allocate_parms.f90 File Reference

Functions/Subroutines

• subroutine allocate_parms
this subroutine allocates array sizes

7.1.1 Detailed Description

this subroutine allocates array sizes

Author

modified by Javier Burguete

7.2 ascrv.f90 File Reference

Functions/Subroutines

• subroutine ascrv (x1, x2, x3, x4, x5, x6)

this subroutine computes shape parameters x5 and x6 for the S curve equation

7.2.1 Detailed Description

file containing the subroutine ascrv

Author

modified by Javier Burguete

7.2.2 Function/Subroutine Documentation

7.2.2.1 ascrv()

```
subroutine ascrv (
    real*8, intent(in) x1,
    real*8, intent(in) x2,
    real*8, intent(in) x3,
    real*8, intent(in) x4,
    real*8, intent(out) x5,
    real*8, intent(out) x6)
```

this subroutine computes shape parameters x5 and x6 for the S curve equation

$$x = \frac{y}{y + \exp(x5 + x6y)}$$

given 2 (x,y) points along the curve. x5 is determined by solving the equation with x and y values measured around the midpoint of the curve (approx. 50% of the maximum value for x) and x6 is determined by solving the equation with x and y values measured close to one of the endpoints of the curve (100% of the maximum value for x). This subroutine is called from readbsn.f90 and readplant.f90

Parameters

| in | х1 | value for x in the above equation for first datapoint, x1 should be close to 0.5 (the midpoint of the curve) |
|-----|----|--|
| in | x2 | value for x in the above equation for second datapoint, x2 should be close to 0.0 or 1.0 |
| in | хЗ | value for y in the above equation corresponding to x1 |
| in | x4 | value for y in the above equation corresponding to x2 |
| out | x5 | 1st shape parameter for S curve equation characterizing the midpoint of the curve |
| out | х6 | 2nd shape parameter for S curve equation characterizing the regions close to the endpoints of |
| | | the curve |

7.3 aunif.f90 File Reference

Functions/Subroutines

• real *8 function aunif (x1)

This function generates random numbers ranging from 0.0 to 1.0. In the process of calculating the random number, the seed (x1) is set to a new value. This function implements the prime-modulus generator.

7.3.1 Detailed Description

file containing the function aunif

Author

modified by Javier Burguete

7.3.2 Function/Subroutine Documentation

7.3.2.1 aunif()

This function generates random numbers ranging from 0.0 to 1.0. In the process of calculating the random number, the seed (x1) is set to a new value. This function implements the prime-modulus generator.

$$xi = 16807 \, xi \, \text{mod} \, \left(2^{31} - 1\right)$$

using code which ensures that no intermediate result uses more than 31 bits. The theory behind the code is summarized in [1]

Parameters

x1 random number generator seed (integer) where 0 < x1 < 2147483647

Returns

random number ranging from 0.0 to 1.0

7.4 caps.f90 File Reference

Functions/Subroutines

• subroutine caps (file name)

this subroutine reads the input and output names given in file.cio and converts all capital letters to lowercase letters.

7.4.1 Detailed Description

file containing the subroutine caps

Author

modified by Javier Burguete

7.4.2 Function/Subroutine Documentation

7.4.2.1 caps()

this subroutine reads the input and output names given in file.cio and converts all capital letters to lowercase letters.

Parameters

| file_name | dummy argument, file name character string |
|-----------|--|
|-----------|--|

7.5 gcycl.f90 File Reference

Functions/Subroutines

· subroutine gcycl

This subroutine initializes the random number seeds. If the user desires a different set of random numbers for each simulation run, the random number generator is used to reset the values of the seeds.

7.5.1 Detailed Description

file containing the subroutine gcycl

Author

modified by Javier Burguete

7.6 getallo.f90 File Reference

Functions/Subroutines

· subroutine getallo

This subroutine calculates the number of HRUs, subbasins, etc. in the simulation. These values are used to allocate array sizes.

7.6.1 Detailed Description

file containing the subroutine getallo

Author

modified by Javier Burguete

7.7 jdt.f90 File Reference

Functions/Subroutines

• integer function jdt (numdays, i, m)

this function computes the julian date given the month and the day of the month

7.8 main.f90 File Reference 77

7.7.1 Detailed Description

file containing the function jdt

Author

modified by Javier Burguete

7.7.2 Function/Subroutine Documentation

7.7.2.1 jdt()

this function computes the julian date given the month and the day of the month

Parameters

| in | numdays | julian date for last day of preceding month (where the array location is the number of the month). The dates are for leap years (numdays=ndays) (julian date) |
|----|---------|---|
| in | i | day |
| in | m | month |

7.8 main.f90 File Reference

Functions/Subroutines

program main

this is the main program that reads input, calls the main simulation model, and writes output

7.8.1 Detailed Description

file containing the main program that reads input, calls the main simulation model, and writes output.

Author

modified by Javier Burguete Tolosa

7.9 modparm.f90 File Reference

Data Types

- interface parm::atri
- · interface parm::aunif
- · interface parm::dstn1
- interface parm::ee
- interface parm::expo
- · interface parm::fcgd
- interface parm::qman
- interface parm::regres
- · interface parm::tair
- · interface parm::theta
- · interface parm::ascrv
- interface parm::HQDAV
- interface parm::layersplit
- interface parm::ndenit
- interface parm::rsedaa
- · interface parm::vbl

Modules

· module parm

main module containing the global variables

Variables

- integer, parameter parm::mvaro = 33
 - max number of variables routed through the reach
- integer, parameter parm::mhruo = 79
 - max number of variables in output.hru
- integer, parameter parm::mrcho = 62
 - max number of variables in reach file
- integer, parameter parm::msubo = 24
- max number of variables in output.subinteger, parameter parm::mstdo = 113
- max number of variables summarized in output.std
- integer, parameter parm::motot = 600
- integer parm::icalen
- real *8 parm::prf_bsn

Basinwide peak rate adjustment factor for sediment routing in the channel. Allows impact of peak flow rate on sediment routing and channel reshaping to be taken into account.

- real *8 parm::co2_x2
- real *8 parm::co2_x
- real *8, dimension(:), allocatable parm::alph_e
- real *8, dimension(:), allocatable parm::cdn
 - denitrification exponential rate coefficient
- real *8, dimension(:), allocatable parm::nperco

nitrate percolation coefficient (0-1) 0:concentration of nitrate in surface runoff is zero 1:percolate has same concentration of nitrate as surface runoff

real *8, dimension(:), allocatable parm::surlag

Surface runoff lag time. This parameter is needed in subbasins where the time of concentration is greater than 1 day. SURLAG is used to create a "storage" for surface runoff to allow the runoff to take longer than 1 day to reach the subbasin outlet (days)

- real *8, dimension(:), allocatable parm::co p
- real *8, dimension(:), allocatable parm::cmn

rate factor for humus mineralization on active organic N

real *8, dimension(:), allocatable parm::phoskd

Phosphorus soil partitioning coefficient. Ratio of soluble phosphorus in surface layer to soluble phosphorus in runoff.

real *8, dimension(:), allocatable parm::psp

Phosphorus availibility index. The fraction of fertilizer P remaining in labile pool after initial rapid phase of P sorption.

• real *8, dimension(:), allocatable parm::sdnco

denitrification threshold: fraction of field capacity triggering denitrification

real *8 parm::r2adj_bsn

basinwide retention parameter adjustment factor (greater than 1)

- real *8 parm::yield
- real *8 parm::burn_frlb
- real *8 parm::pst kg
- real *8 parm::yieldgrn
- real *8 parm::yieldbms
- real *8 parm::vieldtbr
- real *8 parm::yieldn
- real *8 parm::yieldp
- real *8 parm::hi bms
- real *8 parm::hi_rsd
- real *8 parm::yieldrsd
- real *8, dimension(:), allocatable parm::l k1
- real *8, dimension(:), allocatable parm::l_k2
- real *8, dimension(:), allocatable parm::l_lambda
- real *8, dimension(:), allocatable parm::l_beta
- real *8, dimension(:), allocatable parm::l_gama
- real *8, dimension(:), allocatable parm::l harea
- real *8, dimension(:), allocatable parm::l_vleng
- real *8, dimension(:), allocatable parm:: vslope
- real *8, dimension(:), allocatable parm::l_ktc
- real *8, dimension(:), allocatable parm::biofilm_mumax
- real *8, dimension(:), allocatable parm::biofilm kinv
- real *8, dimension(:), allocatable parm::biofilm klw
- real *8, dimension(:), allocatable parm::biofilm_kla
- real *8, dimension(:), allocatable parm::biofilm_cdet
- real *8, dimension(:), allocatable parm::biofilm_bm
- real *8, dimension(:,:), allocatable parm::hru_rufr
- real *8, dimension(:,:), allocatable parm::daru_km
- real *8, dimension(:,:), allocatable parm::ru_k
- real *8, dimension(:,:), allocatable parm::ru c
- real *8, dimension(:,:), allocatable parm::ru_eiq
- real *8, dimension(:,:), allocatable parm::ru_ovsl
- real *8, dimension(:,:), allocatable parm::ru a
- real *8, dimension(:,:), allocatable parm::ru_ovs
- real *8, dimension(:,:), allocatable parm::ru ktc
- real *8, dimension(:), allocatable parm::gwq_ru

```
• real *8, dimension(:), allocatable parm::qdayout
• integer, dimension(:), allocatable parm::ils2
• integer, dimension(:), allocatable parm::ils2flag
· integer parm::iru
• integer parm::mru
integer parm::irch
· integer parm::isub
• integer parm::idum
• integer parm::mhyd_bsn
integer parm::ipest

    integer parm::ils_nofig

· integer parm::mhru1
• integer, dimension(:), allocatable parm::mhyd1
• integer, dimension(:), allocatable parm::irtun
real *8 parm::wshd_sepno3
real *8 parm::wshd_sepnh3
real *8 parm::wshd_seporgn
real *8 parm::wshd_sepfon
real *8 parm::wshd_seporgp
real *8 parm::wshd_sepfop
real *8 parm::wshd_sepsolp

    real *8 parm::wshd sepbod

real *8 parm::wshd_sepmm
• integer, dimension(:), allocatable parm::isep_hru
· real *8 parm::fixco
     nitrogen fixation coefficient

    real *8 parm::nfixmx

     maximum daily n-fixation (kg/ha)
real *8 parm::res_stlr_co
     reservoir sediment settling coefficient
real *8 parm::rsd_covco
     residue cover factor for computing frac of cover
· real *8 parm::vcrit
     critical velocity
real *8 parm::wshd sw
real *8 parm::wshd_snob
real *8 parm::wshd_pndfr
real *8 parm::wshd_pndv
real *8 parm::wshd_pndsed

    real *8 parm::percop

     pesticide percolation coefficient (0-1)
     0: concentration of pesticide in surface runoff is zero
     1: percolate has same concentration of pesticide as surface runoff
real *8 parm::wshd_wetfr
real *8 parm::wshd_resfr

    real *8 parm::wshd resha

real *8 parm::wshd_pndha

    real *8 parm::wshd_fminp

real *8 parm::wshd_ftotn
real *8 parm::wshd_fnh3
real *8 parm::wshd fno3
real *8 parm::wshd_forgn

    real *8 parm::wshd_forgp
```

real *8 parm::wshd_ftotp

```
real *8 parm::wshd_yldn
real *8 parm::wshd_yldp

    real *8 parm::wshd_fixn

real *8 parm::wshd pup
real *8 parm::wshd wstrs

    real *8 parm::wshd_nstrs

real *8 parm::wshd_pstrs
real *8 parm::wshd_tstrs

    real *8 parm::wshd_astrs

real *8 parm::ffcb
     initial soil water content expressed as a fraction of field capacity
real *8 parm::wshd_hmn
real *8 parm::wshd_rwn
real *8 parm::wshd_hmp
real *8 parm::wshd_rmn

    real *8 parm::wshd_dnit

real *8 parm::wdpq
     die-off factor for persistent bacteria in soil solution (1/day)
real *8 parm::wshd_rmp
real *8 parm::wshd_voln
real *8 parm::wshd_nitn
real *8 parm::wshd_pas
real *8 parm::wshd pal
real *8 parm::wof_p
     wash off fraction for persistent bacteria on foliage during a rainfall event
real *8 parm::wshd_plch
real *8 parm::wshd raino3
real *8 parm::ressedc
real *8 parm::basno3f
· real *8 parm::basorgnf
real *8 parm::wshd_pinlet
real *8 parm::wshd_ptile
real *8 parm::sftmp
     Snowfall temperature (deg C)
real *8 parm::smfmn
     Minimum melt rate for snow during year (Dec. 21) where deg C refers to the air temperature. (mm/deg C/day)
real *8 parm::smfmx
     Maximum melt rate for snow during year (June 21) where deg C refers to the air temperature. SMFMX and SM←
     FMN allow the rate of snow melt to vary through the year. These parameters are accounting for the impact of soil
     temperature on snow melt. (mm/deg C/day)
real *8 parm::smtmp
     Snow melt base temperature. Mean air temperature at which snow melt will occur. (deg C)
real *8 parm::wgpq
     growth factor for persistent bacteria in soil solution (1/day)
real *8 parm::basminpf

    real *8 parm::basorgpf

    real *8 parm::wdlpq

     die-off factor for less persistent bacteria in soil solution (1/day)
real *8 parm::wshd_resv

    real *8 parm::wshd_ressed

• real *8 parm::basno3i

    real *8 parm::basorgni
```

real *8 parm::basminpi

real *8 parm::wdps

die-off factor for persistent bacteria adsorbed to soil particles (1/day)

real *8 parm::wglpq

growth factor for less persistent bacteria in soil solution (1/day)

- real *8 parm::basorgpi
- real *8 parm::peakr
- real *8 parm::pndsedin
- real *8 parm::sw_excess
- real *8 parm::albday
- real *8 parm::timp

Snow pack temperature lag factor (0-1)

1 = no lag (snow pack temp=current day air temp) as the lag factor goes to zero, the snow pack's temperature will be less influenced by the current day's air temperature.

- real *8 parm::wtabelo
- real *8 parm::tilep
- real *8 parm::wt_shall
- real *8 parm::sq_rto
- real *8 parm::tloss
- real *8 parm::inflpcp
- real *8 parm::snomlt
- real *8 parm::snofall
- real *8 parm::fixn
- real *8 parm::qtile
- real *8 parm::crk
- real *8 parm::latlyr
- real *8 parm::pndloss
- real *8 parm::wetloss
- real *8 parm::potloss
- real *8 parm::lpndloss
- real *8 parm::lwetloss
- real *8 parm::sedrch
- real *8 parm::fertn
- real *8 parm::sol_rd
- real *8 parm::cfertnreal *8 parm::cfertp
- real *8 parm::sepday
- real *8 parm::bioday
- real *8 parm::sepcrk
- real *8 parm::sepcrktot
- real *8 parm::fertno3
- real *8 parm::fertnh3
- real *8 parm::fertorgn
- real *8 parm::fertsolp
- real *8 parm::fertorgp
- real *8 parm::wgps

growth factor for persistent bacteria adsorbed to soil particles (1/day)

- real *8 parm::fertp
- real *8 parm::grazn
- real *8 parm::grazp
- real *8 parm::soxy
- real *8 parm::qdfr
- real *8 parm::sdti
- real *8 parm::rtwtr
- real *8 parm::ressa

· real *8 parm::wdlps

die-off factor for less persistent bacteria absorbed to soil particles (1/day)

real *8 parm::wglps

growth factor for less persistent bacteria adsorbed to soil particles (1/day)

real *8 parm::da_km

area of the watershed in square kilometers (km²)

- real *8 parm::rttime
- real *8 parm::rchdep
- real *8 parm::rtevp
- real *8 parm::rttlc
- real *8 parm::resflwi
- real *8 parm::wdprch

die-off factor for persistent bacteria in streams (1/day)

- real *8 parm::resflwo
- real *8 parm::respcp
- real *8 parm::resev
- real *8 parm::ressep
- real *8 parm::ressedi
- real *8 parm::ressedo
- real *8 parm::dtot
- real *8 parm::pperco_bsn

phosphorus percolation coefficient. Ratio of soluble phosphorus in surface to soluble phosphorus in percolate

• real *8 parm::nperco bsn

basin nitrate percolation coefficient (0-1)

0:concentration of nitrate in surface runoff is zero

1:percolate has same concentration of nitrate as surface runoff

real *8 parm::rsdco

residue decomposition coefficient. The fraction of residue which will decompose in a day assuming optimal moisture, temperature, C:N ratio, and C:P ratio

- real *8 parm::phoskd_bsn
- real *8 parm::voltot
- real *8 parm::msk_x

weighting factor controling relative importance of inflow rate and outflow rate in determining storage on reach

- real *8 parm::volcrmin
- real *8 parm::bactkdq

bacteria soil partitioning coefficient. Ratio of solution bacteria in surface layer to solution bacteria in runoff soluble and sorbed phase in surface runoff.

real *8 parm::wdpf

die-off factor for persistent bacteria on foliage (1/day)

- real *8 parm::uno3d
- real *8 parm::canev
- real *8 parm::usle
- real *8 parm::rcn
- real *8 parm::surlag bsn
- real *8 parm::precipday
- real *8 parm::thbact

temperature adjustment factor for bacteria die-off/growth

real *8 parm::wlpq20

overall rate change for less persistent bacteria in soil solution (1/day)

real *8 parm::wlps20

overall rate change for less persistent bacteria adsorbed to soil particles (1/day)

real *8 parm::wpq20

overall rate change for persistent bacteria in soil solution (1/day)

real *8 parm::wps20

overall rate change for persistent bacteria adsorbed to soil particles (1/day)

- real *8 parm::bactrop
- real *8 parm::bactsedp
- real *8 parm::wgpf

growth factor for persistent bacteria on foliage (1/day)

- real *8 parm::bactlchp
- real *8 parm::bactlchlp
- real *8 parm::enratio
- real *8 parm::wetpcp
- real *8 parm::pndpcp
- real *8 parm::wetsep
- real *8 parm::pndsep
- real *8 parm::wetev
- real *8 parm::pndev
- real *8 parm::pndsedo
- real *8 parm::wetsedo
- real *8 parm::pndflwi
- real *8 parm::wetflwi
- real *8 parm::pndflwo
- real *8 parm::wetflwo
- real *8 parm::wetsedi
- real *8 parm::da_ha
- real *8 parm::vpd
- real *8 parm::evlai

leaf area index at which no evaporation occurs. This variable is used in ponded HRUs where evaporation from the water surface is restricted by the plant canopy cover. Evaporation from the water surface equals potential ET when LAI = 0 and decreased linearly to O when LAI = EVLAI

real *8 parm::evrch

Reach evaporation adjustment factor. Evaporation from the reach is multiplied by EVRCH. This variable was created to limit the evaporation predicted in arid regions.

real *8 parm::wdlpf

die-off factor for less persistent bacteria on foliage (1/day)

- real *8 parm::bactrolp
- real *8 parm::bactsedlp
- real *8 parm::pet_day
- real *8 parm::ep_day
- real *8 parm::adj_pkr

peak rate adjustment factor in the subbasin. Used in the MUSLE equation to account for impact of peak flow on erosion.

real *8 parm::n_updis

nitrogen uptake distribution parameter. This parameter controls the amount of nitrogen removed from the different soil layer layers by the plant. In particular, this parameter allows the amount of nitrogen removed from the surface layer via plant uptake to be controlled. While the relationship between UBN and N removed from the surface layer is affected by the depth of the soil profile, in general, as UBN increases the amount of N removed from the surface layer relative to the amount removed from the entire profile increases

real *8 parm::nactfr

nitrogen active pool fraction. The fraction of organic nitrogen in the active pool.

real *8 parm::p_updis

phosphorus uptake distribution parameter This parameter controls the amount of phosphorus removed from the different soil layers by the plant. In particular, this parameter allows the amount of phosphorus removed from the surface layer via plant uptake to be controlled. While the relationship between UBP and P uptake from the surface layer is affected by the depth of the soil profile, in general, as UBP increases the amount of P removed from the surface layer relative to the amount removed from the entire profile increases

real *8 parm::snoev

- real *8 parm::sno3upreal *8 parm::reactw
- real *8 parm::sdiegropq
- real *8 parm::sdiegrolpq
- real *8 parm::sdiegrops
- real *8 parm::sdiegrolps
- real *8 parm::es_day
- real *8 parm::wof_lp

wash off fraction for less persistent bacteria on foliage during a rainfall event

- real *8 parm::sbactrop
- real *8 parm::sbactrolp
- real *8 parm::sbactsedp
- real *8 parm::sbactsedlp
- real *8 parm::ep_max
- real *8 parm::sbactlchp
- real *8 parm::sbactlchlp
- real *8 parm::psp bsn
- real *8 parm::rchwtr
- real *8 parm::resuspst
- real *8 parm::setlpst
- real *8 parm::bsprev
- real *8 parm::bssprev
- real *8 parm::spadyo
- real *8 parm::spadyev
- real *8 parm::spadysp
- real *8 parm::spadyrfv
- real *8 parm::spadyosp
- real *8 parm::qday
- real *8 parm::usle_ei
- real *8 parm::al5
- real *8 parm::pndsedc
- real *8 parm::no3pcp
- real *8 parm::rcharea
- real *8 parm::volatpst
- real *8 parm::ubw

water uptake distribution parameter. This parameter controls the amount of water removed from the different soil layers by the plant. In particular, this parameter allows the amount of water removed from the surface layer via plant uptake to be controlled. While the relationship between UBW and H2O removed from the surface layer is affected by the depth of the soil profile, in general, as UBW increases the amount of water removed from the surface layer relative to the amount removed from the entire profile increases

real *8 parm::uobn

nitrogen uptake normalization parameter. This variable normalizes the nitrogen uptake so that the model can easily verify that upake from the different soil layers sums to 1.0

real *8 parm::uobp

phosphorus uptake normalization parameter. This variable normalizes the phosphorus uptake so that the model can easily verify that uptake from the different soil layers sums to 1.0

real *8 parm::uobw

water uptake normalization parameter. This variable normalizes the water uptake so that the model can easily verify that uptake from the different soil layers sums to 1.0

real *8 parm::wglpf

growth factor for less persistent bacteria on foliage (1/day)

- real *8 parm::wetsedc
- real *8 parm::respesti
- real *8 parm::rcor

correction coefficient for generated rainfall to ensure that the annual means for generated and observed values are comparable (needed only if IDIST=1)

real *8 parm::rexp

value of exponent for mixed exponential rainfall distribution (needed only if IDIST=1)

real *8 parm::snocov1

1st shape parameter for snow cover equation. This parameter is determined by solving the equation for 50% snow cover

real *8 parm::snocov2

2nd shape parameter for snow cover equation. This parameter is determined by solving the equation for 95% snow cover

real *8 parm::snocovmx

Minimum snow water content that corresponds to 100% snow cover. If the snow water content is less than SNOC← OVMX, then a certain percentage of the ground will be bare (mm H2O)

- real *8 parm::lyrtile
- real *8 parm::lyrtilex
- real *8 parm::sno50cov

Fraction of SNOCOVMX that corresponds to 50% snow cover. SWAT assumes a nonlinear relationship between snow water and snow cover.

real *8 parm::ai0

ratio of chlorophyll-a to algal biomass (ug chla/mg alg)

real *8 parm::ai1

fraction of algal biomass that is nitrogen (mg N/mg alg)

real *8 parm::ai2

fraction of algal biomass that is phosphorus (mg P/mg alg)

real *8 parm::ai3

the rate of oxygen production per unit of algal photosynthesis (mg O2/mg alg)

real *8 parm::ai4

the rate of oxygen uptake per unit of algae respiration (mg O2/mg alg)

real *8 parm::ai5

the rate of oxygen uptake per unit of NH3 nitrogen oxidation (mg O2/mg N)

real *8 parm::ai6

the rate of oxygen uptake per unit of NO2 nitrogen oxidation (mg O2/mg N)

real *8 parm::rhoq

algal respiration rate (1/day or 1/hr)

real *8 parm::tfact

fraction of solar radiation computed in the temperature heat balance that is photosynthetically active

real *8 parm::k l

half-saturation coefficient for light (MJ/(m2*hr))

real *8 parm::k_n

michaelis-menton half-saturation constant for nitrogen (mg N/L)

real *8 parm::k_p

michaelis-menton half saturation constant for phosphorus (mg P/L)

• real *8 parm::lambda0

non-algal portion of the light extinction coefficient (1/m)

real *8 parm::lambda1

linear algal self-shading coefficient (1/(m*ug chla/L))

real *8 parm::lambda2

nonlinear algal self-shading coefficient ((1/m)(ug chla/L)**(-2/3))

real *8 parm::mumax

maximum specific algal growth rate (1/day or 1/hr)

real *8 parm::p_n

algal preference factor for ammonia

- real *8 parm::rnum1
- real *8 parm::autop
- real *8 parm::auton
- real *8 parm::etday
- real *8 parm::hmntl
- real *8 parm::rwntl
- real *8 parm::hmptl
- real *8 parm::rmn2tl
- real *8 parm::rmptl
- real *8 parm::wdntl
- real *8 parm::cmn_bsn
- real *8 parm::rmp1tl
- real *8 parm::roctl
- real *8 parm::gwseep
- real *8 parm::revapday
- real *8 parm::reswtr
- real *8 parm::wdlprch

die-off factor for less persistent bacteria in streams (1/day)

real *8 parm::wdpres

die-off factor for persistent bacteria in reservoirs (1/day)

- real *8 parm::bury
- real *8 parm::difus
- real *8 parm::reactb
- real *8 parm::solpesto
- real *8 parm::petmeas
- real *8 parm::wdlpres

die-off factor for less persistent bacteria in reservoirs (1/day)

- real *8 parm::sorpesto
- real *8 parm::spcon_bsn
- real *8 parm::spexp_bsn
- real *8 parm::solpesti
- real *8 parm::sorpesti
- real *8 parm::msk_co1

calibration coefficient to control impact of the storage time constant for the reach at bankfull depth (phi(10,:) upon the storage time constant for the reach used in the Muskingum flow method

real *8 parm::msk_co2

calibration coefficient to control impact of the storage time constant for the reach at 0.1 bankfull depth (phi(13,:) upon the storage time constant for the reach used in the Muskingum flow method

- real *8 parm::snoprev
- real *8 parm::swprev
- real *8 parm::shallstp
- real *8 parm::deepstp
- real *8 parm::ressolpo
- real *8 parm::resorgno
- real *8 parm::resorgpo
- real *8 parm::resno3o
- real *8 parm::reschlao
- real *8 parm::resno2o
- real *8 parm::resnh3o
- real *8 parm::qdbank
- real *8 parm::potpcpmm
- real *8 parm::potevmm
- real *8 parm::potsepmm
- real *8 parm::potflwo

 real *8 parm::bactminlp Threshold detection level for less persistent bacteria. When bacteria levels drop to this amount the model considers bacteria in the soil to be insignificant and sets the levels to zero (cfu/m²) real *8 parm::bactminp Threshold detection level for persistent bacteria. When bacteria levels drop to this amount the model considers bacteria in the soil to be insignificant and sets the levels to zero (cfu/m^2) real *8 parm::trnsrch fraction of transmission losses from main channel that enter deep aquifer real *8 parm::wp20p plt overall rate change for persistent bacteria on foliage (1/day) real *8 parm::potsedo real *8 parm::pest_sol real *8 parm::bact_swf fraction of manure containing active colony forming units (cfu) real *8 parm::bactmx bacteria percolation coefficient. Ratio of solution bacteria in surface layer to solution bacteria in percolate real *8 parm::cncoef plant ET curve number coefficient real *8 parm::wp20lp plt overall rate change for less persistent bacteria on foliage (1/day) real *8 parm::cdn_bsn real *8 parm::sdnco bsn real *8 parm::bactmin real *8 parm::cn_froz drainge coefficient (mm day -1) real *8 parm::dorm_hr time threshold used to define dormant (hours) real *8 parm::smxco adjustment factor for max curve number s factor (0-1) real *8 parm::tb adj adjustment factor for subdaily unit hydrograph basetime • real *8 parm::chla_subco regional adjustment on sub chla_a loading (fraction) • real *8 parm::depimp bsn depth to impervious layer. Used to model perched water tables in all HRUs in watershed (mm) • real *8 parm::ddrain_bsn depth to the sub-surface drain (mm) real *8 parm::tdrain_bsn time to drain soil to field capacity (hours) real *8 parm::gdrain bsn real *8 parm::rch san • real *8 parm::rch_sil • real *8 parm::rch_cla real *8 parm::rch_sag real *8 parm::rch_lag real *8 parm::rch gra real *8 parm::hlife_ngw_bsn Half-life of nitrogen in groundwater? (days) real *8 parm::ch_opco_bsn real *8 parm::ch_onco_bsn

real *8 parm::decr min

Minimum daily residue decay.

```
real *8 parm::rcn_sub_bsn
     Concentration of nitrogen in the rainfall (mg/kg)
real *8 parm::bc1 bsn
real *8 parm::bc2 bsn
real *8 parm::bc3_bsn
real *8 parm::bc4_bsn

    real *8 parm::anion excl bsn

• real *8, dimension(:), allocatable parm::wat_tbl
• real *8, dimension(:), allocatable parm::sol_swpwt
real *8, dimension(:,:), allocatable parm::vwt
real *8 parm::re_bsn
     Effective radius of drains (range 3.0 - 40.0) (mm)
• real *8 parm::sdrain bsn
     Distance bewtween two drain or tile tubes (range 7600.0 - 30000.0) (mm)
real *8 parm::sstmaxd_bsn
  real *8 parm::drain_co_bsn
     Drainage coeffcient (range 10.0 - 51.0) (mm-day-1)

    real *8 parm::latksatf bsn

     Multiplication factor to determine lateral ksat from SWAT ksat input value for HRU (range 0.01 - 4.0)
• real *8 parm::pc_bsn
     Pump capacity (def val = 1.042 mm h-1 or 25 mm day-1) (mm h-1)
• integer parm::i subhw
· integer parm::imgt
integer parm::idlast
· integer parm::iwtr
· integer parm::ifrttyp
· integer parm::mo_atmo
integer parm::mo_atmo1

    integer parm::ifirstatmo

integer parm::iyr_atmo
· integer parm::iyr_atmo1
• integer parm::matmo

    integer parm::mch

     maximum number of channels
· integer parm::mcr
     maximum number of crops grown per year
· integer parm::mcrdb
     maximum number of crops/landcover in database file (crop.dat)

    integer parm::mfcst

     maximum number of forecast stations

    integer parm::mfdb

     max number of fertilizers in fert.dat
• integer parm::mhru
     maximum number of HRUs in watershed
· integer parm::mhyd
     maximum number of hydrograph nodes

    integer parm::mpdb

     max number of pesticides in pest.dat

    integer parm::mrg

     max number of rainfall/temp gages

    integer parm::mcut
```

maximum number of cuttings per year

· integer parm::mgr maximum number of grazings per year · integer parm::mnr max number of years of rotation integer parm::myr max number of years of simulation · integer parm::isubwq subbasin water quality code 0 do not calculate algae/CBOD 1 calculate algae/CBOD drainmod tile equations integer parm::ffcst integer parm::isproj special project code: 1 test rewind (run simulation twice) · integer parm::nbyr number of calendar years simulated · integer parm::irte water routing method: 0 variable storage method 1 Muskingum method integer parm::nrch number of reaches in watershed (none) integer parm::nres number of reservoirs in watershed (none) • integer parm::nhru · integer parm::mo · integer parm::immo · integer parm::i_mo integer parm::wndsim wind speed input code 1 measured data read for each subbasin 2 data simulated for each subbasin · integer parm::ihru HRU number (none) • integer parm::icode integer parm::ihout · integer parm::inum1 · integer parm::inum2 · integer parm::inum3 integer parm::inum4 · integer parm::icfac icfac = 0 for C-factor calculation using Cmin (as described in manual) = 1 for new C-factor calculation from RUSLE (no minimum needed) • integer parm::inum5 · integer parm::inum6 integer parm::inum7 • integer parm::inum8 integer parm::mrech maximum number of rechour files integer parm::nrgage number of raingage files integer parm::nrgfil number of rain gages per file

integer parm::nrtot

total number of rain gages

· integer parm::ntgage

number of temperature gage files

· integer parm::ntgfil

number of temperature gages per file

· integer parm::nttot

total number of temperature gages

integer parm::tmpsim

temperature input code

1 measured data read for each subbasin

2 data simulated for each subbasin

· integer parm::icrk

crack flow code

1: compute flow in cracks

· integer parm::irtpest

number of pesticide to be routed through the watershed

· integer parm::igropt

Qual2E option for calculating the local specific growth rate of algae

1: multiplicative.

integer parm::lao

Qual2E light averaging option. Qual2E defines four light averaging options. The only option currently available in SWAT is #2.

integer parm::npmx

number of different pesticides used in the simulation (none)

- · integer parm::curyr
- · integer parm::iihru
- integer parm::itdrn

tile drainage equations flag/code

1 simulate tile flow using subroutine drains(wt_shall)

0 simulate tile flow using subroutine origtile(wt_shall,d)

• integer parm::iwtdn

water table depth algorithms flag/code

1 simulate wt_shall using subroutine new water table depth routine

0 simulate wt_shall using subroutine original water table depth routine

integer parm::ismax

maximum depressional storage selection flag/code

 $0 = static\ depressional\ storage$

1 = dynamic storage based on tillage and cumulative rainfall

integer parm::iroutunit

not being implemented in this version drainmod tile equations

- integer parm::ires_nut
- · integer parm::iclb

auto-calibration flag

integer parm::mrecc

maximum number of reccnst files

· integer parm::mrecd

maximum number of recday files

integer parm::mrecm

maximum number of recmon files

integer parm::mtil

max number of tillage types in till.dat

integer parm::mudb

maximum number of urban land types in urban.dat

· integer parm::idist

rainfall distribution code

0 for skewed normal dist

1 for mixed exponential distribution

integer parm::mrecy

maximum number of recyear files

· integer parm::nyskip

number of years to not print output

integer parm::slrsim

solar radiation input code

1 measured data read for each subbasin

2 data simulated for each subbasin

· integer parm::ideg

channel degredation code

1: compute channel degredation (downcutting and widening)

• integer parm::ievent

rainfall/runoff code

0 daily rainfall/curve number technique 1 sub-daily rainfall/Green&Ampt/hourly routing 3 sub-daily rainfall/ \leftarrow Green&Ampt/hourly routing

· integer parm::ipet

code for potential ET method

0 Priestley-Taylor method

1 Penman/Monteith method

2 Hargreaves method

3 read in daily potential ET data

- integer parm::iopera
- integer parm::idaf

beginning day of simulation (julian date)

· integer parm::idal

ending day of simulation (julian date)

· integer parm::rhsim

relative humidity input code

1 measured data read for each subbasin

2 data simulated for each subbasin

- integer parm::id1
- integer parm::leapyr
- integer parm::mo_chk
- · integer parm::nhtot

number of relative humidity records in file

integer parm::nstot

number of solar radiation records in file

integer parm::nwtot

number of wind speed records in file

- · integer parm::ifirsts
- · integer parm::ifirsth
- · integer parm::ifirstw
- integer parm::icst
- integer parm::ilog

streamflow print code

integer parm::itotr

number of output variables printed (output.rch)

· integer parm::iyr

beginning year of simulation (year)

· integer parm::iwq

```
stream water quality code
     0 do not model stream water quality
      1 model stream water quality (QUAL2E & pesticide transformations)

    integer parm::i

     forecast region number or subbasin number (none)
· integer parm::iskip
• integer parm::ifirstpet
· integer parm::iprp
     print code for output.pst file
     0 do not print pesticide output
      1 print pesticide output

    integer parm::itotb

     number of output variables printed (output.sub)

    integer parm::itots

      number of output variables printed (output.hru)

    integer parm::itoth

      number of HRUs printed (output.hru/output.wtr)
· integer parm::pcpsim
     rainfall input code
      1 measured data read for each subbasin
     2 data simulated for each subbasin
integer parm::nd 30
integer parm::iops
integer parm::iphr
· integer parm::isto
· integer parm::isol
• integer parm::fcstcycles
     number of times forecast period is simulated (using different weather generator seeds each time)

    integer parm::fcstday

     beginning date of forecast period (julian date)
· integer parm::fcstyr
     beginning year of forecast period

    integer parm::iscen

      scenarios counter

    integer parm::subtot

      number of subbasins in watershed (none)
• integer parm::ogen
  integer parm::mapp
      maximum number of applications

    integer parm::mlyr

      maximum number of soil layers

    integer parm::mpst

      max number of pesticides used in wshed
integer parm::mres
      maximum number of reservoirs
• integer parm::msub
     maximum number of subbasins
· integer parm::igen
     random number generator code:
     0: use default numbers
      1: generate new numbers in every simulation

    integer parm::iprint

     print code: 0=monthly, 1=daily, 2=annual
```

- · integer parm::iida
- integer parm::icn

CN method flag (for testing alternative method):

0 use traditional SWAT method which bases CN on soil moisture

1 use alternative method which bases CN on plant ET.

integer parm::ised_det

max half-hour rainfall fraction calc option:

0 generate max half-hour rainfall fraction from triangular distribution

1 use monthly mean max half-hour rainfall fraction

- integer parm::fcstcnt
- · integer parm::mtran
- integer parm::idtill
- integer, dimension(100) parm::ida_lup
- integer, dimension(100) parm::iyr_lup
- integer parm::no_lup
- integer parm::no_up
- · integer parm::nostep
- character(len=8) parm::date

date simulation is performed where leftmost eight characters are set to a value of yyyymmdd, where yyyy is the year, mm is the month and dd is the day

· character(len=10) parm::time

time simulation is performed where leftmost ten characters are set to a value of hhmmss.sss, where hh is the hour, mm is the minutes and ss.sss is the seconds and milliseconds

character(len=5) parm::zone

time difference with respect to Coordinated Universal Time (ie Greenwich Mean Time)

character(len=80) parm::prog

SWAT program header string.

character(len=13) parm::calfile

name of file containing calibration parameters

character(len=13) parm::rhfile

relative humidity file name (.hmd)

character(len=13) parm::slrfile

solar radiation file name (.slr)

character(len=13) parm::wndfile

wind speed file name (.wnd)

character(len=13) parm::petfile

potential ET file name (.pet)

- character(len=13) parm::atmofile
- character(len=13) parm::lucfile
- character(len=13) parm::septdb

name of septic tank database file (septwq1.dat)

- character(len=13) parm::dpd_file
- character(len=13) parm::wpd_file
- character(len=13) parm::rib_file
- character(len=13) parm::sfb file
- character(len=13) parm::lid_file
- integer, dimension(9) parm::idg

array location of random number seed used for a given process

- integer, dimension(:), allocatable parm::ifirstr
- · integer, dimension(:), allocatable parm::ifirsthr
- integer, dimension(8) parm::values

```
values(1): year simulation is performed
     values(2): month simulation is performed
     values(3): day in month simulation is performed
     values(4): time difference with respect to Coordinated Universal Time (ie Greenwich Mean Time)
     values(5): hour simulation is performed
     values(6): minute simulation is performed
     values(7): second simulation is performed
     values(8): millisecond simulation is performed

    integer, dimension(13) parm::ndays

     julian date for last day of preceding month (where the array location is the number of the month) The dates are for
     leap years (julian date)
  integer, dimension(13) parm::ndays_noleap
  integer, dimension(13) parm::ndays_leap
  integer parm::mapex
  real *8, dimension(:), allocatable parm::flodaya
  real *8, dimension(:), allocatable parm::seddaya
  real *8, dimension(:), allocatable parm::orgndaya
  real *8, dimension(:), allocatable parm::orgpdaya
  real *8, dimension(:), allocatable parm::no3daya
  real *8, dimension(:), allocatable parm::minpdaya
  real *8, dimension(:), allocatable parm::hi targ
     index target of cover defined at planting

    real *8, dimension(:), allocatable parm::bio_targ

  real *8, dimension(:), allocatable parm::tnyld
  integer, dimension(:), allocatable parm::idapa
• integer, dimension(:), allocatable parm::iypa
  integer, dimension(:), allocatable parm::ifirsta
  integer, dimension(100) parm::mo_transb
  integer, dimension(100) parm::mo_transe
  integer, dimension(100) parm::ih_tran
· integer parm::msdb
· integer parm::iseptic
  real *8, dimension(:), allocatable parm::sptqs

    real *8, dimension(:), allocatable parm::percp

 real *8, dimension(:), allocatable parm::sptbodconcs

    real *8, dimension(:), allocatable parm::spttssconcs

• real *8, dimension(:), allocatable parm::spttnconcs
  real *8, dimension(:), allocatable parm::sptnh4concs
  real *8, dimension(:), allocatable parm::sptno3concs
  real *8, dimension(:), allocatable parm::sptno2concs
  real *8, dimension(:), allocatable parm::sptorgnconcs

    real *8, dimension(:), allocatable parm::spttpconcs

    real *8, dimension(:), allocatable parm::sptminps

  real *8, dimension(:), allocatable parm::sptorgps
• real *8, dimension(:), allocatable parm::sptfcolis
  real *8, dimension(:), allocatable parm::failyr
  real *8, dimension(:), allocatable parm::qstemm
• real *8, dimension(:), allocatable parm::bio_amn
  real *8, dimension(:), allocatable parm::bio bod

    real *8, dimension(:), allocatable parm::biom

    real *8, dimension(:), allocatable parm::rbiom

  real *8, dimension(:), allocatable parm::fcoli
  real *8, dimension(:), allocatable parm::bio_ntr
  real *8, dimension(:), allocatable parm::bz_perc
```

real *8, dimension(:), allocatable parm::sep_cap

number of permanent residents in the hourse (none) real *8, dimension(:), allocatable parm::plgm real *8, dimension(:), allocatable parm::bz_area real *8, dimension(:), allocatable parm::bz z Depth of biozone layer(mm) real *8, dimension(:), allocatable parm::bz thk thickness of biozone (mm) real *8, dimension(:), allocatable parm::bio bd density of biomass (kg/m^{\(^{\)}3) carbon outputs for .hru file real *8, dimension(:), allocatable parm::cmup kgh real *8, dimension(:), allocatable parm::cmtot_kgh real *8, dimension(:), allocatable parm::coeff_denitr denitrification rate coefficient (none) real *8, dimension(:), allocatable parm::coeff bod dc BOD decay rate coefficient (m^3/day) real *8, dimension(:), allocatable parm::coeff_bod_conv BOD to live bacteria biomass conversion factor (none) real *8, dimension(:), allocatable parm::coeff fc1 field capacity calibration parameter 1 (none) real *8, dimension(:), allocatable parm::coeff fc2 field capacity calibration parameter 2 (none) real *8, dimension(:), allocatable parm::coeff_fecal fecal coliform bacteria decay rate coefficient (m^{\(\circ\)} 3/day) real *8, dimension(:), allocatable parm::coeff mrt mortality rate coefficient (none) • real *8, dimension(:), allocatable parm::coeff_nitr nitrification rate coefficient (none) real *8, dimension(:), allocatable parm::coeff_plq conversion factor for plaque from TDS (none) real *8, dimension(:), allocatable parm::coeff rsp respiration rate coefficient (none) real *8, dimension(:), allocatable parm::coeff_slg1 slough-off calibration parameter (none) real *8, dimension(:), allocatable parm::coeff_slg2 slough-off calibration parameter (none) real *8, dimension(:), allocatable parm::coeff_pdistrb real *8, dimension(:), allocatable parm::coeff_solpslp real *8, dimension(:), allocatable parm::coeff solpintc real *8, dimension(:), allocatable parm::coeff_psorpmax integer, dimension(:), allocatable parm::isep_typ septic system type (none) integer, dimension(:), allocatable parm::i sep integer, dimension(:), allocatable parm::isep_opt septic system operation flag (1=active, 2=failing, 3=not operated) (none) integer, dimension(:), allocatable parm::sep_tsincefail integer, dimension(:), allocatable parm::isep_tfail integer, dimension(:), allocatable parm::isep_iyr • integer, dimension(:), allocatable parm::sep_strm_dist • integer, dimension(:), allocatable parm::sep den • real *8, dimension(:), allocatable parm::sol_sumno3 real *8, dimension(:), allocatable parm::sol_sumsolp

real *8, dimension(:), allocatable parm::strsw_sum

- real *8, dimension(:), allocatable parm::strstmp sum real *8, dimension(:), allocatable parm::strsn sum real *8, dimension(:), allocatable parm::strsp_sum • real *8, dimension(:), allocatable parm::strsa_sum real *8, dimension(:), allocatable parm::spill hru real *8, dimension(:), allocatable parm::tile_out • real *8, dimension(:), allocatable parm::hru in real *8, dimension(:), allocatable parm::spill_precip real *8, dimension(:), allocatable parm::pot_seep real *8, dimension(:), allocatable parm::pot evap real *8, dimension(:), allocatable parm::pot_sedin real *8, dimension(:), allocatable parm::pot solp real *8, dimension(:), allocatable parm::pot_solpi • real *8, dimension(:), allocatable parm::pot_orgp real *8, dimension(:), allocatable parm::pot_orgpi real *8, dimension(:), allocatable parm::pot_orgn real *8, dimension(:), allocatable parm::pot orgni real *8, dimension(:), allocatable parm::pot_mps real *8, dimension(:), allocatable parm::pot mpsi real *8, dimension(:), allocatable parm::pot_mpa real *8, dimension(:), allocatable parm::pot mpai real *8, dimension(:), allocatable parm::pot no3i real *8, dimension(:), allocatable parm::precip_in real *8, dimension(:), allocatable parm::tile_sedo real *8, dimension(:), allocatable parm::tile_no3o • real *8, dimension(:), allocatable parm::tile_solpo real *8, dimension(:), allocatable parm::tile orgno real *8, dimension(:), allocatable parm::tile orgpo real *8, dimension(:), allocatable parm::tile_minpso real *8, dimension(:), allocatable parm::tile_minpao integer parm::ia b integer parm::ihumus integer parm::itemp integer parm::isnow integer, dimension(41) parm::icolrsv integer, dimension(mhruo) parm::icols integer, dimension(mrcho) parm::icolr integer, dimension(msubo) parm::icolb integer, dimension(46) parm::ipdvar output variable codes for output.rch file integer, dimension(mhruo) parm::ipdvas output varaible codes for output.hru file
- integer, dimension(msubo) parm::ipdvab output variable codes for output.sub file
- integer, dimension(:), allocatable parm::ipdhru

HRUs whose output information will be printed to the output.hru and output.wtr files.

- real *8, dimension(mstdo) parm::wshddayo
- real *8, dimension(mstdo) parm::wshdmono
- real *8, dimension(mstdo) parm::wshdyro
- real *8, dimension(16) parm::fcstaao
- real *8, dimension(mstdo) parm::wshdaao
- real *8, dimension(:,:), allocatable parm::wpstdayo
- real *8, dimension(:,:), allocatable parm::wpstmono
- real *8, dimension(:,:), allocatable parm::wpstyro

```
    real *8, dimension(:,:), allocatable parm::yldkg

    real *8, dimension(:,:), allocatable parm::bio hv

    real *8, dimension(:,:), allocatable parm::wpstaao

    real *8, dimension(:,:), allocatable parm::rchmono

    real *8, dimension(:,:), allocatable parm::rchyro

    real *8, dimension(:,:), allocatable parm::rchaao

    real *8, dimension(:.:), allocatable parm::rchdy

  real *8, dimension(:,:), allocatable parm::hrumono
  real *8, dimension(:,:), allocatable parm::hruyro

    real *8, dimension(:,:), allocatable parm::hruaao

    real *8, dimension(:,:), allocatable parm::submono

    real *8, dimension(:,:), allocatable parm::subyro

• real *8, dimension(:,:), allocatable parm::subaao

    real *8, dimension(:,:), allocatable parm::resoutm

    real *8, dimension(:,:), allocatable parm::resouty

  real *8, dimension(:,:), allocatable parm::resouta

    real *8, dimension(12, 8) parm::wshd_aamon

    real *8, dimension(:,:), allocatable parm::wtrmon

  real *8, dimension(:,:), allocatable parm::wtryr
  real *8, dimension(:,:), allocatable parm::wtraa

    real *8, dimension(:,:), allocatable parm::sub_smfmx

      max melt rate for snow during year (June 21) for subbasin(:) where deg C refers to the air temperature. SUB_SMFMX
     and SMFMN allow the rate of snow melt to vary through the year. These parameters are accounting for the impact of
     soil temperature on snow melt (range: -5.0/5.0) (mm/deg C/day)

    real *8, dimension(:,:), allocatable parm::sub_smfmn

     min melt rate for snow during year (Dec 21) for subbasin(:) (range: -5.0/5.0) where deg C refers to the air temperature
      (mm/deg C/day)

    real *8, dimension(:,:,:), allocatable parm::hrupstd

    real *8, dimension(:..:), allocatable parm::hrupsta

    real *8, dimension(:,:,:), allocatable parm::hrupstm

    real *8, dimension(:,:,:), allocatable parm::hrupsty

    integer, dimension(:), allocatable parm::ifirstt

• integer, dimension(:), allocatable parm::ifirstpcp

    integer, dimension(:), allocatable parm::elevp

• integer, dimension(:), allocatable parm::elevt

    real *8, dimension(:,:), allocatable parm::ftmpmn

      avg monthly minimum air temperature (deg C)

    real *8, dimension(:,:), allocatable parm::ftmpmx

      avg monthly maximum air temperature (deg C)

    real *8, dimension(:,:), allocatable parm::ftmpstdmn

      standard deviation for avg monthly minimum air temperature (deg C)

    real *8, dimension(:,:), allocatable parm::ftmpstdmx

      standard deviation for avg monthly maximum air temperature (deg C)

    real *8, dimension(:,:,:), allocatable parm::fpcp_stat

      fpcp_stat(:,1,:): average amount of precipitation falling in one day for the month (mm/day)
      fpcp_stat(:,2,:): standard deviation for the average daily precipitation (mm/day)
      fpcp_stat(:,3,:): skew coefficient for the average daily precipitationa (none)

    real *8, dimension(:,:), allocatable parm::fpr w1

     probability of wet day after dry day in month (none)
  real *8, dimension(:,:), allocatable parm::fpr w2
     probability of wet day after wet day in month (none)
```

real *8, dimension(:,:), allocatable parm::fpr_w3
 proportion of wet days in the month (none)
 real *8, dimension(:), allocatable parm::flwin

real *8, dimension(:), allocatable parm::flwout real *8, dimension(:), allocatable parm::bankst real *8, dimension(:), allocatable parm::ch wi real *8, dimension(:), allocatable parm::ch d real *8, dimension(:), allocatable parm::ch onco channel organic n concentration (ppm) real *8, dimension(:), allocatable parm::ch_opco channel organic p concentration (ppm) real *8, dimension(:), allocatable parm::ch_orgn real *8, dimension(:), allocatable parm::ch_orgp real *8, dimension(:), allocatable parm::drift real *8, dimension(:), allocatable parm::rch_dox real *8, dimension(:), allocatable parm::rch_bactp real *8, dimension(:), allocatable parm::alpha bnk real *8, dimension(:), allocatable parm::alpha_bnke real *8, dimension(:), allocatable parm::disolvp real *8, dimension(:), allocatable parm::algae real *8, dimension(:), allocatable parm::sedst real *8, dimension(:), allocatable parm::rchstor real *8, dimension(:), allocatable parm::organicn real *8, dimension(:), allocatable parm::organicp real *8, dimension(:), allocatable parm::chlora real *8, dimension(:), allocatable parm::nitraten real *8, dimension(:), allocatable parm::nitriten real *8, dimension(:), allocatable parm::ch_li real *8, dimension(:), allocatable parm::ch_si real *8, dimension(:), allocatable parm::ch_bnk_san real *8, dimension(:), allocatable parm::ch_bnk_sil real *8, dimension(:), allocatable parm::ch_bnk_cla real *8, dimension(:), allocatable parm::ch bnk gra real *8, dimension(:), allocatable parm::ch_bed_san real *8, dimension(:), allocatable parm::ch bed sil real *8, dimension(:), allocatable parm::ch_bed_cla real *8, dimension(:), allocatable parm::ch_bed_gra real *8, dimension(:), allocatable parm::depfp real *8, dimension(:), allocatable parm::depsanfp real *8, dimension(:), allocatable parm::depsilfp real *8, dimension(:), allocatable parm::depclafp real *8, dimension(:), allocatable parm::depsagfp real *8, dimension(:), allocatable parm::deplagfp real *8, dimension(:), allocatable parm::depch real *8, dimension(:), allocatable parm::depsanch real *8, dimension(:), allocatable parm::depsilch real *8, dimension(:), allocatable parm::depclach real *8, dimension(:), allocatable parm::depsagch real *8, dimension(:), allocatable parm::deplagch real *8, dimension(:), allocatable parm::depgrach real *8, dimension(:), allocatable parm::depgrafp real *8, dimension(:), allocatable parm::grast real *8, dimension(:), allocatable parm::depprch real *8, dimension(:), allocatable parm::depprfp real *8, dimension(:), allocatable parm::prf

real *8, dimension(:), allocatable **parm::r2adj** real *8, dimension(:), allocatable **parm::spcon**

linear parameter for calculating sediment reentrained in channel sediment routing

real *8, dimension(:), allocatable parm::spexp

exponent parameter for calculating sediment reentrained in channel sediment routing

- real *8, dimension(:), allocatable parm::sanst
- real *8, dimension(:), allocatable parm::silst
- real *8, dimension(:), allocatable parm::clast
- real *8, dimension(:), allocatable parm::sagst
- real *8, dimension(:), allocatable parm::lagst
- real *8, dimension(:), allocatable parm::pot san
- real *8, dimension(:), allocatable parm::pot sil
- real *8, dimension(:), allocatable parm::pot_cla
- real *8, dimension(:), allocatable parm::pot_sag
- real *8, dimension(:), allocatable parm::pot_lag
- real *8, dimension(:), allocatable parm::potsani
- real *8, dimension(:), allocatable parm::potsili
- real *8, dimension(:), allocatable parm::potclai
- real *8, dimension(:), allocatable parm::potsagi
- real *8, dimension(:), allocatable parm::potlagi
- real *8, dimension(:), allocatable parm::sanyld
- real *8, dimension(:), allocatable parm::silyld
- real *8, dimension(:), allocatable parm::clayld
- real *o, differision(.), allocatable parm...clayid
- real *8, dimension(:), allocatable parm::sagyld
 real *8, dimension(:), allocatable parm::lagyld
- real *8, dimension(:), allocatable parm::grayId
- real *8, dimension(:), allocatable parm::res san
- real *8, dimension(:), allocatable parm::res sil
- real *8, dimension(:), allocatable parm::res_cla
- real *8, dimension(:), allocatable parm::res_sag
- real *8, dimension(:), allocatable parm::res_lag
- real *8, dimension(:), allocatable parm::res_gra
- real *8, dimension(:), allocatable parm::pnd san
- real *8, dimension(:), allocatable parm::pnd_sil
- real *8, dimension(:), allocatable parm::pnd_cla
- real *8, dimension(:), allocatable parm::pnd_sag
- real *8, dimension(:), allocatable parm::pnd_lag
- real *8, dimension(:), allocatable parm::wet_san
- real *8, dimension(:), allocatable parm::wet_sil
- real *8, dimension(:), allocatable parm::wet_cla
- real *8, dimension(:), allocatable parm::wet_lag
- real *8, dimension(:), allocatable parm::wet sag
- real *8 parm::ressano
- real *8 parm::ressilo
- real *8 parm::resclao
- real *8 parm::ressago
- real *8 parm::reslago
- real *8 parm::resgrao
- real *8 parm::ressani
- real *8 parm::ressili
- real *8 parm::resclai
- real *8 parm::ressagi
- real *8 parm::reslagi
- real *8 parm::resgrai
- real *8 parm::potsano
- real *8 parm::potsilo

- real *8 parm::potclao
- · real *8 parm::potsago
- real *8 parm::potlago
- real *8 parm::pndsanin
- real *8 parm::pndsilin
- real *8 parm::pndclain
- real *8 parm::pndsagin
- real *8 parm::pndlagin
- real *8 parm::pndsano
- real *8 parm::pndsilo
- real *8 parm::pndclao
- real *8 parm::pndsago
- real *8 parm::pndlago
- real *8, dimension(:), allocatable parm::ch_di
- real *8, dimension(:), allocatable parm::ch_erod
- real *8, dimension(:), allocatable parm::ch | 12
- real *8, dimension(:), allocatable parm::ch_cov
- real *8, dimension(:), allocatable parm::ch_cov1
- real *8, dimension(:), allocatable parm::ch_cov2
- real *8, dimension(:), allocatable parm::ch_bnk_bd
- real *8, dimension(:), allocatable parm::ch_bed_bd
- real *8, dimension(:), allocatable parm::ch bnk kd
- real *8, dimension(:), allocatable parm::ch bed kd
- real *8, dimension(:), allocatable parm::ch_bnk_d50
- real *8, dimension(:), allocatable parm::ch bed d50
- real *8, dimension(:), allocatable parm::tc_bed
- real *8, dimension(:), allocatable parm::tc_bnk
- integer, dimension(:), allocatable parm::ch eqn
- real *8, dimension(:), allocatable parm::chpst conc
- real *8, dimension(:), allocatable parm::chpst_rea
- real *8, dimension(:), allocatable parm::chpst_vol
- real *8, dimension(:), allocatable parm::chpst_koc
- real *8, dimension(:), allocatable parm::chpst_stl
- real *8, dimension(:), allocatable parm::chpst_rsp
- real *8, dimension(:), allocatable parm::chpst_mix
- real *8, dimension(:), allocatable parm::sedpst_conc
- real *8, dimension(:), allocatable parm::ch_wdr
- real *8, dimension(:), allocatable parm::sedpst_rea
- real *8, dimension(:), allocatable parm::sedpst_bry
- real *8, dimension(:), allocatable parm::sedpst_act
- real *8, dimension(:), allocatable parm::rch cbod
- real *8, dimension(:), allocatable parm::rch_bactlp
- real *8, dimension(:), allocatable parm::chside
- real *8, dimension(:), allocatable parm::rs1
- real *8, dimension(:), allocatable parm::rs2
- real *8, dimension(:), allocatable parm::rs3
- real *8, dimension(:), allocatable parm::rs4
- real *8, dimension(:), allocatable parm::rs5
- real *8, dimension(:), allocatable parm::rs6
- real *8, dimension(:), allocatable parm::rs7
- real *8, dimension(:), allocatable parm::rk1
- real *8, dimension(:), allocatable parm::rk2
- real *8, dimension(:), allocatable parm::rk3
- real *8, dimension(:), allocatable parm::rk4
- real *8, dimension(:), allocatable parm::rk5

```
    real *8, dimension(:), allocatable parm::bc1

      rate constant for biological oxidation of NH3 to NO2 in reach at 20 deg C (1/hr)

    real *8, dimension(:), allocatable parm::bc2

      rate constant for biological oxidation of NO2 to NO3 in reach at 20 deg C (1/hr)

    real *8, dimension(:), allocatable parm::bc3

      rate constant for hydrolysis of organic N to ammonia in reach at 20 deg C (1/hr)

    real *8. dimension(:), allocatable parm::bc4

      rate constant for the decay of organic P to dissolved P in reach at 20 deg C (1/hr)

    real *8, dimension(:), allocatable parm::rk6

• real *8, dimension(:), allocatable parm::ammonian

    real *8, dimension(:), allocatable parm::orig sedpstconc

    real *8, dimension(:,:), allocatable parm::wurch

• integer, dimension(:), allocatable parm::icanal

    integer, dimension(:), allocatable parm::itb

    real *8, dimension(:), allocatable parm::ch_revap

• real *8, dimension(:), allocatable parm::dep_chan

    real *8, dimension(:), allocatable parm::harg_petco

      coefficient related to radiation used in hargreaves eq (range: 0.0019 - 0.0032)

    real *8, dimension(:), allocatable parm::subfr_nowtr

    real *8, dimension(:), allocatable parm::cncoef sub

      soil water depletion coefficient used in the new (modified curve number method) same as soil index coeff used in
      APEX range: 0.5 - 2.0

    real *8, dimension(:), allocatable parm::dr_sub

    real *8, dimension(:), allocatable parm::wcklsp

    real *8, dimension(:), allocatable parm::sub fr

    real *8, dimension(:), allocatable parm::sub_minp

    real *8, dimension(:), allocatable parm::sub sw

    real *8, dimension(:), allocatable parm::sub_sumfc

    real *8, dimension(:), allocatable parm::sub_gwno3

  real *8, dimension(:), allocatable parm::sub gwsolp

    real *8, dimension(:), allocatable parm::co2

      CO2 concentration (ppmv)

    real *8, dimension(:), allocatable parm::sub_km

      area of subbasin in square kilometers (km<sup>2</sup>)
• real *8, dimension(:), allocatable parm::sub_tc

    real *8, dimension(:), allocatable parm::wlat

    real *8, dimension(:), allocatable parm::sub_pet

    real *8, dimension(:), allocatable parm::welev

    real *8, dimension(:), allocatable parm::sub_orgn

    real *8, dimension(:), allocatable parm::sub_orgp

real *8, dimension(:), allocatable parm::sub_bd

    real *8, dimension(:), allocatable parm::sub wtmp

    real *8, dimension(:), allocatable parm::sub sedpa

    real *8, dimension(:), allocatable parm::sub sedps

    real *8, dimension(:), allocatable parm::sub_minpa

    real *8, dimension(:), allocatable parm::sub_minps

• real *8, dimension(:), allocatable parm::dayImn

    real *8, dimension(:), allocatable parm::latcos

• real *8, dimension(:), allocatable parm::latsin

    real *8, dimension(:), allocatable parm::phutot
```

real *8, dimension(:), allocatable parm::plaps

```
precipitation lapse rate: precipitation change due to change in elevation (mm H2O/km)

    real *8, dimension(:), allocatable parm::tlaps

     temperature lapse rate: temperature change due to change in elevation (deg C/km)

    real *8, dimension(:), allocatable parm::tmp an

    real *8, dimension(:), allocatable parm::sub precip

    real *8, dimension(:), allocatable parm::pcpdays

  real *8, dimension(:), allocatable parm::rcn_sub

    real *8, dimension(:), allocatable parm::rammo_sub

    real *8. dimension(:), allocatable parm::atmo_day

    real *8, dimension(:), allocatable parm::sub snom

    real *8, dimension(:), allocatable parm::sub_qd

    real *8, dimension(:), allocatable parm::sub_sedy

• real *8, dimension(:), allocatable parm::sub_tran

    real *8, dimension(:), allocatable parm::sub_no3

    real *8, dimension(:), allocatable parm::sub latno3

    real *8, dimension(:,:), allocatable parm::sub_sftmp

     snowfall temperature for subbasin(:). Mean air temperature at which precip is equally likely to be rain as snow/freezing
     rain (range: -5.0/5.0) (deg C)

    real *8, dimension(:,:), allocatable parm::sub_smtmp

     snow melt base temperature for subbasin(:) mean air temperature at which snow melt will occur (range: -5.0/5.0)
     (dea C)

    real *8, dimension(:,:), allocatable parm::sub_timp

     snow pack temperature lag factor (0-1) (none)

    real *8, dimension(:), allocatable parm::sub_tileno3

    real *8, dimension(:), allocatable parm::sub solp

  real *8, dimension(:), allocatable parm::sub_subp

    real *8, dimension(:), allocatable parm::sub_etday

    real *8, dimension(:), allocatable parm::sub_elev

     average elevation of subbasin (m)

    real *8, dimension(:), allocatable parm::sub wyld

    real *8, dimension(:), allocatable parm::sub_surfq

  real *8, dimension(:), allocatable parm::gird

    real *8, dimension(:), allocatable parm::sub_gwq

• real *8, dimension(:), allocatable parm::sub sep

    real *8, dimension(:), allocatable parm::sub chl

    real *8, dimension(:), allocatable parm::sub cbod

    real *8, dimension(:), allocatable parm::sub dox

    real *8, dimension(:), allocatable parm::sub_solpst

    real *8, dimension(:), allocatable parm::sub sorpst

    real *8, dimension(:), allocatable parm::sub_yorgn

    real *8, dimension(:), allocatable parm::sub_yorgp

    real *8, dimension(:), allocatable parm::sub_lat

     latitude of subbasin (degrees)

    real *8, dimension(:), allocatable parm::sub_bactp

    real *8, dimension(:), allocatable parm::sub bactlp

    real *8, dimension(:), allocatable parm::sub latq

    real *8, dimension(:), allocatable parm::sub gwq d

    real *8, dimension(:), allocatable parm::sub_tileq

    real *8, dimension(:), allocatable parm::sub_vaptile

    real *8, dimension(:), allocatable parm::sub_dsan

• real *8, dimension(:), allocatable parm::sub dsil
real *8, dimension(:), allocatable parm::sub_dcla

    real *8, dimension(:), allocatable parm::sub dsag
```

real *8, dimension(:), allocatable parm::sub_dlag

- real *8 parm::vap tile
- real *8, dimension(:), allocatable parm::wnan
- real *8, dimension(:,:), allocatable parm::sol_stpwt
- real *8, dimension(:,:), allocatable parm::sub_pst
- real *8, dimension(:,:), allocatable parm::sub_hhqd
- real *8, dimension(:,:), allocatable parm::sub_hhwtmp
- real *8, dimension(:,:), allocatable parm::huminc

monthly humidity adjustment. Daily values for relative humidity within the month are rasied or lowered by the specified amount (used in climate change studies) (none)

real *8, dimension(:,:), allocatable parm::radinc

monthly solar radiation adjustment. Daily radiation within the month is raised or lowered by the specified amount. (used in climate change studies) (MJ/m^2)

real *8, dimension(:,:), allocatable parm::rfinc

monthly rainfall adjustment. Daily rainfall within the month is adjusted to the specified percentage of the original value (used in climate change studies)(%)

• real *8, dimension(:,:), allocatable parm::tmpinc

monthly temperature adjustment. Daily maximum and minimum temperatures within the month are raised or lowered by the specified amount (used in climate change studies) (deg C)

real *8, dimension(:), allocatable parm::ch k1

effective hydraulic conductivity of tributary channel alluvium (mm/hr)

- real *8, dimension(:), allocatable parm::ch_k2
- real *8, dimension(:,:), allocatable parm::elevb

elevation at the center of the band (m)

real *8, dimension(:,:), allocatable parm::elevb_fr

fraction of subbasin area within elevation band (the same fractions should be listed for all HRUs within the subbasin) (none)

- real *8, dimension(:,:), allocatable parm::wndav
- real *8, dimension(:), allocatable parm::ch_n1

Manning's "n" value for the tributary channels (none)

- real *8, dimension(:), allocatable parm::ch_n2
- real *8, dimension(:), allocatable parm::ch_s1

average slope of tributary channels (m/m)

- real *8, dimension(:), allocatable parm::ch s2
- real *8, dimension(:), allocatable parm::ch_w1

average width of tributary channels (m)

- real *8, dimension(:), allocatable parm::ch_w2
- real *8, dimension(:,:), allocatable parm::dewpt
- real *8, dimension(:,:), allocatable parm::amp_r
- real *8, dimension(:,:), allocatable parm::solarav
- real *8, dimension(:,:), allocatable parm::tmpstdmx
- real *8, dimension(:,:), allocatable parm::tmpstdmn
- real *8, dimension(:,:), allocatable parm::pcf
- real *8, dimension(:,:), allocatable parm::tmpmn
- real *8, dimension(:,:), allocatable parm::tmpmx
- real *8, dimension(:,:), allocatable parm::otmpstdmn
- real *8, dimension(:,:), allocatable parm::otmpmn
- real *8, dimension(:,:), allocatable parm::otmpmx
- real *8, dimension(:,:), allocatable parm::otmpstdmx
- real *8, dimension(:,:), allocatable parm::ch_erodmo
- real *8, dimension(:,:), allocatable parm::uh
- real *8, dimension(:,:), allocatable parm::hqdsave
- real *8, dimension(:,:), allocatable parm::hsdsave
- real *8, dimension(:,:), allocatable parm::pr_w1
- real *8, dimension(:,:), allocatable parm::pr_w2

```
    real *8, dimension(:,:), allocatable parm::pr_w3

 real *8, dimension(:,:,:), allocatable parm::pcp_stat
  real *8, dimension(:,:), allocatable parm::opr_w1

    real *8, dimension(:,:), allocatable parm::opr_w2

    real *8, dimension(:,:), allocatable parm::opr w3

  real *8, dimension(:,:,:), allocatable parm::opcp_stat
  integer, dimension(:), allocatable parm::hrutot
  integer, dimension(:), allocatable parm::hru1
  integer, dimension(:), allocatable parm::ireg
 integer, dimension(:), allocatable parm::ihgage
     subbasin relative humidity data code (none)

    integer, dimension(:), allocatable parm::isgage

     subbasin radiation gage data code (none)
• integer, dimension(:), allocatable parm::iwgage
     subbasin wind speed gage data code (none)
• integer, dimension(:), allocatable parm::subgis
     GIS code printed to output files (output.sub) (none.

    integer, dimension(:), allocatable parm::irgage

     subbasin rain gage data code (none)

    integer, dimension(:), allocatable parm::itgage

     subbasin temp gage data code (none)
  integer, dimension(:), allocatable parm::fcst reg
  integer, dimension(:), allocatable parm::irelh
  real *8, dimension(:,:), allocatable parm::sol_aorgn
  real *8, dimension(:,:), allocatable parm::sol tmp
real *8, dimension(:,:), allocatable parm::sol_fon
  real *8, dimension(:.:), allocatable parm::sol awc
  real *8, dimension(:,:), allocatable parm::sol_prk
• real *8, dimension(:,:), allocatable parm::volcr

    real *8, dimension(:,:), allocatable parm::pperco_sub

     subbasin phosphorus percolation coefficient. Ratio of soluble phosphorus in surface to soluble phosphorus in perco-

    real *8, dimension(:,:), allocatable parm::sol_actp

  real *8, dimension(:,:), allocatable parm::sol_stap
 real *8, dimension(:,:), allocatable parm::conv wt

    real *8, dimension(:,:), allocatable parm::sol_solp

     soluble P concentration in top soil layer (mg P/kg soil)
  real *8, dimension(:,:), allocatable parm::sol_ul
  real *8, dimension(:,:), allocatable parm::sol_fc
  real *8, dimension(:,:), allocatable parm::crdep
  real *8, dimension(:,:), allocatable parm::sol z
  real *8, dimension(:.:), allocatable parm::sol up

    real *8, dimension(:,:), allocatable parm::sol_bd

real *8, dimension(:,:), allocatable parm::sol_st
  real *8, dimension(:,:), allocatable parm::flat
  real *8, dimension(:,:), allocatable parm::sol_nh3

    real *8, dimension(:,:), allocatable parm::sol hk

  real *8, dimension(:,:), allocatable parm::sol_clay
real *8, dimension(:,:), allocatable parm::sol_ec
 real *8, dimension(:,:), allocatable parm::sol_orgn
     organic N concentration in top soil layer (mg N/kg soil)
 real *8, dimension(:,:), allocatable parm::sol por
 real *8, dimension(:,:), allocatable parm::sol_wp
```

```
organic P concentration in top soil layer (mg P/kg soil)
real *8, dimension(:,:), allocatable parm::sol hum
real *8, dimension(:,:), allocatable parm::sol wpmm
real *8, dimension(:,:), allocatable parm::sol no3
   concentration of nitrate in soil layer (mg N/kg)
real *8, dimension(:,:), allocatable parm::sol_k
real *8, dimension(:,:), allocatable parm::sol cbn
real *8, dimension(:,:), allocatable parm::sol rsd
real *8, dimension(:,:), allocatable parm::sol_fop
real *8, dimension(:,:), allocatable parm::sol silt
real *8, dimension(:,:), allocatable parm::sol_sand
real *8, dimension(:,:), allocatable parm::sol rock
real *8, dimension(:,:), allocatable parm::orig solno3
real *8, dimension(:,:), allocatable parm::orig_solorgn
real *8, dimension(:,:), allocatable parm::orig solsolp
real *8, dimension(:,:), allocatable parm::orig solorgp
real *8, dimension(:,:), allocatable parm::orig_soltmp
real *8, dimension(:,:), allocatable parm::orig solrsd
real *8, dimension(:,:), allocatable parm::orig_solfop
real *8, dimension(:,:), allocatable parm::orig solfon
real *8, dimension(:,:), allocatable parm::orig solaorgn
real *8, dimension(:,:), allocatable parm::orig_solst
real *8, dimension(:,:), allocatable parm::orig solactp
real *8, dimension(:,:), allocatable parm::orig_solstap
real *8, dimension(:,:), allocatable parm::orig volcr
real *8, dimension(:,:), allocatable parm::conk
real *8, dimension(:,:,:), allocatable parm::sol_pst
   sol pst(:,:,1) pesticide concentration in soil (mg/kg)
real *8, dimension(:,:,:), allocatable parm::sol kp
real *8, dimension(:,:,:), allocatable parm::orig_solpst
real *8, dimension(:), allocatable parm::velsetIr
real *8, dimension(:), allocatable parm::velsetlp
real *8, dimension(:), allocatable parm::br1
real *8, dimension(:), allocatable parm::res k
real *8, dimension(:), allocatable parm::lkpst_conc
real *8, dimension(:), allocatable parm::evrsv
real *8, dimension(:), allocatable parm::res evol
real *8, dimension(:), allocatable parm::res_pvol
real *8, dimension(:), allocatable parm::res vol
real *8, dimension(:), allocatable parm::res_psa
real *8, dimension(:), allocatable parm::lkpst_rea
real *8, dimension(:), allocatable parm::lkpst vol
real *8, dimension(:), allocatable parm::br2
real *8, dimension(:), allocatable parm::res_rr
real *8, dimension(:), allocatable parm::res_sed
real *8, dimension(:), allocatable parm::lkpst koc
real *8, dimension(:), allocatable parm::lkpst stl
real *8, dimension(:), allocatable parm::lkpst_rsp
real *8, dimension(:), allocatable parm::lkpst_mix
real *8, dimension(:), allocatable parm::lkspst conc
real *8, dimension(:), allocatable parm::lkspst_rea
real *8, dimension(:), allocatable parm::theta n
real *8, dimension(:), allocatable parm::theta p
```

real *8, dimension(:,:), allocatable parm::sol orgp

- real *8, dimension(:), allocatable parm::con_nirr
- real *8, dimension(:), allocatable parm::con_pirr
- real *8, dimension(:), allocatable parm::lkspst_bry
- real *8, dimension(:), allocatable parm::lkspst_act
- real *8, dimension(:), allocatable parm::sed_stlr
- real *8, dimension(7) parm::resdata
- real *8, dimension(:), allocatable parm::wurtnf
- real *8, dimension(:), allocatable parm::res_nsed
- real *8, dimension(:), allocatable parm::chlar
- real *8, dimension(:), allocatable parm::res_orgn
- real *8, dimension(:), allocatable parm::res_orgp
- real *8, dimension(:), allocatable parm::res_no3
- real *8, dimension(:), allocatable parm::res_solp
- real *8, dimension(:), allocatable parm::res_chla
- real *8, dimension(:), allocatable parm::res_seci
- real *8, dimension(:), allocatable parm::res esa
- real *8, dimension(:), allocatable parm::seccir
- real *8, dimension(:), allocatable parm::res no2
- real *8, dimension(:), allocatable parm::res_nh3
- real *8, dimension(:), allocatable parm::res_bactp
- real *8, dimension(:), allocatable parm::res_bactlp
- real *8, dimension(:), allocatable parm::oflowmn_fps
- real *8, dimension(:), allocatable parm::starg fps
- real *8, dimension(:), allocatable parm::weirc
- real *8, dimension(:), allocatable parm::weirk
- real *8, dimension(:), allocatable parm::weirw
- real *8, dimension(:), allocatable parm::acoef
- real *8, dimension(:), allocatable parm::bcoef
- real *8, dimension(:), allocatable parm::ccoef
- real *8, dimension(:), allocatable parm::orig_resvol
- real *8, dimension(:), allocatable parm::orig_ressed
- real *8, dimension(:), allocatable parm::orig_lkpstconc
- real *8, dimension(:), allocatable parm::orig_lkspstconc
- real *8, dimension(:), allocatable parm::orig_ressolp
- real *8, dimension(:), allocatable parm::orig_resorgp
- real *8, dimension(:), allocatable parm::orig_resno3
- real *8, dimension(:), allocatable parm::orig_resno2
- real *8, dimension(:), allocatable parm::orig_resnh3
- real *8, dimension(:), allocatable parm::orig_resorgn
- real *8, dimension(:,:), allocatable parm::starg
- real *8, dimension(:,:), allocatable parm::oflowmx
- real *8, dimension(:,:), allocatable parm::oflowmn
- real *8, dimension(:,:), allocatable parm::psetIr
- real *8, dimension(:,:), allocatable parm::nsetIr
- real *8, dimension(:,:), allocatable parm::wuresn
- real *8, dimension(:,:,:), allocatable parm::res_out
- integer, dimension(:), allocatable parm::ires1
- integer, dimension(:), allocatable parm::ires2
- integer, dimension(:), allocatable parm::res_sub
- · integer, dimension(:), allocatable parm::iresco
- · integer, dimension(:), allocatable parm::mores
- integer, dimension(:), allocatable parm::iyres
- integer, dimension(:), allocatable parm::iflod1r
- integer, dimension(:), allocatable parm::iflod2r
- integer, dimension(:), allocatable parm::ndtargr

```
    real *8, dimension(:), allocatable parm::ap_ef

      application efficiency (0-1) (none)

    real *8, dimension(:), allocatable parm::decay f

      exponential of the rate constant for degradation of the pesticide on foliage (none)

    real *8, dimension(:), allocatable parm::skoc

      soil adsorption coefficient normalized for soil organic carbon content ((mg/kg)/(mg/L))
• real *8, dimension(:), allocatable parm::decay s
      exponential of the rate constant for degradation of the pesticide in soil (none)

    real *8, dimension(:), allocatable parm::hlife f

     half-life of pesticide on foliage (days)

    real *8, dimension(:), allocatable parm::hlife s

     half-life of pesticide in soil (days)

    real *8, dimension(:), allocatable parm::pst_wof

      fraction of pesticide on foliage which is washed-off by a rainfall event (none)

    real *8, dimension(:), allocatable parm::pst wsol

      solubility of chemical in water (mg/L (ppm))
• real *8, dimension(:), allocatable parm::irramt
• real *8, dimension(:), allocatable parm::phusw
  real *8, dimension(:), allocatable parm::phusw_nocrop
  integer, dimension(:), allocatable parm::pstflg
      flag for types of pesticide used in watershed array location is pesticide ID number
     0: pesticide not used
      1: pesticide used

    integer, dimension(:), allocatable parm::nope

      sequence number of pesticide in NPNO(:) (none)
  integer, dimension(:), allocatable parm::nop
integer, dimension(:), allocatable parm::yr_skip

    integer, dimension(:), allocatable parm::isweep

• integer, dimension(:), allocatable parm::icrmx

    integer, dimension(:), allocatable parm::nopmx

    integer, dimension(:,:), allocatable parm::mgtop

    integer, dimension(:,:), allocatable parm::idop

  integer, dimension(:,:), allocatable parm::mgt1iop
• integer, dimension(:,:), allocatable parm::mgt2iop

    integer, dimension(:,:), allocatable parm::mgt3iop

    real *8, dimension(:,:), allocatable parm::mgt4op

    real *8, dimension(:,:), allocatable parm::mgt5op

    real *8, dimension(:,:), allocatable parm::mgt6op

    real *8, dimension(:,:), allocatable parm::mgt7op

  real *8, dimension(:,:), allocatable parm::mgt8op

    real *8, dimension(:,:), allocatable parm::mgt9op

    real *8, dimension(:,:), allocatable parm::mgt10iop

    real *8, dimension(:,:), allocatable parm::phu op

    real *8, dimension(:), allocatable parm::cnyld

      fraction of nitrogen in yield (kg N/kg yield)

    real *8, dimension(:), allocatable parm::rsdco pl

      plant residue decomposition coefficient. The fraction of residue which will decompose in a day assuming optimal
      moisture, temperature, C:N ratio, and C:P ratio (none)

    real *8, dimension(:), allocatable parm::wac21

      1st shape parameter for radiation use efficiency equation (none)
  real *8, dimension(:), allocatable parm::wac22
      2nd shape parameter for radiation use efficiency equation (none)

    real *8, dimension(:), allocatable parm::alai min
```

```
minimum LAI during winter dormant period (m^2/m^2)

    real *8, dimension(:), allocatable parm::leaf1

      1st shape parameter for leaf area development equation (none)

    real *8, dimension(:), allocatable parm::leaf2

      2nd shape parameter for leaf area development equation (none)
• real *8, dimension(:), allocatable parm::wsyf
      Value of harvest index between 0 and HVSTI which represents the lowest value expected due to water stress
      ((kg/ha)/(kg/ha))

    real *8, dimension(:), allocatable parm::bio e

     biomass-energy ratio. The potential (unstressed) growth rate per unit of intercepted photosynthetically active
     radiation.((kg/ha)/(MJ/m**2))

    real *8, dimension(:), allocatable parm::hvsti

     harvest index: crop yield/aboveground biomass ((kg/ha)/(kg/ha))

    real *8, dimension(:), allocatable parm::t_base

     minimum temperature for plant growth (deg C)

    real *8, dimension(:), allocatable parm::t_opt

      optimal temperature for plant growth (deg C)

    real *8, dimension(:), allocatable parm::chtmx

      maximum canopy height (m)

    real *8, dimension(:), allocatable parm::cvm

      natural log of USLE_C (none)

    real *8, dimension(:), allocatable parm::gsi

      maximum stomatal conductance (m/s)

    real *8, dimension(:), allocatable parm::vpd2

      rate of decline in stomatal conductance per unit increase in vapor pressure deficit ((m/s)*(1/kPa))

    real *8, dimension(:), allocatable parm::wavp

      rate of decline in radiation use efficiency as a function of vapor pressure deficit (none)
• real *8, dimension(:), allocatable parm::bio leaf
     fraction of leaf/needle biomass that drops during dormancy (for trees only) (none)
• real *8, dimension(:), allocatable parm::blai
     maximum (potential) leaf area index (none)

    real *8, dimension(:), allocatable parm::cpyld

      fraction of phosphorus in yield (kg P/kg yield)

    real *8, dimension(:), allocatable parm::dlai

      fraction of growing season when leaf area declines (none)

    real *8, dimension(:), allocatable parm::rdmx

      maximum root depth (m)

    real *8, dimension(:), allocatable parm::bio n1

      1st shape parameter for plant N uptake equation (none)

    real *8, dimension(:), allocatable parm::bio_n2

      2nd shape parameter for plant N uptake equation (none)

    real *8, dimension(:), allocatable parm::bio p1

      1st shape parameter for plant P uptake equation (none)

    real *8, dimension(:), allocatable parm::bio_p2

      2st shape parameter for plant P uptake equation (none)

    real *8, dimension(:), allocatable parm::bm dieoff

      fraction above ground biomass that dies off at dormancy (fraction)

    real *8, dimension(:), allocatable parm::bmx_trees

real *8, dimension(:), allocatable parm::ext_coef
  real *8, dimension(:), allocatable parm::rsr1
```

initial root to shoot ratio at the beg of growing season

```
    real *8, dimension(:), allocatable parm::rsr2

      root to shoot ratio at the end of the growing season

    real *8, dimension(:), allocatable parm::pltnfr1

      nitrogen uptake parameter #1: normal fraction of N in crop biomass at emergence (kg N/kg biomass)

    real *8, dimension(:), allocatable parm::pltnfr2

      nitrogen uptake parameter #2: normal fraction of N in crop biomass at 0.5 maturity (kg N/kg biomass)

    real *8, dimension(:), allocatable parm::pltnfr3

      nitrogen uptake parameter #3: normal fraction of N in crop biomass at maturity (kg N/kg biomass)

    real *8, dimension(:), allocatable parm::pltpfr1

      phosphorus uptake parameter #1: normal fraction of P in crop biomass at emergence (kg P/kg biomass)

    real *8, dimension(:), allocatable parm::pltpfr2

      phosphorus uptake parameter #2: normal fraction of P in crop biomass at 0.5 maturity (kg P/kg biomass)

    real *8, dimension(:), allocatable parm::pltpfr3

      phosphorus uptake parameter #3: normal fraction of P in crop biomass at maturity (kg P/kg biomass)

    integer, dimension(:), allocatable parm::idc

      crop/landcover category:
      1 warm season annual legume
      2 cold season annual legume
      3 perennial legume
      4 warm season annual
      5 cold season annual
      6 perennial
      7 trees
integer, dimension(:), allocatable parm::mat_yrs
  real *8, dimension(:), allocatable parm::bactpdb
      concentration of persistent bacteria in manure (fertilizer) (cfu/g manure)

    real *8, dimension(:), allocatable parm::fminn

      fraction of mineral N (NO3 + NH3) (kg minN/kg fert)

    real *8, dimension(:), allocatable parm::forgn

      fraction of organic N (kg orgN/kg fert)

    real *8, dimension(:), allocatable parm::forgp

      fraction of organic P (kg orgP/kg fert)

    real *8, dimension(:), allocatable parm::bactkddb

      bacteria partition coefficient (none):
      1: all bacteria in solution
      0: all bacteria sorbed to soil particles

    real *8, dimension(:), allocatable parm::bactlpdb

      concentration of less persistent bacteria in manure (fertilizer) (cfu/g manure)

    real *8, dimension(:), allocatable parm::fminp

      fraction of mineral P (kg minP/kg fert)

    real *8, dimension(:), allocatable parm::fnh3n

      fraction of NH3-N in mineral N (kg NH3-N/kg minN)

    character(len=8), dimension(200) parm::fertnm

      name of fertilizer
• real *8, dimension(:), allocatable parm::curbden
      curb length density in HRU (km/ha)

    real *8, dimension(:), allocatable parm::dirtmx

      maximum amount of solids allowed to build up on impervious surfaces (kg/curb km)

    real *8, dimension(:), allocatable parm::fimp

      fraction of HRU area that is impervious (both directly and indirectly connected)(fraction)

    real *8, dimension(:), allocatable parm::urbcoef

      wash-off coefficient for removal of constituents from an impervious surface (1/mm)
```

```
    real *8, dimension(:), allocatable parm::thalf

      time for the amount of solids on impervious areas to build up to 1/2 the maximum level (days)

    real *8, dimension(:), allocatable parm::tnconc

     concentration of total nitrogen in suspended solid load from impervious areas (mg N/kg sed)

    real *8, dimension(:), allocatable parm::tno3conc

     concentration of NO3-N in suspended solid load from impervious areas (mg NO3-N/kg sed)

    real *8, dimension(:), allocatable parm::tpconc

     concentration of total phosphorus in suspended solid load from impervious areas (mg P/kg sed)

    real *8, dimension(:), allocatable parm::fcimp

     fraction of HRU area that is classified as directly connected impervious (fraction)

    real *8, dimension(:), allocatable parm::urbcn2

      SCS curve number for moisture condition II in impervious areas (none)
real *8 parm::sweepeff

    real *8 parm::frt kg

    real *8 parm::pst_dep

real *8 parm::fr_curb
• real *8, dimension(:), allocatable parm::ranrns_hru

    integer, dimension(:), allocatable parm::itill

• real *8, dimension(:), allocatable parm::deptil
      depth of mixing caused by operation (mm)
• real *8, dimension(:), allocatable parm::effmix
      mixing efficiency of operation (none)

    real *8, dimension(:), allocatable parm::ranrns

      random roughness of a given tillage operation (mm)

    character(len=8), dimension(550) parm::tillnm

      8-character name for the tillage operation

    real *8, dimension(:), allocatable parm::rnum1s

      For ICODES equal to (none)
      0,1,3,5,9: not used
     2: Fraction of flow in channel
      4: amount of water transferred (as defined by INUM4S)
      7,8,10,11: drainage area in square kilometers associated with the record file.
• real *8, dimension(:), allocatable parm::hyd_dakm

    real *8, dimension(:,:), allocatable parm::varoute

    real *8, dimension(:,:), allocatable parm::shyd

• real *8, dimension(:,:), allocatable parm::vartran
• real *8, dimension(:,:,:), allocatable parm::hhvaroute
· integer, dimension(:), allocatable parm::icodes
     routing command code (none):
     0 = finish
      1 = subbasin
     2 = route
     3 = routres
      4 = transfer
     5 = add
     6 = rechour
      7 = recmon
     8 = recyear
     9 = save
      10 = recday
      11 = reccnst
      12 = structure
```

13 = apex 14 = saveconc

15 =

• integer, dimension(:), allocatable parm::ihouts For ICODES equal to (none) 0: not used 1,2,3,5,7,8,10,11: hydrograph storage location number 4: departure type (1=reach, 2=reservoir) 9: hydrograph storage location of data to be printed to event file 14:hydrograph storage location of data to be printed to saveconc file. • integer, dimension(:), allocatable parm::inum1s For ICODES equal to (none) 0: not used 1: subbasin number 2: reach number 3: reservoir number 4: reach or res # flow is diverted from 5: hydrograph storage location of 1st dataset to be added 7,8,9,10,11,14: file number. • integer, dimension(:), allocatable parm::inum2s For ICODES equal to (none) 0,1,7,8,10,11: not used 2,3: inflow hydrograph storage location 4: destination type (1=reach, 2=reservoir) 5: hydrograph storage location of 2nd dataset to be added 9,14:print frequency (0=daily, 1=hourly) integer, dimension(:), allocatable parm::inum3s For ICODES equal to (none) 0,1,2,3,5,7,8,10,11: not used 4: destination number. Reach or reservoir receiving water 9: print format (0=normal, fixed format; 1=txt format for AV interface, recday) • integer, dimension(:), allocatable parm::inum4s For ICODES equal to (none) 0,2,3,5,7,8,9,10,11: not used 1: GIS code printed to output file (optional) 4: rule code governing transfer of water (1=fraction transferred out, 2=min volume or flow left, 3=exact amount trans-• integer, dimension(:), allocatable parm::inum5s • integer, dimension(:), allocatable parm::inum6s • integer, dimension(:), allocatable parm::inum7s • integer, dimension(:), allocatable parm::inum8s integer, dimension(:), allocatable parm::subed character(len=10), dimension(:), allocatable parm::recmonps character(len=10), dimension(:), allocatable parm::reccnstps character(len=5), dimension(:), allocatable parm::subnum • character(len=4), dimension(:), allocatable parm::hruno real *8, dimension(:), allocatable parm::grwat n real *8, dimension(:), allocatable parm::grwat i real *8, dimension(:), allocatable parm::grwat_l real *8, dimension(:), allocatable parm::grwat_w real *8, dimension(:), allocatable parm::grwat_d real *8, dimension(:), allocatable parm::grwat_s real *8, dimension(:), allocatable parm::grwat spcon real *8, dimension(:), allocatable parm::tc_gwat real *8, dimension(:), allocatable parm::pot_volmm • real *8, dimension(:), allocatable parm::pot_tilemm real *8, dimension(:), allocatable parm::pot_volxmm real *8, dimension(:), allocatable parm::pot_fr real *8, dimension(:), allocatable parm::pot tile

real *8, dimension(:), allocatable parm::pot_vol

real *8, dimension(:), allocatable parm::potsa real *8, dimension(:), allocatable parm::pot_volx real *8, dimension(:), allocatable parm::potflwi real *8, dimension(:), allocatable parm::potsedi real *8, dimension(:), allocatable parm::wfsh real *8, dimension(:), allocatable parm::pot_nsed real *8, dimension(:), allocatable parm::pot_no3l real *8, dimension(:), allocatable parm::newrti real *8, dimension(:), allocatable parm::gwno3 real *8, dimension(:), allocatable parm::pot_sed real *8, dimension(:), allocatable parm::pot_no3 real *8, dimension(:), allocatable parm::fsred real *8, dimension(:), allocatable parm::tmpavp real *8, dimension(:), allocatable parm::evpot real *8, dimension(:), allocatable parm::dis_stream real *8, dimension(:), allocatable parm::pot solpl real *8, dimension(:), allocatable parm::sed_con real *8, dimension(:), allocatable parm::orgn_con real *8, dimension(:), allocatable parm::orgp_con real *8, dimension(:), allocatable parm::soln_con real *8, dimension(:), allocatable parm::solp con real *8, dimension(:), allocatable parm::pot_k real *8, dimension(:), allocatable parm::n_reduc real *8, dimension(:), allocatable parm::n_lag real *8, dimension(:), allocatable parm::n_ln real *8, dimension(:), allocatable parm::n_Inco integer, dimension(:), allocatable parm::ioper integer, dimension(:), allocatable parm::ngrwat real *8, dimension(:), allocatable parm::filterw real *8, dimension(:), allocatable parm::sumix real *8, dimension(:), allocatable parm::usle Is real *8, dimension(:), allocatable parm::phuacc real *8, dimension(:), allocatable parm::epco plant water uptake compensation factor (0-1) real *8, dimension(:), allocatable parm::esco soil evaporation compensation factor (0-1) real *8, dimension(:), allocatable parm::slsubbsn real *8, dimension(:), allocatable parm::hru_slp real *8, dimension(:), allocatable parm::erorgn real *8, dimension(:), allocatable parm::erorgp real *8, dimension(:), allocatable parm::biomix real *8, dimension(:), allocatable parm::pnd_seci real *8, dimension(:), allocatable parm::flowmin real *8, dimension(:), allocatable parm::divmax real *8, dimension(:), allocatable parm::canmx real *8, dimension(:), allocatable parm::usle p real *8, dimension(:), allocatable parm::lat_sed real *8, dimension(:), allocatable parm::rch_dakm real *8, dimension(:), allocatable parm::pnd_no3s real *8, dimension(:), allocatable parm::cn1 real *8, dimension(:), allocatable parm::cn2 real *8, dimension(:), allocatable parm::lat_ttime real *8, dimension(:), allocatable parm::flowfr

real *8, dimension(:), allocatable parm::sol_zmx

```
real *8, dimension(:), allocatable parm::tile ttime
real *8, dimension(:), allocatable parm::slsoil
real *8, dimension(:), allocatable parm::sed_stl
real *8, dimension(:), allocatable parm::gwminp
real *8, dimension(:), allocatable parm::sol cov
real *8, dimension(:), allocatable parm::yldanu
real *8, dimension(:), allocatable parm::pnd_solp
real *8, dimension(:), allocatable parm::pnd_no3
real *8, dimension(:), allocatable parm::ov n
real *8, dimension(:), allocatable parm::driftco
   coefficient for pesticide drift directly onto stream (none)
real *8, dimension(:), allocatable parm::pnd orgp
real *8, dimension(:), allocatable parm::pnd_orgn
real *8, dimension(:), allocatable parm::cn3
real *8, dimension(:), allocatable parm::twlpnd
real *8, dimension(:), allocatable parm::twlwet
real *8, dimension(:), allocatable parm::sol sumul
real *8, dimension(:), allocatable parm::pnd_chla
real *8, dimension(:), allocatable parm::hru_fr
real *8, dimension(:), allocatable parm::hru km
   area of HRU in square kilometers (km<sup>2</sup>)
real *8, dimension(:), allocatable parm::bio ms
real *8, dimension(:), allocatable parm::sol_alb
real *8, dimension(:), allocatable parm::strsw
real *8, dimension(:), allocatable parm::pnd_fr
real *8, dimension(:), allocatable parm::pnd_psa
real *8, dimension(:), allocatable parm::pnd pvol
real *8, dimension(:), allocatable parm::pnd k
real *8, dimension(:), allocatable parm::pnd_esa
real *8, dimension(:), allocatable parm::pnd evol
real *8, dimension(:), allocatable parm::pnd_vol
real *8, dimension(:), allocatable parm::yldaa
real *8, dimension(:), allocatable parm::pnd_sed
real *8, dimension(:), allocatable parm::pnd_nsed
real *8, dimension(:), allocatable parm::strsa
real *8, dimension(:), allocatable parm::dep_imp
real *8, dimension(:), allocatable parm::evpnd
real *8, dimension(:), allocatable parm::evwet
real *8, dimension(:), allocatable parm::wet_fr
real *8, dimension(:), allocatable parm::wet nsa
real *8, dimension(:), allocatable parm::wet nvol
real *8, dimension(:), allocatable parm::wet k
integer, dimension(:), allocatable parm::iwetgw
integer, dimension(:), allocatable parm::iwetile
real *8, dimension(:), allocatable parm::wet mxsa
real *8, dimension(:), allocatable parm::wet_mxvol
real *8, dimension(:), allocatable parm::wet_vol
real *8, dimension(:), allocatable parm::wet sed
real *8, dimension(:), allocatable parm::wet_nsed
real *8, dimension(:), allocatable parm::smx
real *8, dimension(:), allocatable parm::sci
real *8, dimension(:), allocatable parm::bp1
real *8, dimension(:), allocatable parm::bp2
real *8, dimension(:), allocatable parm::bw1
```

real *8, dimension(:), allocatable parm::bw2 real *8, dimension(:), allocatable parm::bactpq real *8, dimension(:), allocatable parm::bactp_plt real *8, dimension(:), allocatable parm::bactlp_plt real *8, dimension(:), allocatable parm::cnday real *8, dimension(:), allocatable parm::bactlpq real *8, dimension(:), allocatable parm::auto_eff real *8, dimension(:), allocatable parm::sol_sw real *8, dimension(:), allocatable parm::secciw real *8, dimension(:), allocatable parm::bactps real *8, dimension(:), allocatable parm::bactlps real *8, dimension(:), allocatable parm::tmpav real *8, dimension(:), allocatable parm::chlaw real *8, dimension(:), allocatable parm::sno_hru amount of water stored as snow (mm H2O) real *8, dimension(:), allocatable parm::subp real *8, dimension(:), allocatable parm::hru_ra real *8, dimension(:), allocatable parm::wet_orgn real *8, dimension(:), allocatable parm::tmx real *8, dimension(:), allocatable parm::tmn real *8, dimension(:), allocatable parm::rsdin real *8, dimension(:), allocatable parm::tmp_hi real *8, dimension(:), allocatable parm::tmp_lo real *8, dimension(:), allocatable parm::rwt real *8, dimension(:), allocatable parm::olai real *8, dimension(:), allocatable parm::usle_k real *8, dimension(:), allocatable parm::tconc real *8, dimension(:), allocatable parm::hru_rmx real *8, dimension(:), allocatable parm::usle_cfac real *8, dimension(:), allocatable parm::usle_eifac real *8, dimension(:), allocatable parm::anano3 real *8, dimension(:), allocatable parm::aird real *8, dimension(:), allocatable parm::t_ov real *8, dimension(:), allocatable parm::sol_sumfc real *8, dimension(:), allocatable parm::sol_avpor real *8, dimension(:), allocatable parm::usle mult real *8, dimension(:), allocatable parm::wet_orgp real *8, dimension(:), allocatable parm::aairr real *8, dimension(:), allocatable parm::cht real *8, dimension(:), allocatable parm::u10 real *8, dimension(:), allocatable parm::rhd real *8, dimension(:), allocatable parm::shallirr real *8, dimension(:), allocatable parm::deepirr real *8, dimension(:), allocatable parm::lai_aamx real *8, dimension(:), allocatable parm::ch_l1 longest tributary channel length in subbasin (km) real *8, dimension(:), allocatable parm::canstor real *8, dimension(:), allocatable parm::ovrlnd real *8, dimension(:), allocatable parm::wet_no3 real *8, dimension(:), allocatable parm::irr_mx real *8, dimension(:), allocatable parm::auto_wstr real *8, dimension(:), allocatable parm::cfrt_id

real *8, dimension(:), allocatable parm::cfrt_kg real *8, dimension(:), allocatable parm::cpst_id

- real *8, dimension(:), allocatable parm::cpst_kg
- real *8, dimension(:), allocatable parm::irr_asq
- real *8, dimension(:), allocatable parm::irr_eff
- real *8, dimension(:), allocatable parm::irrsq
- real *8, dimension(:), allocatable parm::irrefm
- real *8, dimension(:), allocatable parm::irrsalt
- real *8, dimension(:), allocatable parm::bio_eat
- real *8, dimension(:), allocatable parm::bio_trmp
- integer, dimension(:), allocatable parm::ifrt_freq
- integer, dimension(:), allocatable parm::ipst_freq
- integer, dimension(:), allocatable parm::irr_noa
- integer, dimension(:), allocatable parm::irr_sc
- integer, dimension(:), allocatable parm::irr_no
- integer, dimension(:), allocatable parm::imp_trig
- integer, dimension(:), allocatable parm::fert_days
- integer, dimension(:), allocatable parm::irr_sca
- integer, dimension(:), allocatable parm::pest_days
- integer, dimension(:), allocatable parm::idplt
- integer, dimension(:), allocatable parm::wstrs_id
- real *8, dimension(:,:), allocatable parm::bio aahv
- real *8, dimension(:), allocatable parm::cumei
- real *8, dimension(:), allocatable parm::cumeira
- real *8, dimension(:), allocatable parm::cumrt
- real *8, dimension(:), allocatable parm::cumrai
- real *8, dimension(:), allocatable parm::wet_solp
- real *8, dimension(:), allocatable parm::wet no3s
- real *8, dimension(:), allocatable parm::wet chla
- real *8, dimension(:), allocatable parm::wet_seci
- real *8, dimension(:), allocatable parm::pnd_no3g
- real *8, dimension(:), allocatable parm::pstsol
- real *8, dimension(:), allocatable parm::gwht
- real *8, dimension(:), allocatable parm::delay
- real *8, dimension(:), allocatable parm::gw_q
- real *8, dimension(:), allocatable parm::pnd_solpg
- real *8, dimension(:), allocatable parm::alpha_bf
- real *8, dimension(:), allocatable parm::alpha_bfe
- real *8, dimension(:), allocatable parm::gw_spyld
- real *8, dimension(:), allocatable parm::alpha bf d
- real *8, dimension(:), allocatable parm::alpha_bfe_d
- real *8, dimension(:), allocatable parm::gw_qdeep
- real *8, dimension(:), allocatable parm::gw_delaye
- real *8, dimension(:), allocatable parm::gw_revap
- real *8, dimension(:), allocatable parm::rchrg_dp
- real *8, dimension(:), allocatable parm::anion_excl

fraction of porosity from which anions are excluded

- real *8, dimension(:), allocatable parm::revapmn
- real *8, dimension(:), allocatable parm::rchrg
- real *8, dimension(:), allocatable parm::ffc
- real *8, dimension(:), allocatable parm::bio_min
- real *8, dimension(:), allocatable parm::surqsolp
- real *8, dimension(:), allocatable parm::cklsp
- real *8, dimension(:), allocatable parm::deepst
- real *8, dimension(:), allocatable parm::shallst
- real *8, dimension(:), allocatable parm::wet_solpg

```
real *8, dimension(:), allocatable parm::rchrg_src
  real *8, dimension(:), allocatable parm::wet_no3g
  real *8, dimension(:), allocatable parm::sol_avbd

    real *8, dimension(:), allocatable parm::trapeff

    real *8, dimension(:), allocatable parm::gwqmn

  real *8, dimension(:), allocatable parm::tdrain
  real *8, dimension(:), allocatable parm::ppInt
  real *8, dimension(:), allocatable parm::snotmp
  real *8, dimension(:), allocatable parm::gdrain
     drain tile lag time (hours)

    real *8, dimension(:), allocatable parm::ddrain

  real *8, dimension(:), allocatable parm::sol_crk
  real *8, dimension(:), allocatable parm::dayl
  real *8, dimension(:), allocatable parm::brt
 real *8, dimension(:), allocatable parm::sstmaxd
     static maximum depressional storage; read from .sdr (mm)
 real *8, dimension(:), allocatable parm::re
     effective radius of drains (mm)

    real *8, dimension(:), allocatable parm::sdrain

     distance between two drain tubes or tiles (mm)

    real *8, dimension(:), allocatable parm::ddrain_hru

  real *8, dimension(:), allocatable parm::drain co
     drainage coefficient (mm/day)
  real *8, dimension(:), allocatable parm::latksatf
     multiplication factor to determine conk(j1,j) from sol k(j1,j) for HRU (none)
  real *8, dimension(:), allocatable parm::pc
     pump capacity (default pump capacity = 1.042mm/hr or 25mm/day) (mm/hr)
  real *8, dimension(:), allocatable parm::stmaxd
  real *8, dimension(:), allocatable parm::twash
  real *8, dimension(:), allocatable parm::rnd2
  real *8, dimension(:), allocatable parm::rnd3
  real *8, dimension(:), allocatable parm::sol_cnsw
  real *8, dimension(:), allocatable parm::doxq
  real *8, dimension(:), allocatable parm::rnd8
  real *8, dimension(:), allocatable parm::rnd9
  real *8, dimension(:), allocatable parm::percn
  real *8, dimension(:), allocatable parm::sol_sumwp
  real *8, dimension(:), allocatable parm::tauton
  real *8, dimension(:), allocatable parm::tautop
  real *8, dimension(:), allocatable parm::cbodu
  real *8, dimension(:), allocatable parm::chl a
  real *8, dimension(:), allocatable parm::qdr
  real *8, dimension(:), allocatable parm::tfertn
  real *8, dimension(:), allocatable parm::tfertp
  real *8, dimension(:), allocatable parm::tgrazn
 real *8, dimension(:), allocatable parm::tgrazp
  real *8, dimension(:), allocatable parm::latno3
  real *8, dimension(:), allocatable parm::latq
  real *8, dimension(:), allocatable parm::minpgw
  real *8, dimension(:), allocatable parm::no3gw
  real *8, dimension(:), allocatable parm::npInt
  real *8, dimension(:), allocatable parm::tileq
  real *8, dimension(:), allocatable parm::tileno3
```

- real *8, dimension(:), allocatable parm::sedminpa
- real *8, dimension(:), allocatable parm::sedminps
- real *8, dimension(:), allocatable parm::sedorgn
- real *8, dimension(:), allocatable parm::sedorgp
- real *8, dimension(:), allocatable parm::sedyld
- real *8, dimension(:), allocatable parm::sepbtm
- real *8, dimension(:), allocatable parm::strsn
- real *8, dimension(:), allocatable parm::strsp
- real *8, dimension(:), allocatable parm::strstmp
- real *8, dimension(:), allocatable parm::surfq
- real *8, dimension(:), allocatable parm::surqno3
- real *8, dimension(:), allocatable parm::tcfrtn
- real *8, dimension(:), allocatable parm::tcfrtp
- real *8, dimension(:), allocatable parm::hru_ha
- real *8, dimension(:), allocatable parm::hru_dafr
- real *8, dimension(:), allocatable parm::drydep_no3
- real *8, dimension(:), allocatable parm::drydep_nh4
- real *8, dimension(:), allocatable parm::phubase
- real *8, dimension(:), allocatable parm::bio_yrms
- real *8, dimension(:), allocatable parm::hvstiadj
- real *8, dimension(:), allocatable parm::laimxfr
- real *8, dimension(:), allocatable parm::laiday
- real *8, dimension(:), allocatable parm::chlap
- real *8, dimension(:), allocatable parm::pnd psed
- real *8, dimension(:), allocatable parm::wet_psed
- real *8, dimension(:), allocatable parm::seccip
- real *8, dimension(:), allocatable parm::plantn
- real *8, dimension(:), allocatable parm::plt_et
- real *8, dimension(:), allocatable parm::plt_pet
- real *8, dimension(:), allocatable parm::plantp
- real *8, dimension(:), allocatable parm::bio_aams
- real *8, dimension(:), allocatable parm::bio_aamx
- real *8, dimension(:), allocatable parm::lai_yrmx
- real *8, dimension(:), allocatable parm::dormhr
- real *8, dimension(:), allocatable parm::lat_pst
- real *8, dimension(:), allocatable parm::orig_snohru
- real *8, dimension(:), allocatable parm::orig_potvol
- real *8, dimension(:), allocatable parm::fld fr
- real *8, dimension(:), allocatable parm::orig_alai
- real *8, dimension(:), allocatable parm::orig bioms
- real *8, dimension(:), allocatable parm::pltfr n
- real *8, dimension(:), allocatable parm::orig_phuacc
- real *8, dimension(:), allocatable parm::orig_sumix
- real *8, dimension(:), allocatable parm::pltfr_p
- real *8, dimension(:), allocatable parm::orig phu
- real *8, dimension(:), allocatable parm::phu plt
- real *8, dimension(:), allocatable parm::orig_shallst
- real *8, dimension(:), allocatable parm::orig deepst
- real *8, dimension(:), allocatable parm::orig pndvol
- real *8, dimension(:), allocatable parm::orig_pndsed
- real *8, dimension(:), allocatable parm::rip_fr
- real *8, dimension(:), allocatable parm::orig_pndno3
- real *8, dimension(:), allocatable parm::orig_pndsolp
- real *8, dimension(:), allocatable parm::orig_pndorgn
- real *8, dimension(:), allocatable parm::orig_pndorgp

real *8, dimension(:), allocatable parm::orig wetvol real *8, dimension(:), allocatable parm::orig_wetsed real *8, dimension(:), allocatable parm::orig_wetno3 real *8, dimension(:), allocatable parm::orig_wetsolp real *8, dimension(:), allocatable parm::orig wetorgn real *8, dimension(:), allocatable parm::orig_wetorgp real *8, dimension(:), allocatable parm::orig_solcov real *8, dimension(:), allocatable parm::orig solsw real *8, dimension(:), allocatable parm::orig potno3 real *8, dimension(:), allocatable parm::orig potsed real *8, dimension(:), allocatable parm::wtab real *8, dimension(:), allocatable parm::wtab_mn real *8, dimension(:), allocatable parm::wtab_mx real *8, dimension(:), allocatable parm::shallst_n real *8, dimension(:), allocatable parm::gw_nloss real *8, dimension(:), allocatable parm::rchrg n real *8, dimension(:), allocatable parm::det_san real *8, dimension(:), allocatable parm::det_sil real *8, dimension(:), allocatable parm::det_cla real *8, dimension(:), allocatable parm::det sag real *8, dimension(:), allocatable parm::det lag real *8, dimension(:), allocatable parm::tnylda real *8, dimension(:), allocatable parm::afrt_surface real *8 parm::frt_surface real *8, dimension(:), allocatable parm::auto_nyr real *8, dimension(:), allocatable parm::auto napp real *8, dimension(:), allocatable parm::manure kg real *8, dimension(:), allocatable parm::auto_nstrs real *8, dimension(:,:), allocatable parm::rcn_mo real *8, dimension(:,:), allocatable parm::rammo_mo real *8, dimension(:,:), allocatable parm::drydep no3 mo real *8, dimension(:,:), allocatable parm::drydep_nh4_mo real *8, dimension(:), allocatable parm::rcn_d real *8, dimension(:), allocatable parm::rammo d real *8, dimension(:), allocatable parm::drydep_no3_d real *8, dimension(:), allocatable parm::drydep_nh4_d real *8, dimension(:,:), allocatable parm::yldn real *8, dimension(:,:), allocatable parm::gwati real *8, dimension(:,:), allocatable parm::gwatn real *8, dimension(:,:), allocatable parm::gwatl real *8, dimension(:,:), allocatable parm::gwatw real *8, dimension(:,:), allocatable parm::gwatd real *8, dimension(:,:), allocatable parm::gwatveg real *8, dimension(:,:), allocatable parm::gwata real *8, dimension(:,:), allocatable parm::gwats real *8, dimension(:,:), allocatable parm::gwatspcon real *8, dimension(:,:), allocatable parm::rfqeo_30d real *8, dimension(:,:), allocatable parm::eo 30d real *8, dimension(:,:), allocatable parm::wgncur real *8, dimension(:,:), allocatable parm::wgnold real *8, dimension(:,:), allocatable parm::wrt real *8, dimension(:,:), allocatable parm::psetlp

pesticide enrichment ratio (none)

real *8, dimension(:,:), allocatable parm::pst_enr

 real *8, dimension(:,:), allocatable parm::zdb real *8, dimension(:,:), allocatable parm::pst_surq real *8, dimension(:,:), allocatable parm::plt pst pesticide on plant foliage (kg/ha) real *8, dimension(:,:), allocatable parm::pst sed real *8, dimension(:,:), allocatable parm::psetlw real *8, dimension(:,:), allocatable parm::pcpband real *8, dimension(:,:), allocatable parm::wupnd real *8, dimension(:,:), allocatable parm::tavband real *8, dimension(:,:), allocatable parm::phi real *8, dimension(:,:), allocatable parm::wat_phi real *8, dimension(:,:), allocatable parm::snoeb initial snow water content in elevation band (mm H2O) real *8, dimension(:,:), allocatable parm::wushal real *8, dimension(:,:), allocatable parm::wudeep real *8, dimension(:,:), allocatable parm::tmnband real *8, dimension(:,:), allocatable parm::nsetlw real *8, dimension(:,:), allocatable parm::snotmpeb real *8, dimension(:,:), allocatable parm::bss real *8, dimension(:,:), allocatable parm::surf bs real *8, dimension(:,:), allocatable parm::tmxband real *8, dimension(:,:), allocatable parm::nsetlp real *8, dimension(:,:), allocatable parm::rainsub real *8, dimension(:,:), allocatable parm::frad real *8, dimension(:), allocatable parm::rstpbsb real *8, dimension(:,:), allocatable parm::orig_snoeb real *8, dimension(:,:), allocatable parm::orig_pltpst real *8, dimension(:,:), allocatable parm::terr p real *8, dimension(:,:), allocatable parm::terr cn real *8, dimension(:,:), allocatable parm::terr_sl real *8, dimension(:,:), allocatable parm::drain d real *8, dimension(:,:), allocatable parm::drain_t real *8, dimension(:,:), allocatable parm::drain_g real *8, dimension(:,:), allocatable parm::drain idep real *8, dimension(:,:), allocatable parm::cont_cn real *8, dimension(:,:), allocatable parm::cont p real *8, dimension(:,:), allocatable parm::filt_w real *8, dimension(:,:), allocatable parm::strip_n real *8, dimension(:,:), allocatable parm::strip cn real *8, dimension(:,:), allocatable parm::strip c real *8, dimension(:,:), allocatable parm::strip p real *8, dimension(:,:), allocatable parm::fire_cn real *8, dimension(:,:), allocatable parm::cropno_upd real *8, dimension(:,:), allocatable parm::hi upd real *8, dimension(:,:), allocatable parm::laimx upd real *8, dimension(:,:,:), allocatable parm::pst_lag real *8, dimension(:,:,:), allocatable parm::phug integer, dimension(:), allocatable parm::hrupest pesticide use flag (none) 0: no pesticides used in HRU 1: pesticides used in HRU integer, dimension(:), allocatable parm::nrelease integer, dimension(:), allocatable parm::swtrg

integer, dimension(:), allocatable parm::nro

integer, dimension(:), allocatable parm::nrot integer, dimension(:), allocatable parm::nfert integer, dimension(:), allocatable parm::igro • integer, dimension(:), allocatable parm::nair integer, dimension(:), allocatable parm::ipnd1 integer, dimension(:), allocatable parm::ipnd2 · integer, dimension(:), allocatable parm::nirr integer, dimension(:), allocatable parm::iflod1 integer, dimension(:), allocatable parm::iflod2 integer, dimension(:), allocatable parm::ndtarg integer, dimension(:), allocatable parm::iafrttyp • integer, dimension(:), allocatable parm::nstress integer, dimension(:), allocatable parm::igrotree • integer, dimension(:), allocatable parm::grz_days integer, dimension(:), allocatable parm::nmgt integer, dimension(:), allocatable parm::icr integer, dimension(:), allocatable parm::ncut integer, dimension(:), allocatable parm::nsweep • integer, dimension(:), allocatable parm::nafert integer, dimension(:), allocatable parm::irn integer, dimension(:), allocatable parm::irrno integer, dimension(:), allocatable parm::sol_nly integer, dimension(:), allocatable parm::npcp · integer, dimension(:), allocatable parm::igrz • integer, dimension(:), allocatable parm::ndeat integer, dimension(:), allocatable parm::ngr integer, dimension(:), allocatable parm::ncf integer, dimension(:), allocatable parm::hru sub subbasin in which HRU is located (none) • integer, dimension(:), allocatable parm::idorm integer, dimension(:), allocatable parm::urblu integer, dimension(:), allocatable parm::ldrain integer, dimension(:), allocatable parm::hru_seq integer, dimension(:), allocatable parm::iurban • integer, dimension(:), allocatable parm::iday_fert • integer, dimension(:), allocatable parm::icfrt integer, dimension(:), allocatable parm::ifld number of HRU (in subbasin) that is a floodplain (none) integer, dimension(:), allocatable parm::irip number of HRU (in subbasin) that is a riparian zone (none) integer, dimension(:), allocatable parm::ndcfrt integer, dimension(:), allocatable parm::hrugis • integer, dimension(:), allocatable parm::orig igro integer, dimension(:), allocatable parm::ntil integer, dimension(:), allocatable parm::irrsc integer, dimension(:), allocatable parm::iwatable • integer, dimension(:), allocatable parm::curyr_mat integer, dimension(:), allocatable parm::ncpest integer, dimension(:), allocatable parm::icpst • integer, dimension(:), allocatable parm::ndcpst integer, dimension(:), allocatable parm::iday pest integer, dimension(:), allocatable parm::irr_flag

integer, dimension(:), allocatable parm::irra_flag
 integer, dimension(:,:), allocatable parm::rndseed

random number generator seed. The seeds in the array are used to generate random numbers for the following purposes: (1) wet/dry day probability (2) solar radiation (3) precipitation (4) USLE rainfall erosion index (5) wind speed (6) 0.5 hr rainfall fraction (7) relative humidity (8) maximum temperature (9) minimum temperature (10) generate new random numbers • integer, dimension(:,:), allocatable parm::iterr • integer, dimension(:,:), allocatable parm::iyterr • integer, dimension(:,:), allocatable parm::itdrain • integer, dimension(:,:), allocatable parm::ivdrain • integer, dimension(:,:), allocatable parm::ncrops integer, dimension(:), allocatable parm::manure_id integer, dimension(:,:), allocatable parm::mgt_sdr • integer, dimension(:,:), allocatable parm::idplrot • integer, dimension(:,:), allocatable parm::icont • integer, dimension(:,:), allocatable parm::iycont integer, dimension(:,:), allocatable parm::ifilt • integer, dimension(:,:), allocatable parm::iyfilt • integer, dimension(:,:), allocatable parm::istrip integer, dimension(:,:), allocatable parm::iystrip integer, dimension(:,:), allocatable parm::iopday • integer, dimension(:,:), allocatable parm::iopyr integer, dimension(:,:), allocatable parm::mgt ops real *8, dimension(:), allocatable parm::wshd_pstap real *8, dimension(:), allocatable parm::wshd_pstdg • integer, dimension(12) parm::ndmo • integer, dimension(:), allocatable parm::npno array of unique pesticides used in watershed (none) • integer, dimension(:), allocatable parm::mcrhru • character(len=13), dimension(18) parm::rfile rainfall file names (.pcp) character(len=13), dimension(18) parm::tfile temperature file names (.tmp) character(len=4), dimension(1000) parm::urbname name of urban land use character(len=1), dimension(:), allocatable parm::hydgrp character(len=1), dimension(:), allocatable parm::kirr character(len=16), dimension(:), allocatable parm::snam character(len=17), dimension(300) parm::pname name of pesticide/toxin adding qtile to output.hru write 3/2/2010 gsm increased heds(70) to heds(71) character(len=13), dimension(79) parm::heds · character(len=13), dimension(24) parm::hedb character(len=13), dimension(46) parm::hedr

- character(len=13), dimension(41) parm::hedrsv
- character(len=13), dimension(40) parm::hedwtr
- character(len=4), dimension(60) parm::title

description lines in file.cio (1st 3 lines)

character(len=4), dimension(5000) parm::cpnm

four character code to represent crop name

character(len=17), dimension(50) parm::fname real *8, dimension(:,:,:), allocatable parm::flomon real *8, dimension(:,:,:), allocatable parm::solpstmon real *8, dimension(:,::), allocatable parm::srbpstmon real *8, dimension(:,:::), allocatable parm::sedmon real *8, dimension(:,:,:), allocatable parm::orgnmon real *8, dimension(:,:,:), allocatable parm::orgpmon real *8, dimension(:,:,:), allocatable parm::no3mon real *8, dimension(:,:,:), allocatable parm::minpmon real *8, dimension(:..:), allocatable parm::nh3mon real *8, dimension(:,:,:), allocatable parm::no2mon real *8, dimension(:,:,:), allocatable parm::bactpmon real *8, dimension(:,:,:), allocatable parm::bactlpmon real *8, dimension(:,:,:), allocatable parm::cmtl1mon real *8, dimension(:,:,:), allocatable parm::cmtl2mon real *8, dimension(:,::), allocatable parm::cmtl3mon real *8, dimension(:,:,:), allocatable parm::chlamon real *8, dimension(:,::), allocatable parm::disoxmon real *8, dimension(:,:,:), allocatable parm::cbodmon real *8, dimension(:,:), allocatable parm::floyr real *8, dimension(:,:), allocatable parm::sedyr real *8, dimension(:,:), allocatable parm::orgnyr real *8, dimension(:,:), allocatable parm::orgpyr real *8, dimension(:,:), allocatable parm::no3yr real *8, dimension(:,:), allocatable parm::minpyr real *8, dimension(:,:), allocatable parm::nh3yr real *8, dimension(:,:), allocatable parm::no2yr real *8, dimension(:,:), allocatable parm::bactpyr real *8. dimension(:.:), allocatable parm::bactlpvr real *8, dimension(:,:), allocatable parm::cmtl1yr real *8, dimension(:,:), allocatable parm::cmtl2yr real *8, dimension(:,:), allocatable parm::cmtl3yr real *8, dimension(:,:), allocatable parm::chlayr real *8, dimension(:,:), allocatable parm::disoxyr real *8, dimension(:,:), allocatable parm::cbodyr real *8, dimension(:.:), allocatable parm::solpstyr real *8, dimension(:,:), allocatable parm::srbpstyr real *8, dimension(:,:), allocatable parm::sol_mc real *8, dimension(:,:), allocatable parm::sol_mn real *8, dimension(:,:), allocatable parm::sol_mp real *8, dimension(:), allocatable parm::flocnst real *8, dimension(:), allocatable parm::sedcnst real *8, dimension(:), allocatable parm::orgncnst real *8, dimension(:), allocatable parm::orgpcnst real *8, dimension(:), allocatable parm::no3cnst real *8, dimension(:), allocatable parm::minpcnst real *8, dimension(:), allocatable parm::nh3cnst real *8, dimension(:), allocatable parm::no2cnst real *8, dimension(:), allocatable parm::bactpcnst real *8, dimension(:), allocatable parm::cmtl1cnst real *8, dimension(:), allocatable parm::cmtl2cnst real *8, dimension(:), allocatable parm::bactlpcnst real *8, dimension(:), allocatable parm::cmtl3cnst

real *8, dimension(:), allocatable parm::chlacnst real *8, dimension(:), allocatable parm::disoxcnst

- real *8, dimension(:), allocatable parm::cbodcnst
- real *8, dimension(:), allocatable parm::solpstcnst
- real *8, dimension(:), allocatable parm::srbpstcnst
- · integer parm::nstep

max number of time steps per day

· integer parm::idt

length of time step used to report precipitation data for sub-daily modeling (minutes)

- real *8, dimension(:), allocatable parm::hrtwtr
- real *8, dimension(:), allocatable parm::hhstor
- real *8, dimension(:), allocatable parm::hdepth
- real *8, dimension(:), allocatable parm::hsdti
- real *8, dimension(:), allocatable parm::hrchwtr
- · real *8, dimension(:), allocatable parm::halgae
- real *8, dimension(:), allocatable parm::horgn
- real *8, dimension(:), allocatable parm::hnh4
- real *8, dimension(:), allocatable parm::hno2
- real *8, dimension(:), allocatable parm::hno3
- real *8, dimension(:), allocatable parm::horgp
- real *8, dimension(:), allocatable parm::hsolp
- real *8, dimension(:), allocatable parm::hbod
- real *8, dimension(:), allocatable parm::hdisox
- real *8, dimension(:), allocatable parm::hchla
- real *8, dimension(:), allocatable parm::hsedyld
- real *8, dimension(:), allocatable parm::hsedst
- real *8, dimension(:), allocatable parm::hharea
- real *8, dimension(:), allocatable parm::hsolpst
- real *8, dimension(:), allocatable parm::hsorpst
- real *8, dimension(:), allocatable parm::hhqday
- real *8, dimension(:), allocatable parm::precipdt
- real *8, dimension(:), allocatable parm::hhtime
- real *8, dimension(:), allocatable parm::hbactp
- real *8, dimension(:), allocatable parm::hbactlp
- integer, dimension(10) parm::ivar orig
- real *8, dimension(10) parm::rvar_orig
- integer parm::nsave

number of save commands in .fig file

- · integer parm::nauto
- integer parm::iatmodep
- real *8, dimension(:), allocatable parm::wattemp
- real *8, dimension(:), allocatable parm::lkpst_mass
- real *8, dimension(:), allocatable parm::lkspst_mass
- real *8, dimension(:), allocatable parm::vel_chan
- real *8, dimension(:), allocatable parm::vfscon
- real *8, dimension(:), allocatable parm::vfsratio
- real *8, dimension(:), allocatable parm::vfsch
- real *8, dimension(:), allocatable parm::vfsi
- real *8, dimension(:,:), allocatable parm::filter_i
- real *8, dimension(:,:), allocatable parm::filter_ratio
- real *8, dimension(:,:), allocatable parm::filter_con
- real *8, dimension(:.:), allocatable parm::filter ch
- real *8, dimension(:,:), allocatable parm::sol_n
- integer parm::cswat

```
= 0 Static soil carbon (old mineralization routines)
      = 1 C-FARM one carbon pool model
      = 2 Century model

    real *8, dimension(:,:), allocatable parm::sol bdp

• real *8, dimension(:,:), allocatable parm::tillagef

    real *8, dimension(:), allocatable parm::rtfr

    real *8, dimension(:), allocatable parm::stsol_rd

· integer parm::urban_flag

    integer parm::dorm_flag

real *8 parm::bf_flg
real *8 parm::iabstr

    real *8, dimension(:), allocatable parm::ubnrunoff

    real *8, dimension(:), allocatable parm::ubntss

    real *8, dimension(:,:), allocatable parm::sub_ubnrunoff

    real *8, dimension(:,:), allocatable parm::sub_ubntss

    real *8, dimension(:,:), allocatable parm::ovrlnd_dt

real *8, dimension(:,:,:), allocatable parm::hhsurf_bs

    integer parm::iuh

      unit hydrograph method: 1=triangular UH; 2=gamma funtion UH;

    integer parm::sed ch

     channel routing for HOURLY; 0=Bagnold; 2=Brownlie; 3=Yang;

    real *8 parm::eros expo

      an exponent in the overland flow erosion equation ranges 1.5-3.0

    real *8 parm::eros spl

      coefficient of splash erosion varing 0.9-3.1

    real *8 parm::rill mult

      Multiplier to USLE_K for soil susceptible to rill erosion, range 0.5-2.0.

    real *8 parm::sedprev

  real *8 parm::c_factor

    real *8 parm::ch d50

      median particle diameter of channel bed (mm)
real *8 parm::sig_g
      geometric standard deviation of particle sizes for the main channel. Mean air temperature at which precipitation is
      equally likely to be rain as snow/freezing rain.

    real *8 parm::uhalpha

      alpha coefficient for estimating unit hydrograph using a gamma function (*.bsn)
real *8 parm::abstinit
real *8 parm::abstmax

    real *8, dimension(:,:), allocatable parm::hhsedy

    real *8, dimension(:,:), allocatable parm::sub subp dt

    real *8, dimension(:,:), allocatable parm::sub hhsedy

    real *8, dimension(:,:), allocatable parm::sub_atmp

    real *8, dimension(:), allocatable parm::rhy

• real *8, dimension(:), allocatable parm::init_abstrc

    real *8, dimension(:), allocatable parm::dratio

    real *8, dimension(:), allocatable parm::hrtevp

    real *8, dimension(:), allocatable parm::hrttlc

    real *8, dimension(:,:,:), allocatable parm::rchhr

• real *8, dimension(:), allocatable parm::hhresflwi
```

real *8, dimension(:), allocatable parm::hhresflwo
 real *8, dimension(:), allocatable parm::hhressedi
 real *8, dimension(:), allocatable parm::hhressedo

integer, dimension(:), allocatable parm::bmpdrain

character(len=4), dimension(:), allocatable parm::lu_nodrain

- real *8, dimension(:), allocatable parm::sub cn2
- real *8, dimension(:), allocatable parm::sub ha urb
- real *8, dimension(:), allocatable parm::bmp_recharge
- real *8, dimension(:), allocatable parm::sub ha imp
- real *8, dimension(:), allocatable parm::subdr_km
- real *8, dimension(:), allocatable parm::subdr_ickm
- real *8, dimension(:,:), allocatable parm::sf_im
- real *8, dimension(:,:), allocatable parm::sf_iy
- real *8, dimension(:,:), allocatable parm::sp sa
- real *8, dimension(:,:), allocatable parm::sp pvol
- real *8, dimension(:,:), allocatable parm::sp_pd
- real *8, dimension(:,:), allocatable parm::sp_sedi
- real *8, dimension(:,:), allocatable parm::sp_sede
- real *8, dimension(:,:), allocatable parm::ft_sa
- real *8, dimension(:,:), allocatable parm::ft_fsa
- real *8, dimension(:,:), allocatable parm::ft_dep
- real *8, dimension(:,:), allocatable parm::ft_h
- real *8, dimension(:,:), allocatable parm::ft pd
- real *8, dimension(:,:), allocatable parm::ft_k
- real *8, dimension(:,:), allocatable parm::ft_dp
- real *8, dimension(:,:), allocatable parm::ft_dc
- real *8, dimension(:,:), allocatable parm::ft por
- real *8, dimension(:,:), allocatable parm::tss den
- real *8, dimension(:,:), allocatable parm::ft alp
- real *8, dimension(:,:), allocatable parm::sf fr
- real *8, dimension(:,:), allocatable parm::sp_qi
- real *8, dimension(:,:), allocatable parm::sp k
- real *8, dimension(:,:), allocatable parm::ft qpnd
- real *8, dimension(:,:), allocatable parm::sp_dp
- real *8, dimension(:,:), allocatable parm::ft_qsw
- real *8, dimension(:,:), allocatable parm::ft_qin
- real *8, dimension(:,:), allocatable parm::ft_qout
- real *8, dimension(:,:), allocatable parm::ft_sedpnd
- real *8, dimension(:,:), allocatable parm::sp_bpw
- real *8, dimension(:,:), allocatable parm::ft_bpw
- real *8, dimension(:,:), allocatable parm::ft_sed_cumul
- real *8, dimension(:,:), allocatable parm::sp_sed_cumul
- · integer, dimension(:), allocatable parm::num_sf
- integer, dimension(:,:), allocatable parm::sf_typ
- integer, dimension(:,:), allocatable parm::sf_dim
- integer, dimension(:,:), allocatable parm::ft qfq
- integer, dimension(:,:), allocatable parm::sp_qfg
- integer, dimension(:,:), allocatable parm::sf_ptp
- integer, dimension(:,:), allocatable parm::ft_fc
- real *8 parm::sfsedmean
- real *8 parm::sfsedstdev
- integer, dimension(:), allocatable parm::dtp_subnum
- integer, dimension(:), allocatable parm::dtp imo
- integer, dimension(:), allocatable parm::dtp iyr
- integer, dimension(:), allocatable parm::dtp_numweir
- integer, dimension(:), allocatable parm::dtp_numstage
- · integer, dimension(:), allocatable parm::dtp_stagdis
- integer, dimension(:), allocatable parm::dtp_reltype
- integer, dimension(:), allocatable parm::dtp onoff
- real *8, dimension(:), allocatable parm::cf

- real *8, dimension(:), allocatable parm::cfh
- real *8, dimension(:), allocatable parm::cfdec
- real *8, dimension(:), allocatable parm::lat_orgn
- real *8, dimension(:), allocatable parm::lat_orgp
- integer, dimension(:,:), allocatable parm::dtp_weirtype
- integer, dimension(:,:), allocatable parm::dtp_weirdim
- real *8, dimension(:), allocatable parm::dtp_evrsv
- real *8, dimension(:), allocatable parm::dtp_inflvol
- real *8, dimension(:), allocatable parm::dtp totwrwid
- real *8, dimension(:), allocatable parm::dtp_lwratio
- real *8, dimension(:), allocatable parm::dtp wdep
- real *8, dimension(:), allocatable parm::dtp_totdep
- real *8, dimension(:), allocatable parm::dtp_watdepact
- real *8, dimension(:), allocatable parm::dtp_outflow
- real *8, dimension(:), allocatable parm::dtp_totrel
- real *8, dimension(:), allocatable parm::dtp_backoff
- real *8, dimension(:), allocatable parm::dtp_seep_sa
- real *8, dimension(:), allocatable parm::dtp evap sa
- real *8, dimension(:), allocatable parm::dtp_pet_day
- real *8, dimension(:), allocatable parm::dtp pcpvol
- real *8, dimension(:), allocatable parm::dtp_seepvol
- real *8, dimension(:), allocatable parm::dtp evapvol
- real *8, dimension(:), allocatable parm::dtp flowin
- real *8, dimension(:), allocatable parm::dtp_backup_length
- real *8, dimension(:), allocatable parm::dtp_intcept
- real *8, dimension(:), allocatable parm::dtp_expont
- real *8, dimension(:), allocatable parm::dtp_coef1
- real *8, dimension(:), allocatable parm::dtp_coef2
- real *8, dimension(:), allocatable parm::dtp_coef3
- real *8, dimension(:), allocatable parm::dtp_dummy1
- real *8, dimension(:), allocatable parm::dtp_dummy2
- real *8, dimension(:), allocatable parm::dtp_dummy3
- real *8, dimension(:), allocatable parm::dtp_ivol
- real *8, dimension(:), allocatable parm::dtp_ised
- integer, dimension(:,:), allocatable parm::so_res_flag
- integer, dimension(:,:), allocatable parm::ro_bmp_flag
- real *8, dimension(:,:), allocatable parm::sol_watp
- real *8, dimension(:,:), allocatable parm::sol_solp_pre
- real *8, dimension(:,:), allocatable parm::psp_store
- real *8, dimension(:,:), allocatable parm::ssp_store
- real *8, dimension(:,:), allocatable parm::so res
- real *8, dimension(:,:), allocatable parm::sol_cal
- real *8, dimension(:,:), allocatable parm::sol_ph
- integer parm::sol_p_model
- integer, dimension(:,:), allocatable parm::a_days
- integer, dimension(:,:), allocatable parm::b_days
- real *8, dimension(:), allocatable parm::harv min
- real *8, dimension(:), allocatable parm::fstap
- real *8, dimension(:), allocatable parm::min res
- real *8, dimension(:,:), allocatable parm::ro_bmp_flo
- real *8, dimension(:,:), allocatable parm::ro_bmp_sed
- real *8, dimension(:,:), allocatable parm::ro_bmp_bac
- real *8, dimension(:,:), allocatable parm::ro_bmp_pp
- real *8, dimension(:,:), allocatable parm::ro_bmp_sp
- real *8, dimension(:,:), allocatable parm::ro bmp pn

- real *8, dimension(:,:), allocatable parm::ro_bmp_sn
- real *8, dimension(:,:), allocatable parm::ro bmp flos
- real *8, dimension(:,:), allocatable parm::ro_bmp_seds
- real *8, dimension(:,:), allocatable parm::ro_bmp_bacs
- real *8, dimension(:,:), allocatable parm::ro_bmp_pps
- real *8, dimension(:,:), allocatable parm::ro_bmp_sps
- real *8, dimension(:,:), allocatable parm::ro bmp pns
- real *8, dimension(:,:), allocatable parm::ro_bmp_sns
- real *8, dimension(:,:), allocatable parm::ro bmp flot
- real *8, dimension(:,:), allocatable parm::ro bmp sedt
- real *8, dimension(:.:), allocatable parm::ro bmp bact
- real *8, dimension(:,:), allocatable parm::ro_bmp_ppt
- real *8, dimension(:,:), allocatable parm::ro bmp spt
- real *8, dimension(:,:), allocatable parm::ro bmp pnt
- real *8, dimension(:,:), allocatable parm::ro bmp snt
- real *8, dimension(:), allocatable parm::bmp_flo
- real *8, dimension(:), allocatable parm::bmp_sed
- real *8, dimension(:), allocatable parm::bmp bac
- real *8, dimension(:), allocatable parm::bmp_pp
- real *8, dimension(:), allocatable parm::bmp sp
- real *8, dimension(:), allocatable parm::bmp_pn
- real *8, dimension(:), allocatable parm::bmp_sn
- real *8, dimension(:), allocatable parm::bmp flag
- real *8, dimension(:), allocatable parm::bmp flos
- real *8, dimension(:), allocatable parm::bmp seds
- real *8, dimension(:), allocatable parm::bmp_bacs
- real *8, dimension(:), allocatable parm::bmp pps
- real *8, dimension(:), allocatable parm::bmp sps
- real *8. dimension(:), allocatable parm::bmp pns
- real *8, dimension(:), allocatable parm::bmp sns
- real *8, dimension(:), allocatable parm::bmp_flot
- real *8, dimension(:), allocatable parm::bmp_sedt
- real *8, dimension(:), allocatable parm::bmp_bact
- real *8, dimension(:), allocatable parm::bmp_ppt
- real *8, dimension(:), allocatable parm::bmp_spt
- real *8, dimension(:), allocatable parm::bmp_pnt
- real *8, dimension(:), allocatable parm::bmp_snt
- real *8, dimension(:,:), allocatable parm::dtp_wdratio
- real *8, dimension(:,:), allocatable parm::dtp_depweir
- real *8, dimension(:,:), allocatable parm::dtp_diaweir
- real *8, dimension(:,:), allocatable parm::dtp_retperd
- real *8, dimension(:,:), allocatable parm::dtp_pcpret
- real *8, dimension(:,:), allocatable parm::dtp_cdis
- real *8, dimension(:,:), allocatable parm::dtp_flowrate
- real *8, dimension(:,:), allocatable parm::dtp_wrwid
- real *8, dimension(:,:), allocatable parm::dtp addon
- real *8. dimension(:), allocatable parm::ri subkm
- real *8, dimension(:), allocatable parm::ri_totpvol
- real *8, dimension(:), allocatable parm::irmmdt
- real *8, dimension(:,:), allocatable parm::ri_sed
 real *8, dimension(:,:), allocatable parm::ri_fr
- real *8, dimension(:::), allocatable parm::ri dim
- real *8, dimension(:,:), allocatable parm::ri_im
- real *8, dimension(:.:), allocatable parm::ri iv
- real *8, dimension(:,:), allocatable parm::ri sa

real *8, dimension(:,:), allocatable parm::ri vol real *8, dimension(:,:), allocatable parm::ri qi real *8, dimension(:,:), allocatable parm::ri_k real *8, dimension(:,:), allocatable parm::ri dd real *8, dimension(:,:), allocatable parm::ri evrsv real *8, dimension(:,:), allocatable parm::ri_dep real *8, dimension(:,:), allocatable parm::ri ndt real *8, dimension(:,:), allocatable parm::ri_pmpvol real *8, dimension(:,:), allocatable parm::ri sed cumul real *8, dimension(:.:), allocatable parm::hrnopcp real *8, dimension(:,:), allocatable parm::ri_qloss real *8, dimension(:,:), allocatable parm::ri_pumpv real *8, dimension(:,:), allocatable parm::ri_sedi character(len=4), dimension(:,:), allocatable parm::ri_nirr integer, dimension(:), allocatable parm::num_ri integer, dimension(:), allocatable parm::ri luflq integer, dimension(:), allocatable parm::num_noirr integer, dimension(:), allocatable parm::wtp subnum integer, dimension(:), allocatable parm::wtp onoff integer, dimension(:), allocatable parm::wtp imo integer, dimension(:), allocatable parm::wtp_iyr integer, dimension(:), allocatable parm::wtp dim integer, dimension(:), allocatable parm::wtp stagdis integer, dimension(:), allocatable parm::wtp_sdtype real *8, dimension(:), allocatable parm::wtp pvol real *8, dimension(:), allocatable parm::wtp_pdepth real *8, dimension(:), allocatable parm::wtp sdslope real *8, dimension(:), allocatable parm::wtp lenwdth real *8, dimension(:), allocatable parm::wtp extdepth real *8, dimension(:), allocatable parm::wtp hydeff real *8, dimension(:), allocatable parm::wtp_evrsv real *8, dimension(:), allocatable parm::wtp_sdintc real *8, dimension(:), allocatable parm::wtp_sdexp real *8, dimension(:), allocatable parm::wtp sdc1 real *8, dimension(:), allocatable parm::wtp_sdc2 real *8, dimension(:), allocatable parm::wtp sdc3 real *8, dimension(:), allocatable parm::wtp_pdia real *8, dimension(:), allocatable parm::wtp_plen real *8, dimension(:), allocatable parm::wtp_pmann real *8, dimension(:), allocatable parm::wtp_ploss real *8, dimension(:), allocatable parm::wtp k real *8, dimension(:), allocatable parm::wtp_dp real *8, dimension(:), allocatable parm::wtp sedi real *8, dimension(:), allocatable parm::wtp_sede real *8, dimension(:), allocatable parm::wtp_qi real *8 parm::bio init real *8 parm::lai init real *8 parm::cnop real *8 parm::hi ovr real *8 parm::harveff real *8 parm::frac harvk real *8 parm::lid vqcl

real *8 parm::lid_vgcm
 real *8 parm::lid_qsurf_total
 real *8 parm::lid_farea_sum

```
    real *8, dimension(:,:), allocatable parm::lid_cuminf_last
    real *8, dimension(:,:), allocatable parm::lid_sw_last
```

- real *8, dimension(:,:), allocatable parm::interval_last
- real *8, dimension(:,:), allocatable parm::lid_f_last
- real *8, dimension(:,:), allocatable parm::lid_cumr_last
- real *8, dimension(:,:), allocatable parm::lid_str_last
- real *8, dimension(:,:), allocatable parm::lid_farea
- real *8, dimension(:,:), allocatable parm::lid_qsurf
- real *8, dimension(:,:), allocatable parm::lid_sw_add
- real *8, dimension(:,:), allocatable parm::lid_cumqperc_last
- real *8, dimension(:,:), allocatable parm::lid_cumirr_last
- real *8, dimension(:,:), allocatable parm::lid_excum_last
- integer, dimension(:,:), allocatable parm::gr_onoff
- integer, dimension(:,:), allocatable parm::gr_imo
- integer, dimension(:,:), allocatable parm::gr_iyr
- real *8, dimension(:,:), allocatable parm::gr farea
- real *8, dimension(:,:), allocatable parm::gr_solop
- real *8, dimension(:,:), allocatable parm::gr etcoef
- real *8, dimension(:,:), allocatable parm::gr_fc
- real *8, dimension(:,:), allocatable parm::gr_wp
- real *8, dimension(:,:), allocatable parm::gr_ksat
- real *8, dimension(:,:), allocatable parm::gr_por
- real *8, dimension(:,:), allocatable parm::gr hydeff
- real *8, dimension(:,:), allocatable parm::gr soldpt
- real *8, dimension(:,:), allocatable parm::gr dummy1
- real *8, dimension(:,:), allocatable parm::gr_dummy2
- real *8, dimension(:,:), allocatable parm::gr dummy3
- real *8, dimension(:,:), allocatable parm::gr dummy4
- real *8. dimension(:.:), allocatable parm::gr dummv5
- integer, dimension(:,:), allocatable parm::rg onoff
- integer, dimension(:,:), allocatable parm::rg_imo
- integer, dimension(:,:), allocatable parm::rg_iyr
- real *8, dimension(:,:), allocatable parm::rg_farea
- real *8, dimension(:,:), allocatable parm::rg_solop
- real *8, dimension(:,:), allocatable parm::rg_etcoef
- real *8, dimension(:,:), allocatable parm::rg_fc
- real *8, dimension(:,:), allocatable parm::rg_wp
- real *8, dimension(:,:), allocatable parm::rg_ksat
- real *8, dimension(:,:), allocatable parm::rg por
- real *8, dimension(:,:), allocatable parm::rg_hydeff
- real *8, dimension(:,:), allocatable parm::rg_soldpt
- real *8, dimension(:,:), allocatable parm::rg_dimop
- real *8, dimension(:,:), allocatable parm::rg_sarea
- real *8, dimension(:,:), allocatable parm::rg_vol
- real *8, dimension(:,:), allocatable parm::rg_sth
 real *8, dimension(:,:), allocatable parm::rg_sdia
- real *8. dimension(:,:), allocatable parm::rg_sula
 real *8. dimension(:,:). allocatable parm::rg_bdia
- real *8, dimension(:,:), allocatable parm::rg sts
- real *8, dimension(:,:), allocatable parm::rg orifice
- real *8, dimension(:,:), allocatable parm::rg_oheight
- real *8, dimension(:,:), allocatable parm::rg odia
- real *8, dimension(:,:), allocatable parm::rg_dummy1
- real *8, dimension(:,:), allocatable parm::rg_dummy2
- real *8, dimension(:,:), allocatable parm::rg_dummy3
- real *8, dimension(:,:), allocatable parm::rg_dummy4

real *8, dimension(:,:), allocatable parm::rg dummy5 integer, dimension(:,:), allocatable parm::cs onoff integer, dimension(:,:), allocatable parm::cs_imo integer, dimension(:,:), allocatable parm::cs iyr integer, dimension(:,:), allocatable parm::cs grcon real *8, dimension(:,:), allocatable parm::cs_farea real *8, dimension(:,:), allocatable parm::cs vol real *8, dimension(:,:), allocatable parm::cs_rdepth real *8, dimension(:,:), allocatable parm::cs dummy1 real *8, dimension(:,:), allocatable parm::cs dummy2 real *8, dimension(:,:), allocatable parm::cs_dummy3 real *8, dimension(:,:), allocatable parm::cs dummy4 real *8, dimension(:,:), allocatable parm::cs dummy5 integer, dimension(:,:), allocatable parm::pv_onoff integer, dimension(:,:), allocatable parm::pv_imo integer, dimension(:,:), allocatable parm::pv ivr integer, dimension(:,:), allocatable parm::pv_solop real *8, dimension(:,:), allocatable parm::pv grvdep real *8, dimension(:,:), allocatable parm::pv_grvpor real *8, dimension(:,:), allocatable parm::pv farea real *8, dimension(:,:), allocatable parm::pv_drcoef real *8, dimension(:,:), allocatable parm::pv fc real *8, dimension(:,:), allocatable parm::pv wp real *8, dimension(:,:), allocatable parm::pv ksat real *8, dimension(:,:), allocatable parm::pv por real *8, dimension(:,:), allocatable parm::pv_hydeff real *8, dimension(:,:), allocatable parm::pv soldpt real *8, dimension(:,:), allocatable parm::pv dummy1 real *8. dimension(:.:), allocatable parm::pv dummv2 real *8, dimension(:,:), allocatable parm::pv dummy3 real *8, dimension(:,:), allocatable parm::pv_dummy4 real *8, dimension(:,:), allocatable parm::pv_dummy5 integer, dimension(:,:), allocatable parm::lid_onoff real *8, dimension(:,:), allocatable parm::sol bmc real *8, dimension(:,:), allocatable parm::sol_bmn real *8, dimension(:.:), allocatable parm::sol hsc real *8, dimension(:,:), allocatable parm::sol_hsn real *8, dimension(:,:), allocatable parm::sol_hpc real *8, dimension(:,:), allocatable parm::sol_hpn real *8, dimension(:,:), allocatable parm::sol_lm real *8, dimension(:,:), allocatable parm::sol Imc real *8, dimension(:,:), allocatable parm::sol_lmn real *8, dimension(:,:), allocatable parm::sol Is real *8, dimension(:,:), allocatable parm::sol_lsl real *8, dimension(:,:), allocatable parm::sol lsc real *8, dimension(:,:), allocatable parm::sol Isn real *8, dimension(:,:), allocatable parm::sol rnmn real *8, dimension(:,:), allocatable parm::sol Islc real *8, dimension(:,:), allocatable parm::sol Islnc real *8, dimension(:,:), allocatable parm::sol_rspc real *8, dimension(:,:), allocatable parm::sol_woc real *8, dimension(:.:), allocatable parm::sol won real *8, dimension(:,:), allocatable parm::sol_hp real *8, dimension(:,:), allocatable parm::sol hs

real *8, dimension(:,:), allocatable parm::sol_bm

- real *8, dimension(:,:), allocatable parm::sol_cac
- real *8, dimension(:,:), allocatable parm::sol cec
- real *8, dimension(:,:), allocatable parm::sol_percc
- real *8, dimension(:,:), allocatable parm::sol_latc
- real *8, dimension(:), allocatable parm::sedc_d
- real *8, dimension(:), allocatable parm::surfqc_d
- real *8, dimension(:), allocatable parm::latc d
- real *8, dimension(:), allocatable parm::percc_d
- real *8, dimension(:), allocatable parm::foc d
- real *8, dimension(:), allocatable parm::nppc_d
- real *8, dimension(:), allocatable parm::rsdc d
- real *8, dimension(:), allocatable parm::grainc_d
- real *8, dimension(:), allocatable parm::stoverc_d
- real *8, dimension(:), allocatable parm::soc d
- real *8, dimension(:), allocatable parm::rspc_d
- real *8, dimension(:), allocatable parm::emitc_d
- real *8, dimension(:), allocatable parm::sub_sedc_d
- real *8, dimension(:), allocatable parm::sub surfac d
- real *8, dimension(:), allocatable parm::sub_latc_d
- real *8, dimension(:), allocatable parm::sub percc d
- real *8, dimension(:), allocatable parm::sub_foc_d
- real *8, dimension(:), allocatable parm::sub_nppc_d
- real *8, dimension(:), allocatable parm::sub rsdc d
- real *8, dimension(:), allocatable parm::sub_grainc_d
- real *8, dimension(:), allocatable parm::sub stoverc d
- real *8, dimension(:), allocatable parm::sub_emitc_d
- real *8, dimension(:), allocatable parm::sub soc d
- real *8, dimension(:), allocatable parm::sub_rspc_d
- real *8, dimension(:), allocatable parm::sedc_m
- real *8, dimension(:), allocatable parm::surfqc m
- real *8, dimension(:), allocatable parm::latc_m
- real *8, dimension(:), allocatable parm::percc_m
- real *8, dimension(:), allocatable parm::foc_m
- real *8, dimension(:), allocatable parm::nppc_m
- real *8, dimension(:), allocatable parm::rsdc_m
- real *8, dimension(:), allocatable parm::grainc_m
- real *8, dimension(:), allocatable parm::stoverc_m
- real *8, dimension(:), allocatable parm::emitc_m
- real *8, dimension(:), allocatable parm::soc_m
- real *8, dimension(:), allocatable parm::rspc m
- real *8, dimension(:), allocatable parm::sedc a
- real *8, dimension(:), allocatable parm::surfqc_a
- real *8, dimension(:), allocatable parm::latc_a
- real *8, dimension(:), allocatable parm::percc_a
- real *8, dimension(:), allocatable parm::foc_a
- real *8, dimension(:), allocatable parm::nppc_a
- real *8, dimension(:), allocatable parm::rsdc_a
- real *8, dimension(:), allocatable parm::grainc_a
 real *8, dimension(:), allocatable parm::stoverc a
- real #0, dimension(.), allocatable parmistovere_t
- real *8, dimension(:), allocatable parm::emitc_a
- real *8, dimension(:), allocatable parm::soc_a
 real *8, dimension(:), allocatable parm::rspc_a
- integer, dimension(:), allocatable parm::tillage switch
- real *8, dimension(:), allocatable parm::tillage depth
- integer, dimension(:), allocatable parm::tillage days

- real *8, dimension(:), allocatable parm::tillage_factor
- · real *8 parm::dthy

time interval for subdaily routing

- integer, dimension(4) parm::ihx
- integer, dimension(:), allocatable parm::nhy
- real *8, dimension(:), allocatable parm::rchx
- real *8, dimension(:), allocatable parm::rcss
- real *8, dimension(:), allocatable parm::qcap
- real *8, dimension(:), allocatable parm::chxa
- real *8, dimension(:), allocatable parm::chxp
- real *8, dimension(:,:,:), allocatable parm::qhy
- real *8 parm::ff1
- · real *8 parm::ff2

7.9.1 Detailed Description

file containing the module parm

Author

modified by Javier Burguete Tolosa

7.10 readbsn.f90 File Reference

Functions/Subroutines

· subroutine readbsn

this subroutine reads data from the basin input file (.bsn). This file contains information related to processes modeled or defined at the watershed level

7.10.1 Detailed Description

file containing the suborutine readbsn

Author

modified by Javier Burguete

7.11 readchm.f90 File Reference

Functions/Subroutines

• subroutine readchm

This subroutine reads data from the HRU/subbasin soil chemical input file (.chm). This file contains initial amounts of pesticides/nutrients in the first soil layer. (Specifics about the first soil layer are given in the .sol file.) All data in the .chm file is optional input.

7.11.1 Detailed Description

file containing the subroutine readchm

Author

modified by Javier Burguete

7.12 readfcst.f90 File Reference

Functions/Subroutines

· subroutine readfcst

this subroutine reads the HRU forecast weather generator parameters from the .cst file

7.12.1 Detailed Description

file containing the subroutine readfcst

Author

modified by Javier Burguete

7.13 readfert.f90 File Reference

Functions/Subroutines

subroutine readfert

this subroutine reads input parameters from the fertilizer/manure (i.e. nutrient) database (fert.dat)

7.13.1 Detailed Description

file containing the subroutine readfert

Author

modified by Javier Burguete

7.14 readfig.f90 File Reference

Functions/Subroutines

subroutine readfig

reads in the routing information from the watershed configuration input file (.fig) and calculates the number of subbasins, reaches, and reservoirs

7.14.1 Detailed Description

file containing the subroutine readfig

Author

modified by Javier Burguete

7.15 readfile.f90 File Reference

Functions/Subroutines

· subroutine readfile

this subroutine opens the main input and output files and reads watershed information from the file.cio

7.15.1 Detailed Description

file containing the subroutine readfile

Author

modified by Javier Burguete

7.16 readhru.f90 File Reference

Functions/Subroutines

• subroutine readhru

this subroutine reads data from the HRU general input file (.hru). This file contains data related to general processes modeled at the HRU level.

7.16.1 Detailed Description

file containing the subroutine readhru

Author

modified by Javier Burguete

7.17 readlup.f90 File Reference

Functions/Subroutines

· subroutine readlup

this subroutine reads data from the HRU/subbasin management input file (.mgt). This file contains data related to management practices used in the HRU/subbasin.

7.17.1 Detailed Description

file containing the subroutine readlup

Author

modified by Javier Burguete

7.18 readpest.f90 File Reference

Functions/Subroutines

· subroutine readpest

this subroutine reads parameters from the toxin/pesticide database (pest.dat)

7.18.1 Detailed Description

file containing the subroutine readpest

Author

modified by Javier Burguete

7.19 readplant.f90 File Reference

Functions/Subroutines

· subroutine readplant

this subroutine reads input parameters from the landuse/landcover database (plant.dat)

7.19.1 Detailed Description

file containing the subroutine readplant

Author

modified by Javier Burguete

7.20 readsdr.f90 File Reference

Functions/Subroutines

subroutine readsdr

this subroutine reads data from the HRU/subbasin management input file (.mgt). This file contains data related to management practices used in the HRU/subbasin.

7.20.1 Detailed Description

file containing the subroutine readsdr

Author

modified by Javier Burguete

7.21 readsepticbz.f90 File Reference

Functions/Subroutines

· subroutine readsepticbz

this subroutine reads data from the septic input file (.sep). This file contains information related to septic tanks modeled or defined at the watershed level

7.21.1 Detailed Description

file containing the subroutine readsepticbz

Author

modified by Javier Burguete

7.22 readsno.f90 File Reference

Functions/Subroutines

· subroutine readsno

this subroutine reads snow data from the HRU/subbasin soil chemical input

7.22.1 Detailed Description

file containing the subroutine readsno

Author

modified by Javier Burguete

7.23 readtill.f90 File Reference

Functions/Subroutines

subroutine readtill

this subroutine reads input data from tillage database (till.dat)

7.23.1 Detailed Description

file containing the subroutine readtill

Author

modified by Javier Burguete

7.24 readurban.f90 File Reference

Functions/Subroutines

· subroutine readurban

this subroutine reads input parameters from the urban database (urban.dat). Information from this database is used only if the urban buildup/washoff routines are selected for the modeling of urban areas

7.24.1 Detailed Description

file containing the subroutine readurban

Author

modified by Javier Burguete

7.25 readwwq.f90 File Reference

Functions/Subroutines

subroutine readwwq

this subroutine reads the watershed stream water quality input data (.wwq file) and initializes the QUAL2E variables which apply to the entire watershed

7.25.1 Detailed Description

file containing the subroutine readwwq

Author

modified by Javier Burguete

7.26 simulate.f90 File Reference

Functions/Subroutines

subroutine simulate

this subroutine contains the loops governing the modeling of processes in the watershed

7.26.1 Detailed Description

file containing the subroutine simulate

Author

modified by Javier Burguete

Bibliography

[1] P Bratley, B L Fox, and L E Schrage. A Guide to Simulation. Springer-Verlag, New York, USA, 1983. 75

140 BIBLIOGRAPHY

Index

| allocate_parms.f90, 73 |
|---|
| ascrv |
| ascrv.f90, 74 ascrv.f90, 73 |
| ascrv, 74 aunif |
| aunif.f90, 75 aunif.f90, 74 aunif, 75 |
| caps |
| caps.f90, 75 caps.f90, 75 caps, 75 |
| gcycl.f90, 76 getallo.f90, 76 |
| igropt parm, 68 |
| jdt |
| jdt.f90, 77 jdt.f90, 76 jdt, 77 |
| |
| main.f90, 77 modparm.f90, 78 |
| |

readfert.f90, 134 readfig.f90, 134 readfile.f90, 135 readhru.f90, 135 readlup.f90, 135 readpest.f90, 136 readplant.f90, 136 readsdr.f90, 136 readsepticbz.f90, 137 readsno.f90, 137 readull.f90, 137 readurban.f90, 138 readwwq.f90, 138