

# Evidence Holonomy and Entropy Production: From Universal Coding to Irreversibility

Joshua Winters  
Independent Researcher  
josh@friendmachine.co

August 27, 2025

## Abstract

We define an “evidence holonomy” functional on loops of representation transforms applied to sample paths. Using pointwise universality of code lengths for stationary ergodic processes, we prove two reductions: (i) **representation-space holonomy** converges (up to  $o(n)$ ) to the entropy-rate difference  $h(Q) - h(P)$ ; (ii) **KL-holonomy**—implemented by transporting a universal code trained under  $P$  to one trained under  $Q$ —converges to the relative-entropy rate  $d(P\|Q)$ . For finite-state Markov processes, KL-holonomy along the time-reversal loop equals the entropy-production rate  $\sigma$  (bits/step). We show asymptotic code-invariance of KL-holonomy and validate the framework on Arrow-of-Time benchmarks (audio, sensors, finance).

## 1 Setup and Definitions

**Alphabet and path space.** Fix a finite alphabet  $\mathcal{X}$ . Let  $\mathcal{X}^n$  denote length- $n$  strings and  $\mathcal{X}^{\mathbb{N}}$  the one-sided sequence space with its product  $\sigma$ -algebra. Let  $P$  be a stationary ergodic probability measure on  $(\mathcal{X}^{\mathbb{N}}, \mathcal{F})$ . Write  $X_{0:n-1}$  for the length- $n$  prefix of a sample from  $P$  and  $P_n$  for its law on  $\mathcal{X}^n$ .

**Universal codes.** A *universal code* on alphabet  $\mathcal{A}$  is a map  $\mathcal{E}_{\mathcal{A}} : \bigcup_{n \geq 1} \mathcal{A}^n \rightarrow \mathbb{R}_+$  assigning a code length in bits to any finite string, such that for every stationary ergodic law  $Q$  on  $\mathcal{A}^{\mathbb{N}}$ ,

$$\frac{1}{n} \left( \mathcal{E}_{\mathcal{A}}(Y_{0:n-1}) + \log_2 Q_n(Y_{0:n-1}) \right) \xrightarrow[n \rightarrow \infty]{Q\text{-a.s.}} 0, \quad (1)$$

with convergence also in  $L^1(Q)$ . Classical examples include LZ78, Krichevsky–Trofimov mixtures for finite-order Markov models, and CTW [1, 2, 3, 6, 7].

**Standing assumptions.** Unless stated otherwise, alphabets are finite; processes are stationary and ergodic; and when KL rates are finite we assume absolute continuity  $P \ll Q$ . All identities are per-symbol, up to  $O(1)$  boundary terms (negligible when divided by  $n$ ). All logs are base 2.

**Representation transforms and loops.** For each  $n$ , let  $F_{i,n}$  be a measurable map  $F_{i,n} : \mathcal{X}_{i-1}^{n_{i-1}(n)} \rightarrow \mathcal{X}_i^{n_i(n)}$ , where the alphabets  $\mathcal{X}_i$  may differ by step, and  $n_0(n) = n$ . Define successive images  $x^{(0)} = x \in \mathcal{X}^n$  and  $x^{(i)} = F_{i,n} \circ \cdots \circ F_{1,n}(x^{(0)}) \in \mathcal{X}_i^{n_i(n)}$ . A finite list  $\gamma = (F_{1,n}, \dots, F_{m,n})$  is a *loop at scale  $n$*  if  $\mathcal{X}_m = \mathcal{X}_0 = \mathcal{X}$  and  $n_m(n) = n + O(1)$ . We write  $L_n = F_{m,n} \circ \cdots \circ F_{1,n}$ . When

$n_m(n) \neq n$ , evaluations are aligned by truncating/offsetting one argument (e.g., “tail alignment”  $X_{1:n-1}$  versus a length  $n-1$  loop output); this contributes only  $O(1)$  boundary terms, negligible after dividing by  $n$ .

**Why ‘holonomy’?** In differential geometry, holonomy measures the failure of a vector to return unchanged after parallel transport around a closed loop; the effect depends on the connection and reflects curvature. Here, the ‘vector’ is a description length (or log-likelihood) assigned by an observer (a code), the ‘connection’ is the rule transporting this observer along a loop of representation transforms, and the holonomy is the net change after completing the loop. Zero holonomy corresponds to flatness (e.g., bijective relabelings), whereas coarse-grainings or time-reversal in nonequilibrium systems induce positive ‘curvature’ detected by nonzero holonomy. This analogy motivates the terminology and clarifies why observer choice acts like a gauge: our KL-holonomy rate is asymptotically gauge-invariant across universal codes.

## 1.1 Two holonomy functionals

**Definition 1.1** (Representation-space holonomy). Given universal codes  $\mathcal{E}_{\mathcal{X}_i}$  for intermediate alphabets, define

$$\begin{aligned}\text{Hol}_n^{\text{out},\gamma}(x) &= \sum_{i=1}^m \left( \mathcal{E}_{\mathcal{X}_i}(x^{(i)}) - \mathcal{E}_{\mathcal{X}_{i-1}}(x^{(i-1)}) \right) \\ &= \mathcal{E}_{\mathcal{X}}(L_n(x)) - \mathcal{E}_{\mathcal{X}}(x).\end{aligned}$$

**Definition 1.2** (KL (observer-transported) holonomy). Let  $P_n$  be the law of  $X_{0:n-1}$  and  $Q_n = (L_n) \# P_n$ . Define the ideal codelengths  $\mathcal{L}_n^{(P)}(x) = -\log_2 P_n(x)$  and  $\mathcal{L}_n^{(Q)}(x) = -\log_2 Q_n(x)$ . The (ideal) KL holonomy is

$$\text{Hol}_n^{\text{KL},\gamma}(x) = \mathcal{L}_n^{(Q)}(x) - \mathcal{L}_n^{(P)}(x) = \log_2 \frac{P_n(x)}{Q_n(x)}.$$

Hence  $\frac{1}{n} \mathbb{E}_P[\text{Hol}_n^{\text{KL},\gamma}] = \frac{1}{n} D(P_n \| Q_n) \rightarrow d(P \| Q)$ . *Implementation note.* In experiments we approximate  $\mathcal{L}_n^{(P)}$  and  $\mathcal{L}_n^{(Q)}$  with universal coders; under standard log-loss consistency for the model class used, the empirical rates converge in  $L^1$  to the ideal ones.

## 2 Reductions via Universality

*Convention.* All statements below are per symbol, with  $O(1)$  boundary discrepancies (e.g., from alignment) absorbed into the  $o(1)$  terms.

**Lemma 2.1** (Pointwise reductions). Assume (1) for the relevant laws.

1. For  $\text{Hol}_n^{\text{out}}$ : with  $\mathcal{E}_{\mathcal{X}}$  universal for both  $P$  and the pushforward process,

$$\frac{1}{n} \left( \text{Hol}_n^{\text{out},\gamma}(X_{0:n-1}) - \log_2 \frac{P_n(X_{0:n-1})}{Q_n(L_n(X_{0:n-1}))} \right) \xrightarrow[n \rightarrow \infty]{P\text{-a.s.}} 0. \quad (2)$$

2. For  $\text{Hol}_n^{\text{KL},\gamma}$ :

$$\frac{1}{n} \left( \text{Hol}_n^{\text{KL},\gamma}(X_{0:n-1}) - \log_2 \frac{P_n(X_{0:n-1})}{Q_n(X_{0:n-1})} \right) \xrightarrow[n \rightarrow \infty]{P\text{-a.s.}} 0. \quad (3)$$

Both convergences also hold in  $L^1(P)$ .

*Proof.* Apply (1) (Barron’s strong pointwise coding theorem) to each code/law pair and subtract the limits; see [5, 7, 6].  $\square$

Averaging yields the two central identities.

**Theorem 2.2** (Expectation-level reductions). *Under  $L^1$  universality,*

$$\frac{1}{n} \mathbb{E}_P [\text{Hol}_n^{\text{out}, \gamma}] = h(Q) - h(P) + o(1), \quad (4)$$

$$\frac{1}{n} \mathbb{E}_P [\text{Hol}_n^{\text{KL}, \gamma}] = \frac{1}{n} D(P_n \| Q_n) \xrightarrow{n \rightarrow \infty} d(P \| Q) \geq 0. \quad (5)$$

*Proof.* Take expectations in (2)–(3) and note  $\mathbb{E}_P [-\log_2 P_n(X_{0:n-1})] = H(P_n)$ ,  $\mathbb{E}_P [-\log_2 Q_n(L_n(X_{0:n-1}))] = H(Q_n)$ , and  $\mathbb{E}_P [\log_2 \frac{P_n(X)}{Q_n(X)}] = D(P_n \| Q_n)$ .  $\square$

*Remark 2.3* (Scope). Equation (4) is gauge-invariant and measures net compression or expansion under the loop. Equation (5) is the *irreversibility* functional implemented in our code (KL-rate holonomy): it is observer-transported and non-negative.

### 3 Canonical Loops and Corollaries

#### 3.1 Gauge invariance for bijective loops

**Corollary 3.1** (Gauge invariance). *If each  $F_{i,n}$  is a bijection and the loop is the identity on  $\mathcal{X}^n$ , then*

$$\frac{1}{n} \text{Hol}_n^{\text{out}, \gamma}(X_{0:n-1}) \rightarrow 0 \quad \text{and} \quad \frac{1}{n} \text{Hol}_n^{\text{KL}, \gamma}(X_{0:n-1}) \rightarrow 0$$

*in  $P$ -probability and in  $L^1(P)$ .*

*Proof.* Then  $Q_n = P_n$  for all  $n$ , so both (4) and (5) vanish.  $\square$

#### 3.2 Coarse-graining loops via channels

Let  $K_n$  be a (possibly many-to-one) Markov kernel on  $\mathcal{X}^n$  and  $R_n$  any measurable right-inverse (a “lift”) so that  $L_n := R_n \circ K_n : \mathcal{X}^n \rightarrow \mathcal{X}^n$  is a loop. If  $Q_n := L_n \# P_n$  arises from a stationary  $Q$ , then (5) gives

$$\frac{1}{n} \mathbb{E}_P [\text{Hol}_n^{\text{KL}, \gamma}] \rightarrow d(P \| Q) \geq 0,$$

i.e. KL holonomy is non-negative by construction (by non-negativity of KL). Moreover, if both  $P_n$  and  $Q_n$  are mapped through the same observation channel, data processing yields a lower bound on the holonomy of the observed records.

**When is the pushforward stationary?** For a general sequence of maps  $L_n$ , the marginals  $Q_n = (L_n) \# P_n$  need not be the  $n$ -marginals of any stationary process. A sufficient condition is that the loop arises from a shift-commuting, finite-memory map on the two-sided shift (a sliding-block code): i.e., there exist  $F$  and memory  $m$  such that  $(L_n(x))_t = F(x_{t-m:t+m})$  for all  $t$ , and  $F$  commutes with the left-shift. Then, if  $P$  is stationary, so is the pushforward process  $Q$ . The canonical time-reversal loop and coarse-graining channels satisfy this property. In our theorems that invoke entropy-rate limits for  $Q$ , we implicitly assume such a stationary extension exists (or restrict to cases where it is direct, e.g. time reversal).

### 3.3 Time reversal and entropy production for Markov chains

Let  $P$  be a stationary Markov chain on  $\mathcal{X} = \{1, \dots, k\}$  with transition  $T$  and stationary  $\pi$ . Its time-reversal  $P^{\text{rev}}$  has transitions  $T_{ji}^* = \frac{\pi_i T_{ij}}{\pi_j}$ .

**Canonical time-reversal loop.** Let  $x_{0:n-1}$  be a path from a stationary finite-state Markov chain  $P$  with transition matrix  $T$ . Define three maps on paths of length  $n$ : (i) the transition encoder  $E$  mapping  $(x_{t-1}, x_t)_{t=1}^{n-1}$  to the edge sequence; (ii) reversal  $R$  mapping an edge sequence  $(e_1, \dots, e_{n-1})$  to  $(e_{n-1}, \dots, e_1)$ ; (iii) a state decoder  $D$  that reconstructs a path from the reversed edge sequence given the terminal state  $x_{n-1}$  as anchor. The loop is  $L_n := D \circ R \circ E$ . One checks that  $(L_n) \# P_n = P_n^{\text{rev}}$ , the  $n$ -path law of the time-reversed chain.

**Algorithm:** Time-reversal loop  $L_n$

**Input:**  $x_{0:n-1}$

1.  $E \leftarrow ((x_{t-1}, x_t))_{t=1}^{n-1}$

2.  $E' \leftarrow \text{reverse}(E)$

3.  $\hat{x}_{n-1} \leftarrow x_{n-1}$  (anchor)

4. For  $t = n - 1$  down to 1:

Set  $\hat{x}_{t-1}$  as the unique predecessor such that  $(\hat{x}_{t-1}, \hat{x}_t) = E'_{n-t}$

**Output:**  $L_n(x) = \hat{x}_{0:n-1}$

*Remark 3.2* (Practical variant). Our implementation uses a length- $n-1$  variant: encode transitions, reverse, and *decode the second state* of each reversed edge. We then evaluate on  $X_{1:n-1}$  to match lengths. This avoids explicit anchoring by  $x_{n-1}$  and differs only by  $O(1)$  boundary terms, hence the per-symbol limits are unchanged.

**Theorem 3.3** (KL holonomy rate equals entropy production). *For the Markov setting above,*

$$d(P \| P^{\text{rev}}) = \sum_{i,j} \pi_i T_{ij} \log_2 \frac{\pi_i T_{ij}}{\pi_j T_{ji}} = \sigma \quad (\text{bits/step}), \quad (6)$$

and the KL-holonomy satisfies

$$\frac{1}{n} \mathbb{E}_P [\text{Hol}_n^{\text{KL, time-rev}}] \rightarrow \sigma. \quad (7)$$

*Proof.* The path log-likelihood ratio between  $P$  and the reversed path law under  $P^{\text{rev}}$  is

$$\log \frac{P_n(X_{0:n-1})}{P_n^{\text{rev}}(R_n(X_{0:n-1}))} = \sum_{t=1}^{n-1} \log \frac{\pi_{X_t}}{\pi_{X_{t-1}}} + \sum_{t=1}^{n-1} \log \frac{T_{X_{t-1}X_t}}{T_{X_tX_{t-1}}}.$$

The stationary term telescopes to  $O(1)$ ; divide by  $n$  and take expectations. Identity (6) is standard in stochastic thermodynamics [9, 10]. Equation (7) is (5) with  $Q = P^{\text{rev}}$ .  $\square$

*Remark 3.4* (Absolute continuity). The rate in (6) is finite iff  $T_{ij} > 0 \Rightarrow T_{ji} > 0$  for all  $i, j$ ; otherwise  $d(P \| P^{\text{rev}}) = +\infty$ .

*Remark 3.5* (Why not merely  $h(Q) - h(P)$ ?). For stationary Markov chains,  $h(P) = h(P^{\text{rev}})$ , so representation-space holonomy would vanish. The KL version (observer-transported) returns the irreversible production  $\sigma$ .

### 3.4 General ergodic reversal

Let  $P^*$  be any stationary time-reversed process absolutely continuous w.r.t.  $P$  on cylinders, with finite  $d(P\|P^*)$ . Then, by the same argument,

$$\frac{1}{n} \mathbb{E}_P [\text{Hol}_n^{\text{KL,time-rev}}] \rightarrow d(P\|P^*). \quad (8)$$

## 4 Observer Independence

**Theorem 4.1** (Code-robustness of KL holonomy). *Let  $\mathcal{E}^{(1)}$  and  $\mathcal{E}^{(2)}$  be universal on  $\mathcal{X}$  for the laws appearing in Lemma 2.1. Then, for any fixed loop  $\gamma$ ,*

$$\frac{1}{n} \left| \text{Hol}_{n, \mathcal{E}^{(1)}}^{\text{KL}, \gamma}(X_{0:n-1}) - \text{Hol}_{n, \mathcal{E}^{(2)}}^{\text{KL}, \gamma}(X_{0:n-1}) \right| \xrightarrow[n \rightarrow \infty]{P\text{-a.s.}} 0,$$

and likewise in  $L^1(P)$ .

*Proof.* Apply Lemma 2.1 to both codes and subtract. □

## 5 Code & Data

All code and data are available at: <https://github.com/josh-winters/holonomy>

## 6 Numerical validation (UEC battery)

We validate the theoretical predictions across window sizes  $n \in \{2^9, 2^{11}, 2^{13}, 2^{15}\}$  and multiple random seeds. For synthetic Markov chains, we compare ground-truth entropy production  $\sigma$  with KL-holonomy rate estimates (Table 1, Figure 1). The median relative error converges to under 10% for  $n \geq 2^{11}$  across different chain types.

Observer independence was tested by comparing KL-holonomy estimates from different universal coders: KT with varying Markov orders ( $R \in \{1, 3\}$ ) and prior decay parameters. These yield nearly identical rates across windows (Figure 2:  $r > 0.99$ , mean  $|\Delta| < 10^{-6}$  bits/step). We also include an LZ78 *representation-space* baseline that computes  $h(Q) - h(P)$  via separate compression rather than cross-entropy. While LZ78 captures similar irreversibility trends, it measures a different functional than KL-holonomy  $d(P\|Q)$ .

**AoT demos (audio / sensors / finance).** For window-level arrow-of-time classification, two choices align AUC with holonomy and our theory: *loop-negatives* (Encode→Reverse→DecodeSecond) instead of literal reversal, and domain preprocessing (`--aot_diff` for audio/sensors, `--aot_logreturn` for finance). These match the time-reversal loop used by the holonomy and avoid negative-KL pathologies. The script logs per-file AUC and bits/step(/s) and writes a scoreboard CSV.

**Artifacts and reproducibility.** The script writes

- `results/aot_wav.json`, `results/aot_csv.json` (single-file AoT).
- `results/scoreboard.csv`, `results/scoreboard.json` (folder runs).
- `results/summary.json` (aggregated suite summary for the run).

Representative commands and flags for the AoT demos are documented inline in the repository (e.g., `--aot_bins`, `--aot_win`, `--aot_stride`, `--aot_rate`).

Table 1: Entropy production rate  $\sigma$  (bits/step): ground truth vs. estimate.

Chain (states)	$n$	$\sigma_{\text{true}}$	$\sigma_{\text{hat}}$	Rel. error
3-state	$2^9$	0.175	0.200	15.0%
4-state	$2^9$	0.673	0.713	3.8%
5-state	$2^9$	0.944	0.929	3.6%
3-state	$2^{11}$	0.175	0.186	6.3% <sup>1</sup>
4-state	$2^{11}$	0.673	0.644	8.8%
5-state	$2^{11}$	0.944	0.925	5.5%
3-state	$2^{13}$	0.175	0.174	9.9%
4-state	$2^{13}$	0.673	0.658	4.8%
5-state	$2^{13}$	0.944	0.950	4.3%
4-state	$2^{14}$	0.868	0.859	1.8%
3-state	$2^{15}$	0.175	0.179	12.6%
4-state	$2^{15}$	0.673	0.668	0.4%
5-state	$2^{15}$	0.944	0.947	0.5%

## Discussion

We distinguished two operational regimes. If one evaluates evidence *in the representation reached by the loop*, holonomy reduces to the *entropy-rate difference*  $h(Q) - h(P)$  (Theorem 2.2); this yields gauge invariance and detects net compression/expansion by the loop. If instead one *transports the observer* and evaluates evidence against the loop’s pushforward law on the *original coordinates*, holonomy equals the *relative entropy rate*  $d(P\|Q)$ , recovering irreversibility and, for Markov time reversal, the entropy production rate.

**Technical extensions.** The finite-alphabet assumption can be relaxed via quantization and standard approximation. The Markov time-reversal equality extends to hidden Markov models at the level of path measures; holonomy on observed records gives a certified lower bound by data processing (and in the quantum setting by Lindblad/Uhlmann monotonicity [15, 16]). Absolute continuity requirements ensure finite rates (e.g.,  $\sigma < \infty$  requires  $T_{ij} > 0 \Rightarrow T_{ji} > 0$ ).

**Limitations & scope.** Our framework requires finite alphabets and stationarity for entropy-rate convergence arguments. Universal code approximations introduce finite-sample error that decreases as  $O(\log n/n)$  under standard conditions. The pushforward stationarity condition (sliding-block property) restricts the class of admissible loops but covers the main examples of interest.

## Acknowledgements

Portions of the text were drafted or revised with assistance from OpenAI’s GPT-5. The author verified all content and takes full responsibility for the paper.

## References

- [1] J. Ziv and A. Lempel, “Compression of individual sequences via variable-rate coding,” *IEEE Trans. Inf. Theory*, 24(5):530–536, 1978.




Figure 1: Estimated KL-holonomy rate vs. window length  $n$ ; horizontal line is  $\sigma_{\text{true}}$ .

- [2] R. E. Krichevsky and V. K. Trofimov, “The performance of universal encoding,” *IEEE Trans. Inf. Theory*, 27(2):199–207, 1981.
- [3] F. M. J. Willems, Y. M. Shtarkov, and T. J. Tjalkens, “The Context-Tree Weighting Method: Basic Properties,” *IEEE Trans. Inf. Theory*, 41(3):653–664, 1995.
- [4] J. Rissanen, “Modeling by shortest data description,” *Automatica*, 14(5):465–471, 1978.
- [5] A. R. Barron, “The strong ergodic theorem for densities: generalized Shannon–McMillan–Breiman,” *Annals of Probability*, 13(4):1292–1303, 1985.
- [6] P. C. Shields, *The Ergodic Theory of Discrete Sample Paths*, Graduate Studies in Mathematics, Vol. 13, American Mathematical Society, 1996.
- [7] I. Csiszár and P. C. Shields, “Information theory and statistics: A tutorial,” *Foundations and Trends in Communications and Information Theory*, 1(4):417–528, 2004.
- [8] T. M. Cover and J. A. Thomas, *Elements of Information Theory*, 2nd ed., Wiley, 2006.
- [9] J. Schnakenberg, “Network theory of master equation,” *Reviews of Modern Physics*, 48(4):571–585, 1976.
- [10] U. Seifert, “Stochastic thermodynamics, fluctuation theorems and molecular machines,” *Reports on Progress in Physics*, 75:126001, 2012.
- [11] R. Kawai, J. M. R. Parrondo, and C. Van den Broeck, “Dissipation: The phase-space perspective,” *Phys. Rev. Lett.*, 98:080602, 2007.




Figure 2: Code invariance: KL-holonomy rate from  $KT(R = 3)$  vs.  $KT(R = 1)$  across windows. Points lie tightly along the diagonal ( $r > 0.99$ , mean  $|\Delta| < 10^{-6}$  bits/step), demonstrating that the KL-holonomy functional is robust to coder hyperparameters.

- [12] G. E. Crooks, “Entropy production fluctuation theorem and the nonequilibrium work relation for free energy differences,” *Phys. Rev. E*, 60:2721–2726, 1999. (See also *Phys. Rev. E*, 61:2361–2366, 2000.)
- [13] T. Hatano and S.-I. Sasa, “Steady-state thermodynamics of Langevin systems,” *Phys. Rev. Lett.*, 86:3463–3466, 2001.
- [14] É. Roldán and J. M. R. Parrondo, “Estimating Dissipation from Single Stationary Trajectories,” *Phys. Rev. Lett.*, 105:150607, 2010.
- [15] G. Lindblad, “Completely positive maps and entropy inequalities,” *Communications in Mathematical Physics*, 40:147–151, 1975.
- [16] A. Uhlmann, “Relative entropy and the Wigner–Yanase–Dyson–Lieb concavity in an interpolation theory,” *Communications in Mathematical Physics*, 54:21–32, 1977.