

# 1 Implementation

## 1.1 Skeleton

### 1.1.1 Independence Test

The first sprint consisted of implementing the PC algorithm. This began with implementing a function to determine the skeleton of the graph. To estimate the skeleton a function to determine independence and conditional independence of data was needed. The chi squared tests for independence and conditional independence were chosen. This test will only work on discrete data however other tests could be substituted for other data.

Pandas dataframes were chosen to store data during the algorithm as they provide easy indexing and many useful functions. The crosstab function was especially useful when implementing the chi squared tests as it could automatically compute the contingency tables needed for the tests.

A function `prepare_data` was implemented to read data from a file into a data frame for processing.

The unconditional independence test was fairly straightforward to implement as it only consisted of computing the contingency tables and then comparing the values in the tables to the sums of the rows and columns in the tables.

The conditional case was more complex, first the conditioning set was combined into a single variable through concatenation of each variable in every data point. This made making a contingency table across all the observed values significantly easier. Next a contingency table across the three variables was needed. Again the cross tab function was used, however calculating the sums of each time a variable takes a particular value was now more complex, this is because the columns for the conditioning set were split between the columns for the Y variable.

On top of this not all values of Y and Z were observed simultaneously in data so we cant simply iterate through all values of y and z and some up the associated columns as some do not exist. First the columns that exist must be found and then they can be summed over. After this the test is similar to the unconditional however the expected valued will now also account for the value of the conditioning set.

The scipy `chi2` function was then used to calculate the chi2 statistic and p-value which is returned by the function.

### 1.1.2 Variables to be tested

With this function the skeleton can be found. A fully connected networkx Graph is generated and then edges between nodes that show conditional independence are removed.

First unconditional independence tests are performed between each pair of variables and edges removed between those that are found to be independent. The conditional tests based on variables adjacent to the first variable with size of the set increasing by one after all tests have been performed. The algorithm tests  $X \perp\!\!\!\perp Y|Z$  and  $Y \perp\!\!\!\perp X|Z$ , this may seem inefficient as it appears that tests are being repeated. However, the members of the set  $Z$  are dependent on the first variable in the statement. This means that the tests must all be performed.

To find the conditioning sets, the combinations function from the python library itertools was used to find all subsets of  $adj(x, G)$  of a certain size.

### 1.1.3 Order dependence

The members of set the conditioning set  $Z$  for the test  $X \perp\!\!\!\perp Y|Z$  depend on the tests performed before it. This is due to  $Z$  consisting of nodes adjacent  $X$ , however the set of nodes adjacent to  $X$  changes as edges are removed.

In the R implementation an order independent version has been developed. When the size of conditioning sets is incremented, the conditioning sets for all pairs of variables are calculated and stored. However the original order dependent version can still be used.

### 1.1.4 Separation sets

Edge orientation requires the separation set of each pair of variables. This was stored as a dictionary of all pairs of edges and simply updated with a conditioning set if that set was found to condition independence between the pair.

Since all of the algorithms learn a skeleton, the function is a method of the GraphLearner class which is the parent class of the other algorithm classes. The function returns a networkx Graph containing the estimated edges of the skeleton and a dictionary containing the separation set of each pair of variables.

## 1.2 PC edge orientation

For the pc algorithm edge orientation is relatively simple. However, the pc algorithm outputs a PDAG which contains a mixture of directed and undirected edges, networkx does not contain a data structure to support this kind of graph so one had to be implemented. This turned out to be fairly trivial, using a

directed graph behind the scenes in which undirected edges were represented as bidirected edge. Since it's a DAG there cant be any actual bidirected edges so all bidirected edges can simply be considered to be undirected.

When finding the edges orientation, one graph was used to store directed and one used to store undirected. When an edge was directed it was simply transferred from one to the other and once all edges that can be oriented are oriented, the two graphs are combined into a PDAG.

### 1.2.1 V-Structures

The first part of edge orientation consists of identifying colliders. This is fairly simple as you simply need to find V structures and test if the node that is adjacent to two of the variables is in their separation set. If it is orient the edges toward that node.

However, there may be situations in which the order of the v-structures you test affects the final orientation of the graph. There may be two connected v-structures where orienting one will also orient the other but not in the direction described by the constraints.





Figure - shows two possible orientations, depending on which v structure is oriented first, in the first case when we arrive at the 2,3,4 triple one of two thing can be done. The edge (3,4) can be left undirected or the new structure can override the old one, as shown in figure - .



In the preexisting R implementation the second approach of overwriting edges was taken so the same was done in the python implementation.

Finally the other orientation rules described in the algorithm were followed, these were easy to implement using the networkx graphs as they consisted of testing for undirected and directed edges, then orienting based on those tests. This was repeated until no more edges were oriented, this completed the algorithm

### 1.2.2 FCI Algorithm

The FCI algorithm was able to use exactly the same code and first round v-structure orientation of the pc algorithm. However after this code unique to the fci algorithm must be developed.

First the final skeleton of the graph must be found. This is done by performing more independence tests, conditioned on the possible d-separating sets of the variables. Finding these sets was made simple by a networkx function to find paths between nodes on a graph.

For the rest of the algorithm the network is a PAG. The data structure used for the PAG was a subclass of the networkx undirected graph. In this graph the direction of an edge was determined by tags stored in a dictionary associated with that edge. This allowed all edge types of a PAG to be stored.

### 1.2.3 Testing

To ensure that the algorithm was behaving as intended all parts must be thoroughly tested. The python unittest module was used to create a test suite covering as many aspects of the algorithm as possible.

For the chi squared independence test a sanity check consisting of testing whether a variable was independent of itself was used. Obviously the test will result in a p-value of 0 so was very easy to test. This test was repeated in the case of a conditioning set of size 1 and size 2 to ensure this did not affect functionality.

Next a pre-existing test from r was used to find results on real data. This data was tested with the python implementation and the results compared. Data from the alarm\_10000 and the sia\_1000 datasets were used. Many tests with different variables and conditioning sets were performed.

To test the skeleton estimation again the R implementation was used. However, the R version does not use a chi squared test, a wrapper needed to be written to make it compatible with the R skeleton function. With this, skeletons could be generated from data in the same way in python and R and the results compared. The separation sets were also recorded and compared.

Testing the edge orientation for the PC algorithm first started with small sanity checks. For example the collider orientation was tested on networks with 3 nodes and two edges and simple separation sets.

The path checking needed for the pc algorithm was also tested on small networks where paths were linear and some with many branches. It was also tested on a few negative examples.

Finally a skeleton and separation set generated from the alarms data was oriented in both R and python to test the whole edge orientation process as a whole. However due to the order dependence of the edge orientation the implementations produced slightly different results for the same graphs

This meant that to test the edge orientation section of the pc algorithm, graphs had to be manually oriented using the algorithm and then compared to those estimated by the software.

### **1.3 Final Structure**