作服 - 修改個人資訊(姓名、戶籍地址)

修改個人資訊

使用此API有以下情境

- 1. 當 開戶狀態為 **審核中,**客人進客服,表明要修改姓名或戶籍地址 需修改
 - a. 開戶案件資料
- API Name
- Request
 - Request Example
- Response
 - 成功
- Response Success Example
- 失敗
 - Response Fail Example
- 程式邏輯
- Relative Table
- Error_Code

API Name

環境	URL Name
	/intranet/api/v1.0/common/UpdatePersonalInfo

Request

階層		欄位名稱	中文名稱	欄位	必填	說明
1		createMasterSeqNo	開戶主檔SeqNo	string	Υ	
1		name	姓名	string		
1		residentAddress				residentAddress
	2	city		string		
	2	district		string		
	2	address	街路地址	string		
	2	postalCode	郵遞區號	string		

Request Example

```
{
   "name": "",
   "residentAddress": {
        "city": ""
        "district": ""
        "address": ""
        "postalCode": "123"
   }
}
```

Response

成功

欄位名稱	中文名稱	欄位	說明	值
success	執行結果	boolean	false	true
data	回應資訊	object		

Response Success Example

```
{
    "success": true, // true
    "data": {
    }
}
```

失敗

欄位名稱		中文名稱	欄位	說明	值
success		執行結果	boolean	false	false
error		回應資訊	object		
	errorCode	錯誤代碼	string	檔案刪除錯誤時的代碼	
	errorMessage	錯誤訊息	string	檔案刪除錯誤時的錯誤訊息	

Response Fail Example

```
{
  "success": false, // false
  "error": {
    "errorCode": string, // e.g: "ORDER_NOT_FOUND" or "10001"
    "errorMessage": string // e.g: "The member does not found"
  }
}
```

程式邏輯

1. 針對 Account.CreateDetail 做資料更新

- a. 如果 rq.name!= null or rq.name!= ""
 - i. Account.CreateDetail.Name = rq.name
 - ii. Account.CreateMaster.Name = rq.name
- $b.\ rq. resident Address. city\ or\ rq. resident Address. district\ or\ rq. resident Address\ or\ rq. resident Address\$
 - i. Account.CreateDetail.ResidentCity = rq.residentAddress.city
 - $ii. \ Account. Create Detail. Resident District = rq. resident Address. district$
 - $iii. \ Account. Create Detail. Resident Address = rq. resident Address. address$
 - $iv.\ Account. Create Detail. Resident Postal Code = rq. resident Address. {\tt postalCode}$

Relative Table

Error_Code

Error_Code	Error_Message	
RESIDENTADDRESS_ERROR	residentAddress	
CASE_NOT_FOUND	查無此案件	
CREATEMASTERSEQNO_MISS	請輸入開戶主檔SeqNo	