


PRODUCT SHEET

SYSTEM COMPONENTS

LRAD 300X can be integrated with a variety of accessories for custom security solutions



CONTROL MODULE

LRAD Corporation's hardened, ruggedized control module can be located up to 50 feet away from the hailer and provides all controls necessary to operate the unit.



AMPLIFIER MODULE

The remote amplifier module is environmentally sealed and can be located remotely from the LRAD acoustic device.



MAXA BEAM

The Maxa Beam searchlight delivers 6 million candlepower in a lightweight, handheld unit. Using a high efficiency 75 watt Xenon short arc lamp with over 500 hours of life, this searchlight illuminates targets up to 1.5 miles away.



THE LRAD-X[™] ADVANTAGE:

EXTENDED DIRECTIONALITY/OUTPUT

- ❑ DETERMINES THE INTENT OF A THREAT AT AN EXTENDED RANGE
- ❑ ASSESSES A THREAT SITUATION PRIOR TO INTERDICTION
- ❑ VARIABLE BEAM WIDTH FOR EXTENDED COVERAGE
- ❑ REDUCES THE RISK OF EXPOSING NEARBY PERSONNEL TO EXCESSIVE AUDIO LEVELS

EXTENDED FREQUENCY RANGE

- ❑ BROADCAST FULL VOICE SPECTRUM AT EXTENDED RANGES

COST EFFECTIVE SOLUTION

- ❑ INCREASED SECURITY COVERAGE
- ❑ REDUCED MANPOWER
- ❑ IMPROVED RESPONSE TIMES
- ❑ IMPROVED COORDINATION EFFORTS

EASE OF USE

- ❑ RUGGEDIZED PACKAGE
- ❑ LOW POWER REQUIREMENTS
- ❑ ALL WEATHER CAPABILITY
- ❑ LIGHTWEIGHT
- ❑ FLEXIBLE MOUNTING

STRONG, LOUD AND CLEAR WITH LRAD 300X

LRAD 300X is a compact, lightweight solution for use on small vessels, CROs and vehicle mounted armor. It can be easily transported to provide security personnel long range communications and a highly effective hailing and warning capability where needed.

LRAD 300X produces highly intelligible voice transmissions over 88dB of background noise beyond 350 meters and beyond 1500 meters in a benign environment. LRAD 300X operators have the ability to issue clear, authoritative verbal commands, followed with powerful deterrent tones to enhance response capabilities. The extended frequency range of LRAD 300X ensures voice commands will be clearly understood.



ACOUSTIC PERFORMANCE

Maximum Continuous Output
Beam Width
Frequency Range
Communications Range

143dB SPL @ 1 meter, A-weighted
+/- 15° at 1 kHz/-3dB
See frequency response curve below
Highly intelligible speech transmissions over 1000 meters;
*Max range of 350 meters over 88 dB of background noise.

ENVIRONMENTAL PERFORMANCE

Hot Operating Temperature
Cold Operating Temperature
Rain
Salt Fog
Shipboard Vibration
Shipboard Shock
Random Vibration
SRS Shock
Hot Storage Temperature
Cold Storage Temperature
Operating Humidity

MIL-STD-810G, Method 501.5, Procedure II, Design type Hot, 60°C
MIL-STD-810G, Method 502.5, Procedure II, Design type Basic Cold, -33°C
MIL-STD-810G, Method 506.5, Procedure I, Blowing rain
MIL-STD-810G, Method 509.5
MIL-STD-167-1A
MIL-S-901D, Class I, Shock grade B
MIL-STD-810G, Method 514.6, Wheeled vehicles
MIL-STD-810G, Method 516.6, Procedure I, (Functional shock)
MIL-STD-810G, Method 501.5, Procedure I, 70°C
MIL-STD-810G, Method 502.5, Procedure I, -40°C
MIL-STD 810G, Method 507.5, Procedure II – Aggravated Cycle

MECHANICAL

Emitter Array Dimension
Emitter Array Weight
Construction

25" W x 14" H x 10" D
25 lbs without accessories
Molded low smoke composite 6061 Aluminum
Stainless steel 316 Stainless hardware

ELECTRICAL REQUIREMENTS

Power Consumption

Typical Power consumption 150 Watts (With Warning tone)
Normal power consumption 50 Watts (With voice content,
sound projection is wide and voice boost is off)

Power Input

12 – 28VDC

SAFETY

MIL-STD-1474D

ELECTROMAGNETIC COMPATIBILITY (EMC)

FCC Part 15 class B radiated emissions, MIL-STD-461E, CE

COLORS

Gray 
Tan 

Catalog No. LRAD-300X-G-SYS
Catalog No. LRAD-300X-T-SYS

NSN

5830015784368

*6+ dB above background noise is based on field trials conducted by independent sources.

