PACS — Onboarding guide

For a developer joining the project. The goal of this document is narrow: to get you from a fresh clone to a merged pull request, understanding why the code looks the way it does rather than only where things are.

It should take about a day to work through. Nothing here asks you to read the whole codebase, and nothing here asks you to deploy anything.

---

1. Before anything: what the product is, in sixty seconds

A residential building has fewer parking bays than residents. PACS hands them out on a recurring period — three months by default — by one stated rule, and keeps enough of a record that a resident who did not get a bay can be shown exactly why.

The rule, in full:

1. Whoever has waited longest goes first.
2. On a tie, whoever has had the fewest bays in the past goes first.
3. On a remaining exact tie, a seeded draw decides.

That is the entire fairness policy. It is not a lottery with weights, and if you find a document in this repository describing one — `docs/analisis.html` sections 12 and 13 — you have found a superseded design.

Two vocabulary notes, because they are enforced in code review:

- In the user interface it is a **bay**, never a "spot". In the database and in the code it is `parking_spot`, because renaming the schema was not worth the migration. Both are correct in their own place.
- A resident is **removed** from the register, never "deleted". Allocation history is never reset, because past draws must stay explainable.

---

2. What to read, in this order

Stop after each one and let it settle. Items 1 to 5 are the day; 6 and 7 are for when you need them.

#	Read	Why this, now	Time
1	`apps/web/PRODUCT.md`	The shortest statement of who the users are, what they need, and what may never change. 80 lines	10 min
2	`docs/delivery/01-technical-documentation.md` §1–§3	What the system is, how the repository is laid out, and the two architecture diagrams. Do not try to absorb the AWS sections yet	30 min
3	`apps/api/src/modules/allocation/domain/priority-key.ts`	130 lines, and the heart of the product. Read every comment. If you understand this file you understand the thing PACS is judged on	30 min
4	`apps/api/src/modules/allocation/domain/allocate.ts`	How that key becomes an allocation: one sort, three passes, and the hashes that make a run contestable	20 min
5	`apps/api/src/main/routes.ts`	The whole API surface in one file, with the two authorisation guards that a route's role list cannot express. Skim the presentation functions; read the guards properly	30 min
6	`apps/api/migrations/1759600000000_init-schema.ts` and `…_waiting-time-fairness.ts`	The schema, as raw SQL with the reasoning in comments. The second one is also a worked example of expand / migrate / contract in a single migration	30 min
7	`apps/api/README.md`, especially "Where this deviates from analisis.html"	Why the deployed reality differs from the specification. Every row is a constraint, not a preference	15 min

Deliberately not on that list: `docs/analisis.html`. It is the original specification, it is 280 kB, and parts of it have been superseded by the code. Read it when you need the history of a decision, and read it knowing that where it and the code disagree, the code wins.

---

3. Getting it running

Prerequisites: Node 22 or later (24 is what CI uses) and pnpm 9. No AWS account, no database, no credentials.

```
git clone https://github.com/jcallisayaunosquare/pacs-parking-allocation.git
cd pacs-parking-allocation
pnpm install
```

`pnpm install` also runs the root `prepare` script, which points git at `.githooks`. That is how you get the pre-commit hook; you do not have to install anything else.

Two terminals:

```
# terminal 1 — the stub API
pnpm --filter @pacs/api local        # http://localhost:4300

# terminal 2 — the app
cd apps/web && pnpm offline          # http://localhost:4200
```

Sign in as **`admin@local`** or **`resident@local`**, with any password at all.

What you are actually running

`apps/api/scripts/local-api.mjs` is an in-memory implementation of the same contract the real API implements (`packages/contracts/openapi.yaml`), seeded with 72 residents, 56 bays, four periods, a vehicle register, and a gate log with reads already waiting in the review queue. The whole product works against it: you can run a draw, release a bay, review a plate.

It is a **fixture, not a second implementation**. When its behaviour disagrees with `openapi.yaml`, the YAML is right and the stub is the bug. Keep that straight, because "it works in the stub" is not evidence.

Its bearer token is `local.<base64url json>` with no signature, and only the stub accepts it. The deployed API rejects such a token at the Cognito authorizer before any handler of ours runs.

Then run the tests, so you know what green looks like

```
pnpm --filter @pacs/api test      # 231 tests, 21 files, about 3 seconds
cd apps/web && pnpm test          # 29 tests
cd apps/web && pnpm e2e           # Playwright; it starts both servers itself
```

If the API suite takes noticeably longer than a few seconds, the slow one is `priority-key.properties.spec.ts` — it runs the draw ten thousand times to check the raffle is uniform across a k-way tie. That is not a mistake, and it is the test most worth reading.

Things you will want, but do not need yet


You do **not** need AWS credentials, the database, or a deploy to do useful work. If you eventually do: the database sits behind a security group that admits one address, so you will need your own `/32` added before `DATABASE_URL` is of any use to you. Ask before assuming it is broken.

---

4. The shape of the code

Three rings, and the direction of dependency

Every backend module — `allocation`, `residents`, `inventory`, `fairness`, `identity`, `plates` — has the same three directories, and the arrows only ever point inwards.



The test for whether something is in the right place is short: **if it decides, it belongs in `domain/`. If it coordinates, it belongs in `application/`. If it talks to something outside the process, it belongs in `infrastructure/`.**

Two consequences you will feel immediately:

- A `domain/` file that needs the current time takes a `Date` as an argument. A `domain/` file that needs randomness takes a seed as a string. This is why the draw can be replayed and why ten thousand of them run in under two seconds.
- The snapshot query in `kysely-allocation.repository.ts` returns *facts* — anchors, counts, flags — and never a ranking. Computing the priority key in SQL would mean the formula existed twice, and the drift between the two would be invisible until a resident compared their dashboard against the run page.

The frontend mirrors it: `domain/` (models and abstract repository contracts), `data/` (the only ring that knows `HttpClient` exists), `application/` (signal facades that own the refetch and the five view states), `features/` (presentational lazy pages). `app.config.ts` is the composition root; it binds each abstract repository to its HTTP implementation, and swapping a line there runs the whole app against a fake.

Where things are when you are looking for them

Looking for	Go to
A business rule	`apps/api/src/modules/<module>/domain/`
The route that exposes it	`apps/api/src/main/routes.ts` — all of them, one file
What the API promises	`packages/contracts/openapi.yaml`
A table or a column	`apps/api/migrations/` — five files, in order
What a screen does	`apps/web/src/app/features/<area>/`
How a screen gets its data	`apps/web/src/app/application/*.facade.ts`
What the infrastructure is	`apps/api/serverless.yml`, `pipeline/dev/*.yml`

---

5. The conventions, and why each one exists

These are not style preferences. Each one is here because the absence of it cost this project something.

5.1 Comments say *why*, at length

This codebase comments far more heavily than most, and specifically it comments the reasoning rather than the mechanics. A comment that restates the code is noise and will be asked about in review. A comment that records the option that was rejected is the only durable place that reasoning will ever live.

What a good comment here looks like — this is real, from `vehicle.ts`, explaining why only three confusable glyph pairs are folded:

> The pairs deliberately NOT folded are S/5, B/8, Z/2, G/6 and D/0. They are real OCR confusions, but the cost here is asymmetric: folding them makes "BS12" and "8512" collide, so a resident is told their plate is already registered to someone else when it is not, and there is no action they can take about it. A miss at the gate is recoverable — the recognition module has a confidence score and a fallback — while a false collision in the register is a refusal with no way through.

Note what it contains: the rejected alternative, the asymmetry that decided it, and the consequence for a real person. A reader six months from now who is tempted to "improve" the folding is stopped by it.

A practical rule: **if you had to think about it for more than a minute, write down what you thought.** If the diff makes a non-obvious choice and does not say why, that is the most common review comment on this project.

5.2 Tests sit next to the code they test

`priority-key.ts` and `priority-key.spec.ts` in the same directory. Not a parallel `test/` tree. A rule and its tests move together, get read together, and get deleted together.

A new rule in `domain/` without a spec file beside it is incomplete, not "to be followed up". The suites are three seconds; there is no cost to this.

Two patterns worth copying when you write one:

- **Table tests for decision tables.** `access-decision.spec.ts` walks every row of the gate's decision table. When you add a row, you add a case.
- **Property tests for ordering.** `priority-key.properties.spec.ts` asserts transitivity and the uniformity of the raffle, rather than a handful of examples. Ordering bugs hide from examples.

5.3 Conventional commits

`type(scope): subject`, lower case, imperative, describing the behaviour rather than the edit. Real ones from this repository:

```
feat(api): DELETE /spots/{id} for a bay that was never assigned
fix(smoke): delete the Cognito users the suites create
fix(hooks): refuse a BOM before running the suites
feat: order the admin menu by the work, and refuse a draw while one is in effect
```

The scope is optional and is the package or area. The body is for *why*, when the subject cannot carry it. Branch names follow the same shape: `feat/…`, `fix/…`, one subject each.

5.4 Encoding, which this project has strong feelings about

The pre-commit hook will refuse your commit for three things, and all three happened here:

- **A UTF-8 BOM.** Written by PowerShell 5.1's `Set-Content -Encoding utf8` and by several Windows editors. Invisible in a diff. Vite refuses to parse a `package.json` that has one, with an error that names no file.
- **Doubly-encoded UTF-8**, where an em dash arrives as three characters beginning with a circumflexed lower-case a. Unlike a BOM it stays in the file for everyone to read. (The exact byte sequences are in the hook; writing them here would make this document one the hook refuses.)
- **A lone carriage return**, one that is not part of a CRLF pair. Git's `text=auto` detection treats it as a sign of a binary file, so `.gitattributes`'s `eol=lf` stops applying — which is how four admin pages were classified as binary, one of them with a CR sitting where the "r" of "resident" belonged, inside a comment.

On Windows, write files as UTF-8 **without** a BOM and with LF endings. If the hook refuses you, it is a one-line fix and the message says which file.

5.5 Smaller rules you will meet

- **Nothing in `domain/` is `async`.** If you reach for `await` there, the logic belongs in `application/`.
- **A refusal returns a sentence, not a boolean.** Every `*RemovalBlocker` in this codebase returns the words an administrator is shown. "No" without "why" sends somebody to support.
- **A resident's identity comes from the token and nowhere else.** `resolveResidentId` is the only place it is decided. Never read an id from a path, query or body to decide *who is asking*.
- **Error codes over prose, across a boundary.** `access_event.reason` stores `PLATE_NOT_REGISTERED`, and the wording lives in `features/plates/reason-label.ts`. The one place this was got wrong — the fairness explanation, which crosses the API as finished English — is the frontend's single real design debt, and it is documented as such.
- **No policy number is a literal.** The period length, the bias window, the wait quantum and the thresholds all live in versioned tables. If you find yourself typing `24` or `0.85`, you are probably in the wrong file.
- **Keyset paging, never offset.** Offset paging shifts rows under an administrator who is working through a queue.
- **British-flavoured neutral English** in comments, documents and user-facing strings.

---

6. Your first issue

`plate_config.cooldown_seconds` is stored and never read

What is wrong. `plate_config` is the append-only table of plate-recognition settings. Its own doc comment, and the comment at the top of `kysely-plate-thresholds.provider.ts`, promise the same thing: recalibrating is an `INSERT`, not a deploy, because a threshold that needs a deploy to move will not be moved.

Three of its four settings keep that promise. `min_fused`, `review_fused` and `max_fuzzy_distance` are read out of the newest row by `KyselyPlateThresholdProvider`. The fourth, `cooldown_seconds`, is not read by anything.

The cooldown that is actually applied comes from the `PLATES_COOLDOWN_SECONDS` environment variable, wired in `composition-root.ts`:

```
const cooldownSeconds = Number(process.env.PLATES_COOLDOWN_SECONDS ?? 30);
```

So an operator who inserts a new `plate_config` row to widen the cooldown changes nothing, and gets no error telling them so. The column is a promise the code does not keep.

Why it is a good first issue. It is small, it is real, it is wanted, and it walks you through four of the five places a backend change usually touches: a port, a domain type, an infrastructure adapter, the composition root, and a test. It has an obvious right answer and no product decision hiding inside it.

What to do.

1. Read `kysely-plate-thresholds.provider.ts` in full, including the comment about the one-minute container cache and why it is a minute. Read `ingest-plate-read.ts` to see where `config.cooldownSeconds` is consumed.
2. Decide where the value should surface. The provider already returns a `Thresholds` value object; the cooldown is the same kind of thing and probably belongs in it, which means `Thresholds` grows a field and `DEFAULT_THRESHOLDS` grows a default. Check what else constructs a `Thresholds` before you change the shape — `plate-recognizer.ts` does, and it has no database.
3. Keep the order of authority the provider already documents: **the newest row, then the environment variable, then the code's default.** Do not reverse it, and do not make a missing table fatal — the existing `catch` falls back deliberately, because losing captures over a configuration lookup is worse than running on yesterday's number.
4. Make `IngestPlateRead` take the cooldown from the provider rather than from construction time, so an inserted row takes effect within the provider's cache window instead of at the next deploy.
5. Write the test next to the provider or next to the ingest use case, whichever your change actually lands in. At minimum: a stored row wins over the environment variable; a missing row falls back; a value inserted after the cache has expired is picked up.
6. Update the comments that are now wrong. There will be at least one.

What "done" looks like: `pnpm --filter @pacs/api test` is green with at least one new test, and an operator can change the cooldown by inserting a `plate_config` row.

Roughly where the change lands (do not treat this as a specification — if the code tells you otherwise, the code is right):

```
apps/api/src/modules/plates/domain/access-decision.ts      Thresholds, DEFAULT_THRESHOLDS
apps/api/src/modules/plates/application/ports.ts           PlateThresholdProvider
apps/api/src/modules/plates/application/ingest-plate-read.ts
apps/api/src/modules/plates/infrastructure/kysely-plate-thresholds.provider.ts
apps/api/src/main/composition-root.ts
apps/api/src/main/plate-recognizer.ts                      the static provider, no database
… and a *.spec.ts beside whichever of those you changed
```

If that one is taken, three more of the same size

- **`GET /config/plates`.** There is an admin endpoint to read the allocation policy and its history (`/config/allocation`, `/config/allocation/history`) and none at all for the plate policy. Same shape,

one module across.

- **`apps/api/README.md` is out of date.** It reports 213 unit tests (there are 231), says the project is not a git repository yet, and lists CI as not built. Mechanical, but you have to run everything to know what the right numbers are, which is a good way to meet the suites.
- **The stale doc comment in `plates/domain/access-decision.ts`** says the thresholds are read from `allocation_config`. They are read from `plate_config`, and the migration explains at length why they had to be separated. A two-line fix, and a good excuse to read that explanation.

---

7. Getting your pull request through review

Before you open it

```
pnpm -r lint
pnpm -r typecheck
pnpm --filter @pacs/api test
cd apps/web && pnpm test && pnpm e2e
```

That is the same set the pull request will run, and running it locally costs a few minutes against a round trip of twenty. The pre-commit hook already runs the unit suites of whatever you touched, so in practice the gap is lint, typecheck and Playwright.

Then read your own diff on the pull request page, as a reviewer rather than as the author. It catches more than it has any right to.

What happens when you open it

Against `development`. Six checks run — **Lint, Typecheck, Unit tests API, Unit tests Web, Build, End to end** — and all six must be green. None of them touches AWS, so none of them can fail for a reason outside your diff. The branch must also be up to date with `development` before it can merge, so rebase rather than letting it drift.

One approving review is required, every conversation thread must be resolved, and pushing a new commit dismisses the approval you had.

What a reviewer will look for, in order

1. **Is the rule in the right ring?** The most common structural comment on this project is "this is a decision, and it is in `infrastructure/`."
2. **Does the comment say why?** See §5.1. If you considered an alternative and rejected it, the diff should say so.
3. **Is there a test beside the code?**
4. **Does it widen a boundary?** A new route, a new role check, a new IAM statement, a column on an append-only table, or anything that makes an identifier reachable from a path, gets read twice. Expect more questions, and do not take them personally.
5. **Would the person on the other end understand the refusal?**

6. **Is the pull request one subject?** If it has grown two, it is two pull requests. The seven merged so far each have a single subject in the title.

Answering review comments

- Reply in the thread, in writing, even if you also discussed it in a call. The thread is what the next person reads.
- Disagreeing is fine and expected; say why, concretely. "Two defensible options and no evidence" is a spike, not an argument to win.
- Resolve a thread when you have acted on it; the reviewer confirms. The branch cannot merge with one open, so an unresolved preference becomes an accidental blocker.
- If a comment asks for something you think is out of scope, say so and offer the backlog item. Growing a pull request to satisfy a reviewer is how one subject becomes two.

After it merges

Nothing deploys. That is on purpose: the pipeline's source action has `DetectChanges: false`, so a merge into `development` lands the code and the environment does not move until a human starts `pacs-development` in CodePipeline. If your change needs to be on the dev environment, say so — and if it includes a database migration, say so loudly, because migrations are applied by hand from a machine the database's security group admits, **before** the deploy that needs them. That ordering is the single most likely way to break the environment.

---

8. Things that will confuse you, answered in advance

"Why is there a Lambda outside the VPC?" Because there is no NAT gateway, and an in-VPC function can reach exactly two things: RDS, and DynamoDB through a free gateway endpoint. Anything needing Cognito, S3 or Rekognition runs outside the VPC and is fed by a DynamoDB stream — which works because a stream is polled by the Lambda service, not by the function, so a function with no outbound route can still be invoked by one. That one trick explains `integrations`, `plateRecognizer` and `plateIngest`.

"Why are the tests run twice, in Actions and then again in CodeBuild?" Because branch protection does not apply to administrators on this repository, so the pipeline does not trust a check it did not run itself.

"Why is there no `fairness_state` table, when the first migration creates one?" The `waiting-time-fairness` migration drops it. Waiting time is computed from timestamps at read time, so there is no stored number to drift and no nightly job to fail. The table exists only in that migration's `down`.

"Why does the API refuse my admin account the dashboard?" An administrator operates the draw, so they are never a party to it — separation of duties. The refusal exists three times over: the register row's `is_admin`, the `ADMIN` role on the token, and the snapshot query, which skips such a row with the reason `ADMIN_ACCOUNT`.

"Why does `pnpm --filter web test` work when the package is called `@pacs/web`?" pnpm resolves the unscoped name. Note that a filter matching *nothing* exits 0, which is how the web test job once reported green for three commits while running nothing at all — the CI workflow now runs it from the package directory instead, and the comment there says why.

"Why is the draw not run by the pipeline's smoke stage?" A committed run is a record, and `cycleRemovalBlocker` refuses to delete a period that has one — so running the draw there would make the test period permanent and leave it on an administrator's screen. Set `DATABASE_URL` locally and the suite runs the draw and cleans up afterwards.

"The specification says X and the code does Y." The code wins, and the difference is usually already documented: see the deviations table in `apps/api/README.md` and §13 of the technical documentation. If it is not documented, you have found a gap worth a pull request.