# PACS — Technical documentation

Parking Allocation Context System. This document is written for the next engineer on the project: what the system is, how it is put together, how to run it, how to deploy it, what the data and the rules are, and where the edges are.

Everything here was checked against the code in this repository and, where it concerns deployed infrastructure, against the `dev` account itself. Where the code and the older specification disagree, the code wins and the disagreement is stated.

**Last verified on 2026-10-14 against `development` at `3d02e2b` (pull request #22).** §15 lists what changed since the first edition, pull request by pull request.

| | |
|---|---|
| Repository | `jcallisayaunosquare/pacs-parking-allocation`, default working branch `development` |
| Account · region | `309887812390` · `us-east-2` — the only region the organisation's SCP permits |
| API | `https://frd8e8nkhl.execute-api.us-east-2.amazonaws.com` |
| Site | `https://d2gamvhpvfk16e.cloudfront.net` |
| Identity | Cognito user pool `pacs-dev` (`us-east-2_NsdZ4M0mj`), app client `2tu4q5vefr1g98u90u8dspmife` |
| Database | RDS PostgreSQL 18.3, instance `hotel-db`, database `pacs_dev` |
| Stacks | `pacs-api-dev` (Serverless Framework v4) · `pacs-web-hosting-dev` · `pacs-pipeline-dev` (CloudFormation) |

---

## 1. What the system is

A residential building has fewer parking bays than residents. PACS allocates them on a recurring period — three months by default, but the duration is a configuration value, not a constant — by a stated rule rather than by discretion or by who asked first.

The shape of the work:

1. An administrator maintains the register of residents and the inventory of bays.
2. A period is created and registration is opened. Residents enter.
3. Registration closes. The administrator runs the draw.
4. Every entrant is ranked by one deterministic ordering; the top *n* get the *n* bays and the rest take numbered waitlist places.
5. The period runs. A resident may give up a bay, which promotes the head of the waitlist.
6. The period ends — on its own date, or because an administrator closed it early — and everybody's waiting time starts again from the instant their bay ended.

Alongside that sits the gate: a camera photographs a plate, the system reads it, matches it against the register of residents' vehicles, and records allow, deny, or "a human should look at this".

Two properties make the product what it is, and most of the design follows from them:

- **The result is explainable and re-derivable.** A run stores the configuration version it used, every candidate's computed key, the random seed and a hash of both its inputs and its output. A resident who disputes the outcome is shown the arithmetic, not a policy.
- **The record is append-only.** `allocation_history`, `allocation_run_candidate`, `allocation_config`, `plate_config` and `access_event` cannot be updated or deleted by the application's database role. This is a database privilege, not a convention, so a compromised application credential still cannot rewrite why somebody lost.

---

## 2. Repository layout

A pnpm workspace (`pnpm-workspace.yaml` takes `apps/*` and `packages/*`), pinned to `pnpm@9.15.9` through `packageManager` in the root `package.json`.

```
code/
├── apps/api/                backend — TypeScript, Lambda, Serverless Framework v4
│   ├── serverless.yml       functions, events, Cognito, DynamoDB, S3, VPC endpoint, alarms
│   ├── migrations/          node-pg-migrate, raw SQL, up and down — six files
│   ├── scripts/             seed, offline stub API, smoke suites, operational scripts
│   └── src/
│       ├── shared/          kernel: Result, errors, Clock, db, cache, events, http
│       ├── modules/         one Clean Architecture ring set per module
│       │   ├── allocation/  M-1  periods, runs, the draw, the waitlist
│       │   ├── residents/   M-2  the register, the vehicle register
│       │   ├── inventory/   M-3  bays
│       │   ├── fairness/    M-4  standings, explanations, metrics
│       │   ├── identity/    M-6  JWT claims → Principal, RBAC
│       │   └── plates/      M-7  recognition, the gate log, access events
│       └── main/            composition roots and Lambda handlers — the only `new`
├── apps/web/                frontend — Angular 22, standalone, zoneless, signals
├── packages/contracts/      OpenAPI 3.1 — the contract both sides are checked against
├── pipeline/dev/            CloudFormation: CodePipeline, CodeBuild, S3 + CloudFront
├── .github/workflows/ci.yml the six pull request checks
├── .githooks/pre-commit     the local gate
└── docs/                    analisis.html (the original specification) and this set
```

Inside every backend module the same three rings, with source dependencies pointing inward only:


- `domain/` — pure TypeScript. No `async`, no I/O, no clock, no random number generator. The instant and the seed are arguments. This is why the draw can be run ten thousand times in a unit test and the whole plate decision table verified in milliseconds.
- `application/` — use cases. Knows ports (interfaces), never an implementation.
- `infrastructure/` — Kysely, DynamoDB, S3, Rekognition, Cognito.

`src/main/` wires them. It is the only place that calls a constructor on an adapter, which is what makes a fake repository a one-line substitution.

---

## 3. Architecture


### 3.1 The whole system at a glance




Two things in that picture are unusual and both come from one decision: **there is no NAT gateway** (ADR-016, roughly 32 USD/month avoided). A Lambda attached to the VPC can reach exactly two things — RDS, and DynamoDB through a free gateway endpoint. It cannot reach Cognito, S3 or Rekognition.

So anything that needs the internet runs *outside* the VPC and is fed by a DynamoDB stream. A stream is polled by the Lambda service, not by the function, so a function with no outbound route can still be invoked by one. That single trick is what makes the whole topology work, and it appears twice: once for Cognito provisioning (`integrations`) and once, inverted, for plate recognition (`plateRecognizer` outside, `plateIngest` inside).

### 3.2 Back-end architecture — where each service intervenes




Reading that from the top, with what each layer is responsible for and what it is deliberately *not*:

| Stage | What it does | What it must never do |
|---|---|---|
| API Gateway | Verifies the JWT's signature, issuer, audience and expiry against the Cognito pool before any code of ours runs. Answers CORS preflight itself — `OPTIONS` is left unrouted on purpose, because an `ANY` route would send the preflight to the authorizer, which would 401 it for having no `Authorization` header. | Authorise. It knows nothing about roles. |
| `api.ts` | One handler for every route (a lambdalith, ADR-014). Mints the trace id that appears in every log line and in every error body. | Hold business logic. |
| `router.ts` | Matches the path, checks the caller holds one of the route's roles, rejects any parameter whose *name* ends in `id` (`{id}`, `{cycleId}`, `{vehicleId}`) if its value is not a UUID *before* it reaches a query, parses the body. A parameter that carries a code rather than a UUID must therefore not be named like an id — which is why the lot route is `/lots/{level}/occupancy` and not `{levelId}`: the first deploy named it `{levelId}` and answered `B1` with a 400 (`router.spec.ts` pins both cases). | Decide which resident the caller is. It only knows the token. |
| `principal.ts` | Maps verified claims to a `Principal`: subject, email, roles from `cognito:groups`, `custom:resident_id` when present. | Read an identity from a path, query or body. |
| `routes.ts` | Zod schemas at the edge, presentation on the way out. Two guards live here because a route's `roles` list cannot express them: `adminHasNoResidentSurface` (a role list is an OR, so a principal in both groups would satisfy `['RESIDENT']`) and `residentScope` (a record-level rule the role list knows nothing about). | Reach a repository directly for a decision. |
| `application/` | Idempotency, the run lock, transactions, cache invalidation, event publication. | Contain the fairness policy. |
| `domain/` | The ordering, the state machines, the removal rules, the plate decision table. Pure. | Know that Postgres exists. |
| `infrastructure/` | SQL through Kysely, DynamoDB through the document client, presigned S3 URLs, Rekognition calls. | Make a decision. The snapshot query emits *facts* — anchors, counts, flags — and never a priority key, because duplicating the key formula in SQL and TypeScript would guarantee drift. |

The other five functions in the same stack:


| Function | Trigger | In VPC | Memory · timeout | What it is for |
|---|---|---|---|---|
| `api` | HTTP API | yes | 512 MB · 10 s | Every route |
| `runRaffle` | EventBridge `cron(0 6 * * ? *)`, plus a pre-warm at 05:55 | yes | 512 MB · 60 s | Draws for whichever period is in `REGISTRATION_CLOSED`; returns `NO_RUNNABLE_CYCLE` otherwise. A daily poll rather than a quarterly cron, because the period length is configurable and a quarterly cron would hard-code "every three months" into infrastructure no administrator can edit. |
| `sweeper` | EventBridge `rate(5 minutes)` | yes | 512 MB · 60 s | Fails runs stuck `RUNNING` for 15 minutes, expires assignments whose period has ended and closes those periods, relays the event outbox |
| `integrations` | `pacs-events-dev` stream | **no** | 512 MB · 30 s | Cognito provisioning: `AdminCreateUser`, add to `RESIDENT`, write the `link#<sub>` item back. Addresses on reserved test domains (`.test`, `example.com`…) are created with the invitation suppressed — see §8.5 |
| `plateRecognizer` | S3 `ObjectCreated:Put` on `raw/*.jpg` and `raw/*.png` | **no** | 1024 MB · 30 s | Rekognition `DetectText` → a `PlateRecognized` event |
| `plateIngest` | `pacs-events-dev` stream, filtered to `pk` prefix `plateread#` | yes | 512 MB · 30 s | Applies the event to Postgres: `plate_read` + usually `access_event` |

Three details in that table carry weight:

- **`plateRecognizer` has 1024 MB and not 512.** A full vCPU is allocated at 1769 MB and the share below that is proportional. The inference is Rekognition's, but this function still pays for JSON, signing and the SDK on a cold start, and 1024 is where the duration stops falling. Measure with Lambda Power Tuning before changing it.
- **`plateIngest` must keep its `filterPatterns`.** Without them it wakes for every Cognito provisioning and allocation event on the shared table and pays for an RDS connection to discard each one.
- **No function has `reservedConcurrency`.** The account's Lambda quota is 10 concurrent executions and AWS requires 10 to stay unreserved, so nothing can be reserved at all. The quota itself bounds the connection pool: at most 10 containers × 2 connections = 20, inside a `t4g.micro`'s budget.

### 3.3 Front-end architecture — where each service intervenes

Angular 22, standalone components, **zoneless** (no `zone.js`), signals throughout, Angular Material 22 with the project's own theme. The rings mirror the backend's.



What each part is for, and the rule it enforces:

- **`app.config.ts` is the only binding site.** `{ provide: ResidentRepository, useClass: HttpResidentRepository }` and eleven more like it. Swap a line and the whole application runs against fakes — which is exactly what the unit tests do. `LotRepository` is bound to `HttpLotRepository`: the levels come from `GET /lots` (only levels with at least one bay in service), and each bay's code, type, status, holder and "is it mine" from `GET /lots/{level}/occupancy`. Only the *geometry* is still generated, because there are no geometry tables: the generator lays out as many places as the level has bays and each place is given a real bay in code order. The day `GET /lots/{level}/layout` lands, one line changes and nothing above the data ring notices.
- **`domain/` holds repository *contracts as abstract classes*.** Abstract classes rather than interfaces because Angular's injector needs a runtime token, and an interface has none.
- **Facades own asynchrony, pages do not.** A page reads signals and renders. The facade decides when to refetch and holds the five states the `view-state` host renders (idle, loading, empty, error, loaded) — which is why no page in this codebase contains a `subscribe`.
- **Guards are usability, never security.** They stop a resident landing on a page that would only 403. The server is the boundary, always; the API repeats every one of these rules and is the one that counts.
- **Routes are lazy, one bundle per screen**, so a resident never downloads the admin screens.

The navigation is a sidebar for every role (a drawer at 64 rem and narrower), built from the roles on the principal, in the order the work is done — because the order is not obvious and the menu is the only place it is written down. For an administrator it is grouped in three:

| Group | Links |
|---|---|
| **Set up** | Residents · Bays · Fairness & rules |
| **Run a period** | Periods · Run the draw · The lot |
| **Watch and report** | Gate · Reports |

"Fairness & rules" sits before "Periods" because it holds the rules editor, and the allocation duration there decides how long the period about to be created will run. For a resident: **My parking · The lot · History.** A `CAMERA` account gets one link, `Gate camera`, and nothing else: it is a device, and the only route the server will serve it is `POST /captures`. The gate page lists the browser's cameras when it opens and follows a camera being plugged in, unplugged or switched (`devicechange`).


Navigation between screens uses the View Transitions API where the browser has it, and every table sits in a horizontal scroller so a phone at 390 px never scrolls the page sideways.

Sign-in does not use the Cognito hosted page. `CognitoService` drives `amazon-cognito-identity-js` with `USER_SRP_AUTH` from the product's own form, so the password is never transmitted and the wrong-password, first-sign-in and MFA states are the product's screens rather than someone else's. See §8.1.


---

## 4. AWS services

Two views of the same account. This one is the map: every service PACS uses, with its own mark, and the path a request takes across them. The one after it is the same estate annotated — resource names, sizes and the settings that matter — because a logo cannot tell you that the bucket is private or that two of the functions sit outside the VPC.




Rekognition and the camera carry no mark: the `logos` icon set has no Rekognition glyph, and the camera is a device rather than a service. Everything else is the vendor's own.




Service by service, with the boundary each one sits on:


| Service | Resource | What it does here | Boundary |
|---|---|---|---|
| CloudFront | `E3O4NI6BRCU0X3` | Serves the Angular bundle over TLS; rewrites 403 and 404 to `/index.html` with a 200 so deep links and refreshes work in a client-routed app; adds HSTS, `X-Content-Type-Options`, `X-Frame-Options: DENY` and a referrer policy | Public internet → the only public door to the frontend |
| S3 | `pacs-web-development-309887812390` | Holds the built bundle. Private, versioned, reachable only through the distribution by origin access control, scoped by `AWS:SourceArn` to that one distribution | Private; no public read, no website mode |
| Cognito | `us-east-2_NsdZ4M0mj` | Issues and signs the tokens. Groups `ADMIN`, `RESIDENT`, `CAMERA`. 12-character password policy, optional TOTP MFA, `PreventUserExistenceErrors` on | The identity boundary. Everything downstream trusts its signature and nothing else |
| API Gateway | HTTP API | Route matching, CORS, and the native JWT authorizer that rejects an invalid token before a Lambda is invoked | Public internet → the only public door to the backend |
| Lambda | six functions | All application code | The VPC boundary runs through the middle of this row — see §5 |
| RDS | `hotel-db` / `pacs_dev` | The record. PostgreSQL 18.3 on `db.t4g.micro`, 20 GB gp3, encrypted, single-AZ, IAM database authentication enabled | Inside the VPC, but the instance is **publicly accessible** — see §5 |
| DynamoDB | `pacs-cache-dev` | Read cache with TTL: the resident dashboard for 5 minutes, the fairness and plate metrics for 10. A GSI on `prefix` makes prefix invalidation one query | Reached from in-VPC functions through a free gateway endpoint |
| DynamoDB | `pacs-events-dev` | The relay between inside and outside the VPC. Carries outbox events, the `link#<sub>` subject mappings `integrations` writes back, and the `plateread#<captureId>` recognition events. `NEW_IMAGE` stream, TTL on `expiresAt` | Same gateway endpoint; the stream is polled by the Lambda service, not by our functions |
| S3 | `pacs-captures-dev` | Gate frames under `raw/<cameraId>/<yyyy>/<mm>/<dd>/<captureId>.jpg`. `DeletionPolicy: Retain`, versioned, SSE-S3, all public access blocked. Lifecycle: `raw/` to Glacier IR at 90 days and deleted at 400; `crops/` deleted at 120 | Written by a presigned PUT the camera executes; read only by `plateRecognizer` |
| Rekognition | `DetectText` | Reads text out of a frame. Behind the `PlateRecognizer` port, so replacing it is one class in `infrastructure/` and one line in `src/main` | The one IAM statement that cannot be resource-scoped — Rekognition operations that work without a collection have no ARNs — so it is scoped by action and said out loud in `serverless.yml` |

| Service | Resource | What it does here | Boundary |
|---|---|---|---|
| Secrets Manager | `dev/hotel-db/connection`, `pacs/serverless-access-key` | The master connection details for migrations from a laptop, and the Serverless Framework licence key the deploy stage reads | Never reached by a deployed function: the functions use IAM database authentication and hold no secret at all |
| CloudWatch | logs, X-Ray, 2 alarms | 30-day log retention, tracing on every function. Alarms: `plateRecognizer` errors ≥ 3 in 5 minutes, and `plateIngest` iterator age > 60 s for two periods — a minute behind on that stream means the access log is behind the cars that have already driven in | — |

**IAM database authentication is the piece worth understanding.** The deployed functions hold no database password. `connection.ts` gives `pg` an async `password` function that mints a token with `@aws-sdk/rds-signer` per connection; the SDK signs locally, so there is no network call and it works from inside a VPC with no internet route. The token is valid 15 minutes. The role it signs for is `pacs_app`, granted `rds_iam` and `app_user` and nothing else. There is no database credential in the function configuration, in SSM, or in git.

---

# 5. Network


The DEFAULT VPC · 172.31.0.0/16
The DEFAULT security group · sg-0b745610ae460e557
Developer workstation
one /32, named in the rule
CodeBuild
outside the VPC, address changes every run
λ api · runRaffle · sweeper · plateIngest
ENIs, no public IP
5432, refused: address not in the group
5432, allowed: one /32
5432, allowed: the group references itself
RDS hotel-db :5432
PubliclyAccessible = true
Main route table rtb-090c848e1b269f5c4
172.31.0.0/16 → local
0.0.0.0/0 → igw
pl-4ca54025 (DynamoDB) → vpce-00f6412d33110bf53
vpc-09eae635faf1365ee
Three default subnets, one per AZ, all with MapPublicIpOnLaunch = true
subnet-074cfaf86f9c6ac2e · 172.31.0.0/20 · us-east-2a
subnet-0e4e6f399e1acdf12 · 172.31.16.0/20 · us-east-2b
subnet-0a003bbfbed471a68 · 172.31.32.0/20 · us-east-2c
Gateway endpoint vpce-00f6412d33110bf53
DynamoDB · free · no ENI
Internet gateway
igw-058ae4f96a2e9cc89
λ integrations · λ plateRecognizer
no VPC configuration at all
DynamoDB
Internet

The facts, and what each one costs:


- **It is the account's default VPC.** Three default subnets, one per availability zone, the main route table, and the default security group. Nothing bespoke was created. The original specification describes dedicated private subnets with a Lambda-only security group; that is not what exists.
- **The subnets carry a `0.0.0.0/0` route to an internet gateway**, which by the usual definition makes them public subnets. The in-VPC Lambdas still have no outbound internet, and the reason is worth being precise about: a Lambda ENI is never assigned a public IP, and an internet gateway only forwards traffic for addresses that have one. So the subnets are public and the functions in them are effectively isolated — which is why `integrations` and `plateRecognizer` have to sit outside the VPC, and why DynamoDB is reached through a gateway endpoint rather than over the internet. *(The comment at the top of `pipeline/dev/buildspec-deploy.yml` says "RDS sits in private subnets". It does not; the conclusion it draws — that CodeBuild cannot reach the database — is right, but the reason is the security group, not the subnet.)*
- **`sg-0b745610ae460e557` is the default security group**, and it holds both the Lambdas and the database. Inbound: TCP 5432 from a single `/32` (a developer workstation, named in the rule's description), plus all protocols from the group itself. Outbound: all. The Lambdas reach the database through that self-reference, which is why they need no CIDR rule of their own.
- **`hotel-db` is publicly accessible.** This was asked for, so migrations and scripts can run from a laptop without a bastion. The security group is the whole of the protection, and it admits one address. Closing it again is two commands, both in the API README.
- **CodeBuild cannot reach the database at all**, and that is a consequence rather than an oversight: it runs outside the VPC and its source address changes every run, so no `/32` rule can cover it. Two things follow. Database migrations are not in the deploy stage — they are applied by hand from an admitted machine before the deploy that needs them, and that is a known gap, not a decision. And the smoke suites cannot clean up their own database rows; the draw in `scripts/smoke.mjs` is gated behind `DATABASE_URL` for exactly this reason, so the pipeline runs everything except the draw.

---

# 6. The data model

## 6.1 Conceptual

What the business is about, before any decision about how it is stored:




Entities only: the attributes are in §6.2 to §6.4, where they are the columns that actually exist rather than a second, slightly different list.

Four things in that picture are deliberate and are the reason the physical schema looks the way it does:

1. **A resident's waiting time is not an attribute of the resident.** It is derived at read time from two timestamps: when they started participating, and when their last bay stopped being a benefit. There is no counter to drift and no nightly job to fail.
2. `CANDIDATE_KEY` **exists as a thing in its own right.** Every entrant in every run gets a stored row with the key that ranked them. "Why did I lose?" is answered from the record of that run, not recomputed against data that has since moved.
3. `POLICY` **governs a draw, it does not configure the system.** A run points at the policy version in force when it ran, so changing the bias tomorrow cannot rewrite why somebody lost today.
4. **A plate read and an access decision are separate.** A mis-read can be corrected without rewriting the access log; a decision is overturned by inserting a new row that the old one points at, never by editing one.


## 6.2 Physical — what a period is made of

From `apps/api/migrations/`, as the database actually stands after all six migrations (the sixth, `absence-and-forfeit`, carries rules G and H — §7.3). Split in two because a draw has an input side and an output side, and they are read at different times: this is what exists before a draw runs.




## 6.3 Physical — a run and what it produced

The output side. Every table here is written in the one transaction that commits a run, and four of the five are append-only to the application role.




`event_outbox` has no foreign key to anything, deliberately: it is a relay, written in the same transaction as the state change it announces and emptied by the sweeper. Nothing may depend on a row that is about to be deleted.

## 6.4 Physical — the vehicle register and the gate




### 6.5 Things about the schema that are easy to get wrong

- **There is no `fairness_state` table.** The initial migration created one; the `waiting-time-fairness` migration drops it in `up` and recreates it only in `down`. Fairness is derived from `spot_assignment` and `allocation_history`, which is the whole point — there is no stored score to drift.
- **The registration table is `raffle_registration`**, not `cycle_registration`.
- **`allocation_cycle.label` is unique**, and the default label is derived from the start month and the duration (`2026-10+3M`), so two periods starting in the same month collide. `POST /cycles` checks first and answers `400 VALIDATION_FAILED` with the field `label`. Before that check the constraint surfaced as a bare 500 — and the 500's log line was empty, because Powertools' logger reserves the key `message` and silently dropped the error text written under it. The unhandled-error log now writes it as `detail`, with the Postgres code and constraint when there is one.
- **`allocation_cycle` has a `state` column**, not `status`.
- **The run lock is a partial unique index**: `CREATE UNIQUE INDEX uq_single_running_run ON allocation_run ((state)) WHERE state = 'RUNNING'`. It needs no infrastructure, holds across containers and deployments, and survives a process restart. A second concurrent run gets a unique violation, which the repository turns into `RunLockHeldError` and the use case into a 409.
- **The append-only privileges.** `app_user` — and therefore `pacs_app`, which holds it — has `UPDATE` and `DELETE` revoked on `allocation_history`, `allocation_run_candidate`, `allocation_config` and `plate_config`, and on `allocation_run` has `UPDATE` granted on six named columns only. On `access_event` it has `SELECT, INSERT` plus column-level `UPDATE (superseded_by)`: a decision is overturned by inserting a new row and pointing the old one at it, so the only mutable field is the link.
- **Plate thresholds live in `plate_config`, not `allocation_config`.** The allocation module builds each new policy version from the one in force and lists its own columns, so threshold columns sitting there would be reset to their defaults every time an administrator changed the period length. *(The doc comment at the top of `access-decision.ts` still says `allocation_config`; the migration and the provider say `plate_config`, and they are what runs.)*
- **Two plate columns, deliberately.** `plate` is the canonical key — uppercase, no separators, confusables folded (`O` and `Q` → `0`, `I` → `1`), defined once in `residents/domain/vehicle.ts`. `plate_display` is what the resident typed. Folding the display form would print "ABC 123" back with the O turned into a zero, and a resident who cannot find their own plate in the list stops trusting the list.
- **Plate uniqueness is partial on `is_active`.** The rule is "two residents cannot have the same plate registered at the same time", not "this plate may only ever be registered once in the history of the building" — otherwise a car sold to a neighbour could never be registered again.

---

# 7. The domain rules


## 7.1 Who does what



Two boundaries in that diagram are enforced rather than drawn:

- **An administrator has no resident surface.** They operate the draw, so they are never a party to it. The refusal exists three times over: `resident.is_admin` on the register row, the `ADMIN` role on the verified token (checked first, because the token is what actually grants the powers), and the snapshot query, which skips an admin row with the reason `ADMIN_ACCOUNT`. Administrators are also excluded from `GET /residents` — in the query, not in the client, so a page of fifteen is fifteen. The one exception is *withdrawal*, which is deliberately allowed: an account promoted to administrator after it had already registered needs a way out of a draw it may no longer enter.
- **A resident can only ever reach their own data.** `resolveResidentId` is the single place a caller's resident id is decided, and it comes from the verified token and nowhere else — never from a path, a query or a body. On the vehicle routes, where a path id is unavoidable, a resident asking for somebody else's record is answered `NOT_FOUND` rather than `FORBIDDEN`: a 403 would confirm the record exists, which turns the route into a way of enumerating residents.

## 7.2 The period state machine




Every other transition is a 422 with the states named in the message. The table lives in one constant, `CYCLE_TRANSITIONS` in `allocation/domain/cycle.ts`, and the assignment lifecycle sits beside it: `ACTIVE → RELEASED | REVOKED | EXPIRED`, all three terminal and all three kept distinct on purpose, because the termination policy reads them.

Two rules attach to the ends of that machine:

**A period can be removed only before it has had consequences** (`cycleRemovalBlocker`). If it has handed out bays, or a draw has run, or it is ACTIVE or CLOSED, removal is refused and the refusal says why in the words an administrator reads — "Allocation history is never reset, so it cannot be removed. Close it instead when it ends." Before a draw it is a plan, and a plan can be abandoned.

**A draw is refused while another period is in effect** (`drawBlocker`). This one was added after the dev environment reached a state where 2026-Q4 and 2027-Q1 were both ACTIVE with bay B1-08 assigned in both, to two different residents, and nothing in the system treated that as wrong. It is worse than cosmetic: holding a bay moves a resident's waiting anchor, so a second draw would reset the anchors of people whose benefit from the first has not ended. The way forward is `POST /cycles/{id}/close`, which ends the period in effect and expires its assignments with `benefit_ended_at` set to **now** rather than to `valid_until` — because that is when the benefit actually stopped.

**What a resident sees at each state.** The dashboard's "next period" is chosen by `nextPeriodFor`: an open period the resident can enter, or — if they entered one whose registration has since closed — that period, still shown as **Entered**, until the draw makes it ACTIVE. Without that second case an entrant saw the period vanish from their screen the moment the administrator closed registration, and reasonably concluded they had been dropped. Creating, opening or closing a period invalidates every cached dashboard (`dashboard:` prefix), so the change is visible on the next request rather than after the five-minute cache expires.

### 7.3 The draw


**This is rules A–H, deterministic. It is not a weighted lottery.** Sections 12 and 13 of `docs/analisis.html` describe an earlier probabilistic model with accumulating scores; it was replaced and is not what runs. §31 of the same document states all eight rules in one place, each with its arithmetic and a worked example.

| Rule | In one line |
|---|---|
| A | The building sets the policy: the period length (`allocationDurationMonths`, default 3), the bias window (`earlyWaitingBiasHours`, default 24) and the rest are configuration, versioned, never literals |
| B | You are in a draw because you entered it — a registration per period, not a standing list |
| C | Waiting time is a subtraction, never a counter: the decision instant minus an anchor, which is the latest of participation start, the end of the last bay held, the last withdrawal (G) and the last absence reset (H) |
| D | Ties on waiting time go to whoever has held fewest bays — a lifetime count that is never reset |
| E | The total order: waiting time, then the lifetime count, then a seeded raffle token — the raffle settles only an exact tie |
| F | Early-Waiting Bias: a resident whose bay ended within the window ranks below everyone still waiting, first-timers included |
| G | **Letting a bay go costs what holding one costs.** Withdrawing an entry, declining a bay won, or giving a held bay back: +1 to the lifetime count and the clock restarts. No free window |
| H | **Sitting periods out restarts the clock.** A resident who entered none of the last `absenceResetPeriods` periods (default 1) comes back at zero, anchored on the entry that brings them back. The lifetime count is untouched |

G and H are both resets of the one anchor rule C defines, and the anchor is a `max`, so "which reset wins" is always "the latest one" — that is why they can be stated as separate rules without contradicting each other.

Three keys, compared in order:

1. **Longest effective waiting time first** (descending).
2. On a tie, **fewest past allocations first** (ascending).
3. On a remaining exact tie, **the raffle token**, ascending — `sha256(seed : runId : residentId)`, truncated to 128 bits.


Entrants of this period
raffle_registration, withdrawn = false
Skip?
yes
no
SKIPPED, with a reason
DEACTIVATED · ADMIN_ACCOUNT
·
NOT_ELIGIBLE ·
HOLDS_ACTIVE_SPOT
anchor =
max(participation_started_at,
last benefit_ended_at that
counted as served,
last withdrawn_at — rule G,
absence reset — rule H)
raw_wait_quanta =
floor((decided_at − anchor) /
quantum)
clamped at 0: a clock that went backwards mints nothing
Did a bay end within
early_waiting_bias_hours
of decided_at?
yes
no
effective = raw − bias_quanta
drives this candidate strictly negative
effective = raw
non-negative
Sort by
1. effective_wait DESC
2. served_count ASC
3. raffle_token ASC
4. resident_id — a 128-bit
collision guard only
Pass 1 — ACCESSIBLE
residents needing one, against accessible bays
Pass 2 — EV
Pass 3 — STANDARD
everyone still unassigned, against every bay left
Take the first n of each pass,
n = open bays in that pass,
bays handed out in spot_code
order
spot_assignment +
allocation_history
+ allocation_run_candidate, one
transaction
The rest become the waitlist,
same order, positions 1..m

The parts of that worth defending:

- **Rule F is arithmetic, not a second comparison.** A resident whose bay ended very recently is "cooling": they rank below everyone whose wait is still running, including first-time participants. Implemented as a *subtraction* from the key rather than as a pairwise special case — because a resident is cooling exactly while their raw wait is below the bias window, the subtraction drives every cooling resident strictly negative and everyone else non-negative, and rule F becomes a theorem of the arithmetic. The pairwise reading admits a three-resident cycle, which would make the comparator non-transitive and the sort undefined. There is a regression test for exactly that cycle, and the pairwise version must never be implemented.
- **Which bay you get is not a lottery; only whether you get one is.** Bays are handed out in `spot_code` order within each pass.
- **Restricted pools run first and spill.** A resident who loses the accessible pass falls through to the standard pass with their key unchanged, and an accessible bay nobody claimed returns to the general pool — an empty accessible bay is worse than a standard-need resident parking in it.
- **The raffle token is derived from identity, never from position in the input array.** A resident can recompute their own token with `sha256sum` and three strings. That is the whole of the fairness proof offered, and it is enough.
- **The seed is drawn and persisted before the candidate list is read**, and `sha256(seed)` is stored as `seed_commitment` at the same moment. Re-rolling for a nicer result is therefore a hash preimage problem rather than an operational one.
- **`decided_at` is frozen once per run.** Never `Date.now()` inside the loop: two candidates' waiting times computed microseconds apart would make hour-bucket membership a race, and no replay could reproduce it.
- **The snapshot is read in one `REPEATABLE READ` transaction**, so a registration committed halfway through cannot produce a candidate list that no replay can reproduce.
- **The decision is pure and in memory; the transaction opens afterwards.** The database is held open only for the writes.

The policy values behind all of it live in `allocation_config`, are administrator-editable and versioned, and appear as literals nowhere else in the codebase: `allocationDurationMonths` (3), `earlyWaitingBiasHours` (24), `waitQuantumMinutes` (60), `absenceResetPeriods` (1, nullable — `null` turns rule H off), `totalBays` (0 = the whole active inventory). `declineGraceHours` no longer exists: rule G removed it, because a free decline would be the cheaper way to do exactly what withdrawing does. `configWarnings()` surfaces legal-but-surprising combinations rather than rejecting them — a bias wider than the allocation period would leave every previous holder permanently cooling and freeze the ordering, which is a plausible and catastrophic typo.

**What counts as having been served** is one pure function, `terminationPolicy`, and it writes one boolean, `counts_as_served`, once when an assignment terminates — so the hot ranking query filters on a boolean and never reasons about reason codes:

| Termination | Counts as served? | Why |
|---|---|---|
| `EXPIRED` | yes | The normal path; the benefit ended when the period did |
| `RELEASED` | yes, from the moment it actually ended | A resident who gives a bay back on day 1 of 90 starts accruing on day 1. Parking days are traded for waiting days one for one; the brake on serial early release is the served count, which increments anyway |
| `REVOKED` | yes | They held and consumed the bay and lost it through their own conduct. Not resetting would reward misconduct with priority |
| `DECLINED` | yes, with no grace window (rule G) | Turning down a bay won is the same decision as withdrawing before the draw. A free decline would let the resident who took a bay off the board and handed it back pay less than the one who never registered |
| Withdrawn registration | yes (rule G) | Not an assignment, so not in `terminationPolicy`: `raffle_registration.withdrawn_at` is read as a benefit end by the snapshot query, and counted in the lifetime count. Re-registering afterwards does not undo it |
| `CANCELLED` with `make_whole` | **no** | Our mistake — admin error, building works — must not cost the resident their place in the queue |
| `CANCELLED` without `make_whole` | yes | The administrator chose not to make the resident whole |

The release and withdraw dialogs state that cost before the resident confirms. The resident dashboard reads the absence window exactly as the draw does, and when rule H has reset someone's clock it says so in words — a waiting time of zero with no explanation gets reported as a fault.


### 7.4 Removal: the same line, drawn three times

| Rule | Where | The line |
|---|---|---|
| `cycleRemovalBlocker` | `DELETE /cycles/{id}` | A period with no run and no assignments can be deleted. Otherwise: close it |
| `spotRemovalBlocker` | `DELETE /spots/{id}` | A bay never assigned and not named by `allocation_history` can be deleted. Otherwise: retire it (`PATCH`), which takes it out of the inventory without touching what it is named in |
| `residentRemovalBlocker` | `DELETE /residents/{id}` | A resident named nowhere — no registration, no assignment, no history row, no config change, no reviewed plate read — is deleted outright. Otherwise the row is hidden and kept |

All three are pure functions with their own unit tests, all three return the sentence an administrator is shown rather than a boolean, and all three exist for the same reason: the schema puts `ON DELETE RESTRICT` on the audit paths, so the alternative to refusing early is a foreign key violation surfacing as a 500. `DELETE /residents/{id}` answers 204 either way, because the caller asked for the person to come off the register and that is what happened.

## 7.5 The gate decision table

One pure function, `decide()`, evaluated in this order — and the order *is* the function:



Three rows are worth defending, because in each one the obvious choice is wrong:

- **An unreadable frame produces no access event.** A `DENY` there would fill the log with refusals belonging to nobody and make the denial metric a measure of lens dirt. The frame is still recorded, because a camera that reads nothing for a day is a fault the review queue should surface.
- **An ambiguous fuzzy match never opens.** If two registered plates are equally close, opening means picking at random whose entry this was, and the log would then assert something untrue.
- **A clear read that is not registered is `DENY`, not `REVIEW`.** It is a visitor or an intruder: a fact, not a doubt. A visitor lane is a separate feature — a temporary plate with an expiry — and not a loosened threshold.


The thresholds (`0.85` and `0.55`) are a starting point and are labelled as one. They live in `plate_config`, append-only, so recalibrating is an `INSERT` and not a deploy; the environment variables are only the cold-start default. Every administrator correction in the review queue writes a `corrected_plate`, which is a ground-truth label, which means the evaluation set builds itself from day one.

---

# 8. Sequences


## 8.1 Signing in

Not the Cognito hosted page: the product owns the form, and `CognitoService` drives `amazon-cognito-identity-js` with `USER_SRP_AUTH`, which proves knowledge of the password without sending it.




An access token lasts 15 minutes and `accessToken()` refreshes on demand, so a tab left open overnight does not start returning 401s to a signed-in person. The roles the UI uses come from `cognito:groups`; the resident record cannot be decoded from a token at all, which is why `GET /me` is the only source of the principal.

## 8.2 A resident enters the draw




## 8.3 Running the draw




If anything throws after the run row exists, the run is marked `FAILED` with the detail and the caller gets a 500 with a trace id. A run still `RUNNING` fifteen minutes later had its process killed mid-flight; the sweeper fails it and frees the lock.


## 8.4 A plate at the gate, from frame to decision




Idempotency happens in three layers, and only the middle one really matters: the recogniser's conditional write, then `INSERT ... ON CONFLICT (capture_id) DO NOTHING` — the DynamoDB stream delivers at least once, and a shard replay or a redeployed consumer both land on that statement — and then the business cooldown, which is not idempotency at all but dedupe: a car creeping towards the barrier is one arrival, not twenty.

### 8.5 Creating a resident, and how the Cognito user appears

The one flow where "no NAT gateway" is visible from the outside.




Measured end to end: the Cognito user exists about three seconds after the 201, and the subject link about 1.5 seconds after that.

**The invitation email is the fragile step.** The pool sends through Cognito's default sender (`EmailSendingAccount: COGNITO_DEFAULT`), which allows **50 emails a day for the whole account**. On 2026-10-14 the smoke suites, which create residents at `@example.test` on every deploy, had spent that quota by mid-morning; every `AdminCreateUser` after that failed with `LimitExceededException: Exceeded daily email limit`, and a real resident created from the admin screen got no Cognito user, no email and no way to sign in. Two consequences are worth knowing:

- Since pull request #22, `integrations` creates users on reserved, undeliverable domains (RFC 2606 / 6761: `.test`, `.example`, `.invalid`, `.localhost`, `example.com/net/org`) with `MessageAction: SUPPRESS`. Real addresses are invited as before.
- The stream mapping retries a failed record three times and then **drops it** — there is no on-failure destination. A resident whose provisioning failed stays in the register with no Cognito user until somebody provisions them again (§14.2). A DLQ on the mapping and a pool on its own SES identity are both on the gap list (§13).

## 9. The API surface

Full contract: `packages/contracts/openapi.yaml`. Every route except `GET /health`, `GET /docs` and `GET /openapi.yaml` requires a bearer token. Every parameter whose name ends in `id` is a UUID and is rejected before it reaches a query; `{level}` and `{plate}` carry codes and are named so they are not.

| Method and path | Role | Purpose |
|---|---|---|
| `GET /health` | public | Liveness |
| `GET /docs` · `GET /openapi.yaml` | public | Swagger UI over the contract, and the contract itself. **Authorize** takes a Cognito access token; calls made from the page act with that token's permissions |
| `GET /me` | any | The principal, from the token |
| `GET /me/dashboard` | resident | Aggregated status · cached 5 min |
| `GET /me/history` | resident | Own history |
| `POST /me/assignment/release` | resident | Give up a bay · promotes the waitlist head |
| `GET /me/access-events` | resident | Own entries at the gate |
| `GET /cycles/{id}/registrations` | admin | The period's entrants — what "Run the draw" lists, rather than every eligible resident |
| `POST /cycles/{id}/registrations` | resident | Enter the draw · idempotent |
| `DELETE /cycles/{id}/registrations/me` | any | Withdraw while registration is open |
| `GET` · `POST /residents` | admin | The register (administrators excluded) · create + provision |
| `GET` · `PATCH` · `DELETE /residents/{id}` | admin | Detail · edit · remove |
| `PATCH /residents/{id}/eligibility` | admin | Requires a reason |
| `PATCH /residents/{id}/participation-start` | admin | Correct the waiting anchor |
| `GET` · `POST /residents/{id}/vehicles` | admin · own | The resident's plates |
| `PATCH` · `DELETE /residents/{id}/vehicles/{vehicleId}` | admin · own | Edit · deactivate |
| `GET /vehicles/by-plate/{plate}` | admin | Gate lookup · normalises first |
| `GET` · `POST /spots` | admin | Inventory |
| `PATCH /spots/{id}` | admin | Edit or retire |
| `DELETE /spots/{id}` | admin | Remove a bay never assigned |
| `GET /lots` | resident · admin | The levels with at least one bay in service, and how many bays each has |
| `GET /lots/{level}/occupancy` | resident · admin | Every bay on a level: code, type, status, `validUntil`, `isMine`. The holder's name and unit are shown to administrators only |
| `GET` · `PATCH /config/allocation` | admin | The policy in force · new version |
| `GET /config/allocation/history` | admin | Who changed what, and when |
| `GET` · `POST /cycles` | admin · resident reads | Periods · a duplicate label is `400 VALIDATION_FAILED` |
| `PATCH` · `DELETE /cycles/{id}` | admin | Rename (the only editable field) · remove |
| `POST /cycles/{id}/open-registration` | admin | DRAFT → REGISTRATION_OPEN |
| `POST /cycles/{id}/close-registration` | admin | → REGISTRATION_CLOSED |

| Method and path | Role | Purpose |
|---|---|---|
| `POST /cycles/{id}/close` | admin | End the period in effect; expires its assignments |
| `POST /cycles/{id}/runs` | admin | Run the draw · `Idempotency-Key` required |
| `GET /runs` · `GET /runs/{id}` | admin | Runs, and one run with its seed and commitment |
| `GET /runs/{id}/explanation` | admin | The paragraph a contesting resident is shown |
| `GET /runs/{id}/assignments` | admin | The full result set |
| `GET /metrics/fairness` | admin | Dashboard · cached 10 min |
| `GET /metrics/plates` | admin | Match rate, queue depth and age, corrections · cached 10 min |
| `GET /reports/quarterly/{cycleId}` · `/reports/period/{cycleId}` | admin | Export · `?format=csv` |
| `POST /captures` | **camera** · admin | A presigned PUT for one frame |
| `GET /plate-reads` | admin | The gate log, newest first |
| `GET /plate-reads/review` | admin | The review queue, **oldest** first |
| `GET /plate-reads/{id}` | admin | One read, its candidates, and 5-minute image URLs |
| `POST /plate-reads/{id}/resolve` | admin | Review · `Idempotency-Key` required |
| `GET /access-events` | admin | The access log · `?format=csv` |

Errors use one shape, with a `traceId` that matches the log correlation id:

```
{
  "error": "RAFFLE_IN_PROGRESS",
  "message": "An allocation run is already executing for this cycle.",
  "traceId": "7b4e...",
  "timestamp": "2026-03-26T02:00:00Z"
}
```

Two cross-cutting conventions. **Paging is keyset**, with a `limit` capped at 100 and a `nextCursor`; offset paging would shift rows under an administrator working a queue. **`Idempotency-Key` is required** on the two routes where a retried click would otherwise write a second irreversible decision: running a draw, and resolving a plate read.

---

## 10. Running it locally

```
cd code
pnpm install          # also points git at .githooks through the root `prepare` script
```

### No AWS, no database, no deploy

```
pnpm --filter @pacs/api local     # the stub API on http://localhost:4300
cd apps/web && pnpm offline       # http://localhost:4200
```

`scripts/local-api.mjs` is an in-memory implementation of the same contract, seeded with 72 residents, 56 bays, four periods, a vehicle register and a gate log with reads waiting in the review queue. It is a *fixture*, not a second implementation: when a shape there disagrees with `openapi.yaml`, the YAML wins and the stub is the bug. Its bearer token is `local.<base64url json>` with no signature, accepted only by it — the deployed API rejects such a token at the Cognito authorizer before any handler runs. Sign in as `admin@local` or `resident@local` with any password.

This is the loop to use for almost all work. It is also what the Playwright suite runs against.

### Against the real database

Export a connection string once per shell. Nothing is committed and no password is passed on a command line:

```
$s = aws secretsmanager get-secret-value --secret-id dev/hotel-db/connection `
       --profile hotel --region us-east-2 --query SecretString --output text | ConvertFrom-Json
$env:DATABASE_URL =
"postgresql://$($s.username):$([uri]::EscapeDataString($s.password))@$($s.host):$($s.port)/pacs_d
ev?sslmode=no-verify"
```

This only works from a machine the security group admits — see §5.


```
pnpm --filter @pacs/api migrate:up
pnpm --filter @pacs/api seed                        # 24 residents, 10 bays, one open period
pnpm --filter @pacs/api exec tsx scripts/run-draw.ts
```

`run-draw.ts` wires the real repositories to the real use case and asserts the things only Postgres can prove: the run lock, the uniqueness constraints, the waitlist having no gaps, the period moving to ACTIVE, and that `app_user` cannot `UPDATE allocation_history`.

---

## 11. Deploying

Two engines, and the split is forced rather than chosen.



**Why Actions cannot deploy.** This account sits under an organisation whose service control policy denies every IAM action on identity providers — creating one, and even reading one. Keyless GitHub OIDC federation into the account is therefore impossible, and the alternative, an IAM user whose access keys live in a public repository's secrets, is a long-lived credential nobody should have to rotate. CodePipeline runs inside the account on a service role and needs no federation at all.

**Why CodePipeline cannot replace Actions.** It starts after a merge. By then there is nothing to stop. Only a check reported on the pull request itself can prevent bad code landing, which is what the six Actions checks are for — and they need no AWS credentials, no network beyond the registry, and are therefore safe to run on a pull request from a fork.

**Why the pipeline is manual-start.** `DetectChanges: false` on the source action. A merge into `development` lands the code and nothing else happens until somebody releases it, so a merge can never surprise the environment somebody is demonstrating on. It is a V2 pipeline, so an execution can be started against a chosen commit with `--source-revisions`, which is how a loose branch gets tried on the development environment without opening a pull request.

Other things about the pipeline worth knowing before changing it:

- **The Build stage repeats the unit tests Actions already ran.** Deliberately: branch protection can be bypassed by an administrator, and on this project the administrator is also the only engineer. A pipeline that trusts a check it did not run will one day deploy something that does not compile. A minute of CodeBuild buys that away. What is *not* repeated is Playwright — its whole purpose is to block a merge, and after the merge it blocks nothing.
- **The artefact carries no `node_modules`.** pnpm builds them out of symlinks into a content-addressed store, and those do not survive being zipped and unzipped in another container. The deploy stage reinstalls from the same lockfile, which costs about thirty seconds and is reproducible.
- **Backend before frontend, always.** A frontend that went up first would, for the length of the deploy, be a new client calling an old server.
- **Hashed assets first with a one-year immutable cache, `index.html` last with `no-store`.** If `index.html` went up first it would briefly point browsers at chunks that are not there; if it were cached like the chunks, a returning visitor would never see the deploy at all.
- **The build role is `PowerUserAccess` plus a narrow inline IAM policy**, scoped to `pacs-api-*` roles, with an explicit `Deny` on anything named `pacs-pipeline-*` so it can never rewrite its own trust or permissions. Enumerating every action `serverless deploy` may emit is a policy nobody can keep correct, and getting it wrong surfaces as a deploy that dies half-applied.

To deploy by hand from an admitted machine:

```
cd apps/api
pnpm --filter @pacs/api migrate:up                      # if there are new migrations
serverless deploy --stage dev --aws-profile hotel --region us-east-2
node scripts/smoke.mjs
```

### Two things that will bite on a fresh deploy

**Handler filenames must contain no dots.** The bundle is flattened and the Node runtime splits the handler string at the *first* dot, so `src/main/api.handler.ts` with handler `src/main/api.handler.handler` fails at init with `Cannot find module 'api'`.

**An S3 trigger on a bucket the same stack creates is a circular dependency.** The bucket needs the function's ARN for its notification, the function's invoke permission needs the bucket, and CloudFormation refuses the loop. It is broken by giving `PlateRecognizerLambdaPermissionS3` a **literal** `SourceArn` string rather than `!GetAtt CapturesBucket.Arn`. The same applies to the S3 statements in the service role. After a deploy, confirm the trigger actually attached — this is the step that silently fails:

```
aws s3api get-bucket-notification-configuration \
    --bucket pacs-captures-dev --profile hotel --region us-east-2
```

---

## 12. Test strategy

Five layers, each answering a question none of the others can.

| Layer | Command | Size | What only it can prove |
|---|---|---|---|
| Unit, API | `pnpm --filter @pacs/api test` | **267 tests in 23 files**, about 3 s | The rules. The draw is run ten thousand times with seeded inputs to check it is *fair*, not merely that it runs; the whole plate threshold table is a set of table tests |
| Unit, web | `pnpm test` in `apps/web` | **69 tests in 10 files** | The boundary between DTO and model — the mappers, where a contract change actually bites |
| End to end | `pnpm e2e` in `apps/web` | 2 specs, Playwright, Chromium | That the screens work, against the in-memory stub. One worker, because both servers hold a single in-memory building |
| Post-deploy smoke | `node scripts/smoke.mjs` + `smoke-plates.mjs` | 48 checks + the plate pipeline | That the *deployed* system works. The only layer that can speak for Cognito, for Postgres, or for whether a frame put in an S3 bucket comes back out as a recognised plate |
| Integration, by hand | `tsx scripts/run-draw.ts` | 16 checks | The things only Postgres can prove: the run lock, the constraints, the privilege revocation |

Properties of the suites worth keeping:

- **The statistical suite is the unusual one, and it is the point.** `priority-key.properties.spec.ts` asserts transitivity, the uniformity of the raffle across a k-way tie, and the three-resident cycle that the pairwise reading of rule F would produce.
- **The plate suite is the same argument applied to a different problem**, including the regression that matters most: `VISITAS` canonicalises to `V1S1TAS`, the U/V confusable pair expands that to `U1S1TAS`, and a string the blocklist has never heard of then scores like a plate. The blocklist is therefore checked on the OCR line, before expansion.
- **The E2E suite deliberately does not run against AWS.** It would be slower, cost a Rekognition call and a stored frame per run, fail whenever somebody else was using the dev environment — and, as this project found out, it leaves rows behind: a smoke suite once invented a period called `2235-Q1` that then drove the administrator's "ready to draw" banner on a real screen.
- **The smoke suites clean up after themselves as far as they can.** The Cognito users are deleted on every run; the fixtures are taken down through the API with the administrator's token — the period deleted, the resident deactivated, the bay retired. Two inert rows per run remain, because removing those

means reaching the database, and CodeBuild cannot (§5). `scripts/clean-smoke-data.mjs` clears them from an admitted machine.

- **A smoke check must not depend on what the environment happens to hold.** The paging check seeds two residents of its own so there are always two pages to walk, and the draw check asserts whichever outcome the environment makes true (a draw, or the `drawBlocker` refusal while a period is in effect) rather than assuming one. Both were learned from red Verify stages on an environment somebody was using.
- **Every resident the smoke suites create is on `@example.test`**, so `integrations` creates their Cognito users without an invitation (§8.5). A smoke suite that invents an address on a real domain will spend the day's email quota again.
- **The draw is not run in the pipeline.** A committed run is a record, and `cycleRemovalBlocker` refuses to delete a period that has one, so running the draw there would make the test period permanent. The write path is covered by the unit tests instead. Set `DATABASE_URL` and the suite runs the draw and clears it afterwards — which is what a developer gets and the pipeline deliberately does not.

---

## 13. Known constraints and gaps

Each of these is a decision forced by the real account, or an acknowledged absence. None of them is a surprise waiting to be found.

### Forced by the environment

| | |
|---|---|
| Region | `us-east-2` only. SCP `p-wvjo6arp` denies every other region |
| Identity federation | No GitHub OIDC provider is possible: the SCP denies every IAM action on identity providers. This is the whole reason deployment runs on CodePipeline |
| Lambda concurrency | Quota is 10, and AWS requires 10 unreserved, so no function can reserve any. The quota bounds the connection pool at 10 × 2 = 20 |
| Database | Shares the existing `hotel-db` (PostgreSQL 18.3, `db.t4g.micro`, single-AZ, backup retention **1 day**); `pacs_dev` is its own database. The specification asks for a dedicated instance and 7-day backups |
| Network | The default VPC, the default security group, public subnets, and a publicly accessible instance admitting one `/32`. Requested, so migrations run from a laptop. Reverting is two commands |
| Migrations | Not in the pipeline: CodeBuild cannot reach the database. Applied by hand before the deploy that needs them. The intended answer is a migration Lambda inside the VPC that the Deploy stage invokes |
| TLS to the database | `rejectUnauthorized: false` — the RDS CA bundle is not shipped in the Lambda bundle. Encrypted, not verified. `verify-full` with the RDS global bundle is on the gap list |
| Serverless Framework v4 | Needs a vendor access key in CI, read from Secrets Manager. Free for individuals and for organisations under the vendor's revenue threshold; confirm the licence before using it for a company account |
| Email | Cognito's default sender: **50 emails a day for the account**, from `no-reply@verificationemail.com`, often filed as spam. Enough for a demonstration, not for a building. The way out is the pool's `EmailConfiguration` on a verified SES identity — and SES itself is in sandbox (below) |
| Stream retries | `integrations` retries a failed record 3 times and then drops it; there is no on-failure destination |

### Not built

- SES notification templates. `integrations` already receives the allocation events and logs them; only the templates and the send call are missing. SES is in sandbox (`ProductionAccessEnabled: false`, 200/day), so it can only send to verified addresses.
- The plate crop writer. `plate_read.crop_key`, the `crops/` IAM statement and the lifecycle rule all exist, but nothing writes a crop: cropping needs a native image decoder in the bundle, and the review screen reads the full frame instead.
- Camera firmware. The browser capture page exists — `/gate`, for a `CAMERA` account or an administrator, using whatever camera the browser exposes — but nothing runs on a dedicated gate device.
- An on-failure destination (SQS DLQ) on the `integrations` stream mapping, so a failed provisioning is kept rather than dropped after three retries.
- Lot geometry. `GET /lots/{level}/layout` and the tables behind it; the plan draws real bays on generated places (§3.3).
- Threshold calibration. The procedure and the storage exist; the week of shadow operation that produces real numbers has not happened, so `0.85` and `0.55` are a labelled starting point.
- Transloco is installed but not wired. Spanish and English are required. One sentence resists it: the fairness explanation comes back from the API as finished prose rather than a message key plus parameters, so it cannot be localised without changing the contract. That is the one real design debt on the frontend. The plates module deliberately does not repeat the mistake — `access_event.reason` is a stable code and the wording lives in `features/plates/reason-label.ts`.
- No k6 load suite.

**Where the repository's own documents are out of date**

- **The live user pool has drifted from `serverless.yml`.** The template declares `AllowAdminCreateUserOnly: false`; the deployed pool reports `true` (checked with `aws cognito-idp describe-user-pool` on 2026-10-14). Self sign-up is therefore off, which is what the product wants — residents are created by an administrator — but the next deploy that touches the pool will turn it back on. The template should say `true`.
- `docs/analisis.html` sections 12 and 13 describe the probabilistic weighted lottery that rules A–F replaced. Section 10 still says `us-east-1`, private subnets, per-function IAM roles, a master password in SSM and the `*.handler.ts` filename convention — none of which is what runs.
- `pipeline/dev/buildspec-deploy.yml` says RDS is in private subnets. It is not; the conclusion it draws is still right, but for the security group's reason, not the subnet's.
- The doc comment at the top of `plates/domain/access-decision.ts` says the thresholds are read from `allocation_config`. They are read from `plate_config`.
- `src/main/integrations.ts` logs a failed stream record as `{ message: ... }`. Powertools' logger reserves `message`, so the error text is dropped and the line reads only "record failed" — the same defect pull request #20 fixed in `api.ts`. It is why the email-quota failure of §8.5 had to be read from CloudTrail rather than from the function's logs.

---

## 14. Operating the dev environment

What to reach for when something is wrong. Every command assumes `us-east-2` and the `hotel` profile; the scripts in `apps/api/scripts/` read `DATABASE_URL` from `apps/api/.env` (gitignored) and must run from an

address the database's security group admits (§5). Every script that deletes anything is a **dry run unless given `--apply`**, and prints what it would remove first.

### 14.1 Where to look first

| Symptom | Look at | Command |
|---|---|---|
| A screen shows an error with a trace id | The API's log, filtered by that id | `MSYS_NO_PATHCONV=1 aws logs filter-log-events --log-group-name /aws/lambda/pacs-api-dev-api --filter-pattern '"<traceId>"'` |
| A 500 | The same log; the line carries `detail`, and the Postgres `code` and `constraint` when there is one | as above |
| A new resident never got the invitation | CloudTrail, not the function log (§13) | `aws cloudtrail lookup-events --lookup-attributes AttributeKey=EventName,AttributeValue=AdminCreateUser` — look for `errorCode` |
| The deploy failed | The CodePipeline execution, then the CodeBuild log of the failed stage | `aws codepipeline list-pipeline-executions --pipeline-name pacs-development --max-items 3` |
| Verify failed | The `pacs-smoke-development` build log; every check prints its name and why it failed | — |
| A plate never became a read | The S3 trigger, then `plateRecognizer`'s log, then the `plateIngest` iterator-age alarm | `aws s3api get-bucket-notification-configuration --bucket pacs-captures-dev` |
| A change does not appear on the dashboard | The 5-minute dashboard cache. Writes that change it invalidate it; a hand-edit in the database does not | wait 5 minutes, or delete the `dashboard:` items in `pacs-cache-dev` |

### 14.2 Known incidents and their fix

**Cognito's daily email quota is spent** (`LimitExceededException: Exceeded daily email limit`). The quota resets about 24 hours after the sends that spent it. Residents created in the meantime have a register row and no Cognito user, because the stream record was dropped after three retries. Once the quota is back, provision each one again by replaying the event `integrations` consumes — it is idempotent, so a user who does exist is read, not recreated:

```
aws dynamodb put-item --table-name pacs-events-dev --item '{
  "pk":      {"S": "evt#<a new uuid>"},
  "type":    {"S": "ResidentCreated"},
  "payload": {"M": {"residentId": {"S": "<resident uuid>"},
                    "email":      {"S": "<their email>"},
                    "fullName":   {"S": "<their name>"}}}
}'
```

The stream delivers it, `integrations` creates the user, adds it to `RESIDENT`, sends the invitation and writes the `link#<sub>` item the API claims on first sign-in.

**A route answers 400 to a valid code** (`B1`, a plate). The parameter is named like an id, so the router demanded a UUID (§3.2). Rename the parameter; do not loosen the router.

**`POST /cycles` answers 400 on the label.** A period with that label exists. Give the new one a different label, or remove the old one if it never ran (§7.4).

**Two periods ACTIVE at once.** Cannot happen any more (`drawBlocker`), but data from before it can still show it. Close the older one with `POST /cycles/{id}/close`.

### 14.3 Operator scripts

| Script | What it does |
|---|---|
| `clean-smoke-data.mjs [--apply]` | Removes what the smoke suites leave behind: their rows in the database and their accounts in the user pool. Matches only the patterns the suites generate |
| `reset-periods.mjs [--apply]` | Removes **every** period and everything hanging off it — history, waitlist, assignments, runs, registrations — in one transaction. Residents, bays, vehicles and rules are untouched; everybody's waiting time starts again. The product refuses this on purpose (history is never reset); this is for clearing a development environment before a demonstration |
| `keep-only-users.mjs --keep <prefix> [--apply]` | Removes every user whose email does not start with the prefix, from the database and the user pool. The prefix is required; it refuses if nobody would stay |
| `set-admin-flag.mjs <email> [--clear] [--apply]` | Sets or clears `resident.is_admin`, the register-side half of separation of duties |
| `create-gate-user.mjs <gate-id>` | Creates one `CAMERA` account for one lane. The password comes from `GATE_PASSWORD` and is never generated, printed or logged |
| `apply-login-branding.mjs` | Applies the PACS branding to Cognito's managed login page |
| `seed.ts` · `run-draw.ts` | 24 residents, 10 bays and an open period · a real draw against the real database, with its assertions (§10) |
| `smoke.mjs` · `smoke-plates.mjs` | The Verify stage, runnable by hand against the deployed API |

`reset-periods.mjs` and `keep-only-users.mjs` cannot be undone. Run the dry run, read the list, and only then add `--apply`. On a shared environment, say so in the team channel first: whoever is demonstrating on it loses their data too.

---

## 15. What changed since the first edition

The first edition of this document was written on 2026-10-11 against pull request #8. These are the merged changes since, each one subject, in order. The sections above already describe the result; this list is for a reader who knew the earlier version.

| PR | Change | Sections |
|---|---|---|
| #9 | Rules G and H: withdrawing counts as holding a bay; missing a period restarts the clock. `declineGraceHours` removed; `absenceResetPeriods` replaces `absenceResetMonths`. Migration 6 | §6.2, §7.3 |
| #7, #10, #12 | The smoke suite asserts whichever draw outcome the environment makes true, and seeds its own residents for the paging check | §12 |
| #11 | The `/docs/` spelling of the Swagger route was removed: an HTTP API route key cannot end in a slash, and CloudFormation rejected the stack. `/docs` remains | §9 |
| #13, #14 | Real lot occupancy, `GET /lots/{level}/occupancy`; the parameter renamed from `{levelId}` because the router refused `B1` | §3.2, §3.3, §9 |
| #15 | Creating, opening or closing a period invalidates every cached dashboard | §7.2 |
| #16 | `GET /cycles/{id}/registrations`: "Run the draw" lists the period's entrants, not every eligible resident | §9 |
| #17 | An entrant keeps seeing their period as **Entered** after registration closes, until the draw | §7.2 |
| #18 | The lot plan draws the building's real bays, can be refreshed, and the draw's map opens on the right level | §3.3 |
| #19 | The gate lists cameras when it opens and follows plug, unplug and switch | §3.3 |
| #20 | A duplicate period label is a 400, and a 500 logs its reason | §6.5 |
| #21 | `GET /lots` lists only levels with a bay in service; the draw's result can be refreshed | §9 |
| #22 | No invitation email to reserved test addresses, after the smoke suites spent Cognito's daily quota | §8.5, §14.2 |