PACS — Technical documentation

Parking Allocation Context System. This document is written for the next engineer on the project: what the system is, how it is put together, how to run it, how to deploy it, what the data and the rules are, and where the edges are.

Everything here was checked against the code in this repository and, where it concerns deployed infrastructure, against the account itself. Where the code and the older specification disagree, the code wins and the disagreement is stated.

Repository	`jcallisayaunosquare/pacs-parking-allocation`, default working branch `development`
Account · region	`309887812390` · `us-east-2` — the only region the organisation's SCP permits
API	`https://frd8e8nkhl.execute-api.us-east-2.amazonaws.com`
Site	`https://d2gamvhpvfk16e.cloudfront.net`
Identity	Cognito user pool `pacs-dev` (`us-east-2_NsdZ4M0mj`), app client `2tu4q5vefr1g98u90u8dspmife`
Database	RDS PostgreSQL 18.3, instance `hotel-db`, database `pacs_dev`
Stacks	`pacs-api-dev` (Serverless Framework v4) · `pacs-web-hosting-dev` · `pacs-pipeline-dev` (CloudFormation)

1. What the system is

A residential building has fewer parking bays than residents. PACS allocates them on a recurring period — three months by default, but the duration is a configuration value, not a constant — by a stated rule rather than by discretion or by who asked first.

The shape of the work:

1. An administrator maintains the register of residents and the inventory of bays.
2. A period is created and registration is opened. Residents enter.
3. Registration closes. The administrator runs the draw.
4. Every entrant is ranked by one deterministic ordering; the top *n* get the *n* bays and the rest take numbered waitlist places.
5. The period runs. A resident may give up a bay, which promotes the head of the waitlist.
6. The period ends — on its own date, or because an administrator closed it early — and everybody's waiting time starts again from the instant their bay ended.

Alongside that sits the gate: a camera photographs a plate, the system reads it, matches it against the register of residents' vehicles, and records allow, deny, or "a human should look at this".

Two properties make the product what it is, and most of the design follows from them:

- **The result is explainable and re-derivable.** A run stores the configuration version it used, every candidate's computed key, the random seed and a hash of both its inputs and its output. A resident who disputes the outcome is shown the arithmetic, not a policy.
- **The record is append-only.** `allocation_history`, `allocation_run_candidate`, `allocation_config`, `plate_config` and `access_event` cannot be updated or deleted by the application's database role. This is a database privilege, not a convention, so a compromised application credential still cannot rewrite why somebody lost.

---

2. Repository layout

A pnpm workspace (`pnpm-workspace.yaml` takes `apps/*` and `packages/*`), pinned to `pnpm@9.15.9` through `packageManager` in the root `package.json`.

```
code/
├── apps/api/                backend — TypeScript, Lambda, Serverless Framework v4
│   ├── serverless.yml       functions, events, Cognito, DynamoDB, S3, VPC endpoint, alarms
│   ├── migrations/          node-pg-migrate, raw SQL, up and down
│   ├── scripts/             seed, offline stub API, smoke suites, operational scripts
│   └── src/
│       ├── shared/          kernel: Result, errors, Clock, db, cache, events, http
│       ├── modules/         one Clean Architecture ring set per module
│       │   ├── allocation/  M-1  periods, runs, the draw, the waitlist
│       │   ├── residents/   M-2  the register, the vehicle register
│       │   ├── inventory/   M-3  bays
│       │   ├── fairness/    M-4  standings, explanations, metrics
│       │   ├── identity/    M-6  JWT claims → Principal, RBAC
│       │   └── plates/      M-7  recognition, the gate log, access events
│       └── main/            composition roots and Lambda handlers — the only `new`
├── apps/web/                frontend — Angular 22, standalone, zoneless, signals
├── packages/contracts/      OpenAPI 3.1 — the contract both sides are checked against
├── pipeline/dev/            CloudFormation: CodePipeline, CodeBuild, S3 + CloudFront
├── .github/workflows/ci.yml  the six pull request checks
├── .githooks/pre-commit     the local gate
└── docs/                    analisis.html (the original specification) and this set
```

Inside every backend module the same three rings, with source dependencies pointing inward only:


- `domain/` — pure TypeScript. No `async`, no I/O, no clock, no random number generator. The instant and the seed are arguments. This is why the draw can be run ten thousand times in a unit test and the whole plate decision table verified in milliseconds.
- `application/` — use cases. Knows ports (interfaces), never an implementation.
- `infrastructure/` — Kysely, DynamoDB, S3, Rekognition, Cognito.

`src/main/` wires them. It is the only place that calls a constructor on an adapter, which is what makes a fake repository a one-line substitution.

---

3. Architecture


3.1 The whole system at a glance


Resident browser
Administrator browser
Gate camera CAMERA account
CloudFront E3O4NI6BRCU0X3 + S3 pacs-web-development-309887812390 the Angular bundle
fetch, Bearer token
API Gateway HTTP API native Cognito JWT authorizer
token verified before the handler runs
λ api — lambdalith in VPC
sign in
sign in
PUT frame
presigned PUT
S3 pacs-captures-dev
DynamoDB pacs-cache-dev · pacs-events-dev
ObjectCreated
stream
stream, filtered
λ integrations · λ plateRecognizer outside the VPC
λ runRaffle · λ sweeper in VPC, EventBridge schedules
Cognito user pool pacs-dev SRP sign-in, JWT issuance
RDS PostgreSQL 18.3 hotel-db / pacs_dev
Amazon Rekognition DetectText

Two things in that picture are unusual and both come from one decision: **there is no NAT gateway** (ADR-016, roughly 32 USD/month avoided). A Lambda attached to the VPC can reach exactly two things — RDS, and DynamoDB through a free gateway endpoint. It cannot reach Cognito, S3 or Rekognition.

So anything that needs the internet runs *outside* the VPC and is fed by a DynamoDB stream. A stream is polled by the Lambda service, not by the function, so a function with no outbound route can still be invoked by one. That single trick is what makes the whole topology work, and it appears twice: once for Cognito provisioning (`integrations`) and once, inverted, for plate recognition (`plateRecognizer` outside, `plateIngest` inside).

3.2 Back-end architecture — where each service intervenes



Reading that from the top, with what each layer is responsible for and what it is deliberately *not*:

Stage	What it does	What it must never do
API Gateway	Verifies the JWT's signature, issuer, audience and expiry against the Cognito pool before any code of ours runs. Answers CORS preflight itself — `OPTIONS` is left unrouted on purpose, because an `ANY` route would send the preflight to the authorizer, which would 401 it for having no `Authorization` header.	Authorise. It knows nothing about roles.
`api.ts`	One handler for every route (a lambdalith, ADR-014). Mints the trace id that appears in every log line and in every error body.	Hold business logic.
`router.ts`	Matches the path, checks the caller holds one of the route's roles, rejects any `{…id}` parameter that is not a UUID *before* it reaches a query, parses the body.	Decide which resident the caller is. It only knows the token.
`principal.ts`	Maps verified claims to a `Principal`: subject, email, roles from `cognito:groups`, `custom:resident_id` when present.	Read an identity from a path, query or body.
`routes.ts`	Zod schemas at the edge, presentation on the way out. Two guards live here because a route's `roles` list cannot express them: `adminHasNoResidentSurface` (a role list is an OR, so a principal in both groups would satisfy `['RESIDENT']`) and `residentScope` (a record-level rule the role list knows nothing about).	Reach a repository directly for a decision.
`application/`	Idempotency, the run lock, transactions, cache invalidation, event publication.	Contain the fairness policy.
`domain/`	The ordering, the state machines, the removal rules, the plate decision table. Pure.	Know that Postgres exists.
`infrastructure/`	SQL through Kysely, DynamoDB through the document client, presigned S3 URLs, Rekognition calls.	Make a decision. The snapshot query emits *facts* — anchors, counts, flags — and never a priority key, because duplicating the key formula in SQL and TypeScript would guarantee drift.

The other five functions in the same stack:


Function	Trigger	In VPC	Memory · timeout	What it is for
`api`	HTTP API	yes	512 MB · 10 s	Every route
`runRaffle`	EventBridge `cron(0 6 * * ? *)`, plus a pre-warm at 05:55	yes	512 MB · 60 s	Draws for whichever period is in `REGISTRATION_CLOSED`; returns `NO_RUNNABLE_CYCLE` otherwise. A daily poll rather than a quarterly cron, because the period length is configurable and a quarterly cron would hard-code "every three months" into infrastructure no administrator can edit.
`sweeper`	EventBridge `rate(5 minutes)`	yes	512 MB · 60 s	Fails runs stuck `RUNNING` for 15 minutes, expires assignments whose period has ended and closes those periods, relays the event outbox
`integrations`	`pacs-events-dev` stream	**no**	512 MB · 30 s	Cognito provisioning: `AdminCreateUser`, add to `RESIDENT`, write the `link#<sub>` item back
`plateRecognizer`	S3 `ObjectCreated:Put` on `raw/*.jpg` and `raw/*.png`	**no**	1024 MB · 30 s	Rekognition `DetectText` → a `PlateRecognized` event
`plateIngest`	`pacs-events-dev` stream, filtered to `pk` prefix `plateread#`	yes	512 MB · 30 s	Applies the event to Postgres: `plate_read` + usually `access_event`

Three details in that table carry weight:

- **`plateRecognizer` has 1024 MB and not 512.** A full vCPU is allocated at 1769 MB and the share below that is proportional. The inference is Rekognition's, but this function still pays for JSON, signing and the SDK on a cold start, and 1024 is where the duration stops falling. Measure with Lambda Power Tuning before changing it.
- **`plateIngest` must keep its `filterPatterns`.** Without them it wakes for every Cognito provisioning and allocation event on the shared table and pays for an RDS connection to discard each one.
- **No function has `reservedConcurrency`.** The account's Lambda quota is 10 concurrent executions and AWS requires 10 to stay unreserved, so nothing can be reserved at all. The quota itself bounds the connection pool: at most 10 containers × 2 connections = 20, inside a `t4g.micro`'s budget.

3.3 Front-end architecture — where each service intervenes

Angular 22, standalone components, **zoneless** (no `zone.js`), signals throughout, Angular Material 22 with the project's own theme. The rings mirror the backend's.



What each part is for, and the rule it enforces:

- **`app.config.ts` is the only binding site.** `{ provide: ResidentRepository, useClass: HttpResidentRepository }` and eleven more like it. Swap a line and the whole application runs against fakes — which is exactly what the unit tests do. `LotRepository` is bound to `SeedLotRepository` today because there is no layout endpoint yet; the day `GET /lots/{id}/layout` lands, one line changes and nothing above the data ring notices.

- `domain/` **holds repository *contracts as abstract classes*.** Abstract classes rather than interfaces because Angular's injector needs a runtime token, and an interface has none.
- **Facades own asynchrony, pages do not.** A page reads signals and renders. The facade decides when to refetch and holds the five states the `view-state` host renders (idle, loading, empty, error, loaded) — which is why no page in this codebase contains a `subscribe`.
- **Guards are usability, never security.** They stop a resident landing on a page that would only 403. The server is the boundary, always; the API repeats every one of these rules and is the one that counts.
- **Routes are lazy, one bundle per screen**, so a resident never downloads the admin screens.


The navigation is built from the roles on the principal, in the order the work is done — because the order is not obvious and the menu is the only place it is written down. For an administrator: **Residents · Bays · Fairness & rules · Periods · Run the draw · The lot · Gate · Reports.** "Fairness & rules" sits before "Periods" because it holds the rules editor, and the allocation duration there decides how long the period about to be created will run. For a resident: **My parking · The lot · History.** A `CAMERA` account gets one link, `Gate`, and nothing else: it is a device, and the only route the server will serve it is `POST /captures`.

Sign-in does not use the Cognito hosted page. `CognitoService` drives `amazon-cognito-identity-js` with `USER_SRP_AUTH` from the product's own form, so the password is never transmitted and the wrong-password, first-sign-in and MFA states are the product's screens rather than someone else's. See §8.1.


---

4. AWS services

Two views of the same account. This one is the map: every service PACS uses, with its own mark, and the path a request takes across them. The one after it is the same estate annotated — resource names, sizes and the settings that matter — because a logo cannot tell you that the bucket is private or that two of the functions sit outside the VPC.


Delivery
GitHub Actions
checks only
gates the merge
CodePipeline
CodeBuild ×3
CloudFormation
The browser
Resident or
administrator
sign in
Delivery and identity
CloudFront
Cognito
verifies the token
S3 — Angular bundle
The gate
Camera
CAMERA account
a frame
Application
API Gateway
creates and updates
Lambda ×6
read at deploy
Rekognition
DetectText
SES
Operations
CloudWatch, X-Ray
Secrets Manager
State
RDS PostgreSQL
DynamoDB — cache, events
S3 — captures

Rekognition and the camera carry no mark: the `logos` icon set has no Rekognition glyph, and the camera is a device rather than a service. Everything else is the vendor's own.


Delivery — stack pacs-pipeline-dev
CodePipeline pacs-development
manual start
CodeBuild ×3
build · deploy · smoke
GitHub Actions
PR checks, no AWS
S3 pipeline artefacts
14-day expiry
sync + invalidate
serverless deploy
Operations
CloudWatch Logs, 30 d
X-Ray tracing
2 alarms
Secrets Manager
dev/hotel-db/connection
pacs/serverless-access-key
Frontend delivery — stack pacs-
S3 pacs-web-development-309887812390
private; versioned; OAC only
CloudFront E3O4NI6BRCU0X3
OAC · HSTS, nosniff, DENY, strict-origin
403/404 → /index.html 200
Backend — stack pacs-api-dev
API Gateway HTTP API
JWT authorizer
λ api
presign
verifies
Data
DynamoDB pacs-cache-dev
TTL · prefix-index
S3 pacs-captures-dev
Retain · versioned · lifecycle
ObjectCreated
λ plateRecognizer
no VPC
λ sweeper
Vision
Rekognition DetectText
DynamoDB pacs-events-dev
stream NEW_IMAGE · TTL
stream, filtered
stream
λ plateIngest
λ runRaffle
λ integrations
no VPC
RDS hotel-db · pacs_dev
db.t4g.micro, 20 GB, encrypted
Identity
Cognito user pool pacs-dev
ADMIN · RESIDENT · CAMERA
access/id 15 min, refresh 30 d


Service by service, with the boundary each one sits on:

Service	Resource	What it does here	Boundary
CloudFront	`E3O4NI6BRCU0X3`	Serves the Angular bundle over TLS; rewrites 403 and 404 to `/index.html` with a 200 so deep links and refreshes work in a client-routed app; adds HSTS, `X-Content-Type-Options`, `X-Frame-Options: DENY` and a referrer policy	Public internet → the only public door to the frontend
S3	`pacs-web-development-309887812390`	Holds the built bundle. Private, versioned, reachable only through the distribution by origin access control, scoped by `AWS:SourceArn` to that one distribution	Private; no public read, no website mode
Cognito	`us-east-2_NsdZ4M0mj`	Issues and signs the tokens. Groups `ADMIN`, `RESIDENT`, `CAMERA`. 12-character password policy, optional TOTP MFA, `PreventUserExistenceErrors` on	The identity boundary. Everything downstream trusts its signature and nothing else
API Gateway	HTTP API	Route matching, CORS, and the native JWT authorizer that rejects an invalid token before a Lambda is invoked	Public internet → the only public door to the backend
Lambda	six functions	All application code	The VPC boundary runs through the middle of this row — see §5
RDS	`hotel-db` / `pacs_dev`	The record. PostgreSQL 18.3 on `db.t4g.micro`, 20 GB gp3, encrypted, single-AZ, IAM database authentication enabled	Inside the VPC, but the instance is **publicly accessible** — see §5
DynamoDB	`pacs-cache-dev`	Read cache with TTL: the resident dashboard for 5 minutes, the fairness and plate metrics for 10. A GSI on `prefix` makes prefix invalidation one query	Reached from in-VPC functions through a free gateway endpoint
DynamoDB	`pacs-events-dev`	The relay between inside and outside the VPC. Carries outbox events, the `link#<sub>` subject mappings `integrations` writes back, and the `plateread#<captureId>` recognition events. `NEW_IMAGE` stream, TTL on `expiresAt`	Same gateway endpoint; the stream is polled by the Lambda service, not by our functions
S3	`pacs-captures-dev`	Gate frames under `raw/<cameraId>/<yyyy>/<mm>/<dd>/<captureId>.jpg`. `DeletionPolicy: Retain`, versioned, SSE-S3, all public access blocked. Lifecycle: `raw/` to Glacier IR at 90 days and deleted at 400; `crops/` deleted at 120	Written by a presigned PUT the camera executes; read only by `plateRecognizer`
Rekognition	`DetectText`	Reads text out of a frame. Behind the `PlateRecognizer` port, so replacing it is one class in `infrastructure/` and one line in `src/main`	The one IAM statement that cannot be resource-scoped — Rekognition operations that work without a collection have no ARNs — so it is scoped by action and said out loud in `serverless.yml`
Secrets Manager	`dev/hotel-db/connection`, `pacs/serverless-access-key`	The master connection details for migrations from a laptop, and the Serverless Framework licence key the deploy stage reads	Never reached by a deployed function: the functions use IAM database authentication and hold no secret at all
CloudWatch	logs, X-Ray, 2 alarms	30-day log retention, tracing on every function. Alarms: `plateRecognizer` errors ≥ 3 in 5 minutes, and `plateIngest` iterator age > 60 s for two periods — a minute behind on that	—

Service	Resource	What it does here	Boundary
		stream means the access log is behind the cars that have already driven in	

IAM database authentication is the piece worth understanding. The deployed functions hold no database password. `connection.ts` gives `pg` an async `password` function that mints a token with `@aws-sdk/rds-signer` per connection; the SDK signs locally, so there is no network call and it works from inside a VPC with no internet route. The token is valid 15 minutes. The role it signs for is `pacs_app`, granted `rds_iam` and `app_user` and nothing else. There is no database credential in the function configuration, in SSM, or in git.

5. Network



The facts, and what each one costs:


- **It is the account's default VPC.** Three default subnets, one per availability zone, the main route table, and the default security group. Nothing bespoke was created. The original specification describes dedicated private subnets with a Lambda-only security group; that is not what exists.
- **The subnets carry a `0.0.0.0/0` route to an internet gateway**, which by the usual definition makes them public subnets. The in-VPC Lambdas still have no outbound internet, and the reason is worth being precise about: a Lambda ENI is never assigned a public IP, and an internet gateway only forwards traffic for addresses that have one. So the subnets are public and the functions in them are effectively isolated — which is why `integrations` and `plateRecognizer` have to sit outside the VPC, and why DynamoDB is reached through a gateway endpoint rather than over the internet. *(The comment at the top of `pipeline/dev/buildspec-deploy.yml` says "RDS sits in private subnets". It does not; the conclusion it draws — that CodeBuild cannot reach the database — is right, but the reason is the security group, not the subnet.)*
- **`sg-0b745610ae460e557` is the default security group**, and it holds both the Lambdas and the database. Inbound: TCP 5432 from a single `/32` (a developer workstation, named in the rule's description), plus all protocols from the group itself. Outbound: all. The Lambdas reach the database through that self-reference, which is why they need no CIDR rule of their own.
- **`hotel-db` is publicly accessible.** This was asked for, so migrations and scripts can run from a laptop without a bastion. The security group is the whole of the protection, and it admits one address. Closing it again is two commands, both in the API README.
- **CodeBuild cannot reach the database at all**, and that is a consequence rather than an oversight: it runs outside the VPC and its source address changes every run, so no `/32` rule can cover it. Two things follow. Database migrations are not in the deploy stage — they are applied by hand from an admitted machine before the deploy that needs them, and that is a known gap, not a decision. And the smoke suites cannot clean up their own database rows; the draw in `scripts/smoke.mjs` is gated behind `DATABASE_URL` for exactly this reason, so the pipeline runs everything except the draw.

---

6. The data model

6.1 Conceptual

What the business is about, before any decision about how it is stored:


POLICY
PERIOD
governs
is decided by
receives
RESIDENT
BAY
DRAW
enters
is ranked by
computes
takes
appears in
records
registers
holds
is awarded as
awards
assigns
REGISTRATION
CANDIDATE_KEY
ALLOCATION
WAITLIST_PLACE
HISTORY_ENTRY
PLATE_POLICY
CAMERA
VEHICLE
is named in
governs
produces
is recognised as
PLATE_READ
yields
ACCESS_DECISION


Entities only: the attributes are in §6.2 to §6.4, where they are the columns that actually exist rather than a second, slightly different list.

Four things in that picture are deliberate and are the reason the physical schema looks the way it does:

1. **A resident's waiting time is not an attribute of the resident.** It is derived at read time from two timestamps: when they started participating, and when their last bay stopped being a benefit. There is no counter to drift and no nightly job to fail.
2. `CANDIDATE_KEY` **exists as a thing in its own right.** Every entrant in every run gets a stored row with the key that ranked them. "Why did I lose?" is answered from the record of that run, not recomputed against data that has since moved.
3. `POLICY` **governs a draw, it does not configure the system.** A run points at the policy version in force when it ran, so changing the bias tomorrow cannot rewrite why somebody lost today.
4. **A plate read and an access decision are separate.** A mis-read can be corrected without rewriting the access log; a decision is overturned by inserting a new row that the old one points at, never by editing one.


6.2 Physical — what a period is made of

From `apps/api/migrations/`, as the database actually stands after all five migrations. Split in two because a draw has an input side and an output side, and they are read at different times: this is what exists before a draw runs.


resident
uuid id PK
varchar external_subject UK the Cognito sub
citext email UK
varchar full_name
varchar unit_number
boolean is_eligible
varchar ineligible_reason CHECK: needed if not
boolean needs_accessible_spot
boolean has_electric_vehicle
boolean is_admin separation of duties
timestamptz participation_started_at rule C anchor
timestamptz participation_reset_at
timestamptz created_at
timestamptz deactivated_at the soft delete
allocation_cycle
uuid id PK
varchar label UK
date starts_on
date ends_on CHECK after starts_on
cycle_state state 5 states, see 7.2
timestamptz registration_opens_at
timestamptz registration_closes_at
timestamptz created_at
parking_spot
uuid id PK
varchar spot_code UK
varchar level
spot_type type STANDARD ACCESSIBLE EV
boolean is_active
text notes
timestamptz created_at
timestamptz deactivated_at
receives
enters
changed_by
raffle_registration
uuid id PK
uuid cycle_id FK
uuid resident_id FK
timestamptz registered_at
boolean withdrawn
string uq UNIQUE cycle+resident
allocation_config
int version PK identity, append-only
int allocation_duration_months default 3
int early_waiting_bias_hours default 24
int wait_quantum_minutes default 60
int decline_grace_hours default 48
int absence_reset_months nullable
int total_bays 0 = all active bays
uuid changed_by FK
timestamptz changed_at

6.3 Physical — a run and what it produced

The output side. Every table here is written in the one transaction that commits a run, and four of the five are append-only to the application role.


event_outbox
uuid id PK
varchar event_type
varchar aggregate_type
uuid aggregate_id
jsonb payload
timestamptz occurred_at
timestamptz published_at
int attempts
text last_error
allocation_cycle
allocation_config
is drawn by
config_version
allocation_run
uuid id PK
uuid cycle_id FK
run_state state RUNNING COMPLETED COMPLETED_EMPTY FAILED
bytea random_seed
bytea seed_commitment sha256, written first
bytea input_hash
bytea result_hash
timestamptz decided_at one frozen instant
int config_version FK
varchar algorithm_version
varchar idempotency_key UK
int entrants_count
int spots_count
int assigned_count
timestamptz started_at
timestamptz finished_at
text error_detail
string ix partial UNIQUE on RUNNING = the run lock
resident
parking_spot
ranks
awards
records
assigns
allocation_run_candidate
uuid run_id PK FK — PK is (run_id, resident_id)
uuid resident_id PK FK
timestamptz anchor_at
spot_assignment
uuid id PK
uuid cycle_id FK
uuid run_id FK
uuid resident_id FK ON DELETE RESTRICT
allocation_history
uuid id PK

bigint	raw_wait_quanta		
bigint	effective_wait_quanta		
boolean	bias_applied		
boolean	first_time		
int	served_count		
numeric	raffle_token		128-bit, as decimal
int	final_rank		
text	pool		ACCESSIBLE EV STANDARD
draw_outcome	outcome		
uuid	spot_id	FK	


uuid	spot_id	FK	ON DELETE RESTRICT
assignment_state	state		ACTIVE RELEASED REVOKED EXPIRED
timestamptz	valid_from		
timestamptz	valid_until		
timestamptz	released_at		
timestamptz	benefit_ended_at		materialised
boolean	counts_as_served		the ranking reads this
text	termination_reason		
boolean	make_whole		
string	uq		UNIQUE per cycle: resident, and spot

waitlist_entry			
uuid	id	PK	
uuid	cycle_id	FK	
uuid	run_id	FK	
uuid	resident_id	FK	
int	position		CHECK > 0, UNIQUE
waitlist_state	state		WAITING PROMOTED LAPSED

uuid	run_id	FK	ON DELETE RESTRICT
uuid	cycle_id	FK	ON DELETE RESTRICT
uuid	resident_id	FK	ON DELETE RESTRICT
uuid	spot_id	FK	ON DELETE RESTRICT
draw_outcome	result		ASSIGNED WAITLISTED SKIPPED
numeric	fairness_score_at_draw		legacy, nullable
int	waitlist_position		
timestamptz	recorded_at		

`event_outbox` has no foreign key to anything, deliberately: it is a relay, written in the same transaction as the state change it announces and emptied by the sweeper. Nothing may depend on a row that is about to be deleted.

6.4 Physical — the vehicle register and the gate




6.5 Things about the schema that are easy to get wrong

- **There is no `fairness_state` table.** The initial migration created one; the `waiting-time-fairness` migration drops it in `up` and recreates it only in `down`. Fairness is derived from `spot_assignment` and `allocation_history`, which is the whole point — there is no stored score to drift.
- **The registration table is `raffle_registration`**, not `cycle_registration`.
- **`allocation_cycle` has a `state` column**, not `status`.
- **The run lock is a partial unique index**: `CREATE UNIQUE INDEX uq_single_running_run ON allocation_run ((state)) WHERE state = 'RUNNING'`. It needs no infrastructure, holds across containers and deployments, and survives a process restart. A second concurrent run gets a unique violation, which the repository turns into `RunLockHeldError` and the use case into a 409.
- **The append-only privileges.** `app_user` — and therefore `pacs_app`, which holds it — has `UPDATE` and `DELETE` revoked on `allocation_history`, `allocation_run_candidate`, `allocation_config` and `plate_config`, and on `allocation_run` has `UPDATE` granted on six named columns only. On `access_event` it has `SELECT, INSERT` plus column-level `UPDATE (superseded_by)`: a decision is overturned by inserting a new row and pointing the old one at it, so the only mutable field is the link.
- **Plate thresholds live in `plate_config`, not `allocation_config`.** The allocation module builds each new policy version from the one in force and lists its own columns, so threshold columns sitting there would be reset to their defaults every time an administrator changed the period length. *(The doc comment at the top of `access-decision.ts` still says `allocation_config`; the migration and the provider say `plate_config`, and they are what runs.)*
- **Two plate columns, deliberately.** `plate` is the canonical key — uppercase, no separators, confusables folded (`O` and `Q` → `0`, `I` → `1`), defined once in `residents/domain/vehicle.ts`. `plate_display` is what the resident typed. Folding the display form would print "ABC 123" back with the O turned into a zero, and a resident who cannot find their own plate in the list stops trusting the list.
- **Plate uniqueness is partial on `is_active`.** The rule is "two residents cannot have the same plate registered at the same time", not "this plate may only ever be registered once in the history of the building" — otherwise a car sold to a neighbour could never be registered again.

---

7. The domain rules


7.1 Who does what


Unattended
Draw for a period whose registration has closed
Expire assignments and close finished periods
Relay the event outbox
Release a run lock whose process died
Scheduled jobs
runRaffle · sweeper
The gate
Request a capture ticket
Upload a frame
Gate camera
CAMERA — a device, not a person
The administrator surface
Maintain the register of residents
Maintain the inventory of bays
Set the allocation policy
Create a period · open · close registration
Administrator
Read a run: seed, keys, assignments
Work the plate review queue
Read the gate log and the access log
Export the record of a period
Manage a resident's vehicles
Close the period in effect
Run the draw
is what unblocks
promotes the head of the waitlist
The resident surface
Enter the draw
Withdraw while registration is open
Resident
See my bay and my standing
See my own history
Give up my bay
See my own entries at the gate

Two boundaries in that diagram are enforced rather than drawn:

- **An administrator has no resident surface.** They operate the draw, so they are never a party to it. The refusal exists three times over: `resident.is_admin` on the register row, the `ADMIN` role on the verified token (checked first, because the token is what actually grants the powers), and the snapshot query, which skips an admin row with the reason `ADMIN_ACCOUNT`. Administrators are also excluded from `GET /residents` — in the query, not in the client, so a page of fifteen is fifteen. The one exception is *withdrawal*, which is deliberately allowed: an account promoted to administrator after it had already registered needs a way out of a draw it may no longer enter.
- **A resident can only ever reach their own data.** `resolveResidentId` is the single place a caller's resident id is decided, and it comes from the verified token and nowhere else — never from a path, a query or a body. On the vehicle routes, where a path id is unavoidable, a resident asking for somebody else's record is answered `NOT_FOUND` rather than `FORBIDDEN`: a 403 would confirm the record exists, which turns the route into a way of enumerating residents.

7.2 The period state machine



Every other transition is a 422 with the states named in the message. The table lives in one constant, `CYCLE_TRANSITIONS` in `allocation/domain/cycle.ts`, and the assignment lifecycle sits beside it: `ACTIVE → RELEASED | REVOKED | EXPIRED`, all three terminal and all three kept distinct on purpose, because the termination policy reads them.

Two rules attach to the ends of that machine:

A period can be removed only before it has had consequences (`cycleRemovalBlocker`). If it has handed out bays, or a draw has run, or it is ACTIVE or CLOSED, removal is refused and the refusal says why in the words an administrator reads — "Allocation history is never reset, so it cannot be removed. Close it instead when it ends." Before a draw it is a plan, and a plan can be abandoned.


A draw is refused while another period is in effect (`drawBlocker`). This one was added after the dev environment reached a state where 2026-Q4 and 2027-Q1 were both ACTIVE with bay B1-08 assigned in both, to two different residents, and nothing in the system treated that as wrong. It is worse than cosmetic: holding a bay moves a resident's waiting anchor, so a second draw would reset the anchors of people whose benefit from the first has not ended. The way forward is `POST /cycles/{id}/close`, which ends the period in effect and expires its assignments with `benefit_ended_at` set to **now** rather than to `valid_until` — because that is when the benefit actually stopped.

7.3 The draw

This is rules A–F, deterministic. It is not a weighted lottery. Sections 12 and 13 of `docs/analisis.html` describe an earlier probabilistic model with accumulating scores; it was replaced and is not what runs.

Three keys, compared in order:

1. **Longest effective waiting time first** (descending).
2. On a tie, **fewest past allocations first** (ascending).
3. On a remaining exact tie, **the raffle token**, ascending — `sha256(seed : runId : residentId)`, truncated to 128 bits.



The parts of that worth defending:

- **Rule F is arithmetic, not a second comparison.** A resident whose bay ended very recently is "cooling": they rank below everyone whose wait is still running, including first-time participants. Implemented as a *subtraction* from the key rather than as a pairwise special case — because a resident is cooling exactly while their raw wait is below the bias window, the subtraction drives every cooling resident strictly negative and everyone else non-negative, and rule F becomes a theorem of the arithmetic. The pairwise reading admits a three-resident cycle, which would make the comparator non-transitive and the sort undefined. There is a regression test for exactly that cycle, and the pairwise version must never be implemented.
- **Which bay you get is not a lottery; only whether you get one is.** Bays are handed out in `spot_code` order within each pass.
- **Restricted pools run first and spill.** A resident who loses the accessible pass falls through to the standard pass with their key unchanged, and an accessible bay nobody claimed returns to the general pool — an empty accessible bay is worse than a standard-need resident parking in it.
- **The raffle token is derived from identity, never from position in the input array.** A resident can recompute their own token with `sha256sum` and three strings. That is the whole of the fairness proof offered, and it is enough.
- **The seed is drawn and persisted before the candidate list is read**, and `sha256(seed)` is stored as `seed_commitment` at the same moment. Re-rolling for a nicer result is therefore a hash preimage problem rather than an operational one.
- **`decided_at` is frozen once per run.** Never `Date.now()` inside the loop: two candidates' waiting times computed microseconds apart would make hour-bucket membership a race, and no replay could reproduce it.
- **The snapshot is read in one `REPEATABLE READ` transaction**, so a registration committed halfway through cannot produce a candidate list that no replay can reproduce.
- **The decision is pure and in memory; the transaction opens afterwards.** The database is held open only for the writes.

The policy values behind all of it live in `allocation_config`, are administrator-editable and versioned, and appear as literals nowhere else in the codebase: `allocationDurationMonths` (3), `earlyWaitingBiasHours` (24), `waitQuantumMinutes` (60), `declineGraceHours` (48), `absenceResetMonths` (3, nullable), `totalBays` (0 = the whole active inventory). `configWarnings()` surfaces legal-but-surprising combinations rather than rejecting them — a bias wider than the allocation period would leave every previous holder permanently cooling and freeze the ordering, which is a plausible and catastrophic typo.

What counts as having been served is one pure function, `terminationPolicy`, and it writes one boolean, `counts_as_served`, once when an assignment terminates — so the hot ranking query filters on a boolean and never reasons about reason codes:

Termination	Counts as served?	Why
`EXPIRED`	yes	The normal path; the benefit ended when the period did
`RELEASED`	yes, from the moment it actually ended	A resident who gives a bay back on day 1 of 90 starts accruing on day 1. Parking days are traded for waiting days one for one; the brake on serial early release is the served count, which increments anyway
`REVOKED`	yes	They held and consumed the bay and lost it through their own conduct. Not resetting would reward misconduct with priority
`DECLINED` inside the grace window	**no**	Nothing was consumed. Penalising a free decline would make residents accept bays they cannot use, and an empty bay nobody may use is worse for everyone
`DECLINED` after the window	yes	It is an early release
`CANCELLED` with `make_whole`	**no**	Our mistake — admin error, building works — must not cost the resident their place in the queue


7.4 Removal: the same line, drawn three times

Rule	Where	The line
`cycleRemovalBlocker`	`DELETE /cycles/{id}`	A period with no run and no assignments can be deleted. Otherwise: close it
`spotRemovalBlocker`	`DELETE /spots/{id}`	A bay never assigned and not named by `allocation_history` can be deleted. Otherwise: retire it (`PATCH`), which takes it out of the inventory without touching what it is named in
`residentRemovalBlocker`	`DELETE /residents/{id}`	A resident named nowhere — no registration, no assignment, no history row, no config change, no reviewed plate read — is deleted outright. Otherwise the row is hidden and kept

All three are pure functions with their own unit tests, all three return the sentence an administrator is shown rather than a boolean, and all three exist for the same reason: the schema puts `ON DELETE RESTRICT` on the audit paths, so the alternative to refusing early is a foreign key violation surfacing as a 500. `DELETE /residents/{id}` answers 204 either way, because the caller asked for the person to come off the register and that is what happened.

7.5 The gate decision table

One pure function, `decide()`, evaluated in this order — and the order *is* the function:


best candidate, crop quality, the register, thresholds in force
fused = confidence × (0.6 + 0.4 × quality)
within the cooldown for this camera and plate?
yes
DISCARDED · no access event DUPLICATE_WITHIN_COOLDOWN
no
no candidate, or score below the format floor, or fused < review_fused?
yes
REVIEW · no access event UNREADABLE
no
exact match in the register? an ACTIVE row wins over a removed one
yes
the registration was removed?
yes
DENY · VEHICLE_INACTIVE
no
the resident is not eligible?
yes
DENY · RESIDENT_NOT_ELIGIBLE
no
fused < min_fused?
yes
REVIEW · LOW_CONFIDENCE
no
ALLOW · EXACT_MATCH
no
fuzzy matches within max_fuzzy_distance
two or more equally close
REVIEW · FUZZY_MATCH_AMBIGUOUS
exactly one
fused < min_fused?
none, fused < min_fused
REVIEW · LOW_CONFIDENCE
none, fused high
DENY · PLATE_NOT_REGISTERED
ALLOW · FUZZY_MATCH_SINGLE

Three rows are worth defending, because in each one the obvious choice is wrong:

- **An unreadable frame produces no access event.** A `DENY` there would fill the log with refusals belonging to nobody and make the denial metric a measure of lens dirt. The frame is still recorded, because a camera that reads nothing for a day is a fault the review queue should surface.
- **An ambiguous fuzzy match never opens.** If two registered plates are equally close, opening means picking at random whose entry this was, and the log would then assert something untrue.
- **A clear read that is not registered is `DENY`, not `REVIEW`.** It is a visitor or an intruder: a fact, not a doubt. A visitor lane is a separate feature — a temporary plate with an expiry — and not a loosened threshold.


The thresholds (`0.85` and `0.55`) are a starting point and are labelled as one. They live in `plate_config`, append-only, so recalibrating is an `INSERT` and not a deploy; the environment variables are only the cold-start default. Every administrator correction in the review queue writes a `corrected_plate`, which is a ground-truth label, which means the evaluation set builds itself from day one.

---

8. Sequences


8.1 Signing in

Not the Cognito hosted page: the product owns the form, and `CognitoService` drives `amazon-cognito-identity-js` with `USER_SRP_AUTH`, which proves knowledge of the password without sending it.



Person
Angular app
CognitoService (SRP)
Cognito user pool
API Gateway JWT authorizer
λ api
email + password on the product's own form
1
signIn(email, password)
2
InitiateAuth USER_SRP_AUTH
3
SRP challenge
4
PASSWORD_VERIFIER response
5
alt
[first sign-in of an administered account]
NEW_PASSWORD_REQUIRED
6
outcome new-password-required
7
completeNewPassword(new password)
8
RespondToAuthChallenge
9
[TOTP enrolled]
SOFTWARE_TOKEN_MFA
10
outcome mfa-required
11
submitMfaCode(code)
12
RespondToAuthChallenge
13
id, access and refresh tokens
14
outcome signed-in
15
AuthStore.adopt()
16
GET /me, Authorization: Bearer {access token}
17
verify signature, issuer, audience, expiry
18
invoke with the verified claims
19
resolveResidentId — claim, then linked row, then a pending link
20
subject, email, roles, resident (or null)
21
roles drive the navigation and the guards
22
Guards are usability. Every rule they imply is repeated and enforced by the API.

An access token lasts 15 minutes and `accessToken()` refreshes on demand, so a tab left open overnight does not start returning 401s to a signed-in person. The roles the UI uses come from `cognito:groups`; the resident record cannot be decoded from a token at all, which is why `GET /me` is the only source of the principal.

8.2 A resident enters the draw




8.3 Running the draw



If anything throws after the run row exists, the run is marked `FAILED` with the detail and the caller gets a 500 with a trace id. A run still `RUNNING` fifteen minutes later had its process killed mid-flight; the sweeper fails it and frees the lock.


8.4 A plate at the gate, from frame to decision



Idempotency happens in three layers, and only the middle one really matters: the recogniser's conditional write, then `INSERT ... ON CONFLICT (capture_id) DO NOTHING` — the DynamoDB stream delivers at least once, and a shard replay or a redeployed consumer both land on that statement — and then the business cooldown, which is not idempotency at all but dedupe: a car creeping towards the barrier is one arrival, not twenty.

8.5 Creating a resident, and how the Cognito user appears

The one flow where "no NAT gateway" is visible from the outside.



Measured end to end: the Cognito user exists about three seconds after the 201, and the subject link about 1.5 seconds after that.

---

9. The API surface

Full contract: `packages/contracts/openapi.yaml`. Every route except `GET /health` requires a bearer token. Every `{…id}` parameter is a UUID and is rejected before it reaches a query.

Method and path	Role	Purpose
`GET /health`	public	Liveness
`GET /me`	any	The principal, from the token
`GET /me/dashboard`	resident	Aggregated status · cached 5 min
`GET /me/history`	resident	Own history
`POST /me/assignment/release`	resident	Give up a bay · promotes the waitlist head
`GET /me/access-events`	resident	Own entries at the gate
`POST /cycles/{id}/registrations`	resident	Enter the draw · idempotent
`DELETE /cycles/{id}/registrations/me`	any	Withdraw while registration is open
`GET · POST /residents`	admin	The register (administrators excluded) · create + provision
`GET · PATCH · DELETE /residents/{id}`	admin	Detail · edit · remove
`PATCH /residents/{id}/eligibility`	admin	Requires a reason
`PATCH /residents/{id}/participation-start`	admin	Correct the waiting anchor
`GET · POST /residents/{id}/vehicles`	admin · own	The resident's plates
`PATCH · DELETE /residents/{id}/vehicles/{vehicleId}`	admin · own	Edit · deactivate
`GET /vehicles/by-plate/{plate}`	admin	Gate lookup · normalises first
`GET · POST /spots`	admin	Inventory
`PATCH /spots/{id}`	admin	Edit or retire
`DELETE /spots/{id}`	admin	Remove a bay never assigned
`GET · PATCH /config/allocation`	admin	The policy in force · new version
`GET /config/allocation/history`	admin	Who changed what, and when
`GET · POST /cycles`	admin · resident reads	Periods
`PATCH · DELETE /cycles/{id}`	admin	Rename (the only editable field) · remove
`POST /cycles/{id}/open-registration`	admin	DRAFT → REGISTRATION_OPEN
`POST /cycles/{id}/close-registration`	admin	→ REGISTRATION_CLOSED
`POST /cycles/{id}/close`	admin	End the period in effect; expires its assignments
`POST /cycles/{id}/runs`	admin	Run the draw · `Idempotency-Key` required
`GET /runs · GET /runs/{id}`	admin	Runs, and one run with its seed and commitment
`GET /runs/{id}/explanation`	admin	The paragraph a contesting resident is shown
`GET /runs/{id}/assignments`	admin	The full result set
`GET /metrics/fairness`	admin	Dashboard · cached 10 min
`GET /metrics/plates`	admin	Match rate, queue depth and age, corrections · cached 10 min

Method and path	Role	Purpose
`GET /reports/quarterly/{cycleId}` · `/reports/period/{cycleId}`	admin	Export · `?format=csv`
`POST /captures`	**camera** · admin	A presigned PUT for one frame
`GET /plate-reads`	admin	The gate log, newest first
`GET /plate-reads/review`	admin	The review queue, **oldest** first
`GET /plate-reads/{id}`	admin	One read, its candidates, and 5-minute image URLs
`POST /plate-reads/{id}/resolve`	admin	Review · `Idempotency-Key` required
`GET /access-events`	admin	The access log · `?format=csv`

Errors use one shape, with a `traceId` that matches the log correlation id:

```
{
  "error": "RAFFLE_IN_PROGRESS",
  "message": "An allocation run is already executing for this cycle.",
  "traceId": "7b4e...",
  "timestamp": "2026-03-26T02:00:00Z"
}
```

Two cross-cutting conventions. **Paging is keyset**, with a `limit` capped at 100 and a `nextCursor`; offset paging would shift rows under an administrator working a queue. **`Idempotency-Key` is required** on the two routes where a retried click would otherwise write a second irreversible decision: running a draw, and resolving a plate read.

---

10. Running it locally

```
cd code
pnpm install          # also points git at .githooks through the root `prepare` script
```

No AWS, no database, no deploy

```
pnpm --filter @pacs/api local     # the stub API on http://localhost:4300
cd apps/web && pnpm offline       # http://localhost:4200
```

`scripts/local-api.mjs` is an in-memory implementation of the same contract, seeded with 72 residents, 56 bays, four periods, a vehicle register and a gate log with reads waiting in the review queue. It is a *fixture*, not a second implementation: when a shape there disagrees with `openapi.yaml`, the YAML wins and the stub is the bug. Its bearer token is `local.<base64url json>` with no signature, accepted only by it — the deployed API rejects such a token at the Cognito authorizer before any handler runs. Sign in as `admin@local` or `resident@local` with any password.

This is the loop to use for almost all work. It is also what the Playwright suite runs against.

Against the real database

Export a connection string once per shell. Nothing is committed and no password is passed on a command line:

```
$s = aws secretsmanager get-secret-value --secret-id dev/hotel-db/connection `
       --profile hotel --region us-east-2 --query SecretString --output text | ConvertFrom-Json
$env:DATABASE_URL =
"postgresql://$($s.username):$([uri]::EscapeDataString($s.password))@$($s.host):$($s.port)/pacs_d
ev?sslmode=no-verify"
```

This only works from a machine the security group admits — see §5.


```
pnpm --filter @pacs/api migrate:up
pnpm --filter @pacs/api seed                        # 24 residents, 10 bays, one open period
pnpm --filter @pacs/api exec tsx scripts/run-draw.ts
```


`run-draw.ts` wires the real repositories to the real use case and asserts the things only Postgres can prove: the run lock, the uniqueness constraints, the waitlist having no gaps, the period moving to ACTIVE, and that `app_user` cannot `UPDATE allocation_history`.

---

11. Deploying

Two engines, and the split is forced rather than chosen.


On the developer's machine
git commit → .githooks/pre-commit
encoding guards, then the unit suites
of whichever package the commit touches
GitHub Actions —
Lint
Typecheck
Unit tests API
Unit tests Web
Build
uploads web-dist, 7 days
End to end
Playwright against the stub
Branch protection on development:
1 approval · all six checks · up to date · threads resolved
Merge into development
A human starts the release
DetectChanges: false
CodePipeline pacs-development
1 · Source



Why Actions cannot deploy. This account sits under an organisation whose service control policy denies every IAM action on identity providers — creating one, and even reading one. Keyless GitHub OIDC federation into the account is therefore impossible, and the alternative, an IAM user whose access keys live in a public repository's secrets, is a long-lived credential nobody should have to rotate. CodePipeline runs inside the account on a service role and needs no federation at all.

Why CodePipeline cannot replace Actions. It starts after a merge. By then there is nothing to stop. Only a check reported on the pull request itself can prevent bad code landing, which is what the six Actions checks are for — and they need no AWS credentials, no network beyond the registry, and are therefore safe to run on a pull request from a fork.

Why the pipeline is manual-start. `DetectChanges: false` on the source action. A merge into `development` lands the code and nothing else happens until somebody releases it, so a merge can never surprise the environment somebody is demonstrating on. It is a V2 pipeline, so an execution can be started against a chosen commit with `--source-revisions`, which is how a loose branch gets tried on the development environment without opening a pull request.

Other things about the pipeline worth knowing before changing it:

- **The Build stage repeats the unit tests Actions already ran.** Deliberately: branch protection can be bypassed by an administrator, and on this project the administrator is also the only engineer. A pipeline that trusts a check it did not run will one day deploy something that does not compile. A minute of CodeBuild buys that away. What is *not* repeated is Playwright — its whole purpose is to block a merge, and after the merge it blocks nothing.
- **The artefact carries no `node_modules`.** pnpm builds them out of symlinks into a content-addressed store, and those do not survive being zipped and unzipped in another container. The deploy stage reinstalls from the same lockfile, which costs about thirty seconds and is reproducible.

- **Backend before frontend, always.** A frontend that went up first would, for the length of the deploy, be a new client calling an old server.
- **Hashed assets first with a one-year immutable cache, `index.html` last with `no-store`.** If `index.html` went up first it would briefly point browsers at chunks that are not there; if it were cached like the chunks, a returning visitor would never see the deploy at all.
- **The build role is `PowerUserAccess` plus a narrow inline IAM policy**, scoped to `pacs-api-*` roles, with an explicit `Deny` on anything named `pacs-pipeline-*` so it can never rewrite its own trust or permissions. Enumerating every action `serverless deploy` may emit is a policy nobody can keep correct, and getting it wrong surfaces as a deploy that dies half-applied.

To deploy by hand from an admitted machine:

```
cd apps/api
pnpm --filter @pacs/api migrate:up                      # if there are new migrations
serverless deploy --stage dev --aws-profile hotel --region us-east-2
node scripts/smoke.mjs
```

Two things that will bite on a fresh deploy

Handler filenames must contain no dots. The bundle is flattened and the Node runtime splits the handler string at the *first* dot, so `src/main/api.handler.ts` with handler `src/main/api.handler.handler` fails at init with `Cannot find module 'api'`.

An S3 trigger on a bucket the same stack creates is a circular dependency. The bucket needs the function's ARN for its notification, the function's invoke permission needs the bucket, and CloudFormation refuses the loop. It is broken by giving `PlateRecognizerLambdaPermissionS3` a **literal** `SourceArn` string rather than `!GetAtt CapturesBucket.Arn`. The same applies to the S3 statements in the service role. After a deploy, confirm the trigger actually attached — this is the step that silently fails:

```
aws s3api get-bucket-notification-configuration \
    --bucket pacs-captures-dev --profile hotel --region us-east-2
```

---

12. Test strategy

Five layers, each answering a question none of the others can.

Layer	Command	Size	What only it can prove
Unit, API	`pnpm --filter @pacs/api test`	**231 tests in 21 files**, about 3 s	The rules. The draw is run ten thousand times with seeded inputs to check it is *fair*, not merely that it runs; the whole plate threshold table is a set of table tests
Unit, web	`pnpm test` in `apps/web`	**29 tests**	The boundary between DTO and model — the mappers, where a contract change actually bites
End to end	`pnpm e2e` in `apps/web`	2 specs, Playwright, Chromium	That the screens work, against the in-memory stub. One worker, because both servers hold a single in-memory building
Post-deploy smoke	`node scripts/smoke.mjs` + `smoke-plates.mjs`	31 checks + the plate pipeline	That the *deployed* system works. The only layer that can speak for Cognito, for Postgres, or for whether a frame put in an S3 bucket comes back out as a recognised plate
Integration, by hand	`tsx scripts/run-draw.ts`	16 checks	The things only Postgres can prove: the run lock, the constraints, the privilege revocation

Properties of the suites worth keeping:

- **The statistical suite is the unusual one, and it is the point.** `priority-key.properties.spec.ts` asserts transitivity, the uniformity of the raffle across a k-way tie, and the three-resident cycle that the pairwise reading of rule F would produce.
- **The plate suite is the same argument applied to a different problem**, including the regression that matters most: `VISITAS` canonicalises to `V1S1TAS`, the U/V confusable pair expands that to `U1S1TAS`, and a string the blocklist has never heard of then scores like a plate. The blocklist is therefore checked on the OCR line, before expansion.
- **The E2E suite deliberately does not run against AWS.** It would be slower, cost a Rekognition call and a stored frame per run, fail whenever somebody else was using the dev environment — and, as this project found out, it leaves rows behind: a smoke suite once invented a period called `2235-Q1` that then drove the administrator's "ready to draw" banner on a real screen.
- **The smoke suites clean up after themselves as far as they can.** The Cognito users are deleted on every run; the fixtures are taken down through the API with the administrator's token — the period deleted, the resident deactivated, the bay retired. Two inert rows per run remain, because removing those means reaching the database, and CodeBuild cannot (§5). `scripts/clean-smoke-data.mjs` clears them from an admitted machine.
- **The draw is not run in the pipeline.** A committed run is a record, and `cycleRemovalBlocker` refuses to delete a period that has one, so running the draw there would make the test period permanent. The write path is covered by the unit tests instead. Set `DATABASE_URL` and the suite runs the draw and clears it afterwards — which is what a developer gets and the pipeline deliberately does not.

---

13. Known constraints and gaps

Each of these is a decision forced by the real account, or an acknowledged absence. None of them is a surprise waiting to be found.

Forced by the environment

Region	`us-east-2` only. SCP `p-wvjo6arp` denies every other region
Identity federation	No GitHub OIDC provider is possible: the SCP denies every IAM action on identity providers. This is the whole reason deployment runs on CodePipeline
Lambda concurrency	Quota is 10, and AWS requires 10 unreserved, so no function can reserve any. The quota bounds the connection pool at 10 × 2 = 20
Database	Shares the existing `hotel-db` (PostgreSQL 18.3, `db.t4g.micro`, single-AZ, backup retention **1 day**); `pacs_dev` is its own database. The specification asks for a dedicated instance and 7-day backups
Network	The default VPC, the default security group, public subnets, and a publicly accessible instance admitting one `/32`. Requested, so migrations run from a laptop. Reverting is two commands
Migrations	Not in the pipeline: CodeBuild cannot reach the database. Applied by hand before the deploy that needs them. The intended answer is a migration Lambda inside the VPC that the Deploy stage invokes
TLS to the database	`rejectUnauthorized: false` — the RDS CA bundle is not shipped in the Lambda bundle. Encrypted, not verified. `verify-full` with the RDS global bundle is on the gap list
Serverless Framework v4	Needs a vendor access key in CI, read from Secrets Manager. Free for individuals and for organisations under the vendor's revenue threshold; confirm the licence before using it for a company account

Not built

- SES notification templates. `integrations` already receives the allocation events and logs them; only the templates and the send call are missing. SES is in sandbox (`ProductionAccessEnabled: false`, 200/day), so it can only send to verified addresses.
- The plate crop writer. `plate_read.crop_key`, the `crops/` IAM statement and the lifecycle rule all exist, but nothing writes a crop: cropping needs a native image decoder in the bundle, and the review screen reads the full frame instead.
- A capture client. `POST /captures` is the contract a gate camera would call; no camera firmware or web capture page is written.
- Threshold calibration. The procedure and the storage exist; the week of shadow operation that produces real numbers has not happened, so `0.85` and `0.55` are a labelled starting point.
- Transloco is installed but not wired. Spanish and English are required. One sentence resists it: the fairness explanation comes back from the API as finished prose rather than a message key plus parameters, so it cannot be localised without changing the contract. That is the one real design debt on the frontend. The plates module deliberately does not repeat the mistake — `access_event.reason` is a stable code and the wording lives in `features/plates/reason-label.ts`.
- `absenceResetMonths` is stored and validated but nothing triggers it.
- No k6 load suite.

Where the repository's own documents are out of date

- `README.md` reports 213 unit tests; there are 231. It also still says "`git init` — this is not a repository yet" and lists CI as not built. Both have since happened.
- `docs/analisis.html` sections 12 and 13 describe the probabilistic weighted lottery that rules A–F replaced. Section 10 still says `us-east-1`, private subnets, per-function IAM roles, a master password in SSM and the `*.handler.ts` filename convention — none of which is what runs.
- `pipeline/dev/buildspec-deploy.yml` says RDS is in private subnets. It is not; the conclusion it draws is still right, but for the security group's reason, not the subnet's.

- The doc comment at the top of `plates/domain/access-decision.ts` says the thresholds are read from `allocation_config`. They are read from `plate_config`.