## **WELDOX 1100**

2007-02-28

The table shows available dimensions for direct order including the maximum length (m)

Some restrictions, contact your local sales representative for more information

Outside the range of dimensions

Minimum lenght: 2000 mm

## Minimum quantities:

Thickness: Minimum position weight:

3.0-60.0 2.5 tons 60.1-100,0 3.5 tons 100.1-120.0 4.0 tons 120.1- 5.0 tons

WIDTH [mm]	1000-	-1351	-1500	-1601	-1701	-1801	-1901	-2001	-2101	-2201	-2301	-2401	-2501	-2601	-2701	-2801	-2901	-3001	-3101	-3201	-3301
Thickness [mm]	1350	1499	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350
3,0-3.7																					
(3,7)-4,7																					
(4,7)-5,7																					
(5,7)-6,7																					
(6,7)-7,7						Maximum	length 1	4,5m													
(7,7)-8,7																					
(8,7)-10																					
(10)-15																					
(15)-20																					
(20)-26																					
(26)-27	14																				
(27)-28	13,4																		14,2		
(28)-29	13																	14,1	13,7		
(29)-30	12,5																14,1	13,6	13,2		
(30)-31	12,1															14,1	13,6	13,2	12,8		
(31)-32	11,8														14,2	13,7	13,2	12,8	12,4		
(32)-33	11,4													14,2	13,7	13,3	12,8	12,4	12		
(33)-34	11,1												14,4	13,8	13,3	12,9	12,4	12	11,7		
(34)-35	10,7												13,9	13,4	12,9	12,5	12,1	11,7	11,3		
(35)-36	10,4											14,1	13,6	13,1	12,6	12,2	11,7	11,4	11		
(36)-37	10,2										14,3	13,7	13,2	12,7	12,2	11,8	11,4	11,1	10,7		
(37)-38	9,9										13,9	13,4	12,8	12,4	11,9	11,5	11,1	10,8	10,4		
(38)-39	9,6									14,2	13,6	13	12,5	12	11,6	11,2	10,8	10,5	10,2		
(39)-40	9,4								14,4	13,8	13,2	12,7	12,2	11,7	11,3	10,9	10,6	10,2	9,9		

