

HARDOX Extreme 2007-02-28

Minimum length: 2000 mm

Minimum quantities:

Thickness:	Minimum position weight:
3.0-60.0	2.5 tons
60.1-100.0	3.5 tons
100.1-120.0	4.0 tons
120.1-	5.0 tons

The table shows available dimensions for direct order including the maximum length (m)

Some restrictions, contact your local sales representative for more information

Outside the range of dimensions

Width (mm)	1000-	-1351	-1500	-1601	-1701	-1801	-1901	-2001	-2101	-2201	-2301	-2401	-2501	-2601	-2701	-2801	-2901	-3001	-3101	-3201	-3301
Thickness (mm)	1350	1499	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350
3.0-3.7*																					
3.8-4.7*																					
4.8-5.7*																					
5.8-6.7																					
6.8-7.7																					
8.0-8.7																					
8.8-10																					
10.1-13																					
13.1-25																					
25.1-26																					
26.1-27																					
27.1-28																					
28.1-29																					
29.1-30																					
30.1-31																					
31.1-32																					
32.1-33																					
33.1-34																					
34.1-35																					
35.1-36																					
36.1-37																					
37.1-38																					
38.1-39																					
39.1-40																					
40.1-45																					
45.1-50																					
50.1-55																					
55.1-60																					
60.1-65																					
65.1-70																					
70.1-75																					
75.1-80																					
80.1-102																					
102.1-115																					
115.1-130																					
130.1-150																					