

HARDOX 400

2008-01-17

The table shows available dimensions for direct order including the maximum length (m)

Some restrictions, contact your local sales representative for more information

Outside the range of dimensions

Minimum lenght: 2000 mm

Minimum quantities:

Thickness:	Minimum position weight:
3.0-60.0	2.5 tons
60.1-100,0	3.5 tons
100.1-120.0	4.0 tons
120.1-	5.0 tons

Width (mm)	1000-	-1351	-1500	-1601	-1701	-1801	-1900	-2001	-2101	-2201	-2301	-2401	-2501	-2601	-2701	-2801	-2901	-3001	-3101	-3201	-3301
Thickness (mm)	1350	1499	1600	1700	1800	1899	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350
3.0-3.7																					
3.8-4.7*																					
4.8-5.7																					
5.8-6.7																					
6.8-7.7																					
7.8-8.7																					14,5
8.8-10																					14,5
10.1-24																					14,5
24.1-25																					14,5
25.1-26																					14,4
26.1-27	14																			14,2	13,8
27.1-28	13,4																				
28.1-29	13																				
29.1-30	12,5																				
30.1-31	12,1																				
31.1-32	11,8																				
32.1-33	11,4																				
33.1-34	11,1																				
34.1-35	10,7																				
35.1-36	10,4																				
36.1-37	10,2																				
37.1-38	9,9																				
38.1-39	9,6																				
39.1-40	9,4																				
40.1-45	8,3																				
45.1-50	7,5	13,5	13,5	13,5	13,5	13,4	12,7	12,1	11,5	11	10,6	10,1	9,7	9,4	9	8,7	8,4	8,2	7,9	7,7	7,6
50.1-55	6,8	11,2	11,2	11,2	11,2	11,2	11,2	11	10,5	10	9,6	9,2	8,9	8,5	8,2	7,9	7,7	7,4	7,2	7	6,9
55.1-60	7,8	11,2	11,2	11,2	11,2	11,1	10,6	10,1	9,6	9,2	8,8	8,4	8,1	7,8	7,5	7,3	7	6,8	6,6	6,4	6,3
60.1-65	7,2	11,2	11,2	11,2	10,8	10,3	9,7	9,3	8,9	8,5	8,1	7,8	7,5	7,2	6,9	6,7	6,5	6,3			
65.1-70	6,7	10,8	10,8	10,7	10,1	9,5	9	8,6	8,2	7,9	7,5	7,2	6,9	6,7	6,4	6,2					
70.1-75	6,2	10,1	10,1	10	9,4	8,9	8,4	8	7,7	7,3	7	6,7	6,5	6,2							
75.1-80	5,9	9,4	9,4	9,3	8,8	8,3	7,9	7,5	7,2	6,9	6,6	6,3									
80.1-102		7,4	7,4	7,3	7	6,7	6,3	6	5,7	5,5	5,3	5									
102.1-115		6,5	6,5	6,5	6	5,8	5,5	5,2	5	4,8	4,6	4,4									
115.1-130		5,8	5,8	5,7	5,4	5,1	4,8	4,6	4,4	4,2	4	3,9									
130.1-150																					

* 4,0 - 4,7 mm thickness available in some dimensions through stock. Contact your Stock coordinator for more information

