




# Final Survey Report

## BRI-GT-01



# FINAL SURVEY REPORT

FOR

## Aardwarmte Vierpolders



<b>Field</b>	:	<b><u>Vierpolders</u></b>
<b>Well</b>	:	<b><u>BRI-GT-01</u></b>

### Well Coordinates

Grid Coordinates	Easting	:	<u>70427.89 m</u>
	Northing	:	<u>432178.99 m</u>
Grid System		:	<u>Rijkdriehoekmeting / Netherlands New</u>
Geographic Coordinates	Latitude	:	<u>N 51° 52' 21.656"</u>
	Longitude	:	<u>E 4° 09' 33.818"</u>
Depth Reference		:	<u>Rotary Table</u>
Elevation above MSL		:	<u>5.90 m</u>
Elevation above Ground Level		:	<u>6.70 m</u>
Azimuth Reference		:	<u>Grid North</u>
Convergence		:	<u>0.97°W</u>

### Magnetic Data

Declination	:	<u>0.62°E</u>
Dip angle	:	<u>66.96°</u>
Field Strength	:	<u>48948 nT</u>
Date	:	<u>20-June-2015</u>
Source	:	<u>BHI / BGGM 2017</u>

# Aardwarmte Vierpolders

Location: THE NETHERLANDS

Field: Vierpolders

Facility: Vierpolders


Slot: Slot#1

Well: BRI-GT-01

Wellbore: BRI-GT-01 AWB



Scale 1 inch = 300 m

Easting (m)



Plot reference wellpath is BRI-GT-01_AWB	
True vertical depths are referenced to Rig on Slot#1 (RT)	Grid System: Amersfoort / Rijksriehoeksmeting
Measured depths are referenced to Rig on Slot#1 (RT)	North Reference: Grid north
Rig on Slot#1 (RT) to Mean Sea Level: 4.8 meters	Scale: True distance
Mean Sea Level to Mud line (At Slot: Slot#1): 1.9 meters	Depths are in meters
Coordinates are in meters referenced to Facility Center	Created by: patipara on 22/Sep/2015

True Vertical Depth (m)



Azimuth 279.12° with reference 0.00 N, 0.00 E

# Actual Wellpath Report

Positional Uncertainty

**BRI-GT-01\_AWB**

Page 1 of 5

## REFERENCE WELLPATH IDENTIFICATION

Operator	<b>Aardwarmte Vierpolders</b>	Slot	<b>Slot#1</b>
Area	<b>THE NETHERLANDS</b>	Well	<b>BRI-GT-01</b>
Field	<b>Vierpolders</b>	Wellbore	<b>BRI-GT-01_AWB</b>
Facility	<b>Vierpolders</b>		

## REPORT SETUP INFORMATION

Projection System	<b>Amersfoort / Rijksriehoeksmeting</b>	Software System	<b>WellArchitect® 4.0.0</b>
North Reference	<b>Grid</b>	User	<b>Patipara</b>
Scale	<b>0.999958</b>	Report Generated	<b>22/Sep/2015 at 10:53</b>
Convergence at slot	<b>0.97° West</b>	Database/Source file	<b>WA_Server/BRI-GT-01_AWB.xml</b>

## WELLPATH LOCATION

	Local coordinates		Grid coordinates		Geographic coordinates	
	North[m]	East[m]	Easting[m]	Northing[m]	Latitude	Longitude
Slot Location	0.00	0.00	<b>70427.89</b>	<b>432178.99</b>	51°52'21.656"N	4°09'33.818"E
Facility Reference Pt			<b>70427.89</b>	<b>432178.99</b>	51°52'21.656"N	4°09'33.818"E
Field Reference Pt			<b>70428.00</b>	<b>432179.00</b>	51°52'21.657"N	4°09'33.824"E

## WELLPATH DATUM

Calculation method	<b>Minimum curvature</b>	Rig on Slot#1 (RT) to Facility Vertical Datum	<b>6.70m</b>
Horizontal Reference Pt	<b>Facility Center</b>	Rig on Slot#1 (RT) to Mean Sea Level	<b>4.80m</b>
Vertical Reference Pt	<b>Rig on Slot#1 (RT)</b>	Rig on Slot#1 (RT) to Mud Line at Slot (Slot#1)	<b>6.70m</b>
MD Reference Pt	<b>Rig on Slot#1 (RT)</b>	Section Origin	<b>N 0.00, E 0.00 m</b>
Field Vertical Reference	<b>Mean Sea Level</b>	Section Azimuth	<b>279.12°</b>

## POSITIONAL UNCERTAINTY CALCULATION SETTINGS

Ellipse Confidence Limit	<b>3.00 Std Dev</b>	Ellipse Start MD	<b>6.70m</b>	Surface Position Uncertainty	<b>included</b>
Declination	<b>0.64° East of TN</b>	Dip Angle	<b>66.98°</b>	Magnetic Field Strength	<b>48894nT</b>
Slot Surface Uncertainty @1SD		Horizontal	<b>0.610m</b>	Vertical	<b>0.305m</b>
Facility Surface Uncertainty @1SD		Horizontal	<b>6.096m</b>	Vertical	<b>0.914m</b>

Positional Uncertainty values in the WELLPATH DATA table are the projection of the ellipsoid of uncertainty onto the vertical and horizontal planes

# Actual Wellpath Report

Positional Uncertainty

**BRI-GT-01\_AWB**

Page 2 of 5

## REFERENCE WELLPATH IDENTIFICATION

Operator	<b>Aardwarmte Vierpolders</b>	Slot	<b>Slot#1</b>
Area	<b>THE NETHERLANDS</b>	Well	<b>BRI-GT-01</b>
Field	<b>Vierpolders</b>	Wellbore	<b>BRI-GT-01_AWB</b>
Facility	<b>Vierpolders</b>		

## WELLPATH DATA (105 stations) - with Positional Uncertainty values

MD [m]	Inclination [°]	Azimuth [°]	TVD [m]	Vert Sect [m]	North [m]	East [m]	Grid East [m]	Grid North [m]	DLS [°/30m]	Vertical Semi-Axis [m]	Horiz Major Semi-Axis [m]	Horiz Minor Semi-Axis [m]	Horiz Minor Axis Azim [°]
0.00	0.000	336.800	0.00	0.00	0.00	0.00	70427.89	432178.99	0.00	0.00	0.00	0.00	0.000
238.00	0.100	336.800	238.00	0.11	0.19	-0.08	70427.81	432179.18	0.01	3.10	18.40	18.40	247.607
262.00	0.520	301.550	262.00	0.22	0.27	-0.18	70427.71	432179.26	0.55	3.11	18.40	18.40	243.267
291.00	1.500	283.210	290.99	0.72	0.42	-0.66	70427.23	432179.41	1.05	3.12	18.41	18.41	357.810
318.00	2.880	279.510	317.97	1.75	0.62	-1.68	70426.21	432179.61	1.54	3.12	18.42	18.41	353.379
346.00	2.890	280.440	345.94	3.16	0.86	-3.07	70424.82	432179.85	0.05	3.13	18.42	18.42	357.450
374.00	3.680	279.470	373.89	4.77	1.14	-4.65	70423.24	432180.13	0.85	3.14	18.43	18.43	357.692
402.00	3.740	276.740	401.83	6.58	1.39	-6.44	70421.45	432180.38	0.20	3.15	18.44	18.43	358.508
430.00	3.910	277.270	429.77	8.44	1.62	-8.29	70419.60	432180.61	0.19	3.16	18.45	18.44	357.777
459.00	3.590	275.190	458.71	10.34	1.83	-10.18	70417.71	432180.82	0.36	3.17	18.45	18.45	357.480
487.00	3.540	273.160	486.66	12.07	1.95	-11.91	70415.98	432180.94	0.15	3.19	18.46	18.46	359.554
515.00	3.620	274.120	514.60	13.81	2.06	-13.66	70414.23	432181.05	0.11	3.20	18.47	18.47	266.440
543.00	3.520	273.990	542.55	15.55	2.19	-15.40	70412.49	432181.18	0.11	3.22	18.48	18.48	267.758
572.00	3.140	275.640	571.50	17.23	2.33	-17.08	70410.81	432181.32	0.41	3.23	18.50	18.49	268.190
600.00	3.470	274.180	599.45	18.84	2.46	-18.69	70409.21	432181.45	0.36	3.25	18.51	18.50	268.592
628.00	3.250	272.690	627.40	20.47	2.56	-20.32	70407.57	432181.55	0.25	3.27	18.52	18.51	268.540
656.00	4.480	274.940	655.34	22.35	2.69	-22.21	70405.69	432181.68	1.33	3.28	18.54	18.53	267.435
684.00	6.530	281.900	683.21	25.03	3.12	-24.85	70403.04	432182.11	2.31	3.30	18.55	18.54	261.491
712.00	8.470	284.870	710.97	28.68	3.97	-28.40	70399.49	432182.96	2.12	3.32	18.57	18.56	252.710
743.00	10.340	282.510	741.55	33.72	5.16	-33.33	70394.56	432184.15	1.85	3.34	18.60	18.58	253.121
771.00	13.450	275.160	768.95	39.48	6.00	-39.03	70388.87	432184.99	3.70	3.37	18.63	18.60	262.579
799.00	16.140	272.450	796.02	46.60	6.46	-46.16	70381.73	432185.45	2.98	3.39	18.66	18.63	278.791
826.00	18.130	274.110	821.82	54.51	6.92	-54.10	70373.79	432185.91	2.28	3.41	18.70	18.66	278.945
855.00	20.920	277.030	849.15	64.18	7.88	-63.74	70364.15	432186.87	3.06	3.44	18.75	18.68	274.891
883.00	23.090	278.400	875.11	74.67	9.29	-74.13	70353.76	432188.28	2.39	3.47	18.81	18.70	272.775
911.00	26.870	278.560	900.48	86.49	11.04	-85.83	70342.07	432190.03	4.05	3.50	18.89	18.73	273.108
940.00	29.230	278.130	926.07	100.13	13.01	-99.32	70328.58	432192.00	2.45	3.55	18.98	18.76	273.814
968.00	32.430	275.980	950.11	114.46	14.76	-113.56	70314.34	432193.75	3.63	3.59	19.10	18.79	274.717
996.00	35.170	277.440	973.38	130.02	16.59	-129.02	70298.87	432195.58	3.06	3.64	19.24	18.81	275.422
1024.00	36.000	278.370	996.15	146.31	18.83	-145.16	70282.73	432197.82	1.06	3.68	19.40	18.84	275.452
1052.00	38.950	279.760	1018.37	163.34	21.52	-161.98	70265.92	432200.51	3.29	3.72	19.59	18.85	275.791
1080.00	39.790	279.700	1040.02	181.10	24.53	-179.49	70248.41	432203.51	0.90	3.77	19.82	18.88	276.090
1109.00	41.980	280.270	1061.94	200.08	27.82	-198.18	70229.72	432206.81	2.30	3.81	20.08	18.90	276.527
1137.00	43.750	278.830	1082.46	219.13	30.97	-216.96	70210.94	432209.96	2.17	3.87	20.37	18.92	276.834
1165.00	46.180	277.720	1102.27	238.91	33.82	-236.54	70191.36	432212.81	2.74	3.92	20.71	18.94	277.058
1193.00	47.160	277.700	1121.49	259.27	36.55	-256.72	70171.18	432215.54	1.05	3.98	21.09	18.95	277.166
1221.00	48.740	277.220	1140.24	280.05	39.25	-277.34	70150.56	432218.24	1.74	4.03	21.52	18.97	277.197
1250.00	48.090	277.510	1159.49	301.73	42.03	-298.85	70129.05	432221.02	0.71	4.09	22.00	18.99	277.218
1278.00	46.300	278.230	1178.51	322.27	44.84	-319.20	70108.70	432223.83	2.00	4.15	22.47	19.01	277.262
1306.00	46.270	278.440	1197.86	342.51	47.77	-339.22	70088.68	432226.76	0.17	4.21	22.95	19.02	277.332
1334.00	44.760	279.690	1217.48	362.48	50.92	-358.95	70068.96	432229.91	1.88	4.27	23.44	19.04	277.428
1344.00	44.310	279.080	1224.61	369.50	52.06	-365.87	70062.04	432231.05	1.86	4.29	23.62	19.05	277.467
1388.00	44.610	280.310	1256.02	400.31	57.25	-396.25	70031.66	432236.24	0.62	4.36	24.32	19.07	277.637
1416.00	45.570	280.420	1275.78	420.14	60.82	-415.75	70012.16	432239.81	1.03	4.39	24.74	19.07	277.773
1445.00	47.400	280.900	1295.75	441.16	64.71	-436.42	69991.49	432243.70	1.93	4.42	25.21	19.08	277.922

# Actual Wellpath Report

Positional Uncertainty

**BRI-GT-01\_AWB**

Page 3 of 5

## REFERENCE WELLPATH IDENTIFICATION

Operator	<b>Aardwarmte Vierpolders</b>	Slot	<b>Slot#1</b>
Area	<b>THE NETHERLANDS</b>	Well	<b>BRI-GT-01</b>
Field	<b>Vierpolders</b>	Wellbore	<b>BRI-GT-01_AWB</b>
Facility	<b>Vierpolders</b>		

## WELLPATH DATA (105 stations) - with Positional Uncertainty values

MD [m]	Inclination [°]	Azimuth [°]	TVD [m]	Vert Sect [m]	North [m]	East [m]	Grid East [m]	Grid North [m]	DLS [°/30m]	Vertical Semi-Axis [m]	Horiz Major Semi-Axis [m]	Horiz Minor Semi-Axis [m]	Horiz Minor Axis Azim [°]
1473.00	48.030	279.310	1314.59	461.87	68.34	-456.81	69971.10	432247.33	1.43	4.46	25.71	19.08	278.037
1501.00	48.520	279.510	1333.23	482.77	71.76	-477.43	69950.48	432250.75	0.55	4.49	26.23	19.09	278.122
1529.00	48.980	279.450	1351.69	503.82	75.23	-498.19	69929.72	432254.21	0.50	4.53	26.78	19.09	278.197
1558.00	49.100	279.550	1370.70	525.72	78.84	-519.79	69908.12	432257.83	0.15	4.57	27.38	19.10	278.270
1585.00	49.080	278.900	1388.38	546.12	82.11	-539.93	69887.98	432261.10	0.55	4.61	27.95	19.11	278.321
1614.00	49.050	277.950	1407.38	568.03	85.32	-561.60	69866.31	432264.31	0.74	4.65	28.59	19.11	278.339
1642.00	48.990	276.830	1425.74	589.15	88.04	-582.56	69845.35	432267.03	0.91	4.70	29.22	19.12	278.314
1670.00	49.000	277.150	1444.11	610.27	90.61	-603.54	69824.38	432269.60	0.26	4.75	29.87	19.13	278.273
1698.00	49.090	277.090	1462.47	631.40	93.23	-624.52	69803.40	432272.22	0.11	4.80	30.53	19.14	278.238
1727.00	49.050	277.500	1481.47	653.30	96.02	-646.25	69781.66	432275.00	0.32	4.85	31.23	19.15	278.209
1755.00	49.020	278.080	1499.82	674.44	98.88	-667.20	69760.72	432277.87	0.47	4.91	31.92	19.16	278.198
1783.00	48.590	278.590	1518.26	695.51	101.94	-688.05	69739.87	432280.92	0.62	4.96	32.62	19.17	278.205
1811.00	48.580	278.690	1536.79	716.50	105.09	-708.81	69719.11	432284.08	0.08	5.02	33.32	19.18	278.221
1839.00	48.490	279.090	1555.33	737.49	108.33	-729.54	69698.38	432287.32	0.34	5.08	34.03	19.19	278.242
1867.00	49.120	279.610	1573.77	758.56	111.76	-750.33	69677.60	432290.74	0.79	5.15	34.76	19.20	278.276
1896.00	49.050	278.450	1592.76	780.47	115.20	-771.97	69655.95	432294.18	0.91	5.21	35.53	19.22	278.300
1923.00	49.060	278.960	1610.46	800.86	118.28	-792.13	69635.80	432297.27	0.43	5.28	36.25	19.23	278.311
1952.00	49.070	278.980	1629.46	822.77	121.70	-813.77	69614.16	432300.68	0.02	5.35	37.04	19.24	278.330
1980.00	49.090	279.480	1647.80	843.93	125.09	-834.65	69593.27	432304.08	0.41	5.42	37.80	19.26	278.355
2008.00	49.130	279.440	1666.13	865.09	128.57	-855.53	69572.40	432307.56	0.05	5.49	38.57	19.27	278.384
2036.00	49.060	278.930	1684.46	886.26	131.95	-876.42	69551.51	432310.93	0.42	5.56	39.36	19.29	278.404
2064.00	49.120	279.490	1702.80	907.42	135.34	-897.31	69530.62	432314.32	0.46	5.64	40.14	19.30	278.424
2093.00	49.120	278.720	1721.78	929.34	138.81	-918.96	69508.97	432317.79	0.60	5.72	40.96	19.32	278.440
2121.00	49.370	278.710	1740.06	950.55	142.02	-939.92	69488.01	432321.00	0.27	5.79	41.77	19.34	278.446
2149.00	49.270	278.960	1758.31	971.79	145.28	-960.91	69467.02	432324.26	0.23	5.87	42.58	19.36	278.454
2176.00	49.280	278.950	1775.92	992.25	148.47	-981.12	69446.81	432327.45	0.01	5.95	43.36	19.38	278.464
2205.00	49.280	279.040	1794.84	1014.23	151.90	-1002.83	69425.10	432330.89	0.07	6.03	44.21	19.40	278.475
2234.00	49.270	279.550	1813.76	1036.21	155.45	-1024.52	69403.42	432334.44	0.40	6.12	45.06	19.42	278.492
2261.00	49.210	279.360	1831.39	1056.66	158.81	-1044.69	69383.24	432337.80	0.17	6.20	45.86	19.44	278.511
2290.00	49.170	279.660	1850.34	1078.61	162.44	-1066.34	69361.60	432341.42	0.24	6.29	46.72	19.46	278.531
2317.00	48.930	280.260	1868.04	1099.00	165.97	-1086.42	69341.51	432344.95	0.57	6.37	47.52	19.48	278.558
2346.00	48.790	280.470	1887.12	1120.83	169.89	-1107.91	69320.03	432348.88	0.22	6.46	48.37	19.50	278.594
2375.00	48.830	279.330	1906.22	1142.65	173.65	-1129.40	69298.53	432352.63	0.89	6.56	49.23	19.53	278.619
2403.00	48.890	278.970	1924.64	1163.74	177.00	-1150.22	69277.72	432355.98	0.30	6.65	50.07	19.55	278.628
2431.00	48.460	279.590	1943.13	1184.76	180.39	-1170.98	69256.96	432359.37	0.68	6.74	50.90	19.58	278.638
2459.00	48.930	279.190	1961.61	1205.80	183.82	-1191.73	69236.21	432362.80	0.60	6.83	51.74	19.60	278.651
2487.00	48.890	279.070	1980.01	1226.90	187.17	-1212.56	69215.38	432366.15	0.11	6.92	52.59	19.63	278.658
2515.00	48.880	279.010	1998.42	1248.00	190.48	-1233.40	69194.55	432369.47	0.05	7.01	53.43	19.66	278.663
2544.00	48.870	278.780	2017.50	1269.84	193.86	-1254.98	69172.97	432372.84	0.18	7.11	54.32	19.68	278.665
2572.00	48.890	279.980	2035.91	1290.93	197.30	-1275.79	69152.16	432376.28	0.97	7.21	55.17	19.71	278.676
2600.00	48.310	280.140	2054.43	1311.93	200.97	-1296.47	69131.48	432379.95	0.63	7.30	56.02	19.74	278.697
2629.00	48.350	280.250	2073.71	1333.59	204.80	-1317.79	69110.16	432383.78	0.09	7.40	56.89	19.77	278.721
2656.00	48.360	280.750	2091.65	1353.76	208.48	-1337.63	69090.32	432387.46	0.42	7.50	57.70	19.80	278.747
2685.00	48.900	280.490	2110.82	1375.52	212.49	-1359.02	69068.93	432391.47	0.59	7.60	58.58	19.83	278.776
2713.00	49.290	279.600	2129.15	1396.68	216.18	-1379.86	69048.09	432395.16	0.83	7.70	59.45	19.86	278.795

# Actual Wellpath Report

Positional Uncertainty

**BRI-GT-01\_AWB**

Page 4 of 5

## REFERENCE WELLPATH IDENTIFICATION

Operator	<b>Aardwarmte Vierpolders</b>	Slot	<b>Slot#1</b>
Area	<b>THE NETHERLANDS</b>	Well	<b>BRI-GT-01</b>
Field	<b>Vierpolders</b>	Wellbore	<b>BRI-GT-01_AWB</b>
Facility	<b>Vierpolders</b>		

## WELLPATH DATA (105 stations) - with Positional Uncertainty values

MD [m]	Inclination [°]	Azimuth [°]	TVD [m]	Vert Sect [m]	North [m]	East [m]	Grid East [m]	Grid North [m]	DLS [°/30m]	Vertical Semi-Axis [m]	Horiz Major Semi-Axis [m]	Horiz Minor Semi-Axis [m]	Horiz Minor Axis Azim [°]
2741.00	49.450	279.400	2147.39	1417.93	219.69	-1400.81	69027.14	432398.67	0.24	7.80	60.33	19.90	278.805
2769.00	49.390	279.420	2165.60	1439.19	223.17	-1421.79	69006.16	432402.15	0.07	7.90	61.21	19.93	278.812
2798.00	48.820	279.560	2184.59	1461.11	226.78	-1443.42	68984.54	432405.76	0.60	7.97	62.02	19.95	278.822
2827.00	48.860	279.510	2203.67	1482.95	230.40	-1464.95	68963.01	432409.38	0.06	8.01	62.75	19.97	278.833
2855.00	48.920	279.070	2222.08	1504.04	233.80	-1485.77	68942.19	432412.78	0.36	8.05	63.45	19.98	278.840
2883.00	48.840	278.590	2240.50	1525.14	237.04	-1506.61	68921.34	432416.02	0.40	8.10	64.16	20.00	278.841
2911.00	48.900	279.030	2258.91	1546.23	240.27	-1527.45	68900.50	432419.25	0.36	8.14	64.88	20.02	278.842
2939.00	48.870	280.120	2277.33	1567.32	243.78	-1548.25	68879.70	432422.76	0.88	8.19	65.60	20.04	278.852
2968.00	48.920	280.200	2296.39	1589.17	247.63	-1569.76	68858.20	432426.61	0.08	8.23	66.35	20.05	278.869
2996.00	48.960	280.120	2314.78	1610.28	251.36	-1590.54	68837.42	432430.34	0.08	8.28	67.09	20.07	278.886
3024.00	48.880	280.930	2333.18	1631.38	255.21	-1611.29	68816.67	432434.19	0.66	8.33	67.82	20.09	278.906
3052.00	48.850	280.770	2351.60	1652.45	259.18	-1632.00	68795.95	432438.16	0.13	8.39	68.56	20.11	278.930
3080.00	48.870	280.600	2370.02	1673.53	263.09	-1652.73	68775.23	432442.07	0.14	8.44	69.30	20.14	278.951
3087.00	48.850	280.500	2374.63	1678.80	264.06	-1657.91	68770.05	432443.04	0.33	8.46	69.49	20.14	278.956
3101.00	48.850	280.500	2383.84	1689.34	265.98	-1668.27	68759.69	432444.96	0.00	8.48	69.86	20.15	278.965

## HOLE & CASING SECTIONS - Ref Wellbore: BRI-GT-01\_AWB Ref Wellpath: BRI-GT-01\_AWB

String/Diameter	Start MD [m]	End MD [m]	Interval [m]	Start TVD [m]	End TVD [m]	Start N/S [m]	Start E/W [m]	End N/S [m]	End E/W [m]
24in Conductor	0.00	224.00	224.00	0.00	224.00	0.00	0.00	0.17	-0.07
17.5in Open Hole	0.00	1364.00	1364.00	0.00	1238.91	0.00	0.00	54.34	-379.67
13.375in Casing	0.00	1360.00	1360.00	0.00	1236.05	0.00	0.00	53.87	-376.91
12.25in Open Hole	1364.00	2784.00	1420.00	1238.91	2175.39	54.34	-379.67	225.03	-1433.00
9.625in Casing	0.00	2779.00	2779.00	0.00	2172.12	0.00	0.00	224.41	-1429.27
8.5in Open Hole	2784.00	3101.00	317.00	2175.39	2383.84	225.03	-1433.00	265.98	-1668.27
6.625in Liner	2681.50	3070.50	389.00	2108.52	2363.77	212.01	-1356.43	261.77	-1645.69

# Actual Wellpath Report

Positional Uncertainty

**BRI-GT-01\_AWB**

Page 5 of 5

## REFERENCE WELLPATH IDENTIFICATION

Operator	<b>Aardwarmte Vierpolders</b>	Slot	<b>Slot#1</b>
Area	<b>THE NETHERLANDS</b>	Well	<b>BRI-GT-01</b>
Field	<b>Vierpolders</b>	Wellbore	<b>BRI-GT-01_AWB</b>
Facility	<b>Vierpolders</b>		

## TARGETS

Name	MD [m]	TVD [m]	North [m]	East [m]	Grid East [m]	Grid North [m]	Latitude	Longitude	Shape
<b>Target#1</b>		2188.00	227.02	-1446.95	<b>68981.00</b>	<b>432406.00</b>	51°52'28.203"N	4°08'17.984"E	circle

## WELLPATH COMPOSITION - Ref Wellbore: BRI-GT-01\_AWB Ref Wellpath: BRI-GT-01\_AWB

Start MD [m]	End MD [m]	Positional Uncertainty Model	Log Name/Comment	Wellbore
0.00	1344.00	NaviTrak (SAG, MagCorr)	01. BHI NaviGamma MWD 17 1/2" <238m - 1344m>	BRI-GT-01_AWB
1344.00	2769.00	NaviTrak (SAG, MagCorr)	02. BHI NaviGamma MWD 12-1/4" <1388.m - 2769m>	BRI-GT-01_AWB
2769.00	3087.00	NaviTrak (SAG, MagCorr)	03. BHI NaviGamma MWD 8-1/2" <2798m - 3087m>	BRI-GT-01_AWB
3087.00	3101.00	Blind Drilling (std)	Projection to bit	BRI-GT-01_AWB