

NLW-GT-02-S1 Def Survey Survey Geodetic Report

(Def Survey)

Report Date:	May 18, 2018 - 10:49 AM	Survey / DLS Computation:	Minimum Curvature / Lubinski
Client:	Naaldwijk (Trias Westland)	Vertical Section Azimuth:	107.442 ° (Grid North)
Field:	NLW-GT-02 / NLW-GT-02	Vertical Section Origin:	0.000 m, 0.000 m
Structure / Slot:	NLW-GT-02	TVD Reference Datum:	Unknown
Well:	NLW-GT-02-S1	TVD Reference Elevation:	8.420 m above NAP
Borehole:	NLW-GT-02-S1	Seabed / Ground Elevation:	0.900 m below NAP
UWI / API#:	Unknown / Unknown	Magnetic Declination:	1.102 °
Survey Name:	NLW-GT-02-S1 Def Survey	Total Gravity Field Strength:	1000.5836mgm (9.80665 Based)
Survey Date:	April 03, 2018	Gravity Model:	GARM
Tort / AHD / DDI / ERD Ratio:	84.567 ° / 730.906 m / 5.333 / 0.289	Total Magnetic Field Strength:	49039.641 nT
Coordinate Reference System:	Amersfoort * OGP-Nlid / RD Dutch Onshore	Magnetic Dip Angle:	67.069 °
Location Lat / Long:	N 51° 59' 26.96188", E 4° 14' 22.35732"	Declination Date:	February 04, 2018
Location Grid N/E YX:	N 445230.000 m, E 76154.000 m	Magnetic Declination Model:	HDGM 2017
CRS Grid Convergence Angle:	-0.9056 °	North Reference:	Grid North
Grid Scale Factor:	0.99994799	Grid Convergence Used:	-0.9056 °
Version / Patch:	2.10.254.0	Total Corr Mag North->Grid	2.0078 °
		North:	Local Coord Referenced To: Structure Reference Point

Comments	MD (m)	Incl (°)	Azim Grid (°)	TVD (m)	TVDS (m)	VSEC (m)	NS (m)	EW (m)	DLS (°/30m)	Northing (m)	Easting (m)	Latitude (N/S ° *')	Longitude (E/W ° *')
Tie-In	0.00	0.00	0.00	0.00	-8.42	0.00	0.00	0.00	N/A	445230.00	76154.00	N 51 59 26.96	E 4 14 22.36
GL	9.32	0.00	0.00	9.32	0.90	0.00	0.00	0.00	0.00	445230.00	76154.00	N 51 59 26.96	E 4 14 22.36
Conductor interference	143.59	2.13	43.05	143.56	135.14	1.08	1.82	1.70	0.48	445231.82	76155.70	N 51 59 27.02	E 4 14 22.45
DMAG	171.48	2.43	60.83	171.43	163.01	1.71	2.49	2.57	0.82	445232.49	76156.57	N 51 59 27.04	E 4 14 22.49
DMAG	200.72	4.05	79.42	200.62	192.20	3.05	2.98	4.13	1.96	445232.98	76158.13	N 51 59 27.06	E 4 14 22.57
DMAG	228.81	5.71	88.57	228.61	220.19	5.24	3.20	6.50	1.95	445233.20	76160.50	N 51 59 27.07	E 4 14 22.70
Fish Interference	256.86	7.22	88.59	256.48	248.06	8.23	3.28	9.66	1.61	445233.28	76163.66	N 51 59 27.07	E 4 14 22.86
Fish Interference	284.90	6.54	86.73	284.32	275.90	11.39	3.41	13.02	0.77	445233.41	76167.01	N 51 59 27.08	E 4 14 23.04
Fish Interference	312.51	7.69	90.35	311.71	303.29	14.63	3.49	16.43	1.34	445233.49	76170.43	N 51 59 27.08	E 4 14 23.22
Fish Interference	340.21	8.35	88.51	339.14	330.72	18.30	3.53	20.30	0.77	445233.53	76174.30	N 51 59 27.09	E 4 14 23.42
DMAG	368.61	9.23	88.49	367.21	358.79	22.41	3.64	24.63	0.93	445233.64	76178.63	N 51 59 27.09	E 4 14 23.65
DMAG	396.44	10.38	94.74	394.63	386.21	26.97	3.50	29.36	1.69	445233.50	76183.36	N 51 59 27.09	E 4 14 23.89
DMAG	424.21	12.96	99.87	421.83	413.41	32.50	2.76	34.93	3.00	445232.76	76188.93	N 51 59 27.07	E 4 14 24.19
DMAG	451.76	12.67	105.98	448.69	440.27	38.58	1.39	40.88	1.51	445231.39	76194.87	N 51 59 27.03	E 4 14 24.50
DMAG	480.28	11.94	107.66	476.56	468.14	44.66	-0.36	46.69	0.86	445229.64	76206.69	N 51 59 26.97	E 4 14 24.80
DMAG	508.01	13.16	109.74	503.62	495.20	50.68	-2.30	52.40	1.41	445227.70	76206.40	N 51 59 26.91	E 4 14 25.11
DMAG	536.29	14.17	112.19	531.10	522.68	57.34	-4.69	58.63	1.23	445225.31	76212.63	N 51 59 26.84	E 4 14 25.43
DMAG	564.31	13.91	113.38	558.29	549.87	64.11	-7.32	64.90	0.42	445222.68	76218.90	N 51 59 26.76	E 4 14 25.76
DMAG	592.18	13.35	112.05	585.37	576.95	70.65	-9.86	70.96	0.69	445220.14	76224.95	N 51 59 26.68	E 4 14 26.08
DMAG	620.05	13.22	112.05	612.50	604.08	77.04	-12.27	76.89	0.14	445217.73	76230.89	N 51 59 26.60	E 4 14 26.40
DMAG	647.70	13.00	112.85	639.42	631.00	83.28	-14.66	82.69	0.31	445215.34	76236.69	N 51 59 26.53	E 4 14 26.70
DMAG	675.97	12.87	114.06	666.88	658.46	89.55	-17.17	88.47	0.32	445212.83	76242.47	N 51 59 26.45	E 4 14 27.01
DMAG	703.90	12.21	116.00	694.24	685.82	95.59	-19.74	93.99	0.84	445201.26	76247.98	N 51 59 26.37	E 4 14 27.30
DMAG	731.75	12.74	114.18	721.43	713.01	101.55	-22.29	99.44	0.71	445207.71	76253.43	N 51 59 26.29	E 4 14 27.59
DMAG	759.59	13.16	114.62	748.57	740.15	107.74	-24.87	105.12	0.46	445205.13	76259.11	N 51 59 26.21	E 4 14 27.89
DMAG	787.98	12.93	114.75	776.22	767.80	114.10	-27.54	110.94	0.25	445202.46	76264.94	N 51 59 26.13	E 4 14 28.19
DMAG	815.95	11.86	114.15	803.54	795.12	120.06	-30.03	116.41	1.16	445199.77	76270.40	N 51 59 26.05	E 4 14 28.48
DMAG	843.88	11.35	114.64	830.90	822.48	125.63	-32.35	121.52	0.56	445197.65	76275.52	N 51 59 25.98	E 4 14 28.75
DMAG	871.83	11.35	114.42	858.30	849.88	131.09	-34.63	126.53	0.05	445195.37	76280.52	N 51 59 25.91	E 4 14 29.02
DMAG	899.31	11.26	114.67	885.25	876.83	136.44	-36.87	131.43	0.11	445193.13	76285.42	N 51 59 25.84	E 4 14 29.28
DMAG	927.06	11.07	115.71	912.47	904.05	141.76	-39.16	136.29	0.30	445190.84	76290.28	N 51 59 25.76	E 4 14 29.53
DMAG	955.25	10.73	115.25	940.16	931.74	147.04	-41.45	141.10	0.37	445188.65	76295.09	N 51 59 25.69	E 4 14 29.79
DMAG	983.37	10.05	119.06	967.82	959.40	152.04	-43.76	145.61	1.03	445186.24	76299.61	N 51 59 25.62	E 4 14 30.02
DMAG	1011.38	9.28	117.91	995.43	987.01	156.65	-46.01	149.75	0.85	445184.00	76303.74	N 51 59 25.55	E 4 14 30.24
DMAG	1038.94	8.90	120.58	1022.64	1014.22	160.91	-48.13	153.55	0.62	445181.87	76307.54	N 51 59 25.48	E 4 14 30.44
DMAG	1067.19	8.20	121.84	1050.58	1042.16	164.99	-50.30	157.14	0.77	445179.70	76311.13	N 51 59 25.41	E 4 14 30.63
DMAG	1087.46	8.01	119.22	1070.64	1062.22	167.77	-51.76	159.60	0.61	445178.25	76313.59	N 51 59 25.37	E 4 14 30.76
Shoe Interference	1111.90	7.85	120.24	1094.85	1086.43	171.07	-53.43	162.53	0.26	445176.57	76316.52	N 51 59 25.32	E 4 14 30.92
DMAG	1139.92	7.52	120.73	1122.62	1114.20	174.72	-55.33	165.76	0.36	445174.67	76319.75	N 51 59 25.26	E 4 14 31.09
DMAG	1167.90	7.17	121.80	1150.37	1141.95	178.19	-57.18	168.81	0.40	445172.82	76322.81	N 51 59 25.05	E 4 14 31.25
DMAG	1195.69	6.81	122.12	1177.95	1169.53	181.47	-58.97	171.68	0.39	445171.03	76325.67	N 51 59 25.14	E 4 14 31.40
DMAG	1223.97	6.52	122.42	1206.04	1197.62	184.64	-60.73	174.46	0.31	445169.28	76328.45	N 51 59 25.09	E 4 14 31.55
DMAG	1251.62	6.39	121.56	1233.52	1225.10	187.65	-62.37	177.10	0.18	445167.63	76331.09	N 51 59 25.03	E 4 14 31.69
DMAG	1279.60	8.06	120.24	1261.27	1252.85	191.07	-64.18	180.12	1.80	445165.83	76334.11	N 51 59 24.98	E 4 14 31.85
DMAG	1307.40	11.15	117.59	1288.68	1280.26	195.62	-66.40	184.18	3.37	445163.60	76338.17	N 51 59 24.91	E 4 14 32.06
DMAG	1336.11	13.30	117.28	1316.74	1308.32	201.61	-69.20	189.58	2.25	445160.80	76343.57	N 51 59 24.82	E 4 14 32.35
DMAG	1363.50	13.32	117.59	1343.39	1334.97	207.82	-72.11	195.18	0.08	445157.89	76349.17	N 51 59 24.73	E 4 14 32.65
MWD Surveys:	1391.19	12.90	117.05	1370.36	1361.94	214.00	-74.99	200.76	0.47	445155.01	76354.75	N 51 59 24.64	E 4 14 32.94
	1419.25	13.05	115.10	1397.70	1389.28	220.23	-77.76	206.41	0.49	445152.24	76360.40	N 51 59 24.55	E 4 14 33.24
	1447.01	12.97	110.28	1424.75	1416.33	226.45	-80.17	212.18	1.18	445149.83	76366.16	N 51 59 24.48	E 4 14 33.54
	1474.91	12.95	105.31	1451.94	1443.52	232.70	-82.08	218.13	1.20	445147.92	76372.12	N 51 59 24.42	E 4 14 33.86
	1503.47	13.10	101.61	1479.77	1471.35	239.12	-83.58	224.38	0.89	445146.43	76378.37	N 51 59 24.37	E 4 14 34.19
	1531.37	13.21	102.86	1508.43	1508.94	240.52	-84.92	230.59	0.33	445145.08	76348.58	N 51 59 24.33	E 4 14 34.51
	1559.39	13.28	104.61	1534.21	1525.79	251.85	-86.45	236.83	0.44	445143.66	76390.81	N 51 59 24.29	E 4 14 34.84
	1587.32	13.31	105.25	1561.39	1552.97	258.26	-88.10	243.03	0.16	445141.90	76397.02	N 51 59 24.24	E 4 14 35.17
	1615.16	12.95	107.24	1586.50	1580.08	264.59	-89.87	249.10	0.62	445140.14	76403.09	N 51 59 24.18	E 4 14 35.49
	1643.29	12.58	108.43	1615.94	1607.52	270.80	-91.77	255.02	0.48</td				

Comments	MD (m)	Incl (°)	Azim Grid (°)	TVD (m)	TVDSs (m)	VSEC (m)	NS (m)	EW (m)	DLS (°/30m)	Northing (m)	Easting (m)	Latitude (N/S °'")	Longitude (E/W °'")
	2449.50	37.50	107.27	2356.68	2348.26	567.70	-166.30	542.81	1.51	445063.70	76696.78	N 51 59 21.86	E 4 14 50.94
	2477.29	39.17	106.42	2378.48	2370.06	584.94	-171.30	559.31	1.89	445058.71	76713.28	N 51 59 21.70	E 4 14 51.81
	2504.99	40.37	107.06	2399.77	2391.35	602.65	-176.40	576.28	1.37	445053.61	76730.25	N 51 59 21.55	E 4 14 52.70
	2533.26	41.87	107.85	2421.07	2412.65	621.24	-181.98	594.01	1.68	445048.03	76747.98	N 51 59 21.38	E 4 14 53.64
	2561.64	43.89	108.05	2441.86	2433.44	640.55	-187.93	612.38	2.14	445042.08	76766.35	N 51 59 21.19	E 4 14 54.61
	2589.24	45.26	107.83	2461.52	2453.10	659.92	-193.90	630.81	1.50	445036.11	76784.78	N 51 59 21.01	E 4 14 55.58
	2616.70	45.11	107.81	2480.88	2472.46	679.40	-199.86	649.35	0.16	445030.15	76803.32	N 51 59 20.83	E 4 14 56.55
	2644.39	45.07	107.60	2500.43	2492.01	699.01	-205.82	668.04	0.17	445024.19	76822.00	N 51 59 20.64	E 4 14 57.64
	2668.00	45.00	107.91	2517.11	2508.69	715.72	-210.92	683.94	0.29	445019.09	76837.91	N 51 59 20.49	E 4 14 58.37
Proj. to well TD	2680.00	45.00	108.05	2525.60	2517.18	724.20	-213.54	692.02	0.25	445016.47	76845.98	N 51 59 20.41	E 4 14 58.80

Survey Type: Def Survey

Survey Error Model: ISCWSA Rev 0 *** 3-D 95.000% Confidence 2.7955 sigma

Survey Program:

Description	Part	MD From (m)	MD To (m)	EOU Freq (m)	Hole Size (in)	Casing Diameter (in)	Survey Tool Type	Borehole / Survey
	1	0,000	9,320	Act Stns	30,000	30,000	SLB_MWD+SAG-Depth Only	NLW-GT-02-S1 / NLW-GT-02-S1 Def Survey
	1	9,320	137,000	1/30.000	30,000	30,000	SLB_MWD+SAG	NLW-GT-02-S1 / NLW-GT-02-S1 Def Survey
	1	137,000	137,000	Act Stns	30,000	30,000	SLB_MWD+SAG	NLW-GT-02-S1 / NLW-GT-02-S1 Def Survey
	1	137,000	1102,000	Act Stns	24,000	20,000	SLB_MWD+SAG	NLW-GT-02-S1 / NLW-GT-02-S1 Def Survey
	1	1102,000	2376,000	Act Stns	17,500	13,625	SLB_MWD+SAG	NLW-GT-02-S1 / NLW-GT-02-S1 Def Survey
	1	2376,000	2680,000	Act Stns	12,250	12,250	SLB_MWD+SAG	NLW-GT-02-S1 / NLW-GT-02-S1 Def Survey