

Congratulations

You have completed a Codility demo.

Tweet this!

I scored 100% in #ruby on @Codility!
https://codility.com/demo/take-sample-test/passing_cars/

Sign up for our newsletter!

Like us on Facebook!

Demo ticket

Session

ID: demoBQAT8V-36J
 Time limit: 120 min.

Status: closed

Created on: 2014-12-20 12:46 UTC
 Started on: 2014-12-20 12:48 UTC
 Finished on: 2014-12-20 14:06 UTC

Tasks in test

1 |  PassingCars

Correctness

100%

Performance

100%

Task score

100%

Test score

100%
 100 out of 100 points

EASY

1. PassingCars

Count the number of passing cars on the road.

score: 100 of 100



Task description

A non-empty zero-indexed array *A* consisting of *N* integers is given. The consecutive elements of array *A* represent consecutive cars on a road. Array *A* contains only 0s and/or 1s:

- 0 represents a car traveling east,
- 1 represents a car traveling west.

The goal is to count passing cars. We say that a pair of cars (*P*, *Q*), where $0 \leq P < Q < N$, is passing when *P* is traveling to the east and *Q* is traveling to the west.

For example, consider array *A* such that:

```
A[0] = 0
A[1] = 1
A[2] = 0
A[3] = 1
A[4] = 1
```

We have five pairs of passing cars: (0, 1), (0, 3), (0, 4), (2, 3), (2, 4). Write a function:

```
def solution(a)
```

that, given a non-empty zero-indexed array *A* of *N* integers, returns the number of passing cars. The function should return -1 if the number of passing cars exceeds 1,000,000,000.

For example, given:

```
A[0] = 0
A[1] = 1
A[2] = 0
A[3] = 1
A[4] = 1
```

the function should return 5, as explained above. Assume that:

- *N* is an integer within the range [1..100,000];
- each element of array *A* is an integer that can have one of the following values: 0, 1.

Solution

Programming language used: Ruby

Total time used: 79 minutes

Effective time used: 79 minutes

Notes: not defined yet

Task timeline



12:48:15

14:06:19

Code: 14:06:19 UTC, rb, final, score: 100.00

```
1 # you can use puts for debugging purposes, e.g.
2 # puts "this is a debug message"
3
4 def solution(a)
5   total_east = 0
6   total = 0
7   a.each_with_index do |car, index|
8     if car == 0
9       total_east += 1
10    else
11      total += total_east
12      return -1 if total > 1_000_000_000
13    end
14  end
15  total
16 end
```

Analysis

Complexity:

- expected worst-case time complexity is $O(N)$;
- expected worst-case space complexity is $O(1)$, beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2014 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Detected time complexity:
 $O(N)$

test	time	result
Example tests		
example example test	0.064 s	OK
Correctness tests		
single single element	0.064 s	OK
double two elements	0.060 s	OK
simple simple test	0.056 s	OK
small_random random, length = 100	0.056 s	OK
Performance tests		
medium_random random, length = ~10,000	0.076 s	OK
large_random random, length = ~100,000	0.200 s	OK
large_big_answer 0..01..1, length = ~100,000	0.160 s	OK
large_alternate 0101..01, length = ~100,000	0.192 s	OK
large_extreme large test with all 1s/0s, length = ~100,000	0.208 s	OK

Training center