



Congratulations

You have completed a Codility demo.

Tweet this!

I scored 100% in #ruby on @Codility!
https://codility.com/demo/take-sample-test/tape_equilibrium/

Sign up for our newsletter!

Like us on Facebook!

Demo ticket

Session

ID: demo7ANYMF-GGQ
Time limit: 120 min.

Status: closed

Created on: 2014-12-09 09:45 UTC
Started on: 2014-12-09 09:48 UTC
Finished on: 2014-12-09 10:49 UTC

Tasks in test

1 | TapeEquilibrium

Correctness

100%

Performance

100%

Task score

100%

Test score

100%
100 out of 100 points

EASY

1. TapeEquilibrium
Minimize the value $|(A[0] + \dots + A[P-1]) - (A[P] + \dots + A[N-1])|$.

score: 100 of 100

Task description

A non-empty zero-indexed array A consisting of N integers is given. Array A represents numbers on a tape. Any integer P, such that $0 < P < N$, splits this tape into two non-empty parts: $A[0], A[1], \dots, A[P - 1]$ and $A[P], A[P + 1], \dots, A[N - 1]$. The *difference* between the two parts is the value of: $|(A[0] + A[1] + \dots + A[P - 1]) - (A[P] + A[P + 1] + \dots + A[N - 1])|$. In other words, it is the absolute difference between the sum of the first part and the sum of the second part. For example, consider array A such that:

A[0] = 3
A[1] = 1
A[2] = 2
A[3] = 4
A[4] = 3

We can split this tape in four places:

- P = 1, difference = $|3 - 10| = 7$
- P = 2, difference = $|4 - 9| = 5$
- P = 3, difference = $|6 - 7| = 1$
- P = 4, difference = $|10 - 3| = 7$

Write a function:

```
def solution(a)
```

that, given a non-empty zero-indexed array A of N integers, returns the minimal difference that can be achieved. For example, given:

A[0] = 3
A[1] = 1
A[2] = 2
A[3] = 4
A[4] = 3

the function should return 1, as explained above.

Solution

Programming language used: Ruby

Total time used: 62 minutes

Effective time used: 62 minutes

Notes: not defined yet

Task timeline



09:48:00 10:49:32

Code: 10:49:32 UTC, rb, final, score: 100.00

```
1 # you can use puts for debugging purposes, e.g.
2 # puts "this is a debug message"
3
4 def solution(a)
5   sum_a = sum(a)
6   sum = sum_a[-1]
7   a = sum - sum_a[0]
8   b = sum_a[0]
9   min = (a - b).abs
10  (1..sum_a.count - 2).each do |i|
11    a = sum - sum_a[i]
12    b = sum_a[i]
13    n = (a - b).abs
14    if n < min
15      min = n
16    end
17  end
18  min
19 end
```

- the function should return 1, as explained above.
- Assume that:
- N is an integer within the range [2..100,000];
 - each element of array A is an integer within the range [-1,000..1,000].

Complexity:

- expected worst-case time complexity is O(N);
- expected worst-case space complexity is O(N), beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2014 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

```
16         end
17     end
18     min
19 end
20
21 def sum(a)
22     r = []
23     sum = 0
24     a.each do |n|
25         sum += n
26         r << sum
27     end
28     r
29 end
```

Analysis

Detected time complexity:
O(N)

test	time	result
Example tests		
example example test	0.060 s	OK
Correctness tests		
double two elements	0.060 s	OK
simple_positive simple test with positive numbers, length = 5	0.056 s	OK
simple_negative simple test with negative numbers, length = 5	0.064 s	OK
small_random random small, length = 100	0.064 s	OK
small_range range sequence, length = ~1,000	0.056 s	OK
small small elements	0.064 s	OK
Performance tests		
medium_random1 random medium, numbers from 0 to 100, length = ~10,000	0.076 s	OK
medium_random2 random medium, numbers from -1,000 to 50, length = ~10,000	0.080 s	OK
large_ones large sequence, numbers from -1 to 1, length = ~100,000	0.224 s	OK
large_random random large, length = ~100,000	0.228 s	OK
large_sequence large sequence, length = ~100,000	0.144 s	OK
large_extreme large test with maximal and minimal values, length = ~100,000	0.200 s	OK

Training center