

National Research University Higher School of Economics  
Faculty of Computer Science  
Bachelor's Program "HSE University and University of London Double Degree  
Program in Data Science and Business Analytics"

# Introduction to Programming

## Workshop #14

Fri 26.02.2021

Julio Carrasquel



NATIONAL RESEARCH  
UNIVERSITY

## The data – cities.csv

*File with the 500 most populated cities in the world*

1	city	lat	lng	country	population
2	Tokyo	35.6897	139.6922	Japan	37977000
3	Jakarta	6.2146	106.8451	Indonesia	34540000
4	Delhi	28.66	77.23	India	29617000
5	Mumbai	18.9667	72.8333	India	23355000
6	Manila	14.5958	120.9772	Philippines	23088000
7	Shanghai	31.1667	121.4667	China	22120000
8	Sao Paulo	23.5504	46.6339	Brazil	22046000
9	Seoul	37.5833	127	South Korea	21794000
10	Mexico City	19.4333	99.1333	Mexico	20996000
11	Guangzhou	23.1288	113.259	China	20902000
12	Beijing	39.905	116.3914	China	19433000
13	Cairo	30.0561	31.2394	Egypt	19372000
14	New York	40.6943	73.9249	United States	18713220
15	Kolkata	22.5411	88.3378	India	17560000
16	Moscow	55.7558	37.6178	Russia	17125000
17	Bangkok	13.75	100.5167	Thailand	17066000
18	Buenos Aires	34.5997	58.3819	Argentina	16157000

# Task 1

- 1) Create a `std::map<std::string, std::vector<std::pair<std::string,int> >` called `countryMap` where the keys are *country names*, and the values are vectors of *pairs city-population*. Fill the map with the information in the file `cities.csv`

Example of `countryMap`

```
countryMap["USA"] = [ ("New York",18713220) , ("Los Angeles",12750807) ]  
countryMap["China"] = [ ("Shanghai",22120000) , ("Guangzhou",20902000) ) , ("Beijing",18713220) ]  
...
```

- 2) Print the vector of cities-population of the 5 *countries with most population*.

To resolve this task, use the first map `countryMap` to create a second map `std::map<int , std::string> populationMap` where the keys are the *sum of city population of a country* and the values are the *country names*.

Example of `populationMap`

```
populationMap[31464027] = "USA"  
populationMap[61735220] = "China"  
...
```

Then, for finding the 5 *countries with most population*, we need to take the *country names* from *the last 5 elements* of `populationMap` (why? remember, the map is ordered)  
Finally, print the list of vectors city-population of the 5 countries you took.

## Task 2

- 1) Create a `std::map<std::string, std::pair<double, double>>` called `cityMap` where the keys are *city names*, and the values are pairs *latitude-longitude*.  
Fill the map with the information in the file `cities.csv`

Example of `cityMap`

```
cityMap["New York"] = (40.6943, -73.9249)
cityMap["Shanghai"] = (31.1667, 121.4667)
...
```

- 2) Print the 5 pairs of cities with the *farthest distances* between each other.  
To resolve this task, use the first map `cityMap` to create a second map  
`std::map<double, std::pair<std::string, std::string>>` `distanceMap`  
where keys are *distances between cities*\* and values are *pairs of cities*.

Example of `distanceMap`

```
distanceMap[11860.47] = ("New York", "Shanghai")
...
```

Then, for finding the 5 pairs of cities with the *farthest distances* between each other, we simply need to print the *last 5 elements* of `distanceMap` (why? remember, the map is ordered)

\*Note: the function to calculate the distance between cities is provided in the code template.

# Example of Solution Output - Task 1

```
giulio@giulio:~/HSE/repositories/dsba/ws14-26-02-2021$ ./run
Countries with most populated cities: 5
#1 China cities: 250
Shanghai => 22120000
Guangzhou => 20902000
Beijing => 19433000
Shenzhen => 15929000
Nanyang => 12010000
Chengdu => 11309000
Linyi => 10820000
Tianjin => 10800000
Shijiazhuang => 10784600
Baoding => 10700000
Zhoukou => 9901000
Weifang => 9373000
Wuhan => 8962000
Heze => 8750000
Ganzhou => 8677600
Tongshan => 8669000
Handan => 8499000
Fuyang => 8360000
Jining => 8023000
Dongguan => 7981000
Chongqing => 7739000
Changchun => 7674439
Zhumadian => 7640000
Ningbo => 7639000
Nanjing => 7496000
Hefei => 7457027
Nantong => 7282835
Yancheng => 7260240
Foshan => 7194311
Nanning => 7153300
Hengyang => 7148344
Xi'an => 7135000
Shenyang => 7105000
Tangshan => 7100000
```

```
San Antonio => 2049293
St. Louis => 2024074
Sacramento => 1898019
Orlando => 1822394
San Jose => 1798103
Cleveland => 1710093
Pittsburgh => 1703266
Austin => 1687311
Cincinnati => 1662691
Kansas City => 1636715
Manhattan => 1628706
Indianapolis => 1588961
Columbus => 1562009
Charlotte => 1512923
Virginia Beach => 1478868
```

```
#4 Japan cities: 8
Tokyo => 37977000
Osaka => 14977000
Nagoya => 9113000
Yokohama => 3748781
Fukuoka => 2128000
Sapporo => 1958756
Kyoto => 1805000
Kobe => 1522944
```

```
#5 Brazil cities: 11
Sao Paulo => 22046000
Rio de Janeiro => 12272000
Belo Horizonte => 5159000
Brasilia => 3015268
Salvador => 2921087
Fortaleza => 2452185
Curitiba => 1879355
Manaus => 1802014
Vitoria => 1704000
Recife => 1555039
```

## Example of Solution Output - Task 2

```
giulio@giulio:~/HSE/repositories/dsba/ws14-26-02-2021$ ./run
Cities with farthest distances between each other: 5
#0:Brisbane <===> Accra : 15321 kms
#1:Kumasi <===> Brisbane : 15129.6 kms
#2:Brisbane <===> Abidjan : 15077 kms
#3:Lagos <===> Brisbane : 15027 kms
#4:Ibadan <===> Brisbane : 14909.5 kms
```