

Parameterized Restless Temporal Path

Justine Cauvi, Laurent Viennot

École Normale Supérieure de Lyon, Lyon, France
Inria, DI ENS, Paris, France

MoMA 2025

Plan

1 Introduction

2 Results

3 Conclusion

Temporal graphs: motivations, history

Motivations:

- Graphs represent relationships between entities
- In many real-world applications, those relationships are time-related:
 - Public Transit network: there is a bus that goes directly from stop s to stop t only at time $\tau_1, \tau_2, \tau_3 \dots$
 - Phone call network: Alice calls Bob from time τ to time τ'
 - Social network: Alice follows Bob at time τ
 - ...

Temporal graphs: motivations, history

Motivations:


- Graphs represent relationships between entities
- In many real-world applications, those relationships are time-related:
 - Public Transit network: there is a bus that goes directly from stop s to stop t only at time $\tau_1, \tau_2, \tau_3 \dots$
 - Phone call network: Alice calls Bob from time τ to time τ'
 - Social network: Alice follows Bob at time τ
 - ...

History:


- Fragmented literature, plenty of models
- Time-dependent network (e.g.: road networks [Dreyfus 1969])
- Evolving graph (e.g.: ad-hoc networks [Xuan et al. 2003])
- Temporal network (e.g.: social network [Holme et al. 2011]), link stream [Latapy et al. 2017]
- Time-varying graph (ex: distributed computing [Casteigts et al. 2012]), temporal graph (ex: graph theory [Michail 2015])

Temporal graphs: models

Sequence of snapshots:




Labeled graph:




Temporal graphs: models

Sequence of snapshots:




Labeled graph:




Underlying graph

Temporal paths: non strict and strict settings

Non-strict/Strict temporal path: A path and an **non-decreasing/increasing** sequence of times at which arcs can be traversed one after the other




Non-strict setting



Strict setting


Our model

- Directed graph
- Delay: time it takes to traverse an arc




Our model

- Directed graph
- Delay: time it takes to traverse an arc



- Uniform delay zero = non-strict setting
- Uniform delay one = strict setting


Our model



$$[(s, u, 1, 1), (s, u, 2, 1), (u, v, 4, 2) \dots]$$

- Each time we can traverse an arc $\Rightarrow$ a timed arc
- **Timed arc**: an arc, an appearance time, a delay (e.g. $(u, v, 4, 2)$ is a timed arc)

Our model



$$[(s, u, 1, 1), (s, u, 2, 1), (u, v, 4, 2) \dots]$$

- Each time we can traverse an arc $\Rightarrow$ a timed arc
- **Timed arc**: an arc, an appearance time, a delay (e.g. $(u, v, 4, 2)$ is a timed arc)
- Input: sorted list of timed arcs in non-decreasing order of appearance time
- M : number of timed arcs $\Rightarrow$ size of the **input** in $\mathcal{O}(M)$

Generalization of static graph problems

- Revisit classical static graph problems in the context of temporal graphs
- Usually **more difficult**

Generalization of static graph problems

- Revisit classical static graph problems in the context of temporal graphs
- Usually **more difficult**

Definition

A **temporal strongly connected component** (TSCC) is a maximal set of vertices U s.t. for any $s, t \in U$, there is a temporal path from s to t and from t to s using only timed arcs with extremities in U .

Generalization of static graph problems

- Revisit classical static graph problems in the context of temporal graphs
- Usually **more difficult**


Definition

A **temporal strongly connected component** (TSCC) is a maximal set of vertices U s.t. for any $s, t \in U$, there is a temporal path from s to t and from t to s using only timed arcs with extremities in U .

- With static graphs: find SCC in linear time
- With temporal graphs: find TSCC **NP-hard**

In this talk: Restless Temporal Path

Δ -restless temporal path: Cannot wait more than Δ at an intermediate node



$$\Delta = 2$$

In this talk: Restless Temporal Path

RESTLESS-TEMPORAL-PATH

Input: A temporal graph G , a source node s , a target node t and a waiting time $\Delta \in \mathbb{N}$

Question: Is there a Δ -restless temporal path from s to t in G ?

In this talk: Restless Temporal Path

RESTLESS-TEMPORAL-PATH

Input: A temporal graph G , a source node s , a target node t and a waiting time $\Delta \in \mathbb{N}$


Question: Is there a Δ -restless temporal path from s to t in G ?

Applications:

- Detection of a chain of infections in the SIR (Susceptible-Infected-Recovered) model
- Public transit networks

In this talk: Restless Temporal Path

- Computing a restless temporal **walk**: **polynomial time** [Bentert et al. 2020]



- Computing a restless temporal **path**: **NP-hard** [Casteigts et al. 2021]

Parameters

NP-hard problems $\Rightarrow$ find parameters that bring tractability

Parameters

NP-hard problems $\Rightarrow$ find parameters that **bring tractability**

Restless temporal path:

- Output-related parameter: the number of hops of the temporal path [Casteigts et al. 2021, Zschoche 2023]
- Classical parameter applied to the underlying graph: the feedback edge number of the underlying graph [Casteigts et al. 2021]
- New 'temporal' parameter: the timed feedback vertex number [Casteigts et al. 2021]

Parameters

NP-hard problems $\Rightarrow$ find parameters that **bring tractability**

Restless temporal path:

- Output-related parameter: the number of hops of the temporal path [Casteigts et al. 2021, Zschoche 2023]
- Classical parameter applied to the underlying graph: the feedback edge number of the underlying graph [Casteigts et al. 2021]
- New 'temporal' parameter: the timed feedback vertex number [Casteigts et al. 2021]

Invariant by permutation of the snapshots $\Rightarrow$ does not seem to really grasp the **temporal aspect**

The (vertex)-interval-membership-width parameter

Interval-membership-width parameters: [Bumpus and Meeks 2022]

- Novel parameters that capture some temporal aspects
- Promising for reachability problems
 - FPT for temporal Euler circuit
 - NP-hard for MinReachDelete but FPT with the vertex variant
 - Counting the number of temporal paths [Enright et al. 2023]
 - Temporal Firefighter Problem [Hand et al. 2022]

The (vertex)-interval-membership-width parameter


Interval-membership-width parameters: [Bumpus and Meeks 2022]

- Novel parameters that capture some temporal aspects
- Promising for reachability problems
 - FPT for temporal Euler circuit
 - NP-hard for MinReachDelete but FPT with the vertex variant
 - Counting the number of temporal paths [Enright et al. 2023]
 - Temporal Firefighter Problem [Hand et al. 2022]
- Incomparable with the other FPT parameters for the restless temporal path problem

Goal: Study this new parameter for the restless temporal path problem

The (vertex)-interval-membership-width parameter


Active window of an arc:



[first departure time of (u, v) , last arrival time of (u, v)] = $[2, 12]$


The (vertex)-interval-membership-width parameter

Active window of an arc:




[first departure time of (u, v) , last arrival time of (u, v)] = $[2, 12]$

Active window of a vertex: Smallest window containing all active windows of arcs adjacent to the vertex




$[1, 5]$





The (vertex)-interval-membership-width parameter

Active window of an arc:



[first departure time of (u, v) , last arrival time of (u, v)]=[2,12]

Active window of a vertex: Smallest window containing all active windows of arcs adjacent to the vertex



(vertex)-interval-membership-width: Maximum number of arcs (vertices) active at the same time

Plan

1 Introduction

2 Results

3 Conclusion

Uniform delay one (strict setting)

Proposition

RESTLESS-TEMPORAL-PATH is NP-hard, even if the input temporal graph has interval-membership-width equal to three and uniform delay one.

Uniform delay one (strict setting)

Theorem

When the input temporal graph $G = (V, E)$ has uniform delay one, RESTLESS-TEMPORAL-PATH can be solved in $\mathcal{O}(k2^k M)$ deterministic time, where k is the **vertex-interval-membership-width** of G .

Uniform delay one (strict setting)

Theorem

When the input temporal graph $G = (V, E)$ has uniform delay one, RESTLESS-TEMPORAL-PATH can be solved in $\mathcal{O}(k2^k M)$ deterministic time, where k is the **vertex-interval-membership-width** of G .

General idea:

- Scan timed arcs in order of appearance time
- Maintain for each node u the Δ -restless temporal su -paths

Uniform delay one (strict setting)

Theorem

When the input temporal graph $G = (V, E)$ has uniform delay one, RESTLESS-TEMPORAL-PATH can be solved in $\mathcal{O}(k2^k M)$ deterministic time, where k is the **vertex-interval-membership-width** of G .

General idea:

- Scan timed arcs in order of appearance time
- Maintain for each node u the Δ -restless temporal su -paths
- Problem: potentially **exponential** number

Uniform delay one (strict setting)

Theorem

When the input temporal graph $G = (V, E)$ has uniform delay one, RESTLESS-TEMPORAL-PATH can be solved in $\mathcal{O}(k2^k M)$ deterministic time, where k is the **vertex-interval-membership-width** of G .

General idea:

- Scan timed arcs in order of appearance time
- Maintain for each node u the Δ -restless temporal su -paths
- Problem: potentially **exponential** number
- Solution: store only traces of paths (only the nodes on the path that are active at considered time): at most **2^k traces**

Other results

- Arbitrary positive delays: additional computational cost
- NP-hardness in the interval model

Plan

1 Introduction

2 Results

3 Conclusion

Summary and future work

Contributions:

- **FPT algorithms** for the restless temporal path problem with the **vertex-interval-membership-width** in:
 - the point model with uniform delay one
 - the point model with arbitrary (positive) delays (additional computational cost)
- **NP-hardness** in:
 - the point model even if the interval-membership-width is equal to three
 - the interval model even if the vertex-interval-membership-width is equal to three

Summary and future work

Contributions:

- **FPT algorithms** for the restless temporal path problem with the **vertex-interval-membership-width** in:
 - the point model with uniform delay one
 - the point model with arbitrary (positive) delays (additional computational cost)
- **NP-hardness** in:
 - the point model even if the interval-membership-width is equal to three
 - the interval model even if the vertex-interval-membership-width is equal to three

Open questions:

- Interval model with uniform delay one
- What other temporal parameters might bring tractability to the problem and are small in practice?

Summary and future work

Contributions:

- **FPT algorithms** for the restless temporal path problem with the **vertex-interval-membership-width** in:
 - the point model with uniform delay one
 - the point model with arbitrary (positive) delays (additional computational cost)
- **NP-hardness** in:
 - the point model even if the interval-membership-width is equal to three
 - the interval model even if the vertex-interval-membership-width is equal to three

Open questions:

- Interval model with uniform delay one
- What other temporal parameters might bring tractability to the problem and are small in practice?

Thank you for listening!

References (1/2)

- [Dreyfus 1969]: Dreyfus, S.E.. (1969). An Appraisal of Some Shortest Path Algorithm. Oper. Res.. 17. 395-412. 10.1287/opre.17.3.395.
- [Xuan et al. 2003]: Bui-Xuan, Binh-Minh et al. "Computing Shortest, Fastest, and Foremost Journeys in Dynamic Networks." Int. J. Found. Comput. Sci. 14 (2003): 267-285.
- [Holme et al. 2011]: Holme, Petter and Jari Saramäki. "Temporal Networks." ArXiv abs/1108.1780 (2011).
- [Latapy et al. 2017]: Latapy, Matthieu et al. "Stream graphs and link streams for the modeling of interactions over time." Social Network Analysis and Mining 8 (2017).
- [Casteigts et al. 2012]: Casteigts, Arnaud et al. "Time-varying graphs and dynamic networks." International Journal of Parallel, Emergent and Distributed Systems 27 (2010): 387 - 408.
- [Michail 2015]: Michail, Othon. (2015). An Introduction to Temporal Graphs: An Algorithmic Perspective. Internet Mathematics. 12.

References (2/2)

- [Bentert et al. 2020]: Bentert, M., Himmel, AS., Nichterlein, A. et al. Efficient computation of optimal temporal walks under waiting-time constraints. *Appl Netw Sci* 5, 73 (2020).
- [Casteigts et al. 2021]: Casteigts, A., Himmel, AS., Molter, H. et al. Finding Temporal Paths Under Waiting Time Constraints. *Algorithmica* (2021).
- [Zschoche 2023]: Philipp Zschoche. Restless Temporal Path Parameterized Above Lower Bounds (STACS 2023).
- [Bumpus and Meeks 2022]: Benjamin Merlin Bumpus and Kitty Meeks. Edge Exploration of Temporal Graphs. *Algorithmica*, 85(3):688–716, August 2022.
- [Enright et al. 2023]: Jessica Enright, Kitty Meeks, and Hendrik Molter. Counting Temporal Paths (STACS 2023).
- [Hand et al. 2022]: Samuel D. Hand, Jessica Enright, and Kitty Meeks. Making Life More Confusing for Firefighters (FUN 2022).


With the vertex-interval-membership-width

Theorem

When the input temporal graph $G = (V, E)$ has uniform delay one, RESTLESS-TEMPORAL-PATH can be solved in $\mathcal{O}(k2^k M)$ deterministic time, where k is the **vertex-interval-membership-width** of G .

Details: Scanning timed arcs at time τ :

- Basic step: Extending a found Δ -restless temporal path with timed arc (u, v, τ) :
 - Look at the couples (S, σ) in $L[u]$: $S \subseteq V$ is a trace, σ the last arrival time of an associated path
 - Check:
 - $v \notin S \Rightarrow$ valid temporal path
 - $\tau - \sigma \leq \Delta \Rightarrow \Delta$ -restless
 - Add $(S \cup \{v\}, \tau + 1)$ to $L'[v]$
- Clean up step:
 - Clean up lists by updating the traces and keeping the last arrival time for each trace



With the vertex-interval-membership-width

- Previous algorithm cannot be easily adapted
- Reason: Implicitly assumes that all timed arcs with appearance time less than τ have arrival time at most τ

With the vertex-interval-membership-width

- Previous algorithm cannot be easily adapted
- Reason: Implicitly assumes that all timed arcs with appearance time less than τ have arrival time at most τ
- Solution: store **all possible arrival times** at a node for each trace in a self-balancing binary search tree


With the vertex-interval-membership-width

- Previous algorithm cannot be easily adapted
- Reason: Implicitly assumes that all timed arcs with appearance time less than τ have arrival time at most τ
- Solution: store **all possible arrival times** at a node for each trace in a self-balancing binary search tree

Theorem

RESTLESS-TEMPORAL-PATH can be solved in $\mathcal{O}(k2^k M(k + \log M))$ deterministic time, where k is the **vertex-interval-membership-width** of G .

Temporal graphs: interval model



Interval model: More compact $\Rightarrow$ more difficult

Theorem

In the interval model, RESTLESS-TEMPORAL-PATH is **NP-hard**, even if the input temporal graph has **vertex-interval-membership-width** equal to three.

- Reduction from SUBSET-SUM
- Uses intervals of exponential length