


PAD	CONNECTION
1	Enable/Disable
2	Ground
3	Output
4	Supply



TOP VIEW

Features

- Ceramic package with metal lid
- High drive capability - up to 50pF
- Enable / disable tristate function
- Power saving function (P & L variants)

Enable / Disable Function

Input (pad 1)	Output (pad 3)
Open	Enabled
'1' level	Enabled
'0' level	High Impedance

Specifications

GXO-U108P: 5.0V supply, E/D with power saving

GXO-U108H: 5.0V supply, E/D high drive

GXO-U108L: 3.3V supply, E/D with power saving

Parameters	Variant			Option Codes
	P	H	L	
Frequency range: 1.8 ~ 80.0MHz 12.0kHz ~ 170MHz	■	■	■	
Frequency stability*: ±100ppm ±50ppm ±25ppm ±20ppm	■	■	■	B
	□	□	□	A
	□	□	□	D
	□	□	□	
Operating temperature range: -10 to +70°C -40 to +85°C	■	■	■	I
Storage temperature range: -55 to +125°C	■	■	■	
Supply voltage (V_{DD}): +5.0V (±0.5V) +3.3V (±0.3V)	■	■	■	
Supply current (mA max): ≤ 32.0MHz >32.0 ~ 50.0MHz >50.0 ~ 67.0MHz >67.0 ~ 80.0MHz >80.0 ~ 125MHz >125 ~ 170MHz	18	27	12	
	50	45	17	
	50	75	18	
	80	75	40	
	80		40	
	90		50	
Logic levels: '0' level = 10%V _{DD} max '1' level = 90%V _{DD} min	■	■	■	
Start up time: 5ms max (<32MHz) 10ms max (>32MHz)	■	■	■	
Waveform symmetry: 45:55 max 45:55 max (<=50.0MHz) 40:60 max (>50.0MHz) 40:60 max		■		
			■	
	■			
Driving ability: 10 LSTTL 15pF HCMOS 10 TTL 50pF HCMOS	■		■	
	■	■	■	
		■		
		■		
Rise / fall time: 7ns max (<80MHz) 4ns max (80.0 ~ 125MHz) 3ns max (125 ~ 170MHz)	■	■	■	
	■		■	
	■		■	
Enable / disable function: Tristate (control via pad 1) 100ns / 100ns 10ms / 100ns	■	■	■	
		■		
	■		■	
Stand-by current: 10µA	■		■	

■ Standard. □ Optional - Please specify required code(s) when ordering

* Frequency stability is inclusive of calibration @ 25°C, operating temperature range, supply voltage change, load change, ageing, shock and vibration.

Ordering Information

Product name + variant + option codes (if any) + frequency
eg: **GXO-U108H/B 40.0MHz** 5V, ±50ppm, -10+70°C

♦ Available on T&R - 2k pcs per reel. See our website for details