

STATghost

Quick manual

clipboard → local engines → text/plot · v0.4.11 · 2026

A sniper, not a Swiss army knife. No editor; clipboard + R / Python / Julia.

1 30-second start

1. Unzip so `statghost.exe`, `statghost_rhost.exe`, `lexer/`, and `library/` stay together (rhost only for R.dll; `library/` for Explorer companion).
2. Run `statghost.exe` (toolbar, top-right).
3. Under **Set** → **Session**, pick language **R**, **Python**, or **Julia** and (if needed) the engine path.
4. Click **Idle** → **Armed** (amber).
5. In another app, select code and copy (**Ctrl+C**) — or use the optional Capture hotkey with *no* selection (see below).
6. See results in **Console** / **Plot**.

2 Traffic lights

- **Set** — preferences (Appearance includes toolbar icon size 16 px / 24 px / 32 px, default 24).
- **Idle/Armed** — clipboard sniper on/off.
- **Kill** — stop *this app's* current engine child (see below).
- **Panel** — show/hide the output window (**Separados** float bar only; not duplicated on the Unidos tab strip).
- **Clear** — clear console and plot.
- **Unite/Split** — Separados ↔ Unidos (rightmost on the panel tab bar; switch glyph).

STATghost icon: menu *Help / About / OS global hotkeys / Quit* (click the icon). Drag the bar by the background or the name. Status shows engine badge and HK: on|off. Chrome glyphs are flat monochrome, tinted for the active theme.

3 Engines (R / Python / Julia)

Under **Set** → **Session** (Path | Options):

- **Use** — **R** | **Python** | **Julia**.
- **R**: home (empty = newest on this PC); Use {`Rterm.exe` | `R.dll`}. R.dll talks via sidecar `statghost_rhost.exe` (GUI never loads R.dll).
- **Python**: interpreter path (empty = discover); Options — show Matplotlib window; prefetch imports on session start.
- **Julia**: path (empty = discover / `juliaup`); Options — show GR window when relevant. Plot panel PNGs use the same high-res size class as R/Python (`Plots.jl savefig of current()`).
- **R Options**: show `rgl` window when relevant.

Status badge examples: R.dll · 4.5.0, Python · 3.12, Julia · 1.11, or idle.

4 Kill

- Ends only STATghost's current child — Rterm.exe, statghost_rhost.exe, Python, or Julia — not RStudio / other IDEs.
- Works mid-eval (hard terminate). Toolbar returns to green Idle; click **Arm** for a fresh session.
- Changing language / paths / R Use while running kills the old session first.

5 Clipboard and dedup

When **Armed**, eval runs only if clipboard *text* changes. Copying the same selection again does **not** re-run (feature, not a bug). To repeat: change one character, or use a dedicated Capture hotkey (if set).

Current line without selection

Under **Set** → **Hotkeys** → **Capture**, record an **alternative** global chord (optional). That hotkey asks the foreground app to **Copy**, then STATghost evaluates the clipboard. In many editors (VS Code, Notepad++, RStudio, CudaText, ...), Copy with **no selection** copies the **current line** — so you can step a script line by line without selecting. Behaviour depends on the source app; if Copy does nothing without a selection, select text as usual (or use **Ctrl+C** when Armed).

Operational notices go to the console meta stream; the status bar shows the engine badge and short tips. After each eval, Console scroll can sit the new chunk at **Middle** (default), Top, or Bottom (Set → Behavior).

6 Panel

- **Console** — read-only **ATSynEdit** with Cuda lexers from the lexer/ folder beside the EXE (R / Python / Julia); Ctrl+Tab / Shift+Ctrl+Tab switch Console ↔ Plot. The active tab highlight follows the page after eval focus (Auto / Console / Plot). Echo prompts: R >+/, Python >>>/..., Julia julia>/julia| (continuation is classroom-style). Under the Console: small tweaks only inside an echoed **input** chunk (prompt locked; not a free editor), then **Ctrl+Enter** to re-eval (Settings → Shortcuts; Capture stays **Ctrl+C** when Armed). **C+Up/C+Down** (hold letter C, not Ctrl) jump previous/next input cell.
- **Chrome (Separados | Unidos)** — **Unite/Split** button on the tab bar (rightmost). **Separados**: floating traffic bar + panel; lights only on the float (panel shows the mode toggle). **Form único / Unidos** (default): one window — strip on the tab bar (brand | Set | Arm | Kill | Clear); floating bar hidden while the panel is open. Horizontal toolbar magnet: shared left edge under the bar; vertical: tops aligned, rail to the left of the panel.
- After eval, focus is **Auto** by default: **Plot** if this eval drew graphics, else **Console** (Set → Behavior to force Console, Plot, or return to source).
- **Plot** — high-res PNG (R, Python Matplotlib, Julia Plots.jl); zoom, history ←/→, erase-history control after the N/M counter, optional PDF (R). Set → Plot panel → Display chooses **Lazarus TImage** (default) or **ATSynEdit Gaps** (same AT family as Console); switch anytime.
- **Size** (Plot panel) — match plot to pane width (default on); PNG DPI slider (soft green → dark blue, default 288) shared by TImage and AT Gaps.
- Bookmarks (if enabled): Ctrl+Shift+0..9 / Ctrl+0..9.

7 Explorer (R)

Object browser for the active R session (VP-EX-1). Requires `library/STATghostcom_R/STATghostcom` beside the EXE (shipped in the zip) or the installed companion under `AppData`.

- **Open / hide:** traffic-bar **Expl** light, Unidos chrome button, or **Ctrl+E** (configurable under Set → Hotkeys).
- **Dock:** **L** | **R** beside the main window (dock-left/dock-right glyphs), or **Float**. **Top/Normal** stay-on-top (default Top); **Auto/Fill** height; window size and Environment pane height are remembered.
- **Environment:** `search()` list with **.GlobalEnv** always first. Click a row to list Objects in that environment. **Hid/All** toggles hidden names (`all.names`).
- **Objects:** **Tree** (names + type icons) or **Grid** (Name / Type / Class / Dim). Filter by structural type (not S3/S4) and optional Perl-compatible name regex (empty box; hint on hover; Enter stores history). Refresh after eval or the Refresh button. **Clear** removes visible names from `.GlobalEnv` (confirm).
- **Companion:** R package `STATghostcom` under `library/STATghostcom_R/STATghostcom` — installed on first use into `%LOCALAPPDATA%/STATghost/library`; helpers live in exported `.sg` (no attach).

8 Settings

- **Appearance** — opacity; **Toolbar** orientation (Separados only — unmarked/disabled under Form único); **Layout** (**Separados** | **Form único**, default Form único; same as Unite/Split); **Icon size** (**16 px** / **24 px** / **32 px**, default 24); theme. Chrome uses flat monochrome glyphs tinted for the active theme (traffic bar, Unidos strip, Plot bar, Explorer).
- **Behavior** — after-eval focus (Auto / Console / Plot / source); Console scroll after eval (Middle / Top / Bottom); Console echo — optional echo of full-line # comments in input chunks (default off).
- **Session** — Path | Options per language (see Engines); **Ctrl+Tab** / **Shift+Ctrl+Tab** cycle R|Python|Julia pages (does not change Active Use radios).
- **Hotkeys** — OS global: Capture / Arm / Focus / Clear console (**Record** and Clear|Reset). Capture default stays **Ctrl+C** when Armed; optional alternative chord (Copy in the source app → eval; often the current line with no selection — see Clipboard). **Ctrl+L** clears Console text only (plot unchanged); toolbar Clear still wipes console + plot. **Alt+Space** is rejected (Windows system menu).
- **Shortcuts** — Console-local (not OS RegisterHotKey): **Ctrl+Enter** re-evals the input cell at the caret; **C+Up/C+Down** (hold letter C, not Ctrl) jump previous/next input cell (both configurable).
- **Editor** — font, highlighter, view options (Settings Syntax preview mirrors `ATSynEdit` Console chrome; live Console uses `ATSynEdit + lexer/`). Under Syntax → Console: chrome **Moldura (frame)** (default) or **Zebrado (zebra)**; optional frame colour, fill, and small corner chamfer. Moldura outlines echoed input only. **Ctrl+Tab** / **Shift+Ctrl+Tab** cycle Font|Syntax.
- **Plot panel** — Display (TImage | AT Gaps), history **←/→** + erase-history, PDF, Size (match pane + DPI).

9 Hotkeys

- **Ctrl+Alt+R** — Arm / Idle (default; Record under Set → Hotkeys).

- **Ctrl+C** — Capture via system clipboard (when Armed).
- Optional Capture alternative (Record under Set → Hotkeys) — Copy in the foreground app, then eval (current line without selection in many editors).
- **Ctrl+Alt+F** — Focus mode toggle (default).
- **Ctrl+L** — Clear Console text only (default; R console).
- **Ctrl+E** — show / hide Explorer (default).
- Brand menu **OS global hotkeys** — when off, Arm / alt-capture / focus / clear / Explorer chords are unregistered so other apps can use them; status shows HK: ON/HK: OFF. Ctrl+C sniper while Armed still works.

10 Shortcuts (Console)

Local to the Console panel (not OS RegisterHotKey). Set → Shortcuts.

- **Ctrl+Enter** — re-eval the input cell at the caret.
- **C+Up / C+Down** — previous / next input cell (hold letter C, not Ctrl — keeps Ctrl+arrows for scroll).

11 Config

Prefs JSON: %LOCALAPPDATA%\STATghost/statghost.json.

12 Automated checks (lab)

- **Smoke:** statghost.exe --smoke → statg5_report.txt (RESULT=BOK).
- **Arm on start:** statghost.exe --arm (Armed + session up — handy after a rebuild).
- **SR / SP / SJ / ST:** whole-file samples — --sr (R rterm+rdll), --sp (Python), --sj (Julia), --st / --tf-samples (all) → statg_sr|sp|sj|st_report.txt. Or: powershell -File src/tf_samples.ps1 [-Mode ST|SR|SP|SJ].
- **Dev smokes (SRD|SPD|SJD|STD):** random ~20% of scripts per lane (--srd...--std). Prefer these while iterating.
- **BENCH:** same OLS lesson in all four environments (Rterm.exe | R.dll | Python | Julia) — --bench → w_log/benchmark.txt; powershell -File benchmark/run_bench.ps1.

13 Troubleshooting

- No output — **Armed?** New clipboard text? Correct language under Session? Badge not idle?
- No plot — this chunk must draw (plot, Matplotlib, Plots.jl, ...).
- R.dll won't start — is statghost_rhost.exe next to the app? Is R.dll under R home? Or switch Use to Rterm.exe.
- Python / Julia not found — set path under Session → Path, or install and leave empty for discover.
- Stuck eval — press **Kill**, then Arm again.
- Hotkeys clash with another app — turn off **OS global hotkeys** (sniper Ctrl+C when Armed remains).
- Taskbar icon looks outdated after an update — unpin / repin statghost.exe (Windows caches MAINICON).

STATghost v0.4.11 — autonomous product experiment (Lazarus/FPC). Guide D12 / VP-STATG-7.