# Enabling Multirotors to Perform Construction Tasks Using Swarm Algorithms

Jens-Christian Finnerup



Kongens Lyngby 2016

Technical University of Denmark
Department of Applied Mathematics and Computer Science
Richard Petersens Plads, building 324,
2800 Kongens Lyngby, Denmark
Phone +45 4525 3031
compute@compute.dtu.dk
www.compute.dtu.dk

# Summary (English)

The goal of the thesis is to  $\dots$ 

# Summary (Danish)

Målet for denne afhandling er at  $\dots$ 

# **Preface**

This thesis was prepared at DTU Compute in fulfilment of the requirements for acquiring an M.Sc. in Engineering.

The thesis deals with ...

The thesis consists of ...

Lyngby, 01-August-2016

Not Real

Jens-Christian Finnerup

# Acknowledgements

I would like to thank my....

## **Contents**

$\mathbf{S}\mathbf{u}$	ımma	ary (English)	i
Su	ımma	ary (Danish)	iii
Pr	eface	2	$\mathbf{v}$
A	knov	wledgements	vii
1	Intr	roduction	1
	1.1	Problem Description	2
		1.1.1 Main Problem	2
		1.1.2 Sub Problems	3
	1.2	Project plan	3
2	Met	hodology	5
	2.1	Control Problem	5
	2.2	Simulation Construction	6
	2.3	Validation	6
	2.4	Test Metrics	7
	2.5	Experimentation	7
	2.6	Optimization	7
3	Sim	ulation	9
	3.1	Simulation vs. Animation	9
	3.2	Reality criterias	9
	3.3	Assumptions on Physics	9
	3.4	Control Problem	9
	3.5	Construction	9
	3.6	Validation	9

X	CONTEN	ITS
4	Swarm Logic & Swarm Algorithms 4.1 Multi-body vs. Multi-agent path planning	<b>11</b> 11
5	Design	13
Bi	ibliography	14

### CHAPTER 1

### Introduction

In today's world, we increasingly rely on robotics to perform a wide range of tasks, with use cases ranging from complimenting, or even substituting, human labour in factories to more complex tasks such as automated aerial photography. Though technology continues to improve, the use of robotics is often confined to within predictable environments, where machines are told what to do and when to do it. More recently though, as control algorithms improve, autonomous robots are starting to become a practical reality, with increasing ability self-plan and work unsupervised. As such we experience a paradigm shift, where robots are no longer limited to predictable and confined environments, but can act freely and adapt to changing circumstances.

As a consequence of this, new use cases and areas within robotics are starting to gain interest. Specifically the area of autonomous flying vehicles is gaining interest with companies such as amazon, preparing to use flying drones to deliver packages. This requires the drone to be able to plan according to changes in the environment as well as being able to coordinate its movements in relation to other drones around it. At a currently more theoretical scale, using flying drones to perform construction tasks has been subject for testing by universities such as  $ETH\ Zurich$ , where micro drones were used to construct a 6 meter tall tower [ALH+14].

The task of using flying vehicles to perform construction is especially interesting

2 Introduction

because it combines many of the challenges that face robotics today, as agents become more autonomous. A construction task work as a great test bed, for testing flying drones as it involves multiple agents working on the same problem as once and as such they must have the ability to plan according to changes in their individual environment.

One solution to the challenges of enabling drones to collaborate, is to create individual sectors of space in which only a single agent is allowed to move at a certain time. This is a simple way to prevent collisions between the drones, but it also poses some optimization challenges, as the path of the drones cannot intersect. This means that even if a path for a drone towards a goal is optimal (shortest), it cannot be used if it intersects with the path of another agent. Another drawback of this simple solution is that it limits the amount of agents able to act with in a certain space, to a small number, as reach has to have its own designated area. As such there is great motivation to design control algorithms, which can enable drones to collaborate on tasks, while allowing them to avoid collisions without limiting their flight space.

This thesis focuses on how create and use algorithms from the field of swarm robotics as control for flying drones. The different algorithms will be implemented on a simulation test bed, to compare their complexity and their ability to give optimal movements to the drones within the simulation. For the comparison, different metrics will be used measure effectiveness in allowing drones to solve a collaborative problem. As a basis for the comparison, this thesis will document the implementation of the simulation platform and the control algorithms.

#### 1.1 Problem Description

The following will outline the detailed goal of this thesis, as well as the subgoals necessary to achieve it.

#### 1.1.1 Main Problem

To create and use swarm algorithms to enable quadcopters to coordinate their movements in a multi-agent environment.

1.2 Project plan 3

#### 1.1.2 Sub Problems

• To design and implement a simulation platform, based on a physical model, within which the algorithms can be used to control simulated agents

- To design a problem for the agents to collaborate on, to use as a standardized test for performance of the algorithms
- To determine the correct metrics for optimizing and comparing the swarm algorithms
- To implement swarm algorithms based on existing concepts, and test them using the metrics and the simulation platform
- To optimize the control algorithms based on pre mentioned tests, and analyze potential areas of improvement

#### 1.2 Project plan

We note that the contents of the project plan is also something we would like to see in the introductory chapter of your thesis. In fact, you can reuse your final project plan (possibly extended) as the introduction. If you prefer to write an introduction from scratch, it is, of course, important that it is consistent with the final project plan.

4 Introduction

# Chapter 2

# Methodology

In order to evaluate the different control algorithms and their performance, the approach towards designing and testing the algorithms must be systematic and concise. The different subproblems specified in 1.1.2, can be said to either relate to either the simulation design or the algorithm design. As such, for the purpose of this thesis, a different approach will be used when dealing with constructing the simulation and when designing and testing the control algorithms. In this chapter, I will outline these approaches and the methodology used. The first three sections of this chapter will deal with the simulation methodology, whereas the latter three will deal with the implementation and testing of the control algorithms.

#### 2.1 Control Problem

The main research problem os this thesis involves building and evaluating different control algorithms, and as such each algorithm must be subject to the same evaluation technique. This evaluation technique will throughout the thesis be referenced to as the *Control Problem*, and the purpose of the agents will be so solve this problem collectively. As such the problem chosen must be the same problem throughout every simulation and independent of the control algorithms

6 Methodology

themselves. The problem must also be able to be solved collectively, by multiple agents at the same time, while still posing enough challenges to properly test the control algorithms. Posing dangers to the agents, such as the risk of collision.

This control problem will exist within the simulation as a physical task that the agents have to carry out. Chapter 3.4 will outline the concrete control problem used, as well a discussion on the specific control problem's advantages and limitations.

#### 2.2 Simulation Construction

The control problem and the simulation are mutually dependent, as the problem has to able to exist and be solvable within the simulation. As such the simulation has to be designed with the control problem in mind, but the control problem also has to be made with the limitations of the simulation taken into account. The simulation aspect is crucial to the validity of the results expressed in this thesis. For the purpose of solving the problems outlined in this thesis, the simulation will be a virtual environment, in which drones can be deployed. The drones will have to be subject to the same physical laws, as they would in real life such that the findings and test results can by applied to issues and control techniques in the real world.

In order to reduce complexity of the simulation, some physical laws are not taken into account when designing the simulation. This is done based on assumptions on which laws influence the results. An outline of the simulation design, can be found in Chapter 3.

#### 2.3 Validation

Validation is a method to ensure that the simulation is mimicking real life physics and not simply animating the desired behavior of the drones. The validation will be carried out iteratively along with the construction of the simulation, to monitor the progress of the simulation construction, and act as a sort of checklist to the accuracy and capabilities of the simulation. The validation phase consists of multiple validation tests, meant to test if the simulation actually simulates the physical mechanics required. These mechanics can range from gravitational pull to accurate impulse and mass on the bodies in the simulation. The validation tests will when range from checking the accurate acceleration of drones in free

2.4 Test Metrics 7

fall etc. These validation tests are also important because the simulator must have the predictable behavior across many scenarios, such that they can be compatible. The validation tests will be discussed and outlined in Section 3.6

#### 2.4 Test Metrics

Up until now this chapter on methodology has been focused on systematically creating and validating the simulation platform. The following part will be covering my approach to creating and testing the control algorithms.

The comparison of the algorithms tested within this thesis, will be done based on their ability to solve the Control Problem. However the control problem must be designed in such a way, that it can be solved in to various degrees. To measure how well the control problem is solved, some metrics must be chosen so that they represent the challenges of the control problem. I.e. if the control problem challenges the agents in collision avoidance, a test metric could be the each agents distance the all other agents over time. The metrics chosen will be covered in Chapter 3 and will in part be based challenges of swarm robotics covered in Multi-robot navigation in formation via sequential convex programming [AMBR15].

#### 2.5 Experimentation

#### 2.6 Optimization

8 Methodology




Figure 2.1: Acceleration of agent - without velocity limit

# Chapter 3

# Simulation

- 3.1 Simulation vs. Animation
- 3.2 Reality criterias
- 3.3 Assumptions on Physics
- 3.4 Control Problem
- 3.5 Construction
- 3.6 Validation

10 Simulation

## Chapter 4

# Swarm Logic & Swarm Algorithms

4.1 Multi-body vs. Multi-agent path planning

# Chapter 5

# Design

14 Design

## **Bibliography**

- [ALH+14] F. Augugliaro, S. Lupashin, M. Hamer, C. Male, M. Hehn, M. W. Mueller, J. S. Willmann, F. Gramazio, M. Kohler, and R. D'Andrea. The Flight Assembled Architecture installation: Cooperative construction with flying machines. *IEEE Control Systems*, 34(4):46–64, August 2014.
- [AMBR15] J. Alonso-Mora, S. Baker, and D. Rus. Multi-robot navigation in formation via sequential convex programming. In 2015 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS), pages 4634–4641, September 2015.
- [BRG<sup>+</sup>11] Preetha Bhattacharjee, Pratyusha Rakshit, Indrani Goswami, Amit Konar, and Atulya K. Nagar. Multi-robot path-planning using artificial bee colony optimization algorithm. In Nature and Biologically Inspired Computing (NaBIC), 2011 Third World Congress on, pages 219–224. IEEE, 2011.
- [CPD<sup>+</sup>14] Ruaridh Clark, Giuliano Punzo, Gordon Dobie, Rahul Summan, Charles Norman MacLeod, Gareth Pierce, and Malcolm Macdonald. Autonomous swarm testbed with multiple quadcopters. In 1st World Congress on Unmanned Systems Engineering, 2014-WCUSEng, 2014.
- [DHB15] Shreyansh Daftry, Christof Hoppe, and Horst Bischof. Building with drones: Accurate 3d facade reconstruction using mavs. In Robotics and Automation (ICRA), 2015 IEEE International Conference on, pages 3487–3494. IEEE, 2015.

16 BIBLIOGRAPHY

[HM99] Owen Holland and Chris Melhuish. Stigmergy, self-organization, and sorting in collective robotics. *Artificial life*, 5(2):173–202, 1999.

- [LGB<sup>+</sup>] Pierre LATTEUR, Sébastien GOESSENS, Jean-Sébastien BRE-TON, Justin LEPLAT, Zhao MAb, and Caitlin MUELLER. Drone-Based Additive Manufacturing of Architectural Structures.
- [PKG<sup>+</sup>02] Giovanni Cosimo Pettinaro, I. Kwee, Luca Maria Gambardella, Francesco Mondada, Dario Floreano, Stefano Nolfi, J.-L. Deneubourg, and Marco Dorigo. Swarm robotics: A different approach to service robotics. In 33rd International Symposium on Robotics, pages 71–76, 2002.
- [SMVDPB05] John A. Sauter, Robert Matthews, H. Van Dyke Parunak, and Sven A. Brueckner. Performance of digital pheromones for swarming vehicle control. In *Proceedings of the fourth international joint conference on Autonomous agents and multiagent systems*, pages 903–910. ACM, 2005.