

# Содержание

<b>1 Setup &amp; Scripts</b>	<b>8 Number theory</b>	<b>12</b>
1.1 CMake . . . . .	8.1 Chinese remainder theorem without overflows . . . . .	12
1.2 wipe.sh . . . . .	8.2 Integer points under a rational line . . . . .	12
1.3 Stack size & Profiling . . . . .	<b>9 Nimbers</b>	<b>13</b>
<b>2 Language specific</b>	<b>10 Flows, etc.</b>	<b>14</b>
2.1 C++ . . . . .	10.1 Hungarian Algorithm . . . . .	14
2.1.1 G++ builtins . . . . .	<b>11 Something added at the last moment</b>	<b>15</b>
2.1.2 Custom Hash . . . . .	11.1 Dominator Tree . . . . .	15
2.1.3 Allocator . . . . .	11.2 Fast LCS . . . . .	16
2.2 Python . . . . .	11.3 Fast Subset Convolution . . . . .	17
<b>3 Geometry</b>	<b>12 Karatsuba</b>	<b>18</b>
3.1 Пересечение прямых . . . . .	<b>13 Hard Algorithms</b>	<b>19</b>
3.2 Касательные . . . . .	13.1 Two Strong Chinese . . . . .	19
3.3 Пересечение полуплоскостей . . . . .	13.2 Simplex . . . . .	23
<b>4 Numbers</b>	<b>14 OEIS</b>	<b>26</b>
<b>5 Graphs</b>	14.1 Числа Белла . . . . .	26
5.1 Weighted matroid intersection . . . . .	14.2 Числа Каталана . . . . .	26
<b>6 Data structures</b>	<b>1 Setup &amp; Scripts</b>	
6.1 Push-free segment tree . . . . .	<b>1.1 CMake</b>	
6.2 Template DSU . . . . .	1 cmake_minimum_required(VERSION 3.14)	
6.3 Link-Cut Tree . . . . .	2 project(olymp)	
<b>7 Strings</b>	3	
7.1 Suffix Automaton . . . . .	4 set(CMAKE_CXX_STANDARD 17)	
7.2 Palindromic Tree . . . . .	5 add_compile_definitions(LOCAL)	

```

6 #set(CMAKE_CXX_FLAGS "${CMAKE_CXX_FLAGS}
  ↪ -fsanitize=undefined -fno-sanitize-recover")
7 #sanitizers: address, leak, thread, undefined, memory
8
9 add_executable(olymp f.cpp)

```

## 1.2 wipe.sh

```

1 touch {a..l}.cpp
2
3 for file in *.cpp ; do
4     cat template.cpp > $file ;
5 done

```

## 1.3 Stack size & Profiling

```

1 # Print stack limit in Kb
2 ulimit -s
3
4 # Set stack limit in Kb, session-local, so resets after
  ↪ terminal restart
5 ulimit -S -s 131072
6
7 # Profile time
8 time ./olymp
9
10 # Profile time, memory, etc.
11 # Make sure to use the full path
12 /usr/bin/time -v ./olymp

```

## 2 Language specific

### 2.1 C++

#### 2.1.1 G++ builtins

- `__builtin_popcount(x)` — количество единичных бит в двоичном представлении 32-битного (знакового или беззнакового) целого числа.
- `__builtin_popcountll(x)` — то же самое для 64-битных типов.
- `__builtin_ctz(x)` — количество нулей на конце двоичного представления 32-битного целого числа. Например, для 5 вернётся 0, для  $272 = 256 + 16$  — 4 и т. д. Может не работать для нуля (вообще не стоит вызывать для  $x = 0$ , по-моему это и упасть может).
- `__builtin_ctzll(x)` — то же самое для 64-битных типов.
- `__builtin_clz(x)` — количество нулей в начале двоичного представления 32-битного целого числа. Например, для  $2^{31}$  или  $-2^{31}$  вернётся 0, для 1 — 31 и т. д. Тоже не надо вызывать с  $x = 0$ .
- `__builtin_clzll(x)` — то же самое для 64-битных типов.
- `bitset<N>._Find_first()` — номер первой позиции с единицей в битсете или его размер (то есть  $N$ ), если на всех позициях нули.
- `bitset<N>._Find_next(x)` — номер первой позиции с единицей среди позиций с номерами строго больше  $x$ ; если такой нет, то  $N$ .

### 2.1.2 Custom Hash

```

1 namespace std {
2   template <
3     struct hash<pnt> {
4       std::size_t operator()(pnt const &s) const noexcept {
5         return std::hash<ll>{}(s.first * ll(1ull << 32u) +
6                               s.second);
7       }
8     };
9 } // namespace std

```

### 2.1.3 Allocator

```

1 template <size_t sz>
2 class chunk_alloc {
3 public:
4   static constexpr auto chunk_size = sz;
5
6 private:
7   using chunk_t = array<byte, chunk_size>;
8
9   deque<chunk_t> mem;
10  stack<void*> emp;
11
12 public:
13   void* allocate() {
14     if (emp.empty())
15       emp.push(
16         reinterpret_cast<void*>(&mem.emplace_back()));
17
18     auto ans = emp.top();
19     emp.pop();
20

```

```

21     return ans;
22   }
23
24   void deallocate(void* p) noexcept { emp.push(p); }
25 };
26
27 chunk_alloc<64> pool;
28
29 template <class T>
30 struct dummy_alloc {
31   using value_type = T;
32
33   dummy_alloc() noexcept = default;
34
35   template <class U>
36   explicit dummy_alloc(const dummy_alloc<U> &) noexcept {}
37
38   T* allocate(std::size_t n) {
39     if constexpr (sizeof(value_type) ==
40                   decltype(pool)::chunk_size)
41       return static_cast<T*>(pool.allocate());
42     else
43       return static_cast<T*>(
44         ::operator new(n * sizeof(value_type)));
45   }
46
47   void deallocate(T* p, std::size_t n) {
48     if constexpr (sizeof(value_type) ==
49                   decltype(pool)::chunk_size)
50       return pool.deallocate(p);
51     else
52       ::delete (p);
53   }

```

```

54 };
55
56 template <class T, class U>
57 constexpr bool operator==(const dummy_alloc<T> &,
58                           const dummy_alloc<U> &) noexcept
59     → {
60     return true;
61 }
62
63 template <class T, class U>
64 constexpr bool operator!=(const dummy_alloc<T> &,
65                           const dummy_alloc<U> &) noexcept
66     → {
67     return false;
68 }

```

## 2.2 Python

```

1 # stack size
2 import sys
3
4 sys.setrecursionlimit(10**6)
5
6 # memoize
7 import functools
8
9 @functools.lru_cache(maxsize=None)

```

## 3 Geometry

### 3.1 Пересечение прямых

$$AB := A - B; CD := C - D$$

$$(A \times B \cdot CD.x - C \times D \cdot AB.x : A \times B \cdot CD.y - C \times D \cdot AB.y : AB \times CD)$$

### 3.2 Касательные

Точки пересечения общих касательных окружностей с центрами в  $(0, 0)$  и  $(x, 0)$  равны  $\frac{xr_1}{r_1 \pm r_2}$ .  $x$  координата точек касания из  $(x, 0)$  равна  $\frac{r^2}{x}$ .

### 3.3 Пересечение полуплоскостей

Точно так же, как в выпуклой оболочке, но надо добавить bounding box (квадратичного размера относительно координат на входе) и завернуть два раза. Ответ можно найти как подотрезок от первой полуплоскости типа true до нее же самой на втором круге. Проверку на вырожденность лучше делать простой проверкой пары-тройки точек из предполагаемого ответа. Стоит быть аккуратнее с точностью.

## 4 Numbers

A lot of divisors

- $\leq 20 : d(12) = 6$
- $\leq 50 : d(48) = 10$
- $\leq 100 : d(60) = 12$
- $\leq 10^3 : d(840) = 32$
- $\leq 10^4 : d(9240) = 64$
- $\leq 10^5 : d(83160) = 128$
- $\leq 10^6 : d(720720) = 240$

- $\leq 10^7 : d(8648640) = 448$
- $\leq 10^8 : d(91891800) = 768$
- $\leq 10^9 : d(931170240) = 1344$
- $\leq 10^{11} : d(97772875200) = 4032$
- $\leq 10^{12} : d(963761198400) = 6720$
- $\leq 10^{15} : d(866421317361600) = 26880$
- $\leq 10^{18} : d(897612484786617600) = 103680$

Numeric integration

- simple:  $F(0)$
- simpson:  $\frac{F(-1)+4 \cdot F(0)+F(1)}{6}$
- runge2:  $\frac{F(-\sqrt{\frac{1}{3}})+F(\sqrt{\frac{1}{3}})}{2}$
- runge3:  $\frac{F(-\sqrt{\frac{3}{5}}) \cdot 5 + F(0) \cdot 8 + F(\sqrt{\frac{3}{5}}) \cdot 5}{18}$

## 5 Graphs

### 5.1 Weighted matroid intersection

```

1 // here we use T = __int128 to store the independent set
2 // calling expand k times to an empty set finds the maximum
3 // cost of the set with size exactly k,
4 // that is independent in blue and red matroids
5 // ver is the number of the elements in the matroid,
6 // e[i].w is the cost of the i-th element
7 // first return value is new independent set

```

```

8 // second return value is difference between
9 // new and old costs
10 // oracle(set, red) and oracle(set, blue) check whether
11 // or not the set lies in red or blue matroid respectively
12 auto expand = [&](T in) → T {
13     vector<int> ids;
14     for (int i = 0; i < int(es.size()); i++)
15         if (in[i]) ids.push_back(i);
16
17     vector<int> from, to;
18     /// Given a set that is independent in both matroids,
19     /// answers queries "If we add i-th element to the set,
20     /// will it still be independent in red/blue matroid?".
21     /// Usually can be done quickly.
22     can_extend full_can(ids, n, es);
23
24     for (int i = 0; i < int(es.size()); i++)
25         if (!in[i]) {
26             auto new_ids = ids;
27             new_ids.push_back(i);
28
29             auto is_red = full_can.extend_red(i, es);
30             auto is_blue = full_can.extend_blue(i, es);
31
32             if (is_blue) from.push_back(i);
33             if (is_red) to.push_back(i);
34
35             if (is_red && is_blue) {
36                 T swp_mask = in;
37                 swp_mask.flip(i);
38                 return swp_mask;
39             }
40         }

```

```

41
42     vector<vector<int>> g(es.size());
43     for (int j = 0; j < int(es.size()); j++)
44         if (in[j]) {
45             auto new_ids = ids;
46             auto p = find(new_ids.begin(), new_ids.end(), j);
47             assert(p != new_ids.end());
48             new_ids.erase(p);
49
50             can_extend cur(new_ids, n, es);
51
52             for (int i = 0; i < int(es.size()); i++)
53                 if (!in[i]) {
54                     if (cur.extend_red(i, es)) g[i].push_back(j);
55                     if (cur.extend_blue(i, es)) g[j].push_back(i);
56                 }
57         }
58
59     auto get_cost = [&](int x) {
60         const int cost = (!in[x] ? e[x].w : -e[x].w);
61         return (ver + 1) * cost - 1;
62     };
63
64     const int inf = int(1e9);
65     vector<int> dist(ver, -inf), prev(ver, -1);
66     for (int x : from) dist[x] = get_cost(x);
67
68     queue<int> q;
69
70     vector<int> used(ver);
71     for (int x : from) {
72         q.push(x);
73         used[x] = 1;

```

```

74     }
75
76     while (!q.empty()) {
77         int cur = q.front();
78         used[cur] = 0;
79         q.pop();
80
81         for (int to : g[cur]) {
82             int cost = get_cost(to);
83             if (dist[to] < dist[cur] + cost) {
84                 dist[to] = dist[cur] + cost;
85                 prev[to] = cur;
86                 if (!used[to]) {
87                     used[to] = 1;
88                     q.push(to);
89                 }
90             }
91         }
92     }
93
94     int best = -inf, where = -1;
95     for (int x : to) {
96         if (dist[x] > best) {
97             best = dist[x];
98             where = x;
99         }
100     }
101
102     if (best == -inf) return pair<T, int>(cur_set, best);
103
104     while (where != -1) {
105         cur_set ^= (T(1) << where);
106         where = prev[where];

```

```

107     }
108
109     while (best % (ver + 1)) best++;
110     best /= (ver + 1);
111
112     assert(oracle(cur_set, red) && oracle(cur_set, blue));
113     return pair<T, int>(cur_set, best);
114 };

```

## 6 Data structures

### 6.1 Push-free segment tree

```

1  template <class Val, class Change, Change one = Change{}>
2  class pushfreesegetree {
3      vector<pair<Val, Change>> arr;
4
5      void upd(size_t v) {
6          arr[v].first =
7              (arr[2 * v].first + arr[2 * v + 1].first) *
8              arr[v].second;
9      }
10
11  public:
12      explicit pushfreesegetree(size_t n = 0)
13          : arr(2 * n + 2, {Val{}, one}) {}
14
15      template <class It>
16      explicit pushfreesegetree(It be, It en)
17          : arr(2 * distance(be, en) + 2, {Val{}, one}) {
18          transform(be, en, arr.begin() + ssize(arr) / 2,
19                  [](auto x) {
20                      return pair{Val{x}, one};

```

```

21          });
22
23      for (int i = ssize(arr) / 2 - 1; i > 0; i--) upd(i);
24  }
25
26  auto segmult(const Change &x, size_t l, size_t r) {
27      l += arr.size() / 2;
28      r += arr.size() / 2;
29
30      while (true) {
31          if (l < r) {
32              if (l & 1u) {
33                  arr[l].first *= x;
34                  arr[l].second *= x;
35              }
36              if (r & 1u) {
37                  arr[r - 1].first *= x;
38                  arr[r - 1].second *= x;
39              }
40          }
41
42          l = (l + 1) / 2;
43          r /= 2;
44
45          if (r == 0) break;
46
47          upd(l - 1);
48          upd(r);
49      }
50  }
51
52  [[nodiscard]] Val segsum(size_t l, size_t r) const {
53      l += arr.size() / 2;

```

```

54     r += arr.size() / 2;
55
56     Val ansl{}, ansr{};
57
58     while (true) {
59         if (l < r) {
60             if (l & 1u) ansl = ansl + arr[l].first;
61             if (r & 1u) ansr = arr[r - 1].first + ansr;
62         }
63
64         l = (l + 1) / 2;
65         r /= 2;
66
67         if (r == 0) break;
68
69         ansl *= arr[l - 1].second;
70         ansr *= arr[r].second;
71     }
72
73     return ansl + ansr;
74 }
75 };

```

## 6.2 Template DSU

```

1  template <class ... Types>
2  class dsu {
3      vector<int> par, siz;
4      tuple<Types ... > items;
5
6      template <size_t ... t>
7      void merge(int a, int b, std::index_sequence<t ... >) {
8          ((get<t>(items)(a, b)), ...);

```

```

9  }
10
11  public:
12      explicit dsu(int n, Types ... args)
13          : par(n, -1), siz(n, 1), items(args ...) {}
14
15      int get_class(int v) {
16          return par[v] == -1 ? v : par[v] = get_class(par[v]);
17      }
18
19      bool unite(int a, int b) {
20          a = get_class(a);
21          b = get_class(b);
22
23          if (a == b) return false;
24
25          if (siz[a] < siz[b]) swap(a, b);
26          siz[a] += siz[b];
27          par[b] = a;
28
29          merge(a, b, make_index_sequence<sizeof ... (Types)>{});
30
31          return true;
32      }
33 };

```

## 6.3 Link-Cut Tree

```

1  class lct {
2      struct node {
3          using nodeptr = node *;
4
5          array<nodeptr, 2> ch{};

```



```
6     nodeptr par = nullptr;
7     size_t siz = 1;
8     bool rev = false;
9 };
10
11 using nodeptr = node::nodeptr;
12
13 static void reverse(const nodeptr &h) {
14     if (h != nullptr) h->rev = !h->rev;
15 }
16
17 static void push(node &h) {
18     if (h.rev) {
19         swap(h.ch.front(), h.ch.back());
20         h.rev = false;
21
22         for (auto it : h.ch) reverse(it);
23     }
24 }
25
26 static auto size(const nodeptr &h) {
27     return h == nullptr ? 0 : h->siz;
28 }
29
30 static void upd(node &h) {
31     h.siz = 1;
32
33     for (auto it : h.ch) {
34         h.siz += size(it);
35
36         if (it != nullptr) it->par = &h;
37     }
38 }
```

```
39
40 static bool is_root(const node &h) {
41     return h.par == nullptr ||
42         find(h.par->ch.begin(), h.par->ch.end(), &h) ==
43             h.par->ch.end();
44 }
45
46 static bool is_right(const node &h) {
47     assert(!is_root(h));
48     push(*h.par);
49     return get<1>(h.par->ch) == &h;
50 }
51
52 static void zig(node &h) {
53     assert(!is_root(h));
54
55     auto &p = *h.par;
56     push(p);
57     push(h);
58     auto pp = p.par;
59     bool ind = is_right(h);
60     auto &x = p.ch[ind];
61     auto &b = h.ch[!ind];
62
63     x = b;
64     b = &p;
65     h.par = pp;
66
67     upd(p);
68     upd(h);
69
70     if (pp != nullptr)
71         for (auto &it : pp->ch)
```

```

72     if (it == &p) it = &h;
73 }
74
75 static void splay(node &h) {
76     push(h);
77     while (!is_root(h)) {
78         auto &p = *h.par;
79
80         if (is_root(p)) {
81             zig(h);
82         } else if (is_right(h) == is_right(p)) {
83             zig(p);
84             zig(h);
85         } else {
86             zig(h);
87             zig(h);
88         }
89     }
90 }
91
92 static void expose(node &h) {
93     splay(h);
94
95     while (h.par != nullptr) {
96         auto &p = *h.par;
97         splay(p);
98         get<1>(p.ch) = &h;
99         upd(p);
100        splay(h);
101    }
102 }
103 };

```

## 7 Strings

### 7.1 Suffix Automaton

```

1  class tomato {
2      struct node {
3          array<int, 26> nxt{};
4          int link = -1, len = 0;
5
6          explicit node(int len = 0) : len(len) {
7              ranges::fill(nxt, -1);
8          }
9
10         explicit node(int len, node p)
11             : nxt(p.nxt), len(len), link(p.link) {}
12     };
13
14     vector<node> mem = {node(0)};
15     int last = 0;
16
17 public:
18     explicit tomato(string_view sv = "") {
19         for (auto it : sv) (*this) += it;
20     }
21
22     tomato &operator+=(char ch) {
23         const int ind = ch - 'a';
24         auto new_last = int(mem.size());
25         mem.emplace_back(mem[last].len + 1);
26
27         auto p = last;
28         while (p ≥ 0 && mem[p].nxt[ind] == -1) {
29             mem[p].nxt[ind] = new_last;

```

```

30     p = mem[p].link;
31 }
32
33 if (p ≠ -1) {
34     const int q = mem[p].nxt[ind];
35     if (mem[p].len + 1 == mem[q].len) {
36         mem[new_last].link = q;
37     } else {
38         auto clone = int(mem.size());
39         mem.emplace_back(mem[p].len + 1, mem[q]);
40         mem[q].link = clone;
41         mem[new_last].link = clone;
42
43         while (p ≥ 0 && mem[p].nxt[ind] == q) {
44             mem[p].nxt[ind] = clone;
45             p = mem[p].link;
46         }
47     }
48 } else
49     mem[new_last].link = 0;
50
51 last = new_last;
52
53 return *this;
54 }
55 };

```

## 7.2 Palindromic Tree

```

1 class treert {
2     struct node {
3         array<int, 26> nxt;
4         int par, link, siz;

```

```

5
6     node(int siz, int par, int link)
7         : par(par),
8           link(link == -1 ? 1 : link),
9           siz(siz) // note -1 case
10    {
11        fill(nxt.begin(), nxt.end(), -1);
12    }
13 };
14
15 vector<node> mem;
16 vector<int> suff; // longest palindromic suffix
17
18 public:
19 treert(const string &str) : suff(str.size()) {
20     mem.emplace_back(-1, -1, 0);
21     mem.emplace_back(0, 0, 0);
22     mem[0].link = mem[1].link = 0;
23
24     auto link_walk = [&](int st, int pos) {
25         while (pos - 1 - mem[st].siz < 0 ||
26               str[pos] ≠ str[pos - 1 - mem[st].siz])
27             st = mem[st].link;
28
29         return st;
30     };
31
32     for (int i = 0, last = 1; i < str.size(); i++) {
33         last = link_walk(last, i);
34         auto ind = str[i] - 'a';
35
36         if (mem[last].nxt[ind] == -1) {
37             // order is important

```

```

38     mem.emplace_back(
39         mem[last].siz + 2, last,
40         mem[link_walk(mem[last].link, i)].nxt[ind]);
41     mem[last].nxt[ind] = (int)mem.size() - 1;
42 }
43
44     last = mem[last].nxt[ind];
45
46     suff[i] = last;
47 }
48 }
49 };

```

## 8 Number theory

### 8.1 Chinese remainder theorem without overflows

```

1 // Replace T with an appropriate type!
2 using T = long long;
3
4 // Finds x, y such that ax + by = gcd(a, b).
5 T gcdext(T a, T b, T &x, T &y) {
6     if (b == 0) {
7         x = 1, y = 0;
8         return a;
9     }
10
11     T res = gcdext(b, a % b, y, x);
12     y -= x * (a / b);
13     return res;
14 }
15

```

```

16 // Returns true if system  $x = r_1 \pmod{m_1}, x = r_2 \pmod{m_2}$ 
17 // has solutions false otherwise. In first case we know
18 // exactly that  $x = r \pmod{m}$ 
19
20 bool crt(T r1, T m1, T r2, T m2, T &r, T &m) {
21     if (m2 > m1) {
22         swap(r1, r2);
23         swap(m1, m2);
24     }
25
26     T g = __gcd(m1, m2);
27     if ((r2 - r1) % g != 0) return false;
28
29     T c1, c2;
30     auto nrem = gcdext(m1 / g, m2 / g, c1, c2);
31     assert(nrem == 1);
32     assert(c1 * (m1 / g) + c2 * (m2 / g) == 1);
33     T a = c1;
34     a *= (r2 - r1) / g;
35     a %= (m2 / g);
36     m = m1 / g * m2;
37     r = a * m1 + r1;
38     r = r % m;
39     if (r < 0) r += m;
40
41     assert(r % m1 == r1 && r % m2 == r2);
42     return true;
43 }

```

### 8.2 Integer points under a rational line

```

1 // integer  $(x, y) : 0 \leq x < n, 0 < y \leq (kx + b)/d$ 
2 // (real division)

```

```

3 // In other words,  $\sum_{x=0}^{n-1} \lfloor (kx + b)/d \rfloor$ 
4 ll trapezoid(ll n, ll k, ll b, ll d) {
5     if (k == 0) return (b / d) * n;
6     if (k ≥ d || b ≥ d)
7         return (k / d) * n * (n - 1) / 2 + (b / d) * n +
8         trapezoid(n, k % d, b % d, d);
9     return trapezoid((k * n + b) / d, d, (k * n + b) % d, k);
10 }

```

## 9 Nimbers

```

1 template <class T, int lvl>
2 pair<T, T> split(T x) {
3     return {x >> lvl, x & ((T{1} << lvl) - 1)};
4 }
5
6 template <class T, int lvl>
7 T combine(T a, T b) {
8     return (a << lvl) | b;
9 }
10
11 template <class T, int lvl = 8 * sizeof(T)>
12 T nim_hmul(T x) {
13     constexpr int half = lvl / 2;
14     if constexpr (lvl == 1) return x;
15
16     auto [a, b] = split<T, half>(x);
17
18     return combine<T, half>(
19         nim_hmul<T, half>(a ^ b),
20         nim_hmul<T, half>(nim_hmul<T, half>(a)));
21 }
22

```

```

23 template <class T, int lvl = 8 * sizeof(T)>
24 T nim_mul(T x, T y) {
25     constexpr int half = lvl / 2;
26     if constexpr (lvl == 1) return x & y;
27
28     auto [a, b] = split<T, half>(x);
29     auto [c, d] = split<T, half>(y);
30
31     auto ac = nim_mul<T, half>(a, c);
32     auto bd = nim_mul<T, half>(b, d);
33     auto hp = nim_mul<T, half>(a ^ b, c ^ d) ^ bd;
34
35     return combine<T, half>(hp, bd ^ nim_hmul<T, half>(ac));
36 }
37
38 template <class T, int lvl = 8 * sizeof(T)>
39 T nim_sqr(T x) {
40     return nim_mul<T, lvl>(x, x);
41 }
42
43 template <class T, int lvl = 8 * sizeof(T)>
44 T nim_sqrt(T x) {
45     constexpr int half = lvl / 2;
46     if constexpr (lvl == 1) return x;
47
48     auto [a, b] = split<T, half>(x);
49
50     return combine<T, half>(
51         nim_sqrt<T, half>(a),
52         nim_sqrt<T, half>(nim_hmul<T, half>(a ^ b)));
53 }
54
55 template <class T, int lvl = 8 * sizeof(T)>

```

```

56 T nim_recip(T x) {
57     constexpr int half = lvl / 2;
58     if constexpr (lvl == 1) return x;
59
60     auto [a, b] = split<T, half>(x);
61
62     auto ad = nim_mul<T, half>(a ^ b, b);
63     auto bc = nim_hmul<T, half>(nim_sqr<T, half>(a));
64     auto det_recip = nim_recip<T, half>(ad ^ bc);
65
66     return combine<T, half>(nim_mul(a, det_recip),
67                             nim_mul(a ^ b, det_recip));
68 }

```

## 10 Flows, etc.

### 10.1 Hungarian Algorithm

```

1 ld Hungarian(const vector<vector<ld>> &matr) {
2     vector<int> lb(matr.size(), -1), rb(matr[0].size(), -1);
3     vector<ld> rows(matr.size()), cols(rb.size());
4
5     for (int v = 0; v < ssize(matr); v++) {
6         vector<bool> lused(lb.size()), rused(rb.size());
7         vector<int> par(rb.size(), -1);
8         vector<pair<ld, int>> w(
9             rb.size(), {numeric_limits<ld>::max(), -1});
10
11         auto add_row = [&](int i) {
12             lused[i] = true;
13
14             for (int j = 0; j < ssize(w); j++)
15                 remin(w[j], {matr[i][j] + rows[i] + cols[j], i});

```

```

16     };
17
18     add_row(v);
19
20     while (true) {
21         int j = -1;
22
23         for (int k = 0; k < ssize(rb); k++)
24             if (!rused[k] && (j == -1 || w[k] < w[j])) j = k;
25
26         auto [x, i] = w[j];
27
28         for (int k = 0; k < ssize(lused); k++)
29             if (!lused[k]) rows[k] += x;
30         for (int k = 0; k < ssize(rused); k++)
31             if (!rused[k]) {
32                 cols[k] -= x;
33                 w[k].first -= x;
34             }
35
36         par[j] = i;
37         rused[j] = true;
38
39         if (rb[j] == -1) {
40             while (j != -1) {
41                 rb[j] = par[j];
42                 auto nxt = lb[par[j]];
43                 lb[par[j]] = j;
44                 j = nxt;
45             }
46
47             break;
48         }

```

```

49
50     add_row(rb[j]);
51 }
52 }
53
54 ld ans = 0;
55
56 for (int i = 0; i < ssize(lb); i++)
57     if (auto j = lb[i]; j != -1) ans += matr[i][j];
58
59 return ans;
60 }

```

## 11 Something added at the last moment

### 11.1 Dominator Tree

```

1 struct dom_tree {
2     vvi g, rg, tree, bucket;
3     vi sdom, par, dom, dsu, label, in, order, tin, tout;
4     int T = 0, root = 0, n = 0;
5
6     void dfs_tm(int x) {
7         in[x] = T;
8         order[T] = x;
9         label[T] = T, sdom[T] = T, dsu[T] = T, dom[T] = T;
10        T++;
11        for (int to : g[x]) {
12            if (in[to] == -1) {
13                dfs_tm(to);
14                par[in[to]] = in[x];
15            }
16            rg[in[to]].pb(in[x]);

```

```

17     }
18 }
19
20 void dfs_tree(int v, int p) {
21     tin[v] = T++;
22     for (int dest : tree[v]) {
23         if (dest != p) {
24             dfs_tree(dest, v);
25         }
26     }
27     tout[v] = T;
28 }
29
30 dom_tree(const vvi &g_, int root_) {
31     g = g_;
32     n = sz(g);
33     assert(0 ≤ root && root < n);
34     in.assign(n, -1);
35     rg.resize(n);
36     order = sdom = par = dom = dsu = label = vi(n);
37     root = root_;
38     bucket.resize(n);
39     tree.resize(n);
40
41     dfs_tm(root);
42
43     for (int i = n - 1; i ≥ 0; i--) {
44         for (int j : rg[i])
45             sdom[i] = min(sdom[i], sdom[find(j)]);
46         if (i > 0) bucket[sdom[i]].pb(i);
47
48         for (int w : bucket[i]) {
49             int v = find(w);

```

```

50     dom[w] = (sdom[v] == sdom[w] ? sdom[w] : v);
51 }
52
53     if (i > 0) unite(par[i], i);
54 }
55
56     for (int i = 1; i < n; i++) {
57         if (dom[i] != sdom[i]) dom[i] = dom[dom[i]];
58         tree[order[i]].pb(order[dom[i]]);
59         tree[order[dom[i]]].pb(order[i]);
60     }
61
62     T = 0;
63     tin = tout = vi(n);
64     dfs_tree(root, -1);
65 }
66
67     void unite(int u, int v) { dsu[v] = u; }
68
69     int find(int u, int x = 0) {
70         if (u == dsu[u]) return (x ? -1 : u);
71         int v = find(dsu[u], x + 1);
72         if (v == -1) return u;
73         if (sdom[label[dsu[u]]] < sdom[label[u]])
74             label[u] = label[dsu[u]];
75         dsu[u] = v;
76         return (x ? v : label[u]);
77     }
78
79     bool dominated_by(int v, int by_what) {
80         return tin[by_what] ≤ tin[v] &&
81             tout[v] ≤ tout[by_what];
82     }

```

```
83 };
```

## 11.2 Fast LCS

```

1 // assumes that strings consist of lowercase latin letters
2 const int M = ((int)1e5 + 64) / 32 * 32;
3 // maximum value of m
4 using bs = bitset<M>;
5 using uint = unsigned int;
6 const ll bnd = (1LL << 32);
7
8 // WARNING: invokes undefined behaviour of modifying ans
9 // through pointer to another data type (uint) seems to
10 // work, but be wary
11 bs sum(const bs &bl, const bs &br) {
12     const int steps = M / 32;
13     const uint *l = (uint *)&bl;
14     const uint *r = (uint *)&br;
15
16     bs ans;
17     uint *res = (uint *)&ans;
18
19     int carry = 0;
20     for (i, steps) {
21         ll cur = ll(*l++) + ll(*r++) + carry;
22         carry = (cur ≥ bnd);
23         cur = (cur ≥ bnd ? cur - bnd : cur);
24         *res++ = uint(cur);
25     }
26
27     return ans;
28 }
29

```



```

30 int fast_lcs(const string &s, const string &t) {
31     const int m = sz(t);
32     const int let = 26;
33
34     vector<bs> has(let);
35     vector<bs> rev = has;
36
37     forn(i, m) {
38         const int pos = t[i] - 'a';
39         has[pos].set(i);
40         forn(j, let) if (j ≠ pos) rev[j].set(i);
41     }
42
43     bs row;
44     forn(i, m) row.set(i);
45
46     int cnt = 0;
47     for (char ch : s) {
48         const int pos = ch - 'a';
49
50         bs next = sum(row, row & has[pos]) | (row & rev[pos]);
51         cnt += next[m];
52         next[m] = 0;
53
54         row = next;
55     }
56
57     return cnt;
58 }

```

### 11.3 Fast Subset Convolution

```

1 // algorithm itself starts here
2 void mobius(int* a, int n, int sign) {
3     forn(i, n) {
4         int free = ((1 << n) - 1) ^ (1 << i);
5         for (int mask = free; mask > 0;
6             mask = ((mask - 1) & free))
7             (sign == +1 ? add : sub)(a[mask ^ (1 << i)],
8                                     ↪ a[mask]);
8         add(a[1 << i], a[0]);
9     }
10 }
11
12 // maximum number of bits allowed
13 const int B = 20;
14
15 vi fast_conv(vi a, vi b) {
16     assert(!a.empty());
17     const int bits = __builtin_ctz(sz(a));
18     assert(sz(a) == (1 << bits) && sz(a) == sz(b));
19
20     static int trans_a[B + 1][1 << B];
21     static int trans_b[B + 1][1 << B];
22     static int trans_res[B + 1][1 << B];
23
24     forn(cnt, bits + 1) {
25         for (auto cur : {trans_a, trans_b, trans_res})
26             fill(cur[cnt], cur[cnt] + (1 << bits), 0);
27     }
28
29     forn(mask, 1 << bits) {
30         const int cnt = __builtin_popcount(mask);

```

```

31     trans_a[cnt][mask] = a[mask];
32     trans_b[cnt][mask] = b[mask];
33 }
34
35 forn(cnt, bits + 1) {
36     mobius(trans_a[cnt], bits, +1);
37     mobius(trans_b[cnt], bits, +1);
38 }
39
40 // Not really a valid ranked mobius transform! But
41 // algorithm works anyway
42
43 forn(i, bits + 1) forn(j, bits - i + 1)
44     forn(mask, 1 << bits)
45         add(trans_res[i + j][mask],
46             mult(trans_a[i][mask], trans_b[j][mask]));
47
48 forn(cnt, bits + 1) mobius(trans_res[cnt], bits, -1);
49
50 forn(mask, 1 << bits) {
51     const int cnt = __builtin_popcount(mask);
52     a[mask] = trans_res[cnt][mask];
53 }
54
55 return a;
56 }

```

## 12 Karatsuba

```

1 // functon Karatsuba (and stupid as well) computes c += a *
2 // b, not c = a * b
3
4 using hvect = vector<modulo<>>::iterator;

```

```

5 using hvect = vector<modulo<>>::const_iterator;
6
7 void add(hvect abegin, hvect aend, hvect ans) {
8     for (auto it = abegin; it != aend; ++it, ++ans)
9         *ans += *it;
10 }
11
12 void sub(hvect abegin, hvect aend, hvect ans) {
13     for (auto it = abegin; it != aend; ++it, ++ans)
14         *ans -= *it;
15 }
16
17 void stupid(int siz, hvect abegin, hvect bbegin,
18             hvect ans) {
19     for (int i = 0; i < siz; i++)
20         for (int j = 0; j < siz; j++)
21             *(ans + i + j) += *(abegin + i) * *(bbegin + j);
22 }
23
24 void Karatsuba(size_t siz, hvect abegin, hvect bbegin,
25                hvect ans, hvect small, hvect big,
26                hvect sum) {
27     assert((siz & (siz - 1)) == 0);
28
29     if (siz ≤ 32) {
30         stupid(siz, abegin, bbegin, ans);
31
32         return;
33     }
34
35     auto amid = abegin + siz / 2, aend = abegin + siz;
36     auto bmid = bbegin + siz / 2, bend = bbegin + siz;
37     auto smid = sum + siz / 2, send = sum + siz;

```

```

38
39     fill(small, small + siz, 0);
40     Karatsuba(siz / 2, abegin, bbegin, small, small + siz,
41               big + siz, sum);
42     fill(big, big + siz, 0);
43     Karatsuba(siz / 2, amid, bmid, big, small + siz,
44               big + siz, sum);
45
46     copy(abegin, amid, sum);
47     add(amid, aend, sum);
48     copy(bbegin, bmid, sum + siz / 2);
49     add(bmid, bend, sum + siz / 2);
50
51     Karatsuba(siz / 2, sum, smid, ans + siz / 2, small + siz,
52               big + siz, send);
53
54     add(small, small + siz, ans);
55     sub(small, small + siz, ans + siz / 2);
56     add(big, big + siz, ans + siz);
57     sub(big, big + siz, ans + siz / 2);
58 }
59
60 void mult(vector<modulo<>> a, vector<modulo<>> b,
61           vector<modulo<>> &c) {
62     a.resize(up(max(a.size(), b.size()))), 0);
63     b.resize(a.size(), 0);
64
65     c.resize(max(c.size(), a.size() * 2), 0);
66
67     vector<modulo<>> small(2 * a.size());
68     auto big = small;
69     auto sum = small;
70

```

```

71     Karatsuba(a.size(), a.begin(), b.begin(), c.begin(),
72               small.begin(), big.begin(), sum.begin());
73 }

```

## 13 Hard Algorithms

### 13.1 Two Strong Chinese

```

1  template <class T, class Add>
2  class skew_heap {
3      struct node {
4          using nodeptr = unique_ptr<node>;
5
6          nodeptr l = nullptr, r = nullptr;
7          T x;
8
9          explicit node(T x = {}) : x(x) {}
10 };
11
12 using nodeptr = typename node::nodeptr;
13
14 static nodeptr merge(nodeptr &&a, nodeptr &&b) {
15     if (a == nullptr) return std::move(b);
16     if (b == nullptr) return std::move(a);
17     if (b->x < a->x)
18         return merge(std::move(b), std::move(a));
19
20     auto tmp = merge(std::move(a->r), std::move(b));
21     a->r = std::move(a->l);
22     a->l = std::move(tmp);
23
24     return std::move(a);
25 }

```

```

26
27 void add_to_all(nodeptr &a, Add x) {
28     if (a == nullptr) return;
29
30     a->x += x;
31     add_to_all(a->l, x);
32     add_to_all(a->r, x);
33 }
34
35 nodeptr root = nullptr;
36 size_t siz = 0;
37 Add to_add{};
38
39 public:
40 void add(Add x) { to_add += x; }
41
42 [[nodiscard]] T top() const { return root->x + to_add; }
43
44 [[nodiscard]] auto size() const { return siz; }
45
46 [[nodiscard]] auto empty() const { return size() == 0; }
47
48 void pop() {
49     auto q = merge(std::move(root->l), std::move(root->r));
50     siz--;
51     root = std::move(q);
52 }
53
54 void merge(skew_heap &&rhs) {
55     if (size() < rhs.size()) swap(*this, rhs);
56
57     siz += rhs.siz;
58     rhs.siz = 0;
59
60     rhs.add_to_all(rhs.root, rhs.to_add - to_add);
61     auto q = merge(std::move(root), std::move(rhs.root));
62     root = std::move(q);
63 }
64
65 void push(T x) {
66     skew_heap sh;
67     sh.root = make_unique<node>(x);
68     sh.siz = 1;
69
70     merge(std::move(sh));
71 };
72
73 struct edge {
74     ll w;
75     int to;
76     int id;
77
78     strong_ordering operator<=>(const edge &rhs) const {
79         return w <=> rhs.w;
80     }
81
82     edge &operator+=(ll rhs) {
83         w += rhs;
84
85         return *this;
86     }
87
88     edge operator+(ll rhs) const {
89         return edge{w + rhs, to, id};
90     }
91 };

```

```

92
93 enum color_t { White = 0, Grey, Black, Cycle };
94
95 vector<int> solve(size_t n,
96                 const vector<tuple<int, int, int>>
97                 ↪ &edges,
98                 int root = 0) {
99     vector<skew_heap<edge, ll>> rev(n);
100
101     for (int i = 0; i < (int)edges.size(); i++) {
102         auto [a, b, w] = edges[i];
103         if (b ≠ root) rev[b].push(edge{w, a, i});
104     }
105
106     auto mrg = [&](int a, int b) {
107         rev[a].merge(std::move(rev[b]));
108     };
109
110     dsu cc(n, mrg);
111
112     vector<color_t> color(rev.size());
113     color[root] = Black;
114
115     vector<int> ids;
116
117     function<bool(int)> dfs = [&](int v) → bool {
118         v = cc.get_class(v);
119
120         if (color[v] == Black) return false;
121
122         if (color[v] == Grey) {
123             color[v] = Cycle;

```

```

124
125         return true;
126     }
127     color[v] = Grey;
128
129     while (true) {
130         while (!rev[v].empty() &&
131             cc.get_class(rev[v].top().to) == v)
132             rev[v].pop();
133
134         assert(
135             !rev[v]
136             .empty()); // assume that the answer exists
137         auto [w, to, id] = rev[v].top();
138
139         ids.emplace_back(id); // ans += w; if the
140                               ↪ certificate
141                               // is not needed
142
143         rev[v].add(-w);
144
145         if (dfs(to)) {
146             if (color[v] ≠ Cycle) {
147                 cc.unite(v, to);
148                 color[cc.get_class(v)] = Cycle;
149
150                 return true;
151             } else {
152                 v = cc.get_class(v);
153
154                 color[v] = Grey;
155             }
156         } else {

```

```
156         color[v] = Black;
157
158         return false;
159     }
160 }
161 };
162
163 for (int i = 0; i < (int)rev.size(); i++) dfs(i);
164
165 // finding answer, similar to Prim
166 vector<vector<int>> gr(n);
167
168 for (int i = 0; i < int(ids.size()); i++) {
169     auto [a, b, _] = edges[ids[i]];
170
171     gr[a].push_back(i);
172 }
173
174 minheap<int> pq(gr[root].begin(), gr[root].end());
175 vector<bool> used(n);
176 used[root] = true;
177
178 vector<int> ans;
179
180 while (!pq.empty()) {
181     auto i = pq.top();
182     pq.pop();
183     auto v = get<1>(edges[ids[i]]);
184
185     if (used[v]) continue;
186     used[v] = true;
187
188     ans.push_back(ids[i]);
```

```
189
190     for (auto it : gr[v]) pq.push(it);
191 }
192
193 return ans;
194 }
195
196 void dfs(const vector<vector<pair<int, int>>> &gr,
197         vector<bool> &used, int v) {
198     if (used[v]) return;
199     used[v] = true;
200
201     for (auto [u, w] : gr[v]) dfs(gr, used, u);
202 }
203
204 void solve(istream &cin = std::cin,
205           ostream &cout = std::cout) {
206     int n, m;
207
208     cin >> n >> m;
209
210     vector<tuple<int, int, int>> edges(m);
211     vector<vector<pair<int, int>>> gr(n);
212
213     for (int i = 0; i < m; i++) {
214         auto &[a, b, w] = edges[i];
215
216         cin >> a >> b >> w;
217         a--;
218         b--;
219
220         gr[a].emplace_back(b, w);
221     }
```

```

222
223     vector<bool> used(gr.size());
224
225     dfs(gr, used, 0);
226
227     if (ranges::count(used, false)) {
228         cout << "NO" << endl;
229
230         return;
231     }
232
233     cout << "YES" << endl;
234
235     auto ids = solve(gr.size(), edges);
236
237     ll ans = 0;
238
239     for (auto it : ids) ans += get<2>(edges[it]);
240
241     for (auto &row : gr) row.clear();
242
243     for (auto it : ids) {
244         auto [a, b, w] = edges[it];
245
246         gr[a].emplace_back(b, w);
247     }
248
249     used.assign(used.size(), false);
250
251     dfs(gr, used, 0);
252
253     assert(ranges::count(used, false) == 0);
254

```

```

255     cout << ans << endl;
256 }

```

## 13.2 Simplex

```

1  mt19937 mt(736);
2
3  using ld = double;
4  constexpr ld eps = 1e-9;
5
6  bool eps_nonneg(ld x) { return x ≥ -eps; }
7
8  bool eps_zero(ld x) { return abs(x) ≤ eps; }
9
10 bool cmp_abs(ld a, ld b) { return abs(a) < abs(b); }
11
12 vector<ld> &add_prod(vector<ld> &lhs, const vector<ld>
    ↪ &rhs,
13                    ld x) {
14     assert(ssize(lhs) == ssize(rhs));
15
16     for (auto i : ranges::iota_view(0, ssize(lhs)))
17         lhs[i] += rhs[i] * x;
18
19     return lhs;
20 }
21
22 vector<ld> &operator≠(vector<ld> &lhs, ld x) {
23     for (auto &it : lhs) it ≠ x;
24
25     return lhs;
26 }
27

```

```

28 void basis_change(vector<ld> &row, const vector<ld> &nd,
29                 int b) {
30     auto mult = row[b];
31
32     add_prod(row, nd, mult);
33
34     row[b] = 0;
35 }
36
37 void pivot(vector<vector<ld>> &a, vector<int> &b,
38           vector<ld> &func, int wh, int x) {
39     a[wh][b[wh]] = -1;
40     b[wh] = x;
41     auto den = -a[wh][x];
42     a[wh][x] = 0;
43     a[wh] /= den;
44
45     for (auto i : ranges::iota_view(0, ssize(a)))
46         if (i != wh) basis_change(a[i], a[wh], b[wh]);
47     basis_change(func, a[wh], b[wh]);
48 }
49
50 bool simplex(vector<vector<ld>> &a, vector<int> &b,
51             vector<ld> &func) {
52     while (true) {
53         vector<int> cand;
54
55         for (auto i : ranges::iota_view(0, ssize(func) - 1))
56             if (func[i] > eps) cand.push_back(i);
57
58         if (cand.empty()) return true;
59
60         auto x = cand[uniform_int_distribution<int>{
61             0, (int)cand.size() - 1}(mt)];
62
63         vector<ld> len(a.size(), numeric_limits<ld>::max());
64
65         for (auto i : ranges::iota_view(0, ssize(len)))
66             if (a[i][x] < -eps) len[i] = a[i].back() / -a[i][x];
67
68         auto wh = int(ranges::min_element(len) - len.begin());
69
70         if (len[wh] == numeric_limits<ld>::max()) return false;
71
72         pivot(a, b, func, wh, x);
73     }
74 }
75
76 enum results { NO_SOLUTION, UNBOUNDED, BOUNDED };
77
78 /*
79  * Solving system of linear inequalities in the form
80  * $a * x ≤ rhs$
81  * $x ≥ 0$
82  * $costs * x → max$
83  * assumes at least one inequality and at least one
84  * ↪ variable
85  * */
86 results global_solve(vector<vector<ld>> a,
87                     const vector<ld> &rhs,
88                     const vector<ld> &costs,
89                     vector<ld> &ans) {
90     assert(!a.empty() && a.size() == rhs.size() &&
91           !costs.empty() && ans.size() == costs.size());
92     const auto m = costs.size() + a.size() + 2;

```



```

93   for (auto i : ranges::iota_view(0, ssize(a))) {
94       auto &row = a[i];
95
96       row /= -1; // just finding inverse
97       row.resize(m);
98       row.back() = rhs[i];
99       row.rbegin()[1] = 1;
100  }
101
102  vector<ld> func(m), lambda(m);
103  vector<int> b(a.size());
104
105  iota(b.begin(), b.end(), (int)costs.size());
106
107  lambda.rbegin()[1] = -1;
108  for (auto j : ranges::iota_view(0, ssize(costs)))
109      func[j] = costs[j];
110
111  auto wh = int(ranges::min_element(rhs) - rhs.begin());
112
113  if (rhs[wh] < 0) {
114      pivot(a, b, lambda, wh, (int)lambda.size() - 2);
115
116      auto q = simplex(a, b, lambda);
117
118      assert(q);
119  }
120
121  wh = int(ranges::find(b, (int)lambda.size() - 2) -
122          b.begin());
123
124  if (!eps_zero(lambda.back())) return NO_SOLUTION;
125

```

```

126  if (wh != size(b)) {
127      if (!eps_zero(a[wh].back())) return NO_SOLUTION;
128
129      auto q = int(ranges::find_if(a[wh], eps_nonneg) -
130                  a[wh].begin());
131
132      if (q != ssize(a[wh])) {
133          pivot(a, b, lambda, wh, q);
134      } else {
135          q = int(ranges::max_element(a[wh], cmp_abs) -
136              a[wh].begin());
137
138          if (!eps_zero(a[wh][q])) pivot(a, b, lambda, wh, q);
139      }
140  }
141
142  for (auto &row : a) row.rbegin()[1] = 0;
143
144  for (auto i : ranges::iota_view(0, ssize(b)))
145      basis_change(func, a[i], b[i]);
146
147  if (!simplex(a, b, func)) return UNBOUNDED;
148
149  for (auto i : ranges::iota_view(0, ssize(a)))
150      if (b[i] < ssize(ans)) ans[b[i]] = a[i].back();
151
152  return BOUNDED;
153 }

```

## 14 OEIS

### 14.1 Числа Белла

1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, 115975, 678570, 4213597, 27644437, 190899322, 1382958545, 10480142147, 82864869804, 682076806159, 5832742205057, 51724158235372, 474869816156751, 4506715738447323, 44152005855084346, 445958869294805289, 4638590332229999353, 49631246523618756274

### 14.2 Числа Каталана

1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, 208012, 742900, 2674440, 9694845, 35357670, 129644790, 477638700, 1767263190, 6564120420, 24466267020, 91482563640, 343059613650, 1289904147324, 4861946401452, 18367353072152, 69533550916004, 263747951750360, 1002242216651368, 3814986502092304