

Create

1. Get the item id by item barcode

Use section 3.6 in the API documentation to get the item id

<http://esl.zkong.com/zk/item/getItemByBarCodeAndExternalStoreId>

The screenshot shows a REST client interface with a POST request to `http://esl-hz.zkong.com/zk/item/getItemByBarCodeAndExternalStoreId`. The request body is in raw JSON format:

```
1 {
2   "itemBarCode": "20240930",
3   "externalStoreId": ""
4 }
```

The response status is `200 OK` with a response time of `46 ms` and a size of `1013`. The response body is in pretty JSON format:

```
1 {
2   "success": true,
3   "code": 10000,
4   "message": "Operation Succeeded",
5   "data": {
6     "id": 7070002512,
7     "type": 1,
8     "price": "12",
9     "spec": null,
10    "productCode": null,
11    "barCode": "20240930",
12    "agencyId": 1558752736438,
13    "merchantId": 1645409310618,
14    "storeId": 0,
15    "originalPrice": "12",
16    "memberPrice": "12",
17    "productArea": null,
18    "classLevel": null,

```

A red arrow points from the `"itemBarCode": "20240930"` in the request body to the `"id": 7070002512` in the response body.

Postbot

2. Enter item id into the strategy

The screenshot displays a REST client interface with a POST request to `http://esi-hz.zkong.com/zk/strategy/create`. The request body is a JSON object with the following structure:

```
11 {
12   4,
13   7,
14   1
15 },
16 "selectFieldNameNum": [5, 4],
17 "itemActions": [
18   {
19     "itemId": 7070002512,
20     "fieldValues": {
21       "price": "3.5",
22       "memberPrice": "2.5",
23       "unit": null,
24       "classLevel": null
25     }
26   }
27 ]
28 }
```

The response is a 200 OK status with a response time of 60 ms. The response body is a JSON object:

```
1 {
2   "success": true,
3   "code": 10000,
4   "message": "Operation Succeeded",
5   "data": 844,
6   "translate": true,
7   "originalMessage": null
8 }
```

Update

1. Get the strategy id

Use section 8.3 in the API documentation to get the strategy id

<http://esl.zkong.com/zk/strategy/list/1/10?isValid=true>

The screenshot shows a REST client interface with a POST request to `http://esl-hz.zkong.com/zk/strategy/list/1/10?isValid=true`. The request body is a JSON object: `{ "storeId": 1696991838478, "name": "限时" }`. The response is a 200 OK status with a JSON body. A red arrow points to the `"id": 844` field in the first element of the `"list"` array.

```
1 {
2   "storeId": 1696991838478,
3   "name": "限时"
4 }
```

Body Cookies Headers (15) Test Results 200 OK · 201 ms · 1.08 KB

Pretty Raw Preview Visualize JSON

```
5 {
6   "pageSize": 10,
7   "currentPage": 1,
8   "totalPage": 1,
9   "totalElements": 2,
10  "list": [
11    {
12      "id": 844,
13      "name": "限时折扣策略111",
14      "agencyId": 1558752736438,
15      "merchantId": 1645489318618,
16      "storeId": 1696991838478,
17      "code": "2248844",
18      "type": 1,
19      "templateAttrCategory": "default",
20      "templateAttr": "default",
21      "startDate": "2024-09-30T09:00:00+08:00",
22      "endDate": "2024-09-30T09:00:00+08:00"
23    }
24  ]
25 }
```

Postbot

2. Enter strategy id into the update strategy

The screenshot displays a REST client interface with a PUT request to the URL `http://esl-hz.zkong.com/zk/strategy/update`. The request body is a JSON object with the following fields:

```
1 {
2   "id": 844,
3   "name": "限时折扣策略-新zkong",
4   "startDate": 1727658000000,
5   "endDate": 1729891140000,
6   "templateAttr": "default",
7   "templateAttrCategory": "default",
8   "triggerType": 1,
9   "periodType": 1,
10  "periodValue": [
11    2,
```

The response body is a JSON object indicating a successful update:

```
1 {
2   "success": true,
3   "code": 10000,
4   "message": "操作成功",
5   "data": null,
6   "translate": true,
7   "originalMessage": "success"
8 }
```

