



UCAM
UNIVERSIDAD

PRÁCTICA 1

LABORATORIO 1

GIT FUNDAMENTALS

Administración de Bases de Datos

JULIO CHECA ROIG

Profesor

Dr. Richard Avilés López

Grado en Ingeniería Informática

7. Preguntas de comprobación

Responde con tus propias palabras. El objetivo no es memorizar comandos, sino demostrar que entiendes qué ocurre en cada zona de Git.

1. ¿Cuál es la diferencia entre Working Directory, Staging Area y Local Repository? Da un ejemplo de un archivo pasando por las tres.

Working Directory: lo que está en tu disco ahora mismo.

Staging Area: la “bandeja” donde colocas lo que quieres incluir en el próximo commit.

Local Repository: la base de datos interna dentro de .git donde viven los commits.

2. Si modificas un archivo pero no haces git add, ¿aparece ese cambio en tu próximo commit? Explica por qué.

No, porque Git solo confirma lo que está en la Staging Area. Si no haces git add, el archivo sigue en Working Directory y no se incluye en el commit.

3. ¿Por qué git status no mostraba las carpetas vacías que creaste en la Parte C? ¿Qué truco usamos para solucionarlo?

Git no versiona carpetas, solo archivos. Una carpeta vacía no deja “huella” que Git pueda registrar.

4. Explica con tus palabras qué es HEAD.

HEAD es el puntero que indica en qué commit y en qué branch estás trabajando ahora mismo. Cuando cambias de branch, HEAD apunta a otro commit y Git reescribe el Working Directory.

5. ¿Qué diferencia hay entre crear una branch con git switch -c y crear una carpeta nueva con mkdir? ¿Cómo lo comprobamos en la Parte G?

mkdir crea carpetas físicas en el disco.

git switch -c crea una rama, que es solo un puntero dentro de .git, no una carpeta.

6. Durante el conflicto de la Parte H, ¿qué representaba el contenido entre <<<<<< HEAD y =====? ¿Y entre ===== y >>>>>>?

Entre <<<<<< HEAD y =====: tu versión actual (la de main).

Entre ===== y >>>>>>: la versión que viene de la otra branch.

7. ¿Por qué NO se debe hacer git commit --amend sobre un commit que ya se subió con git push?

Porque --amend reescribe el commit, cambiando su hash. Si ya lo subiste, tu historial local y el remoto dejan de coincidir, causando divergencias y conflictos para otros colaboradores.

8. Si borras por accidente la carpeta .git de tu proyecto, ¿qué se pierde exactamente? ¿Se pierde también el código fuente que está en el disco?

Si borras .git pierdes: historial, commits, branches y configuración del repositorio. Pero NO pierdes el código fuente. Los archivos del proyecto siguen en el disco, solo pierdes el control de versiones.

9. Explica con tus propias palabras la diferencia entre Git y GitHub, sin usar la palabra "nube".

Git: programa que funciona en tu ordenador y gestiona historial, commits, branches y merges.

GitHub: plataforma que almacena repositorios Git y añade colaboración: pull requests, issues, revisiones, CI/CD, protección de ramas.

10. ¿Por qué no se debe subir un archivo .env con contraseñas reales a un repositorio, aunque el repositorio sea privado?

Los repos privados pueden compartirse accidentalmente. Un colaborador puede descargar las claves. Si el repo se hace público por error, las credenciales quedan expuestas. Git guarda historial, así que aunque borres el archivo, la contraseña sigue en commits anteriores.

11. Un compañero te dice: "hice push y ahora GitHub me rechaza el segundo push con 'non-fast-forward'". ¿Qué ha ocurrido probablemente y qué comando ejecutarías primero?

Probablemente GitHub tiene commits que tu copia local no tiene (por ejemplo, cambios hechos desde la web).

12. ¿Qué tipo de Conventional Commit (feat, fix, docs, test...) usarías para: añadir un índice de rendimiento a una tabla, corregir una restricción mal definida, y actualizar el README?

Añadir un índice de rendimiento a una tabla: perf

Corregir una restricción mal definida: fix

Actualizar el README: docs

CODIGO DEL LABORATORIO:

```
capit@Portatil_Auxi MINGW64 ~  
$ cd oracle-database-lab
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)  
$ mkdir -p database/schema database/migrations database/rollback database/tests
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)  
$ mkdir -p scripts runbooks playbooks docs
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)  
$ touch README.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)  
$ git status  
On branch master
```

No commits yet

Untracked files:
(use "git add <file>..." to include in what will be committed)
README.md

nothing added to commit but untracked files present (use "git add" to track)

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)  
$ touch runbooks/.gitkeep playbooks/.gitkeep database/schema/.gitkeep  
database/migrations/.gitkeep database/rollback/.gitkeep database/tests/.gitkeep  
scripts/.gitkeep
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)  
$ cmd //c tree
```

Listado de rutas de carpetas para el volumen Windows

El número de serie del volumen es BE17-F46E

C:.

```
|— database  
|   |— migrations  
|   |— rollback  
|   |— schema  
|   |— tests  
|— docs  
|— playbooks  
|— runbooks  
|— scripts
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ find . -print | sed -e 's:[^/]*;/;g'
```

```
.  
| .git  
| | config  
| | description  
| | HEAD  
| | hooks  
| | | applypatch-msg.sample  
| | | commit-msg.sample  
| | | fsmonitor-watchman.sample  
| | | post-update.sample  
| | | pre-applypatch.sample  
| | | pre-commit.sample  
| | | pre-merge-commit.sample  
| | | pre-push.sample  
| | | pre-rebase.sample  
| | | pre-receive.sample  
| | | prepare-commit-msg.sample  
| | | push-to-checkout.sample  
| | | sendemail-validate.sample  
| | | update.sample  
| | info  
| | | exclude  
| | objects  
| | | info  
| | | pack  
| | refs  
| | | heads  
| | | tags  
| database  
| | migrations  
| | | .gitkeep  
| | rollback  
| | | .gitkeep  
| | schema  
| | | .gitkeep  
| | tests  
| | | .gitkeep  
| docs  
| playbooks  
| | .gitkeep  
| README.md  
| runbooks  
| | .gitkeep  
| scripts  
| | .gitkeep
```

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)

```
$ nano README.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ git config --global status.showUntrackedFiles all
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ git status
```

```
On branch master
```

```
No commits yet
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
```

```
README.md
```

```
database/migrations/.gitkeep
```

```
database/rollback/.gitkeep
```

```
database/schema/.gitkeep
```

```
database/tests/.gitkeep
```

```
playbooks/.gitkeep
```

```
runbooks/.gitkeep
```

```
scripts/.gitkeep
```

```
nothing added to commit but untracked files present (use "git add" to track)
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ git add README.md
```

```
warning: in the working copy of 'README.md', LF will be replaced by CRLF the next time Git touches it
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ git status
```

```
On branch master
```

```
No commits yet
```

```
Changes to be committed:
```

```
(use "git rm --cached <file>..." to unstage)
```

```
new file: README.md
```

```
Untracked files:
```

```
(use "git add <file>..." to include in what will be committed)
```

```
database/migrations/.gitkeep
```

```
database/rollback/.gitkeep
```

```
database/schema/.gitkeep
```

```
database/tests/.gitkeep
```

```
playbooks/.gitkeep
```

```
runbooks/.gitkeep
```

```
scripts/.gitkeep
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
$ git diff --staged
diff --git a/README.md b/README.md
new file mode 100644
index 0000000..2265ca7
--- /dev/null
+++ b/README.md
@@ -0,0 +1,6 @@
+# Oracle Database Lab
+
+Training repository for Oracle Database administration, testing, change management and
Git workflows.
+
+Name: Julio Checa Roig
+Professor: Richard Aviles Lopez
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
$ git commit -m "docs: add initial project documentation"
[master (root-commit) 1377cad] docs: add initial project documentation
1 file changed, 6 insertions(+)
create mode 100644 README.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
$ git status
On branch master
Untracked files:
  (use "git add <file>..." to include in what will be committed)
    database/migrations/.gitkeep
    database/rollback/.gitkeep
    database/schema/.gitkeep
    database/tests/.gitkeep
    playbooks/.gitkeep
    runbooks/.gitkeep
    scripts/.gitkeep
```

nothing added to commit but untracked files present (use "git add" to track)

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
$ git log
commit 1377cada379dcec7f94a348878fa9c6f0bf4e1f9 (HEAD -> master)
Author: Julio Checa <jcheca@alu.ucam.edu>
Date: Fri Sep 18 18:21:00 2026 +0200
```

docs: add initial project documentation

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ echo "# Database schema notes" > docs/customer-schema.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ git commit -m "docs: add customer schema notes"
```

On branch master

Untracked files:

(use "git add <file>..." to include in what will be committed)

database/migrations/.gitkeep

database/rollback/.gitkeep

database/schema/.gitkeep

database/tests/.gitkeep

docs/customer-schema.md

playbooks/.gitkeep

runbooks/.gitkeep

scripts/.gitkeep

nothing added to commit but untracked files present (use "git add" to track)

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ git status
```

On branch master

Untracked files:

(use "git add <file>..." to include in what will be committed)

database/migrations/.gitkeep

database/rollback/.gitkeep

database/schema/.gitkeep

database/tests/.gitkeep

docs/customer-schema.md

playbooks/.gitkeep

runbooks/.gitkeep

scripts/.gitkeep

nothing added to commit but untracked files present (use "git add" to track)

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ git log --oneline
```

```
1377cad (HEAD -> master) docs: add initial project documentation
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ git add docs/custome-schema.md
```

```
fatal: pathspec 'docs/custome-schema.md' did not match any files
ggigi
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
```

```
$ git commit -m "docs: add customer schema notes"
```

On branch master

Untracked files:

(use "git add <file>..." to include in what will be committed)

database/migrations/.gitkeep

```
database/rollback/.gitkeep
database/schema/.gitkeep
database/tests/.gitkeep
docs/customer-schema.md
playbooks/.gitkeep
runbooks/.gitkeep
scripts/.gitkeep
```

nothing added to commit but untracked files present (use "git add" to track)

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
$ git log --oneline
1377cad (HEAD -> master) docs: add initial project documentation
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
$ echo "Some content" >> docs/customer-schema.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
$ git add docs/customer-schema.md
warning: in the working copy of 'docs/customer-schema.md', LF will be replaced by CRLF
the next time Git touches it
```

```
g
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
$ git commit -m "dcos:fxi typo"
[master e6737ac] dcos:fxi typo
1 file changed, 2 insertions(+)
create mode 100644 docs/customer-schema.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
$ git commit --amend -m "docs: fix typo in schema notes"
error: unknown option `amed'
usage: git commit [-a | --interactive | --patch] [-s] [-v] [-u[<mode>]] [--amend]
               [--dry-run] [(--c | -C | --squash) <commit> | --fixup [(amend|reword):]<commit>]
               [-F <file> | -m <msg>] [--reset-author] [--allow-empty]
               [--allow-empty-message] [--no-verify] [-e] [--author=<author>]
               [--date=<date>] [--cleanup=<mode>] [--[no-]status]
               [-i | -o] [--pathspec-from-file=<file>] [--pathspec-file-nul]
               [(--trailer <token>[(=|:)<value>])...] [-S[<keyid>]]
               [--] [<pathspec>...]
```

-q, --[no-]quiet suppress summary after successful commit
-v, --[no-]verbose show diff in commit message template

Commit message options

-F, --[no-]file <file>
 read message from file
--[no-]author <author>
 override author for commit

- [no-]date <date> override date for commit
- m, --[no-]message <message>
commit message
- c, --[no-]reedit-message <commit>
reuse and edit message from specified commit
- C, --[no-]reuse-message <commit>
reuse message from specified commit
- [no-]fixup [(amend|reword):]commit
use autosquash formatted message to fixup or amend/reword specified

commit

- [no-]squash <commit>
use autosquash formatted message to squash specified commit
- [no-]reset-author the commit is authored by me now (used with -C/-c/--amend)
- [no-]trailer <trailer>
add custom trailer(s)
- s, --[no-]signoff add a Signed-off-by trailer
- t, --[no-]template <file>
use specified template file
- e, --[no-]edit force edit of commit
- [no-]cleanup <mode> how to strip spaces and #comments from message
- [no-]status include status in commit message template
- S, --[no-]pgp-sign[=<key-id>]
GPG sign commit

Commit contents options

- a, --[no-]all commit all changed files
- i, --[no-]include add specified files to index for commit
- [no-]interactive interactively add files
- p, --[no-]patch interactively add changes
- U, --unified <n> generate diffs with <n> lines context
- inter-hunk-context <n>
show context between diff hunks up to the specified number of lines
- o, --[no-]only commit only specified files
- n, --no-verify bypass pre-commit and commit-msg hooks
- verify opposite of --no-verify
- [no-]dry-run show what would be committed
- [no-]short show status concisely
- [no-]branch show branch information
- [no-]ahead-behind compute full ahead/behind values
- [no-]porcelain machine-readable output
- [no-]long show status in long format (default)
- Z, --[no-]null terminate entries with NUL
- [no-]amend amend previous commit
- no-post-rewrite bypass post-rewrite hook
- post-rewrite opposite of --no-post-rewrite
- u, --[no-]untracked-files[=<mode>]
show untracked files, optional modes: all, normal, no. (Default: all)
- [no-]pathspec-from-file <file>

read pathspec from file
--[no-]pathspec-file-nul
with --pathspec-from-file, pathspec elements are separated with NUL
character

ff

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)

\$ git log --oneline

e6737ac (HEAD -> master) dcos:fxi typo

1377cad docs: add initial project documentation

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)

\$ git log

commit e6737ac4bc2c3ebda2cdfd862b9069feaeff401c (HEAD -> master)

Author: Julio Checa <jcheca@alu.ucam.edu>

Date: Fri Sep 18 18:28:13 2026 +0200

dcos:fxi typo

commit 1377cada379dcec7f94a348878fa9c6f0bf4e1f9

Author: Julio Checa <jcheca@alu.ucam.edu>

Date: Fri Sep 18 18:21:00 2026 +0200

docs: add initial project documentation

itit

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)

\$ git log --oneline

e6737ac (HEAD -> master) dcos:fxi typo

1377cad docs: add initial project documentation

ggitgit

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)

\$ git log --oneline --graph --all

* e6737ac (HEAD -> master) dcos:fxi typo

* 1377cad docs: add initial project documentation

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)

\$ git show <hash>

bash: syntax error near unexpected token `newline'

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)

\$ git diff

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)

\$ git diff --staged

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)

\$ git branch

* master

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (master)
$ git switch -c feature/customer-search
Switched to a new branch 'feature/customer-search'
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)
$ git branch
* feature/customer-search
  master
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)
$ ls -la
total 25
drwxr-xr-x 1 capit 197619  0 Sep 18 18:06 ./
drwxr-xr-x 1 capit 197619  0 Sep 18 18:34 ../
drwxr-xr-x 1 capit 197619  0 Sep 18 18:33 .git/
-rw-r--r-- 1 capit 197619 181 Sep 18 18:17 README.md
drwxr-xr-x 1 capit 197619  0 Sep 18 18:05 database/
drwxr-xr-x 1 capit 197619  0 Sep 18 18:24 docs/
drwxr-xr-x 1 capit 197619  0 Sep 18 18:11 playbooks/
drwxr-xr-x 1 capit 197619  0 Sep 18 18:11 runbooks/
drwxr-xr-x 1 capit 197619  0 Sep 18 18:11 scripts/
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)
$ echo "Draft: customer search notes" > docs/customer-search.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)
$ git add docs/customer-search.md
warning: in the working copy of 'docs/customer-search.md', LF will be replaced by CRLF the
next time Git touches it
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)
$ git commit -m "docs: draft customer search notes"
[feature/customer-search e1c1de8] docs: draft customer search notes
1 file changed, 1 insertion(+)
create mode 100644 docs/customer-search.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)
$ git log --oneline --graph --all
* e1c1de8 (HEAD -> feature/customer-search) docs: draft customer search notes
* e6737ac (master) dcos:fxi typo
* 1377cad docs: add initial project documentation
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)
$ git switch main
fatal: invalid reference: main
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)
```

```
$ ls docs/  
customer-schema.md customer-search.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)  
$ git switch feature/customer-search  
Already on 'feature/customer-search'
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)  
$ ls docs/  
customer-schema.md customer-search.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)  
$ git branch -d nombre-de-una-branch-de-prueba  
error: branch 'nombre-de-una-branch-de-prueba' not found
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)  
$ git switch main  
fatal: invalid reference: main
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (feature/customer-search)  
$ git switch -c fix/readme-tittle  
Switched to a new branch 'fix/readme-tittle'
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-tittle)  
$ nano README.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-tittle)  
$ git status  
On branch fix/readme-tittle  
Changes not staged for commit:  
  (use "git add <file>..." to update what will be committed)  
  (use "git restore <file>..." to discard changes in working directory)  
        modified:   README.md
```

```
Untracked files:  
  (use "git add <file>..." to include in what will be committed)  
        database/migrations/.gitkeep  
        database/rollback/.gitkeep  
        database/schema/.gitkeep  
        database/tests/.gitkeep  
        playbooks/.gitkeep  
        runbooks/.gitkeep  
        scripts/.gitkeep
```

no changes added to commit (use "git add" and/or "git commit -a")

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-tittle)  
$ git add README.md
```

warning: in the working copy of 'README.md', LF will be replaced by CRLF the next time Git touches it

ggigit

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-tittle)

\$ git status

On branch fix/readme-tittle

Changes to be committed:

(use "git restore --staged <file>..." to unstage)

modified: README.md

Untracked files:

(use "git add <file>..." to include in what will be committed)

database/migrations/.gitkeep

database/rollback/.gitkeep

database/schema/.gitkeep

database/tests/.gitkeep

playbooks/.gitkeep

runbooks/.gitkeep

scripts/.gitkeep

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-tittle)

\$ git commit -m "docs: rename project title (training edition)"

[fix/readme-tittle 11c7153] docs: rename project title (training edition)

1 file changed, 1 insertion(+), 1 deletion(-)

ggigi

capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-tittle)

\$ git status -c

error: unknown switch `c'

usage: git status [<options>] [--] [<paths-spec>...]

-v, --[no-]verbose be verbose

-s, --[no-]short show status concisely

-b, --[no-]branch show branch information

--[no-]show-stash show stash information

--[no-]ahead-behind compute full ahead/behind values

--[no-]porcelain[=<version>]

machine-readable output

--[no-]long show status in long format (default)

-z, --[no-]null terminate entries with NUL

-u, --[no-]untracked-files[=<mode>]

show untracked files, optional modes: all, normal, no. (Default: all)

--[no-]ignored[=<mode>]

show ignored files, optional modes: traditional, matching, no. (Default:

traditional)

--[no-]ignore-submodules[=<when>]

ignore changes to submodules, optional when: all, dirty, untracked. (Default:

all)

--[no-]column[=<style>]
list untracked files in columns
--no-renames do not detect renames
--renames opposite of --no-renames
-M, --find-renames[=<n>]
detect renames, optionally set similarity index

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-tittle)
$ git switch main
fatal: invalid reference: main
ggigit
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-tittle)
$ git switch -c fix/readme-subtitle
Switched to a new branch 'fix/readme-subtitle'
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-subtitle)
$ git add README.md
ggi
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-subtitle)
$ git commit -m "docs: rename project tittle (academic version)"
On branch fix/readme-subtitle
Untracked files:
  (use "git add <file>..." to include in what will be committed)
    database/migrations/.gitkeep
    database/rollback/.gitkeep
    database/schema/.gitkeep
    database/tests/.gitkeep
    playbooks/.gitkeep
    runbooks/.gitkeep
    scripts/.gitkeep
```

```
nothing added to commit but untracked files present (use "git add" to track)
ggigit
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-subtitle)
$ git switch main
fatal: invalid reference: main
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-subtitle)
$ git merge fix/readme-tittle
merge: fix/readme-tittle - not something we can merge
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-subtitle)
$ git merge fix/readme-subtitle
Already up to date.
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-subtitle)
$ nano README.md
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-subtitle)
$ git remote add origin https://github.com/jchecha-main/oracle-database-lab..git
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-subtitle)
$ git remote -v
origin https://github.com/jchecha-main/oracle-database-lab..git (fetch)
origin https://github.com/jchecha-main/oracle-database-lab..git (push)
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-subtitle)
$ git branch -Mmain
error: unknown switch `n'
usage: git branch [<options>] [-r | -a] [--merged] [--no-merged]
       or: git branch [<options>] [-f] [--recurse-submodules] <branch-name> [<start-point>]
       or: git branch [<options>] [-l] [<pattern>...]
       or: git branch [<options>] [-r] (-d | -D) <branch-name>...
       or: git branch [<options>] (-m | -M) [<old-branch>] <new-branch>
       or: git branch [<options>] (-c | -C) [<old-branch>] <new-branch>
       or: git branch [<options>] [-r | -a] [--points-at]
       or: git branch [<options>] [-r | -a] [--format]
```

Generic options

- v, --[no-]verbose show hash and subject, give twice for upstream branch
- q, --[no-]quiet suppress informational messages
- t, --[no-]track[=(direct|inherit)]
set branch tracking configuration
- u, --[no-]set-upstream-to <upstream>
change the upstream info
- [no-]unset-upstream unset the upstream info
- [no-]color[=<when>] use colored output
- r, --remotes act on remote-tracking branches
- contains <commit> print only branches that contain the commit
- no-contains <commit>
print only branches that don't contain the commit
- [no-]abbrev[=<n>] use <n> digits to display object names

Specific git-branch actions:

- a, --all list both remote-tracking and local branches
- d, --[no-]delete delete fully merged branch
- D delete branch (even if not merged)
- m, --[no-]move move/rename a branch and its reflog
- M move/rename a branch, even if target exists
- [no-]omit-empty do not output a newline after empty formatted refs
- c, --[no-]copy copy a branch and its reflog
- C copy a branch, even if target exists
- l, --[no-]list list branch names
- [no-]show-current show current branch name
- [no-]create-reflog create the branch's reflog

--[no-]edit-description
 edit the description for the branch
-f, --[no-]force force creation, move/rename, deletion
--merged <commit> print only branches that are merged
--no-merged <commit> print only branches that are not merged
--[no-]column[=<style>]
 list branches in columns
--[no-]sort <key> field name to sort on
--[no-]points-at <object>
 print only branches of the object
-i, --[no-]ignore-case
 sorting and filtering are case insensitive
--[no-]recurse-submodules
 recurse through submodules
--[no-]format <format>
 format to use for the output

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (fix/readme-subtitle)
$ git branch -M main
```

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (main)
```

```
$ git push -u origin main
```

info: please complete authentication in your browser...

Enumerating objects: 14, done.

Counting objects: 100% (14/14), done.

Delta compression using up to 12 threads

Compressing objects: 100% (10/10), done.

Writing objects: 100% (14/14), 1.33 KiB | 195.00 KiB/s, done.

Total 14 (delta 1), reused 0 (delta 0), pack-reused 0 (from 0)

remote: Resolving deltas: 100% (1/1), done.

To https://github.com/jcheca-main/oracle-database-lab..git

* [new branch] main -> main

branch 'main' set up to track 'origin/main'.

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (main)
```

```
$ git push -u origin fix/readme-title
```

error: src refspec fix/readme-title does not match any

error: failed to push some refs to 'https://github.com/jcheca-main/oracle-database-lab..git'

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (main)
```

```
$ git push -u origin fix/readme-subtitle
```

error: src refspec fix/readme-subtitle does not match any

error: failed to push some refs to 'https://github.com/jcheca-main/oracle-database-lab..git'

```
capit@Portatil_Auxi MINGW64 ~/oracle-database-lab (main)
```