

2刃·球头 2-Flute · Ball

De-sinking Prototyping Radius Helical Semi-Finishing Finishing Cutting Conditions

D≤0.1: 0~0.005
0.15≤D≤0.9: 0~0.007
1≤D≤3: 0~0.01
D≤4: 0~0.015

R公差 R tolerance R≤0.2: ±0.003
0.25≤R≤2: ±0.005

h5 0~-0.005 (mm)




高硬度材料加工用。超群的切削排出性能，可实现高效率加工。
For machining of high-hardness materials. Excellent chip removal performance enables high efficiency.

- ★ 高硬度材料用球头铣刀。最适用于精加工。
- ★ 适用于~65HRC的高硬度材料。
- ★ Ball End Milling Cutter For High Hardness Materials. Most Suitable For Finishing.
- ★ Suitable For ~65HRC High Hardness Materials.

产品代码 Code No.	规格型号 Spec Typ.	球头半径(R) Radius	颈长(l1) Under Neck Length	刃长(l) Length of Cut	外径(D) Dia	颈径(d2) Neck Dia	颈角(r) Neck Taper Angle	柄径(d) Shank Dia.	全长(L) Overall Length	定价 Retail Price
FX6MNB008002	R0.04x0.2L	R0.04	0.2	0.07	0.08	0.065	11°	4	45	
FX6MNB008003	R0.04x0.3L		0.3	0.07	0.08	0.065	11°	4	45	
FX6MNB008005	R0.04x0.5L		0.5	0.07	0.08	0.065	11°	4	45	
FX6MNB01002	R0.05x0.2L	R0.05	0.2	0.08	0.1	0.085	11°	4	45	
FX6MNB01003	R0.05x0.3L		0.3	0.08	0.1	0.085	11°	4	45	
FX6MNB01005	R0.05x0.5L		0.5	0.08	0.1	0.085	11°	4	45	
FX6MNB015003	R0.075x0.3L	R0.075	0.3	0.12	0.15	0.13	11°	4	45	
FX6MNB015005	R0.075x0.5L		0.5	0.12	0.15	0.13	11°	4	45	
FX6MNB0150075	R0.075x0.75L		0.75	0.12	0.15	0.13	11°	4	45	
FX6MNB01501	R0.075x1L	R0.1	1	0.12	0.15	0.13	11°	4	45	
FX6MNB02004	R0.1x0.4L		0.4	0.16	0.2	0.18	15°	4	45	
FX6MNB020075	R0.1x0.75L		0.75	0.16	0.2	0.18	15°	4	45	
FX6MNB0201	R0.1x1L	R0.1	1	0.16	0.2	0.18	15°	4	45	
FX6MNB02015	R0.1x1.5L		1.5	0.16	0.2	0.18	15°	4	45	
FX6MNB0202	R0.1x2L		2	0.16	0.2	0.18	15°	4	45	
FX6MNB03005	R0.15x0.5L	R0.15	0.5	0.24	0.3	0.27	15°	4	45	
FX6MNB0301	R0.15x1L		1	0.24	0.3	0.27	15°	4	45	
FX6MNB03015	R0.15x1.5L		1.5	0.24	0.3	0.27	15°	4	45	
FX6MNB0302	R0.15x2L	R0.15	2	0.24	0.3	0.27	15°	4	45	
FX6MNB03025	R0.15x2.5L		2.5	0.24	0.3	0.27	15°	4	45	
FX6MNB0303	R0.15x3L		3	0.24	0.3	0.27	15°	4	45	
FX6MNB0304	R0.15x4L	R0.15	4	0.24	0.3	0.27	15°	4	45	
FX6MNB0305	R0.15x5L		5	0.24	0.3	0.27	15°	4	45	
FX6MNB04005	R0.2x0.5L	R0.2	0.5	0.32	0.4	0.37	15°	4	45	
FX6MNB0401	R0.2x1L		1	0.32	0.4	0.37	15°	4	45	
FX6MNB04015	R0.2x1.5L		1.5	0.32	0.4	0.37	15°	4	45	
FX6MNB0402	R0.2x2L	R0.2	2	0.32	0.4	0.37	15°	4	45	
FX6MNB0403	R0.2x3L		3	0.32	0.4	0.37	15°	4	45	
FX6MNB0404	R0.2x4L		4	0.32	0.4	0.37	15°	4	45	
FX6MNB0406	R0.2x6L	R0.2	6	0.32	0.4	0.37	15°	4	45	

TYPE A:



产品代码 Code No.	规格型号 Spec Typ.	球头半径(R) Radius	颈长(l1) Under Neck Length	刃长(l) Length of Cut	外径(D) Dia	颈径(d2) Neck Dia	颈角(r) Neck Taper Angle	柄径(d) Shank Dia.	全长(L) Overall Length	定价 Retail Price
FX6MNB0501	R0.25x1L	R0.25	1	0.4	0.5	0.46	15°	4	45	
FX6MNB05015	R0.25x1.5L		1.5	0.4	0.5	0.46	15°	4	45	
FX6MNB0502	R0.25x2L		2	0.4	0.5	0.46	15°	4	45	
FX6MNB05025	R0.25x2.5L		2.5	0.4	0.5	0.46	15°	4	45	
FX6MNB0503	R0.25x3L		3	0.4	0.5	0.46	15°	4	45	
FX6MNB05035	R0.25x3.5L		3.5	0.4	0.5	0.46	15°	4	45	
FX6MNB0504	R0.25x4L		4	0.4	0.5	0.46	15°	4	45	
FX6MNB0505	R0.25x5L		5	0.4	0.5	0.46	15°	4	45	
FX6MNB0506	R0.25x6L		6	0.4	0.5	0.46	15°	4	45	
FX6MNB0507	R0.25x7L		7	0.4	0.5	0.46	15°	4	45	
FX6MNB0508	R0.25x8L	R0.3	8	0.4	0.5	0.46	15°	4	45	
FX6MNB0509	R0.25x9L		9	0.4	0.5	0.46	15°	4	45	
FX6MNB0510	R0.25x10L		10	0.4	0.5	0.46	15°	4	45	
FX6MNB0601	R0.3x1L		1	0.48	0.6	0.56	15°	4	45	
FX6MNB06015	R0.3x1.5L		1.5	0.48	0.6	0.56	15°	4	45	
FX6MNB0602	R0.3x2L		2	0.48	0.6	0.56	15°	4	45	
FX6MNB0603	R0.3x3L		3	0.48	0.6	0.56	15°	4	45	
FX6MNB0604	R0.3x4L		4	0.48	0.6	0.56	15°	4	45	
FX6MNB0605	R0.3x5L		5	0.48	0.6	0.56	15°	4	45	
FX6MNB0606	R0.3x6L		6	0.48	0.6	0.56	15°	4	45	
FX6MNB0607	R0.3x7L	R0.35	7	0.48	0.6	0.56	15°	4	45	
FX6MNB0608	R0.3x8L		8	0.48	0.6	0.56	15°	4	45	
FX6MNB0609	R0.3x9L		9	0.48	0.6	0.56	15°	4	45	
FX6MNB0610	R0.3x10L		10	0.48	0.6	0.56	15°	4	45	
FX6MNB0702	R0.35x2L		2	0.56	0.7	0.66	15°	4	45	
FX6MNB0704	R0.35x4L		4	0.56	0.7	0.66	15°	4	45	
FX6MNB0706	R0.35x6L		6	0.56	0.7	0.66	15°	4	45	
FX6MNB0708	R0.35x8L		8	0.56	0.7	0.66	15°	4	45	
FX6MNB0802	R0.4x2L		2	0.64	0.8	0.76	15°	4	45	
FX6MNB0803	R0.4x3L	R0.4	3	0.64	0.8	0.76	15°	4	45	
FX6MNB0804	R0.4x4L		4	0.64	0.8	0.76	15°	4	45	
FX6MNB0806	R0.4x6L		6	0.64	0.8	0.76	15°	4	45	
FX6MNB0808	R0.4x8L		8	0.64	0.8	0.76	15°	4	45	
FX6MNB0810	R0.4x10L		10	0.64	0.8	0.76	15°	4	45	
FX6MNB0902	R0.45x2L		2	0.72	0.9	0.86	15°	4	45	
FX6MNB0904	R0.45x4L	R0.45	4	0.72	0.9	0.86	15°	4	45	
FX6MNB0906	R0.45x6L		6	0.72	0.9	0.86	15°	4	45	
FX6MNB0908	R0.45x8L		8	0.72	0.9	0.86	15°	4	45	
FX6MNB1002	R0.5x2L		2	0.8	1	0.95	15°	4	50	
FX6MNB1003	R0.5x3L		3	0.8	1	0.95	15°	4	50	
FX6MNB1004	R0.5x4L		4	0.8	1	0.95	15°	4	50	
FX6MNB1005	R0.5x5L		5	0.8	1	0.95	15°	4	50	
FX6MNB1006	R0.5x6L		6	0.8	1	0.95	15°	4	50	
FX6MNB1008	R0.5x8L		8	0.8	1	0.95	15°	4	50	
FX6MNB1010	R0.5x10L	R0.5	10	0.8	1	0.95	15°	4	50	
FX6MNB1012	R0.5x12L		12	0.8	1	0.95	15°	4	50	
FX6MNB1016	R0.5x16L		16	0.8	1	0.95	15°	4	50	
FX6MNB1204	R0.6x4L		4	0.96	1.2	1.15	15°	4	50	
FX6MNB1206	R0.6x6L	R0.6	6	0.96	1.2	1.15	15°	4	50	
FX6MNB1208	R0.6x8L		8	0.96	1.2	1.15	15°	4	50	
FX6MNB1210	R0.6x10L		10	0.96	1.2	1.15	15°	4	50	
FX6MNB1212	R0.6x12L		12	0.96	1.2	1.15	15°	4	50	
FX6MNB1216	R0.6x16L		16	0.96	1.2	1.15	15°	4	50	

