

高硬钢用2刃长颈球头铣刀
Hardened Steel 2-Flute Long Neck Ball Endmills

- 碳素钢
Carbon Steel

○ 合金钢
Alloy Steel

○ 调质钢
Prehardened Steel

○ 高硬度钢
Hardened Steel

○ 高硬度钢
Hardened Steel

○ 高硬度钢
Hardened Steel

- 铜合金
Copper

- 长颈球刀
Long Neck Ball



产品代码 Code No.	规格型号 Spec Typ.	球头半径(R) Corner Radius	颈长(t1) Under Neck Length	刃长(t) Length of Cut	外径(D) Dia	颈径(d2) Neck Dia	颈角(r) Neck Taper Angle	柄径(d) Shank Dia.	全长(L) Overall Length	定价 Retail Price
FX6MNB1504	R0.75x4L	R0.75	4	1.2	1.5	1.45	15°	4	50	
FX6MNB1506	R0.75x6L		6	1.2	1.5	1.45	15°	4	50	
FX6MNB1508	R0.75x8L		8	1.2	1.5	1.45	15°	4	50	
FX6MNB1510	R0.75x10L		10	1.2	1.5	1.45	15°	4	50	
FX6MNB1512	R0.75x12L		12	1.2	1.5	1.45	15°	4	50	
FX6MNB1516	R0.75x16L	R0.8	16	1.2	1.5	1.45	15°	4	50	
FX6MNB1604	R0.8x4L		4	1.28	1.6	1.55	15°	4	50	
FX6MNB1608	R0.8x8L		8	1.28	1.6	1.55	15°	4	50	
FX6MNB1612	R0.8x12L		12	1.28	1.6	1.55	15°	4	50	
FX6MNB1616	R0.8x16L		16	1.28	1.6	1.55	15°	4	50	
FX6MNB1620	R0.8x20L	R0.9	20	1.28	1.6	1.55	15°	4	50	
FX6MNB1804	R0.9x4L		4	1.44	1.8	1.75	15°	4	50	
FX6MNB1808	R0.9x8L		8	1.44	1.8	1.75	15°	4	50	
FX6MNB1812	R0.9x12L		12	1.44	1.8	1.75	15°	4	50	
FX6MNB1816	R0.9x16L		16	1.44	1.8	1.75	15°	4	50	
FX6MNB1820	R0.9x20L	R1	20	1.44	1.8	1.75	15°	4	50	
FX6MNB2004	R1x4L		4	1.6	2	1.94	15°	4	50	
FX6MNB2006	R1x6L		6	1.6	2	1.94	15°	4	50	
FX6MNB2008	R1x8L		8	1.6	2	1.94	15°	4	50	
FX6MNB2010	R1x10L		10	1.6	2	1.94	15°	4	50	
FX6MNB2012	R1x12L		12	1.6	2	1.94	15°	4	50	
FX6MNB2016	R1x16L		16	1.6	2	1.94	15°	4	50	
FX6MNB2020	R1x20L		20	1.6	2	1.94	15°	4	65	
FX6MNB2025	R1x25L		25	1.6	2	1.94	15°	4	65	
FX6MNB2030	R1x30L		30	1.6	2	1.94	15°	4	65	
FX6MNB2506	R1.25x6L	R1.25	6	2	2.5	2.4	15°	4	50	
FX6MNB2508	R1.25x8L		8	2	2.5	2.4	15°	4	50	
FX6MNB2512	R1.25x12L		12	2	2.5	2.4	15°	4	50	
FX6MNB2516	R1.25x16L		16	2	2.5	2.4	15°	4	50	
FX6MNB2520	R1.25x20L		20	2	2.5	2.4	15°	4	50	
FX6MNB3006	R1.5x6L	R1.5	6	2.4	3	2.85	15°	4	50	
FX6MNB3008	R1.5x8L		8	2.4	3	2.85	15°	4	50	
FX6MNB3010	R1.5x10L		10	2.4	3	2.85	15°	4	50	
FX6MNB3012	R1.5x12L		12	2.4	3	2.85	15°	4	50	
FX6MNB3016	R1.5x16L		16	2.4	3	2.85	15°	4	50	
FX6MNB3020	R1.5x20L		20	2.4	3	2.85	15°	4	50	
FX6MNB3008L	R1.5x8L		8	2.4	3	2.85	15°	6	60	
FX6MNB3010L	R1.5x10L		10	2.4	3	2.85	15°	6	60	
FX6MNB3012L	R1.5x12L		12	2.4	3	2.85	15°	6	60	
FX6MNB3016L	R1.5x16L		16	2.4	3	2.85	15°	6	60	
FX6MNB3020L	R1.5x20L	R1.75	20	2.4	3	2.85	15°	6	60	
FX6MNB3025L	R1.5x25L		25	2.4	3	2.85	15°	6	75	
FX6MNB3030L	R1.5x30L		30	2.4	3	2.85	15°	6	75	
FX6MNB3510L	R1.75x10L		10	2.8	3.5	3.35	15°	6	60	
FX6MNB3515L	R1.75x15L		15	2.8	3.5	3.35	15°	6	60	
FX6MNB3520L	R1.75x20L	R2	20	2.8	3.5	3.35	15°	6	60	
FX6MNB3525L	R1.75x25L		25	2.8	3.5	3.35	15°	6	75	
FX6MNB3530L	R1.75x30L		30	2.8	3.5	3.35	15°	6	75	
FX6MNB4012L	R2x12L		12	3.2	4	3.8	15°	6	60	
FX6MNB4016L	R2x16L		16	3.2	4	3.8	15°	6	60	
FX6MNB4020L	R2x20L	R2	20	3.2	4	3.8	15°	6	60	
FX6MNB4025L	R2x25L		25	3.2	4	3.8	15°	6	75	
FX6MNB4030L	R2x30L		30	3.2	4	3.8	15°	6	75	

切削参数参考表
Recommended Milling Conditions

- 碳素钢
Carbon Steel

○ 合金钢
Alloy Steel

○ 调质钢
Prehardened Steel

○ 高硬度钢
Hardened Steel

○ 高硬度钢
Hardened Steel

○ 高硬度钢
Hardened Steel

- 铜合金
Copper

- 长颈球刀
Long Neck Ball

加工材料 Work Material		高速钢 High Speed Tool Steels SKH (~65HRC)				淬火钢 Hardened Steels SKD11 (~62HRC)				淬火钢 Hardened Steels SKD61 · STAVAX · HPM-38 (~52HRC)			
球头半径(R) Radius	颈长(t1) Under Neck Length	主轴转速 Spindle Speed	进给速度 Feed	切深量 Depth of Cut		主轴转速 Spindle Speed	进给速度 Feed	切深量 Depth of Cut		主轴转速 Spindle Speed	进给速度 Feed	切深量 Depth of Cut	
		min-1	mm/min	ap mm	ae mm	min-1	mm/min	ap mm	ae mm	min-1	mm/min	ap mm	ae mm
0.04	0.2	40,000	50	0.001	0.002	40,000	80	0.001	0.004	40,000	100	0.002	0.004
	0.3	40,000	30	0.001	0.002	40,000	60	0.001	0.004	40,000	80	0.001	0.004
	0.5	40,000	10	0.001	0.002	40,000	40	0.001	0.003	40,000	60	0.001	0.003
0.05	0.2	40,000	70	0.002	0.001	40,000	100	0.002	0.005	40,000	120	0.003	0.005
	0.3	40,000	50	0.002	0.003	40,000	70	0.002	0.005	40,000	100	0.003	0.005
	0.5	40,000	30	0.001	0.002	40,000	50	0.001	0.003	40,000	70	0.002	0.003
0.075	0.3	40,000	100	0.002	0.003	40,000	150	0.002	0.005	40,000	180	0.003	0.005
	0.5	40,000	70	0.002	0.003	40,000	120	0.002	0.005	40,000	150	0.003	0.005
	0.75	40,000	50	0.001	0.002	40,000	80	0.002	0.004	40,000	11	0.003	0.004
0.1	1	40,000	30	0.001	0.002	40,000	50	0.001	0.003	40,000	70	0.002	0.003
	0.4	40,000	190	0.003	0.003	40,000	290	0.005	0.005	40,000	330	0.009	0.01
	0.75	40,000	150	0.002	0.003	40,000	200	0.003	0.005	40,000	280	0.005	0.01
0.15	1	40,000	120	0.001	0.002	40,000	160	0.002	0.003	40,000	250	0.003	0.005
	1.5	40,000	80	0.001	0.002	40,000	120	0.002	0.003	40,000	150	0.003	0.005
	2	40,000	50	0.001	0.001	40,000	80	0.001	0.002	40,000	100	0.002	0.003
0.2	0.5	40,000	280	0.003	0.005	40,000	300	0.007	0.01	40,000	350	0.01	0.015
	1	40,000	200	0.003	0.005	40,000	250	0.005	0.007	40,000	320	0.007	0.01
	1.5	40,000	120	0.002	0.003	40,000	180	0.003	0.005	40,000	230	0.005	0.007
0.25	2	40,000	90	0.002	0.002	40,000	120	0.002	0.003	40,000	150	0.003	0.005
	2.5	40,000	70	0.001	0.001	40,000	80	0.001	0.002	40,000	100	0.002	0.003
	3	40,000	60	0.001	0.001	40,000	70	0.001	0.002	40,000	80	0.001	0.003
0.3	4	40,000	40	0.001	0.001	40,000	50	0.001	0.001	40,000	60	0.001	0.002
	5	40,000	20	0.001	0.001	40,000	30	0.001	0.001	40,000	40	0.001	0.001
	0.5	40,000	580	0.009	0.02	40,000	720	0.03	0.03	40,000	800	0.03	0.05
0.35	1	40,000	400	0.005	0.01	40,000	500	0.01	0.02	40,000	620	0.01	0.03
	1.5	40,000	300	0.005	0.007	40,000	380	0.01	0.01	40,000	500	0.01	0.02
	3	40,000	200	0.003	0.005	40,000	240	0.005	0.007	40,000	300	0.007	0.01
0.4	4	30,000	90	0.002	0.003	30,000	120	0.003	0.003	30,000	160	0.005	0.005
	6	30,000	30	0.001	0.001	30,000	40	0.001	0.001	30,000	50	0.001	0.002
	1	40,000	650	0.01	0.02	40,000	860	0.02	0.03	40,000	1,000	0.03	0.05
0.45	1.5	40,000	520	0.007	0.02	40,000	720	0.01	0.03	40,000	850	0.02	0.05
	2	40,000	400	0.007	0.01	40,000	650	0.01	0.02	40,000	720	0.02	0.03
	2.5	40,000	360	0.005	0.007	40,000	530	0.007	0.01	40,000	600	0.01	0.02
0.5	3	40,000	320	0.005	0.007	40,000	420	0.007	0.01	40,000	500	0.01	0.02
	3.5	40,000	280	0.003	0.005	40,000	360	0.005	0.007	40,000	420	0.007	0.01
	4	40,000	260	0.003	0.005	40,000	300	0.005	0.007	40,000	350	0.007	0.01
0.55	5	33,000	180	0.002	0.003	33,000	200	0.003	0.003	33,000	240	0.005	0.005
	6	30,000	70	0.001	0.002	30,000	80	0.001	0.002	30,000	120	0.002	0.003
	7	30,000	60	0.001	0.002	30,000	70	0.001	0.002	30,000	90	0.002	0.002
0.6	8	30,000	50	0.001	0.002	30,000	60	0.001	0.002	30,000	75	0.002	0.002
	9	20,000	35	0.001	0.001	25,000	50	0.001	0.002	25,000	60	0.001	0.002
	10	20,000	20	0.001	0.001	20,000	30	0.001	0.002	20,000	40	0.001	0.002
0.65	1	30,000	720	0.02	0.05	40,000	1,000	0.03	0.06	40,000	1,400	0.05	0.1
	1.5	30,000	720	0.02	0.05	40,000	1,000	0.03	0.06	40,000	1,400	0.05	0.1
	2	30,000	720	0.02	0.05	40,000	1,000	0.03	0.06	40,000	1,400	0.05	0.1
0.7	3	30,000	640	0.02	0.03	40,000	840	0.02	0.04	40,000	1,200	0.03	0.05
	4	30,000	480	0.01	0.02	40,000	620	0.01	0.03	40,000	1,000	0.02	0.03
	5	30,000	400	0.007	0.01	30,000	500	0.007	0.015	30,000	720	0.01	0.02
0.75	6	30,000	320	0.004	0.006	30,000	380	0.005	0.007	30,000	500	0.007	0.01
	7	20,000	260	0.003	0.003	25,000	300	0.003	0.005	25,000	400	0.005	0.007
	8	20,000	220	0.002	0.003	25,000	260	0.003	0.003	25,000	320	0.003	0.005
0.8	9	20,000	160	0.001	0.002	25,000	220	0.003	0.002	25,000	280	0.003	0.003
	10	18,000	100	0.001	0.002	20,000	120	0.002	0.002	20,000	150	0.002	0.003
	2	30,000	1,000	0.03	0.07	40,000	1,300	0.05	0.08	40,000	1,600	0.07	0.1
0.85	4	30,000	600	0.015	0.02	40,000	820	0.03	0.04	40,000	1,300	0.04	0.06
	6	25,000	420	0.006	0.01	30,000	500	0.01	0.015	30,000	800	0.01	0.03
	8	20,000	250	0.004	0.006	20,000	380	0.005	0.006	25,000	520	0.006	0.01