

铜·铝合金用4刃圆鼻铣刀

Copper · Aluminum Alloy 4-Flute Corner Radius Endmills

4刃·带R角 4-Flute·Corner Radius

平面 Planing

侧切 Side Cutting

槽切 Slotting

封底 Die-sinking

曲面 Profiling

R Radius

螺旋 Helical

粗加工 Roughing

半精加工 Semi-Finishing

精加工 Finishing

切削条件 Cutting Conditions

外径公差 Dia.tolerance

1≤D≤3: 0~-0.01
4≤D≤10: 0~-0.015

公差 r tolerance

±0.005


h5

0~-0.005


(mm)



TYPE A:




TYPE B:



- 针对铜电极加工用的球头铣刀。
- 采用优化的刀刃形状和tac涂层，可确保长时间进行持续稳定的高品质加工。
- Ball end milling cutter for copper electrode machining.
- High quality and stable milling performance with long tool life by optimized design and tac COATING.

产品代码 Code No.	规格型号 Spec Typ.	外径(D) Dia.	角半径(R) Corner Radius	刃长(l) Length of Cut	颈角(r) Neck Taper Angle	柄径(d) Shank Dia.	全长(L) Overall Length	形状 Type	定价 Retail Price
FX3R01005	1R0.05x3L	1	R0.05	3	12°	4	50	A	
FX3R01005L	1R0.05x4L	1	R0.05	4	12°	4	50	A	
FX3R0101	1R0.1x3L	1	R0.1	3	12°	4	50	A	
FX3R0101L	1R0.1x4L	1	R0.1	4	12°	4	50	A	
FX3R0102	1R0.2x3L	1	R0.2	3	12°	4	50	A	
FX3R0102L	1R0.2x4L	1	R0.2	4	12°	4	50	A	
FX3R0151	1.5R0.1x4.5L	1.5	R0.1	4.5	12°	4	50	A	
FX3R0152	1.5R0.2x4.5L	1.5	R0.2	4.5	12°	4	50	A	
FX3R0201	2R0.1x6L	2	R0.1	6	12°	4	50	A	
FX3R0202	2R0.2x6L	2	R0.2	6	12°	4	50	A	
FX3R0205	2R0.5x6L	2	R0.5	6	12°	4	50	A	
FX3R0302	3R0.2x9L	3	R0.2	9	12°	4	50	A	
FX3R0302D3	3R0.2x9L	3	R0.2	9	-	3	50	B	
FX3R0303	3R0.3x9L	3	R0.3	9	12°	4	50	A	
FX3R0303D3	3R0.3x9L	3	R0.3	9	-	3	50	B	
FX3R0305	3R0.5x9L	3	R0.5	9	12°	4	50	A	
FX3R0305D3	3R0.5x9L	3	R0.5	9	-	3	50	B	
FX3R0401	4R0.1x12L	4	R0.1	12	-	4	50	B	
FX3R0402	4R0.2x12L	4	R0.2	12	-	4	50	B	
FX3IR0402	4R0.2x12L	4	R0.2	12	-	4	75	B	
FX3R0403	4R0.3x12L	4	R0.3	12	-	4	50	B	
FX3R0405	4R0.5x12L	4	R0.5	12	-	4	50	B	
FX3IR0405	4R0.5x12L	4	R0.5	12	-	4	75	B	
FX3R0602	6R0.2x16L	6	R0.2	16	-	6	50	B	
FX3IR0602	6R0.2x18L	6	R0.2	18	-	6	75	B	
FX3JR0602	6R0.2x18L	6	R0.2	18	-	6	100	B	
FX3R0605	6R0.5x16L	6	R0.5	16	-	6	50	B	
FX3R0605L	6R0.5x16L	6	R0.5	16	-	6	60	B	
FX3IR0605	6R0.5x18L	6	R0.5	18	-	6	75	B	
FX3JR0605	6R0.5x18L	6	R0.5	18	-	6	100	B	
FX3R0805	8R0.5x22L	8	R0.5	22	-	8	60	B	
FX3IR0805	8R0.5x24L	8	R0.5	24	-	8	75	B	
FX3JR0805	8R0.5x24L	8	R0.5	24	-	8	100	B	
FX3R1005	10R0.5x30L	10	R0.5	30	-	10	75	B	
FX3JR1005	10R0.5x30L	10	R0.5	30	-	10	100	B	
FX3R1010	10R1x30L	10	R1	30	-	10	75	B	
FX3JR1010	10R1x30L	10	R1	30	-	10	100	B	

加工材料 Work Material	铜合金 Copper		铝合金 Aluminum Alloy	
切削速度 Cutting Speed	60m/min		80～150m/min	
外径 Dia.	主轴转速 Spindle Speed	进给速度 Feed	主轴转速 Spindle Speed	进给速度 Feed
	min-1	mm/min	min-1	mm/min
1	19,000	150	48,000	800
1.5	13,000	150	32,000	1,000
2	9,600	150	24,000	1,000
3	6,400	200	16,000	1,000
4	4,800	200	12,000	1,000
6	3,200	200	8,000	1,000
8	2,400	200	6,000	1,000
10	1,900	200	4,800	1,000
切深量 Depth of Cut (D:刃 径Dia.)	侧面 Side Milling 			
备注 Notes	※ 建议使用油冷却方式。 ※ 请以相同的比率调整主轴转速和进给速度。 ※ 严禁用于钢。 ※ Use cutting fluid. ※ Adjust both spindle speed and feed at the same rate. ※ Don't use for cutting steels.			

切削参数参考表

Recommended Milling Conditions