

铜·铝合金用2刃长颈平底铣刀

Copper · Aluminum Alloy 2-Flute Long Neck Square Endmills

2刃·平底铣刀2-Flute · Square

侧切Side Cutting

槽切Slotting

微细加工Micro Finishing

精加工Finishing

抗振抑振Vib. Min.

切削条件Cutting Conditions

外径公差Tolerance

$D \leq 0.1: 0 \sim -0.005$
 $0.15 \leq D \leq 0.9: 0 \sim -0.007$
 $1 \leq D \leq 2: 0 \sim -0.01$

h5


0 ~ -0.005

(mm)


高耐溶着性能。最适合铝合金·铜的加工。tac涂层。
High welding resistance makes it ideal for machining aluminum alloys and copper.tac coating.



TYPE A:



TYPE B:



- 针对铜电极加工用的平底铣刀。
- 采用锋利度和精加工表面品质兼具的高螺旋角，可抑制加工面产生水平条纹。
- 采用优化的刀刃形状和tac涂层，可确保长时间进行持续稳定的高品质加工。
- Flat end milling cutter for copper electrode machining.
- The high spiral Angle with both edge sharpness and finishing surface quality can restrain the horizontal fringe.
- High quality and stable milling performance with long tool life by optimized design and tac COATING.

- 铝合金 Aluminum Alloy
- 铜合金 Copper
- 树脂 Resin

长颈平底
Long Neck
Square

产品代码 Code No.	规格型号 Spec Typ.	外径(D) Dia.	颈长(t1) Under Neck Length	刃长(t) Length of Cut	颈径(d2) Neck Dia.	颈角(r) Neck Taper Angle	柄径(d) Shank Dia.	全长(L) Overall Length	价格 Retail Price
FX3NE01005	0.1x0.5L	0.1	0.5	0.2	0.085	10+20°	4	50	
FX3NE0101	0.1x1L		1	0.2	0.085	10+20°	4	50	
FX3NE01015	0.1x1.5L		1.5	0.2	0.085	10+20°	4	50	
FX3NE0102	0.1x2L		2	0.2	0.085	10+20°	4	50	
FX3NE01505	0.15x0.5L	0.15	0.5	0.23	0.13	10+20°	4	50	
FX3NE01506	0.15x0.6L		0.6	0.23	0.13	10+20°	4	50	
FX3NE01501	0.15x1L		1	0.23	0.13	10+20°	4	50	
FX3NE015015	0.15x1.5L		1.5	0.23	0.13	10+20°	4	50	
FX3NE01502	0.15x2L	0.2	2	0.23	0.13	10+20°	4	50	
FX3NE015025	0.15x2.5L		2.5	0.23	0.13	10+20°	4	50	
FX3NE0201	0.2x1L		1	0.3	0.18	10+20°	4	50	
FX3NE02015	0.2x1.5L		1.5	0.3	0.18	10+20°	4	50	
FX3NE0202	0.2x2L	0.25	2	0.3	0.18	10+20°	4	50	
FX3NE0203	0.2x3L		3	0.3	0.18	10+20°	4	50	
FX3NE0204	0.2x4L		4	0.3	0.18	10+20°	4	50	
FX3NE02501	0.25x1L		1	0.4	0.23	10+20°	4	50	
FX3NE025015	0.25x1.5L	0.3	1.5	0.4	0.23	10+20°	4	50	
FX3NE02502	0.25x2L		2	0.4	0.23	10+20°	4	50	
FX3NE02503	0.25x3L		3	0.4	0.23	10+20°	4	50	
FX3NE02504	0.25x4L		4	0.4	0.23	10+20°	4	50	
FX3NE0301	0.3x1L	0.3	1	0.5	0.27	10+20°	4	50	
FX3NE03015	0.3x1.5L		1.5	0.5	0.27	10+20°	4	50	
FX3NE0302	0.3x2L		2	0.5	0.27	10+20°	4	50	
FX3NE03025	0.3x2.5L		2.5	0.5	0.27	10+20°	4	50	
FX3NE0303	0.3x3L		3	0.5	0.27	10+20°	4	50	
FX3NE0304	0.3x4L		4	0.5	0.27	10+20°	4	50	
FX3NE0306	0.3x6L		6	0.5	0.27	10+20°	4	50	



产品代码 Code No.	规格型号 Spec Typ.	外径(D) Dia.	颈长(t1) Under Neck Length	刃长(t) Length of Cut	颈径(d2) Neck Dia.	颈角(r) Neck Taper Angle	柄径(d) Shank Dia.	全长(L) Overall Length	价格 Retail Price
FX3NE0402	0.4x2L	0.4	2	0.6	0.37	10+20°	4	50	
FX3NE0403	0.4x3L		3	0.6	0.37	10+20°	4	50	
FX3NE0404	0.4x4L		4	0.6	0.37	10+20°	4	50	
FX3NE0406	0.4x6L		6	0.6	0.37	10+20°	4	50	
FX3NE0502	0.5x2L	0.5	2	0.7	0.46	10+20°	4	50	
FX3NE0503	0.5x3L		3	0.7	0.46	10+20°	4	50	
FX3NE0504	0.5x4L		4	0.7	0.46	10+20°	4	50	
FX3NE0505	0.5x5L		5	0.7	0.46	10+20°	4	50	
FX3NE0506	0.5x6L		6	0.7	0.46	10+20°	4	50	
FX3NE0508	0.5x8L		8	0.7	0.46	10+20°	4	50	
FX3NE0510	0.5x10L		10	0.7	0.46	10+20°	4	50	
FX3NE0512	0.5x12L	0.6	12	0.7	0.46	10+20°	4	50	
FX3NE0602	0.6x2L		2	0.9	0.56	10+20°	4	50	
FX3NE0603	0.6x3L		3	0.9	0.56	10+20°	4	50	
FX3NE0604	0.6x4L		4	0.9	0.56	10+20°	4	50	
FX3NE0606	0.6x6L		6	0.9	0.56	10+20°	4	50	
FX3NE0608	0.6x8L		8	0.9	0.56	10+20°	4	50	
FX3NE0702	0.7x2L	0.7	2	1	0.66	10+20°	4	50	
FX3NE0704	0.7x4L		4	1	0.66	10+20°	4	50	
FX3NE0706	0.7x6L		6	1	0.66	10+20°	4	50	
FX3NE0708	0.7x8L		8	1	0.66	10+20°	4	50	
FX3NE0802	0.8x2L	0.8	2	1.2	0.76	10+20°	4	50	
FX3NE0803	0.8x3L		3	1.2	0.76	10+20°	4	50	
FX3NE0804	0.8x4L		4	1.2	0.76	10+20°	4	50	
FX3NE0806	0.8x6L		6	1.2	0.76	10+20°	4	50	
FX3NE0808	0.8x8L	1	8	1.2	0.76	10+20°	4	50	
FX3NE0810A	0.8x10L		10	1.2	0.76	10+20°	4	50	
FX3NE1004A	1x4L		4	1.5	0.95	12°	4	50	
FX3NE1006A	1x6L		6	1.5	0.95	12°	4	50	
FX3NE1008A	1x8L	1.5	8	1.5	0.95	12°	4	50	
FX3NE1010A	1x10L		10	1.5	0.95	12°	4	50	
FX3NE1012A	1x12L		12	1.5	0.95	12°	4	50	
FX3NE1016A	1x16L		16	1.5	0.95	12°	4	50	
FX3NE1506A	1.5x6L	2	6	2.3	1.45	12°	4	50	
FX3NE1508A	1.5x8L		8	2.3	1.45	12°	4	50	
FX3NE1510A	1.5x10L		10	2.3	1.45	12°	4	50	
FX3NE1512A	1.5x12L		12	2.3	1.45	12°	4	50	
FX3NE1516A	1.5x16L	2	16	2.3	1.45	12°	4	50	
FX3NE1520A	1.5x20L		20	2.3	1.45	12°	4	50	
FX3NE2008A	2x8L		8	3	1.94	12°	4	50	
FX3NE2010A	2x10L		10	3	1.94	12°	4	50	
FX3NE2012A	2x12L	2	12	3	1.94	12°	4	50	
FX3NE2016A	2x16L		16	3	1.94	12°	4	50	
FX3NE2020A	2x20L		20	3	1.94	12°	4	50	



铜·铝合金用2刃长颈平底铣刀

Copper · Aluminum Alloy 2-Flute Long neck Square Endmills

- 铝合金 Aluminum Alloy
- 铜合金 Copper
- 树脂 Resin

长颈平底
Long Neck
Square