

铜·铝合金用4刃长颈圆鼻铣刀
Copper · Aluminum Alloy 4-Flute Long Neck Corner Radius Endmills

4刃·带R角4-Flute · Corner Radius

平面Planing

侧切Side Cutting

槽切Slotting

封底Die-sinking

曲面Profiling

R半径Radius

螺旋Helical

粗加工Roughing

半精加工Semi-Finishing

精加工Finishing

切削条件Cutting Conditions

外径公差
1≤D≤3: 0~-0.01
D≤4: 0~-0.015

长度公差
±0.005

精度
h5 0~-0.005 (mm)

高耐溶着性能。最适合铝合金·铜的加工。tac涂层。
High welding resistance makes it ideal for machining aluminum alloys and copper.tac coating.



- 针对铜电极加工用的球头铣刀。
- 采用优化的刀刃形状和tac涂层，可确保长时间进行持续稳定的高品质加工。
- Ball end mill cutter for copper electrode machining.
- High quality and stable milling performance with long tool life by optimized design and tac COATING.

产品代码 Code No.	规格型号 Spec Typ.	外径(D) Dia.	半径角(R) Corner Radius	颈长(l1) Under Neck Length	刃长(l) Length of Cut	颈径(d2) Neck Dia.	颈角(r) Neck Taper Angle	柄径(d) Shank Dia.	全长(L) Overall Length	定价 Retail Price
FX3NR1004005	1R0.05x4L	1	R0.05	4	1.5	0.95	12°	50	4	
FX3NR1006005	1R0.05x6L			6	1.5	0.95	12°	50	4	
FX3NR1008005	1R0.05x8L			8	1.5	0.95	12°	50	4	
FX3NR1010005	1R0.05x10L			10	1.5	0.95	12°	50	4	
FX3NR100401	1R0.1x4L		R0.1	4	1.5	0.95	12°	50	4	
FX3NR100601	1R0.1x6L			6	1.5	0.95	12°	50	4	
FX3NR100801	1R0.1x8L			8	1.5	0.95	12°	50	4	
FX3NR101001	1R0.1x10L			10	1.5	0.95	12°	50	4	
FX3NR100402	1R0.2x4L		R0.2	4	1.5	0.95	12°	50	4	
FX3NR100502	1R0.2x5L			5	1.5	0.95	12°	50	4	
FX3NR100602	1R0.2x6L			6	1.5	0.95	12°	50	4	
FX3NR100802	1R0.2x8L			8	1.5	0.95	12°	50	4	
FX3NR101002	1R0.2x10L	1.5	R0.2	10	1.5	0.95	12°	50	4	
FX3NR101202	1R0.2x12L			12	1.5	0.95	12°	50	4	
FX3NR150602	1.5R0.2x6L		R0.2	6	2.3	1.45	12°	50	4	
FX3NR150802	1.5R0.2x8L			8	2.3	1.45	12°	50	4	
FX3NR151002	1.5R0.2x10L			10	2.3	1.45	12°	50	4	
FX3NR151202	1.5R0.2x12L			12	2.3	1.45	12°	50	4	
FX3NR151602	1.5R0.2x16L		R0.1	16	2.3	1.45	12°	50	4	
FX3NR200801	2R0.1x8L			8	3	1.94	12°	50	4	
FX3NR201001	2R0.1x10L			10	3	1.94	12°	50	4	
FX3NR201201	2R0.1x12L			12	3	1.94	12°	50	4	

铜·铝合金用4刃长颈圆鼻铣刀
Copper · Aluminum Alloy 4-Flute Long Neck Corner Radius Endmills

产品代码 Code No.	规格型号 Spec Typ.	外径(D) Dia.	半径角(R) Corner Radius	颈长(l1) Under Neck Length	刃长(l) Length of Cut	颈径(d2) Neck Dia.	颈角(r) Neck Taper Angle	柄径(d) Shank Dia.	全长(L) Overall Length	定价 Retail Price
FX3NR200802	2R0.2x8L	2	R0.2	8	3	1.94	12°	50	4	
FX3NR201002	2R0.2x10L			10	3	1.94	12°	50	4	
FX3NR201202	2R0.2x12L			12	3	1.94	12°	50	4	
FX3NR201602	2R0.2x16L			16	3	1.94	12°	50	4	
FX3NR200805	2R0.5x8L		R0.5	8	3	1.94	12°	50	4	
FX3NR201005	2R0.5x10L			10	3	1.94	12°	50	4	
FX3NR201205	2R0.5x12L			12	3	1.94	12°	50	4	
FX3NR201605	2R0.5x16L			16	3	1.94	12°	50	4	
FX3NR202005	2R0.5x20L		3	20	3	1.94	12°	50	4	
FX3NR031002	3R0.2x10L		R0.2	10	4.5	2.85	12°	50	4	
FX3NR301202	3R0.2x12L			12	4.5	2.85	12°	50	4	
FX3NR301402	3R0.2x14L			14	4.5	2.85	12°	50	4	
FX3NR301602	3R0.2x16L			16	4.5	2.85	12°	50	4	
FX3NR301202L	3R0.2x12L		R0.2	12	4.5	2.85	12°	60	6	
FX3NR301602L	3R0.2x16L			16	4.5	2.85	12°	60	6	
FX3NR302002L	3R0.2x20L			20	4.5	2.85	12°	60	6	
FX3NR301203	3R0.3x12L		R0.3	12	4.5	2.85	12°	50	4	
FX3NR301603	3R0.3x16L			16	4.5	2.85	12°	50	4	
FX3NR301203L	3R0.3x12L			12	4.5	2.85	12°	60	6	
FX3NR301603L	3R0.3x16L			16	4.5	2.85	12°	60	6	
FX3NR302003L	3R0.3x20L	4	R0.5	20	4.5	2.85	12°	60	6	
FX3NR301005	3R0.5x10L			10	4.5	2.85	12°	50	4	
FX3NR301205	3R0.5x12L			12	4.5	2.85	12°	50	4	
FX3NR301605	3R0.5x16L			16	4.5	2.85	12°	50	4	
FX3NR301205L	3R0.5x12L		R0.2	12	4.5	2.85	12°	60	6	
FX3NR301605L	3R0.5x16L			16	4.5	2.85	12°	60	6	
FX3NR302005L	3R0.5x20L			20	4.5	2.85	12°	60	6	
FX3NR401202L	4R0.2x12L			12	6	3.8	12°	60	6	
FX3NR401602L	4R0.2x16L		R0.2	16	6	3.8	12°	60	6	
FX3NR402002L	4R0.2x20L			20	6	3.8	12°	60	6	
FX3NR401603L	4R0.3x16L		R0.3	16	6	3.8	12°	60	6	
FX3NR402003L	4R0.3x20L			20	6	3.8	12°	60	6	
FX3NR401205L	4R0.5x12L	4	R0.5	12	6	3.8	12°	60	6	
FX3NR401605L	4R0.5x16L			16	6	3.8	12°	60	6	
FX3NR402005L	4R0.5x20L			20	6	3.8	12°	60	6	