

Class 6 : R functions

Jaimy Chung (PID:A16366976)

2024-01-25

R Functions

Functions are how we get stuff done. We call functions to do everything useful in R.

One cool thing about R is that it makes writing your own functions comparatively easy.

All functions in R have at least three things:

- A **name** (we get to pick this)
- One or more **input arguments** (the input to our function)
- **The body** (lines of code that do the work)

```
funname <- function(input1, input2) {  
  # The body with R code  
}
```

Let's write a silly first function to add two numbers:

```
x <- 5  
y <- 1  
x + y
```

```
[1] 6
```

```
addme <- function(x, y=1) {  
  x + y  
}
```

```
addme(100,100)
```

```
[1] 200
```

```
addme(10)
```

```
[1] 11
```

Lab for today

Write a function to grade student work from class.

Start with a simplified version of the problem:

```
# Example input vectors to start with
student1 <- c(100, 100, 100, 100, 100, 100, 100, 90)
student2 <- c(100, NA, 90, 90, 90, 90, 97, 80)
student3 <- c(90, NA, NA, NA, NA, NA, NA, NA)
```

Let's just find the average.

```
mean(student1)
```

```
[1] 98.75
```

```
mean(student2, na.rm = TRUE)
```

```
[1] 91
```

```
mean(student3, na.rm = TRUE)
```

```
[1] 90
```

This is not fair - there is no way student 3 should have a mean of 90!

Come back to this NA problem. But things worked for 'student1'.

We want to drop the lowest score before getting the 'mean()'

How do I find the lowest (minimum) score?

```
student1
```

```
[1] 100 100 100 100 100 100 100 100 90
```

```
min(student1)
```

```
[1] 90
```

I found the 'which.min()' function. Maybe this is more useful?

```
which.min(student1)
```

```
[1] 8
```

Cool - it is the 8th element of the vector that has the lowest score. Can I remove this one?

```
student1[which.min(student1)]
```

```
[1] 90
```

We can use the wee minus trick for indexing.

```
x <- 1:5  
x[-3]
```

```
[1] 1 2 4 5
```

Now put these bits of knowledge together to make some code that identifies and drops the lowest score (element of the input vector) and then calculates the mean.

```
#Find the lowest score  
ind <- which.min(student1)  
#Remove highest score and find the mean  
mean(student1[-ind])
```

```
[1] 100
```

```
mean(student1[-which.min(student1)])
```

```
[1] 100
```

Use a common shortcut and use 'x' as my input

```
x <- student1  
mean(x[-which.min(x)])
```

```
[1] 100
```

We still have the problem of missing values.

One idea is to replace NA values with zero.

```
y <- 1:5  
y[y == 3] <- 10000  
y
```

```
[1]      1      2 10000      4      5
```

Bummer, this is no good...

```
y <- c(1, 2, NA, 4, 5)  
y == NA
```

```
[1] NA NA NA NA NA
```

```
y
```

```
[1] 1 2 NA 4 5
```

```
is.na(y)
```

```
[1] FALSE FALSE  TRUE FALSE FALSE
```

How can I remove the NA elements from the vector? I first need to flip the TRUE elements

```
!c(F,F,F)
```

```
[1] TRUE TRUE TRUE
```

```
#y[is.na(y)]
```

```
y[ !is.na(y)]
```

```
[1] 1 2 4 5
```

```
y[is.na(y)] <- 10000  
y
```

```
[1]      1      2 10000      4      5
```

Ok lets solve this:

```
x <- student3  
  
#Change NA values to zero  
x[is.na(x)] <- 0  
#Find and remove min values to get mean  
mean(x[-which.min(x)])
```

```
[1] 12.85714
```

Last step now that I have my working code snippet is to make my 'grade()' function.

```
grade <- function(x) {  
  #Change NA values to zero  
  x[is.na(x)] <- 0  
  #Find and remove min values to get mean  
  mean(x[-which.min(x)])  
}
```

```
grade(student1)
```

```
[1] 100
```

```
grade(student2)
```

```
[1] 91
```

```
grade(student3)
```

```
[1] 12.85714
```

Q1. Write a function `grade()` to determine an overall grade from a vector of student homework assignment scores dropping the lowest single score. If a student misses a homework (i.e. has an NA value) this can be used as a score to be potentially dropped. Your final function should be adequately explained with code comments and be able to work on an example class gradebook such as this one in CSV format: “<https://tinyurl.com/gradeinput>” [3pts]

```
grade <- function(x) {  
  #Change NA values to zero  
  x[is.na(x)] <- 0  
  #Find and remove min values to get mean  
  mean(x[-which.min(x)])  
}
```

Now read the online gradebook(CSV file)

```
url<- "https://tinyurl.com/gradeinput"  
gradebook <- read.csv(url,row.names = 1)  
head(gradebook)
```

	hw1	hw2	hw3	hw4	hw5
student-1	100	73	100	88	79
student-2	85	64	78	89	78
student-3	83	69	77	100	77
student-4	88	NA	73	100	76
student-5	88	100	75	86	79
student-6	89	78	100	89	77

```
results <- apply(gradebook, 1, grade)  
results
```

student-1	student-2	student-3	student-4	student-5	student-6	student-7
91.75	82.50	84.25	84.25	88.25	89.00	94.00
student-8	student-9	student-10	student-11	student-12	student-13	student-14
93.75	87.75	79.00	86.00	91.75	92.25	87.75
student-15	student-16	student-17	student-18	student-19	student-20	
78.75	89.50	88.00	94.50	82.75	82.75	

Q2. Using your `grade()` function and the supplied gradebook, Who is the top scoring student overall in the gradebook? [3pts]

```
max(results)
```

```
[1] 94.5
```

```
which.max(results)
```

```
student-18
18
```

Student 18

Q3. From your analysis of the gradebook, which homework was toughest on students (i.e. obtained the lowest scores overall)? [2pts]

```
apply(gradebook,2,mean,na.rm=TRUE)
```

hw1	hw2	hw3	hw4	hw5
89.00000	80.88889	80.80000	89.63158	83.42105

```
which.min(apply(gradebook,2,mean,na.rm=TRUE))
```

```
hw3
3
```

```
which.min(apply(gradebook,2,sum,na.rm=TRUE))
```

```
hw2
2
```

hw2

Q4. Optional Extension: From your analysis of the gradebook, which homework was most predictive of overall score (i.e. highest correlation with average grade score)? [1pt]

```
# Make all (or mask) NA to zero
mask <- gradebook
mask[is.na(mask)] <- 0
#mask
```

We can use the ‘cor()’ function for correlation analysis.

```
cor(mask$hw5, results)
```

```
[1] 0.6325982
```

```
cor(mask$hw4, results)
```

```
[1] 0.3810884
```

```
cor(mask$hw3, results)
```

```
[1] 0.3042561
```

```
cor(mask$hw2, results)
```

```
[1] 0.176778
```

```
cor(mask$hw1, results)
```

```
[1] 0.4250204
```

I need to use ‘apply()’ function to run this analysis over the whole course (i.e. masked gradebook)

```
apply(mask, 2, cor, results)
```


hw1	hw2	hw3	hw4	hw5
0.4250204	0.1767780	0.3042561	0.3810884	0.6325982

Hw5 was most predictive as it has the highest correlation w the avg grade score.

Q5. Make sure you save your Quarto document and can click the “Render” (or Rmark-down”Knit”) button to generate a PDF format report without errors. Finally, submit your PDF to gradescope. [1pt]