

Formal Methods and Functional Programming

Spring 2021

Jean-Claude Graf

September 20, 2021

Contents

I. Functional Programming	3
1. Introduction	4
1.1. Functional Programming	4
1.2. Haskell	4
1.2.1. Syntax	4
1.2.2. Types	5
1.2.3. Input/Output	6
2. Natural Deduction	7
2.1. Natural Deduction	7
2.2. Propositional Logic	7
2.2.1. Syntax	7
2.2.2. Semantics	7
2.2.3. Requirements for Deductive System	7
2.2.4. Natural Deduction	8
2.3. First-Order Logic	9
2.3.1. Syntax	9
2.3.2. Semantics	9
2.3.3. Substitution	10
2.3.4. Natural Deduction	10
2.4. Equality	10
3. Correctness	11
3.1. Termination	11
3.2. Behaviour	11
4. Lists	13
4.1. Introduction	13
4.2. Sorting Algorithms	13
4.3. List Comprehension	14
4.4. Induction Over Lists	14

5. Abstraction	15
5.1. Higher-Order Functions	15
5.1.1. Examples	15
5.2. λ -Expression	16
5.3. Function as Values	16
5.3.1. Examples	16
5.4. Function Arguments	17
6. Types	18
6.1. Mini-Haskell	18
6.2. Type Classes	19
6.2.1. Type Class	19
6.2.2. Derived Classes and Class Hierarchies	20
6.3. Overloading	20
7. Algebraic Data Types	21
7.1. Data Types	21
7.2. Integration with Classes	21
7.3. Recursive Types	22
7.4. Algebraic Types and Type Classes	22
7.5. Correctness	22
8. Lazy Evaluation	24
8.1. Application	24
8.2. Correctness	25
9. Case Study	26
9.1. Overview Interpreter	26
9.2. Overview Parser	26
9.3. Arithmetic Interpretation	29
II. Formal Methods	32
10. Introduction	33
10.1. IMP	35
10.2. Properties	37
10.3. Free Variables	37
11. Operational Semantics	39
11.1. Big-Step Semantics	39
11.2. Small-Step Semantics	41
11.3. Equivalence	43
12. Axiomatic Semantics	44
12.1. Soundness and Completeness	45
13. Model Checking	47
13.1. Promela:	47
13.2. Linear Temporal Logic (LTL)	50

III. Appendix	55
14. Prelude	56
15. Data.List	59

Part I.

Functional Programming

1. Introduction

1.1. Functional Programming

- Like mathematical expressions
- Consists of functions and values
- Functions are actually values themselves
- There is no state
- **Referential Transparency:** Not state \implies expression **always** evaluate to the same value
- No global variables
- Recursion instead of iteration
- + Easy to parallelize
- + Easy to analyze
- + Flexible type system

1.2. Haskell

- **Lazy Evaluation:** expression evaluates always outermost and leftmost expression
 - ◊ But pattern matching and some other functions force evaluation

1.2.1. Syntax

- **Function**
 - ◊ Function name and arguments start with lower-case
 - ◊ Expression after the equal sign is the return value
 - ◊ **Pattern Matching**
 - * Is used for:
 - Check if argument has proper type
 - Bind values to variables
 - * **Pattern**
 - Inductively defined
 - Pattern are
 - ▷ Constants
 - ▷ Variables
 - ▷ Wild Card ($_$)
 - ▷ Tuples (p_1, p_2, \dots, p_k) where p_i is a pattern
 - ▷ Non-Empty Lists $(p_1 : p_2)$ where p_i is a pattern
 - Must be **linear**
 - ▷ I.e. each variable cannot occur more than once
 - ▷ Does not count for wild card
 - * **Pattern Matching**
 - Pattern matching is used to determine right definition
 - Pattern p matches term a by the following recursion on p :
 - ▷ **Constant:** $p = c$ if $c = a$
 - ▷ **Variable:** $p = x$ always succeeds with binding $x = a$
 - ▷ **Wild Card:** $p = _$ always success but without binding
 - ▷ **Tuple:** $p = (p_1, \dots, p_k)$ succeeds if $a = (a_1, \dots, a_k)$ and p_i matches $a_i \quad \forall i \in \{1, \dots, k\}$
 - ▷ **Non-Empty List:** $p = (p_1 : p_2)$ succeeds if $a = (a_1 : a_2)$ and p_i matches $a_i \quad \forall i \in \{1, 2\}$

- Forces evaluation (no longer lazy evaluation)
 - Can define the same function multiple times but with different patterns
- ◊ May Contain several cases (*guards*)
 - * Boolean expression
 - * **otherwise** is the default case
- ◊ **Scope**
 - * Functions have a global scope
 - * Order of declaration does not matter
 - * **let** <local func, var, const decl.> in <expr. using these defs>
 - More powerful than **where**
 - * **where** <local func, var, const decl.>
 - Follows guard or function return
 - Top-Down development (use and then declare)
- Constants can be defined outside of functions
- Program consists of multiple function definitions
- **Indentations**
 - ◊ Determines separation of definitions
 - ◊ All function definitions start at the same indentation
 - ◊ The body of a function definition needs to be indented
 - ◊ If line is split into two, indent new line again
 - * Can be done recursively
 - ◊ Spaces have to be used, not tabs

1.2.2. Types

- Strongly typed
- Can explicitly define function definition or let Haskell do that
- **Integral**
 - ◊ **Int**: Bound
 - ◊ **Integer**: Arbitrary precision
- **Double**
- **Char**
 - ◊ Surrounded by ' '
- **String**
 - ◊ List of characters
 - ◊ Surrounded by " "
 - ◊ Concatenate using ++
- **Bool**
- **Function/Operator**
 - ◊ **Operator**: Binary function which is used infix
 - ◊ 'func' makes function infix
 - ◊ (op) makes operator prefix
- **Tuple**
 - ◊ Compose multiple values of different type
 - ◊ Composed by a *Type Constructor*
 - ◊ If T_1, \dots, T_n are Types, then (T_1, \dots, T_n) is a tuple type
 - ◊ If $v_1 :: T_1, \dots, v_n :: T_n$ are values of matching type, then $(v_1, \dots, v_n) :: (T_1, \dots, T_n)$ is a valid tuple
 - ◊ Can be nested

1.2.3. Input/Output

- I/O is not referential transparent (has side effects)
- Wrap by `IO` to capture side effects
- `getLine :: IO String` reads a string
- `putStrLn :: String -> IO ()` prints a string.
- `do` blocks sequences side effects
- `<-` extract values from `IO`
- `return` wraps values in `IO`

2. Natural Deduction

- Allows formal reasoning (proofs) about systems

2.1. Natural Deduction

- **Rules** allow to derive from assumptions $A_1, \dots, A_n \vdash A$
- Derivations model trees
- Can construct derivation bottom-up or top-down
- **Proof** is a derivation without assumptions in the root
- Can be read as:
 - ◊ **Top-Down:** From the upper statement, the lower follows according to some rule
 - ◊ **Bottom-Up:** To proof the lower statement, it is sufficient to show the upper statement

2.2. Propositional Logic

2.2.1. Syntax

- **Language of Propositional Logic \mathcal{L}_p :** For set of variables \mathcal{V} , \mathcal{L}_p is the minimal set with:
 - ◊ $X \in \mathcal{L}_p$ if $X \in \mathcal{V}$
 - ◊ $\perp \in \mathcal{L}_p$
 - ◊ $A \wedge B \in \mathcal{L}_p$ if $A \in \mathcal{L}_p$ and $B \in \mathcal{L}_p$
 - ◊ $A \vee B \in \mathcal{L}_p$ if $A \in \mathcal{L}_p$ and $B \in \mathcal{L}_p$
 - ◊ $A \rightarrow B \in \mathcal{L}_p$ if $A \in \mathcal{L}_p$ and $B \in \mathcal{L}_p$
- Convention: X stands for variables, A, B for formulae

2.2.2. Semantics

- **Valuation σ :** Mapping assigning truth values to all variables
 - ◊ $\sigma : \mathcal{V} \rightarrow \{True, False\}$
 - ◊ **Valuations:** set of valuations
- **Satisfiability \models :** Smallest relation $\subseteq \text{Valuations} \times \mathcal{L}_p$ such that:
 - ◊ $\sigma \models X$ if $\sigma(X) = True$
 - ◊ $\sigma \models A \wedge B$ if $\sigma \models A$ and $\sigma \models B$
 - ◊ $\sigma \models A \vee B$ if $\sigma \models A$ or $\sigma \models B$
 - ◊ $\sigma \models A \rightarrow B$ if whenever $\sigma \models A$ then $\sigma \models B$
- **Satisfiable:** is formula $A \in \mathcal{L}_p$ if $\exists \sigma, \sigma \models A$
- **Valid/Tautology:** is formula $A \in \mathcal{L}_p$ if $\forall \sigma, \sigma \models A$
- **Semantic Entailment:** $A_1, \dots, A_n \models A$ if $\forall \sigma$ for which $\sigma \models A_i, \forall i \in [1, n]$ then $\sigma \models A$

2.2.3. Requirements for Deductive System

- Syntactic (\vdash) and semantic (\models) entailment should agree:
 - ◊ **Soundness:** If $H \vdash A$ can be derived, then $H \models A$
 - ◊ **Completeness:** If $H \models A$ then $H \vdash A$ can be derived
- Decidability is also a desired property
 - ◊ I.e. is some formula satisfiable, tautology, satisfied by a valuation etc.

2.2.4. Natural Deduction

- **Sequent:** Assertion of the form $A_1, \dots, A_n \vdash A$, where A, A_i are propositional formulae
 - ◊ If deduction system is sound, this is a semantic entailment
- **Axiom:** Leaves of a derivation tree
 - ◊ Starting point for derivation trees
 - ◊

$$\frac{}{\dots A, \dots \vdash A} \text{ (axiom)}$$

- Proof of A if root is $\vdash A$
 - ◊ If deduction system is sound, then A is a tautology
- **Rules:**
 - ◊ Each rule must be sound
 - * I.e. is must preserve semantic entailment
 - ◊ If each rule is sound, then the logic is sound
 - ◊ **Safe** is rule if we only enlarge Γ or we can get back the conclusion
 - ◊ **And:**

$$\frac{\Gamma \vdash A \quad \Gamma \vdash B}{\Gamma \vdash A \wedge B} (\wedge\text{-I}) \quad \frac{\Gamma \vdash A \wedge B}{\Gamma \vdash A} (\wedge\text{-EL}) \quad \frac{\Gamma \vdash A \wedge B}{\Gamma \vdash B} (\wedge\text{-ER})$$

- ◊ **Or:**

$$\frac{\Gamma \vdash A}{\Gamma \vdash A \vee B} (\vee\text{-IL}) \quad \frac{\Gamma \vdash B}{\Gamma \vdash A \vee B} (\vee\text{-IR}) \quad \frac{\Gamma \vdash A \vee B \quad \Gamma, A \vdash C \quad \Gamma, B \vdash C}{\Gamma \vdash C} (\vee\text{-E})$$

- ◊ **Implies:**

$$\frac{\Gamma, A \vdash B}{\Gamma \vdash A \rightarrow B} (\rightarrow\text{-I}) \quad \frac{\Gamma \vdash A \rightarrow B \quad \Gamma \vdash A}{\Gamma \vdash B} (\rightarrow\text{-E})$$

- ◊ **Negation:** Define $\neg A$ as $A \rightarrow \perp$

$$\frac{\Gamma \vdash \neg A \quad \Gamma \vdash A}{\Gamma \vdash B} (\neg\text{-E})$$

- ◊ **Falsity:**

$$\frac{\Gamma \vdash \perp}{\Gamma \vdash A} (\perp\text{-E})$$

- ◊ **tertium non datur:**

$$\frac{}{\Gamma \vdash A \vee \neg A} (\text{TND})$$

- ◊ **reductio ad absurdum:**

$$\frac{\Gamma, \neg A \vdash \perp}{\Gamma \vdash A} (\text{RAA})$$

TODO: Make safe/unsafe

- **Proof Strategy:** Apply safe rules first

2.3. First-Order Logic

2.3.1. Syntax

- **Signature:** Set of function symbols \mathcal{F} and set of predicate symbols \mathcal{P}
 - ◊ f^i/p^i indicate the arity of function f /predicate p
- **Term:** For set of variables \mathcal{V} , the smallest set where:
 - ◊ $x \in \text{Term}$ if $x \in \mathcal{V}$
 - ◊ $f^n(t_1, \dots, t_n) \in \text{Term}$ if $f^n \in \mathcal{F}$ and $t_j \in \text{Term} \forall 1 \leq j \leq n$
- **Formulae:** Smallest set where:
 - ◊ $\perp \in \text{Form}$
 - ◊ $p^n(t_1, \dots, t_n) \in \text{Form}$ if $p^n \in \mathcal{P}$ and $t_j \in \text{Term} \forall 1 \leq j \leq n$
 - ◊ $A \circ B \in \text{Form}$ if $A \in \text{Form}$, $B \in \text{Form}$, and $\circ \in \{\wedge, \vee, \rightarrow\}$
 - ◊ $Qx.A \in \text{Form}$ if $A \in \text{Form}$, $x \in \mathcal{V}$, and $Q \in \{\forall, \exists\}$
- Quantifier extend as far as possible (EOL or closing outer bracket)
- Occurrence of a variable is either free or bound
 - ◊ Variable x is bound in formula A if it occurs within a subformula B of A of the form $Qx.B$, $Q \in \{\exists, \forall\}$
 - ◊ Names of bound variables are irrelevant
 - ◊ **α -Conversion:** Rename bound variables
 - * Keep binding structure (association between quantifier and variables)
 - * Prevent capture (renaming to the name of a free variable)
 - ◊ x not free $\not\Rightarrow$ x bound
 - * x could also just not occur
- **Binding**
 - 1) \neg
 - 2) \wedge
 - 3) \vee
 - 4) \rightarrow
- **Associativity**
 - ◊ **Right:** \rightarrow
 - ◊ **Left:** \wedge, \vee

2.3.2. Semantics

- **Structure:** Pair $S = \langle U_S, I_S \rangle$
 - ◊ U_S is a non-empty universe
 - ◊ I_S is a mapping which assigns each predicate $p^n \in P$ /formulae $f^n \in \mathcal{F}$ its truth value/definition
- **Interpretation:** Pair $\mathcal{I} = \langle S, v \rangle$
 - ◊ $S = \langle U_S, I_S \rangle$ is a structure
 - ◊ $v : \mathcal{V} \rightarrow U_S$ is a valuation
- **Value:** of a term t under the interpretation \mathcal{I} is written as $\mathcal{I}(t)$ with
 - ◊ $\mathcal{I}(x) = v(x), x \in \mathcal{V}$
 - ◊ $\mathcal{I}(f(t_1, \dots, t_n)) = f^S(\mathcal{I}(t_1), \dots, \mathcal{I}(t_n))$
- **Satisfiability** \models : Smallest relation $\subseteq \text{Interpretations} \times \text{Form}$ such that:
 - ◊ $\langle S, v \rangle \models p(t_1, \dots, t_n)$ if $(\mathcal{I}(t_1), \dots, \mathcal{I}(t_n)) \in p^S$
 - ◊ $\langle S, v \rangle \models \forall x.A$ if $\langle S, v[x \mapsto a] \rangle \models A, \forall a \in U_S$
 - ◊ $\langle S, v \rangle \models \exists x.A$ if $\langle S, v[x \mapsto a] \rangle \models A, \exists a \in U_S$
 - ◊ etc
 - ◊ Where

- * $\mathcal{I} = \langle S, v \rangle$
- * $v[x \mapsto a]$ is valuation v' identical to v except that $v'(x) = a$
- If $\langle S, v \rangle \models A$ and A has no free variables, then $S \models A$
- **Valid:** is A if every suitable interpretation is a model
 - ◊ **Notation:** $\models A$
- **Satisfiable:** if \exists a model for A
- **Contradictory:** if $\not\models$ model for A

2.3.3. Substitution

- Replace in A all occurrences of a free variable x with some term t
- **Notation:** $A[x/t]$
- Must avoid capture
 - ◊ Free variables of t must still be free in $A[x/t]$
 - ◊ May need to α -convert first
 - ◊ It is ok if it clashes with another free variable

2.3.4. Natural Deduction

- In addition to the propositional logic rules we have
- **Universal Quantifier:**

$$\frac{\Gamma \vdash A}{\Gamma \vdash \forall x.A} (\forall\text{-I}) \quad x \text{ not free in any formula in } \Gamma \quad \frac{\Gamma \vdash \forall x.A}{\Gamma \vdash A[x/t]} (\forall\text{-E})$$

- **Existential Quantifier:**

$$\frac{\Gamma \vdash A[x/t]}{\Gamma \vdash \exists x.A} (\exists\text{-I}) \quad \frac{\Gamma \vdash \exists x.A \quad \Gamma, A \vdash B}{\Gamma \vdash B} (\exists\text{-E}) \quad x \text{ not free in any formula in } \Gamma \text{ or } B$$

2.4. Equality

- Is a logical symbol and not just a predicate
- **Extend language**
 - ◊ **Formula:** $t_1 = t_2 \in \text{Form}$ if $t_1, t_2 \in \text{Term}$
 - ◊ **Satisfiability:** $\mathcal{I} \models t_1 \underbrace{=}_{\text{syntactic}} t_2$ if $\mathcal{I}(t_1) \underbrace{=}_{\text{semantic}} \mathcal{I}(t_2)$

- **Rules**

- ◊ **Equivalence Relation:**

$$\frac{}{\Gamma \vdash t = t} (\text{ref}) \quad \frac{\Gamma \vdash t = s}{\Gamma \vdash s = t} (\text{sym}) \quad \frac{\Gamma \vdash t = s \quad \Gamma \vdash s = r}{\Gamma \vdash t = r} (\text{trans})$$

- ◊ **Congruence Relation:**

$$\frac{\Gamma \vdash t_1 = s_1 \quad \dots \quad \Gamma \vdash t_n = s_n}{\Gamma \vdash f(t_1, \dots, t_n) = f(s_1, \dots, s_n)} (\text{cong}_1)$$

$$\frac{\Gamma \vdash t_1 = s_1 \quad \dots \quad \Gamma \vdash t_n = s_n \quad \Gamma \vdash p(t_1, \dots, t_n)}{\Gamma \vdash p(s_1, \dots, s_n)} (\text{cong}_2)$$

- Equality proofs are easier in linear way than using natural deduction trees

3. Correctness

- Properties of a correct program:
 - ◊ **Termination:** Does not count for all, but most programs
 - ◊ **Functional Behaviour:** Function should return “correct” value
- Must be proven

3.1. Termination

- If f is composed of functions g_1, \dots, g_k and $g_i \neq f$ and each g_i terminates then f terminates
- Recursive function terminates if the arguments are smaller along a well-founded order on the function’s domain
 - ◊ Is a sufficient condition
 - ◊ **Well-Founded:** is the order $>$ on set S iff there is no infinite decreasing sequence in S
 - * **Relation composition** of two binary relation R_1, R_2 on set S is $R_2 \circ R_1 \equiv \{(a, c) \in S \times S \mid \exists b \in S. aR_1b \wedge bR_2c\}$
 - For $R \subset S \times S$:
 - ▷ $R^1 \equiv R$
 - ▷ $R^{n+1} \equiv R \circ R^n, n \geq 1$
 - ▷ $R^+ \equiv \bigcup_{n \geq 1} R^n$
 - * For $R \subseteq S \times S$, $s_0, s_i \in S$ and $i \geq 1$. Then $s_0 R^i s_i$ iff $\exists s_1, \dots, s_{i-1} \in S$ such that $s_0 R s_1 R \dots R s_{i-1} R s_i$
 - * If $>$ is well-founded order on S then so is $>^+$.

3.2. Behaviour

- **Equality Reasoning**
 - ◊ **Goal:** Show function return is equal to some value
 - ◊ **Idea:** Function are equations
 - ◊ Apply equational reasoning
 - ◊ Proof using FOL with equality
- **Reasoning by Cases**
 - ◊ For predicate functions
 - ◊ Often use
 - * **Excluded Middle (TND):** For all prepositions $P, P \vee \neg P$
 - * **Case Split (\vee -E):** Prove $P = Q \vee R$ by proving $Q \implies P$ and $R \implies P$
- **Induction**
 - ◊ Dual of recursion
 - ◊ Prove $P(n) \forall n \in \text{Nat.}$
 - * **Base Case:** Proof $P[n/0]$
 - * **Step Case:** Proof $P[n/m+1]$ by assuming $P[n/m]$ for some arbitrary but fixed m
 - m must not be free in P
 - Can also take $P[n/n]$ to remove side condition
 - ◊ Natural Deduction
 - *

$$\frac{\Gamma \vdash P[n/0] \quad \Gamma \vdash \forall m \in \text{Nat.} P[n/m] \rightarrow P[n/m+1]}{\Gamma \vdash \forall n \in \text{NAT.} P} \text{ (NAT-IND)}^m \text{ not free in } P$$

- **Well-Founded Induction/Notherian Induction (not exam relevant)**
 - ◊ **Well-Founded Step:** Prove $P[n/m]$ by assuming $P[n/l] \forall l < m$
 - * m and l not free in P
 - ◊ Stronger than normal induction

4. Lists

4.1. Introduction

- **List Type:** If T is a type then $[T]$ is a type
 - ◊ Is a new type constructor
- **Empty List:** $[] :: [T]$
- **Non-Empty List:** $(x : xs) :: [T]$ iff $x :: T$ and $xs :: [T]$
 - ◊ **Cons Operator:** $:$ prepends an element to a list
 - * **Concatenate:** $++$ concatenates two lists
 - ◊ $[a, b, c]$ is syntactic sugar for $a : (b : (c : []))$
- $[n, p \dots m]$ constructs a list from n to m with step $p - n$
 - ◊ p is optional; Default step is 1
 - ◊ Can be seen as, “First element is n , second element is p , continue like this till m ”
 - ◊ m is not necessarily included
- String is a list of chars
 - ◊ $['a', 'b'] == "ab"$

4.2. Sorting Algorithms

- **Insertion Sort**

```
isort :: [Int] -> [Int]
isort [] = []
isort (x: xs) = ins x (isort xs)
```

```
ins :: Int -> [Int] -> [Int]
ins a [] = [a]
ins a (x: xs)
  | a <= x = a : (x: xs)
  | otherwise = x : ins a xs
```

- **Quick Sort (long form)**

```
qsort :: [Int] -> [Int]
qsort [] = []
qsort (x: xs) = qsort (lesseq x xs) ++ [x] ++ qsort (greater x xs)
where
  lesseq _ [] = []
  lesseq x (y: ys)
    | y <= x = y : lesseq x ys
    | otherwise = lesseq x ys
  greater _ [] = []
  greater x (y: ys)
    | y > x = y : greater x ys
    | otherwise = greater x ys
```

- **Quick Sort (short form)**

```
q :: [Int] -> [Int]
q [] = []
q (p:xs) = q [x | x <- xs, x <= p] ++ [p] ++ q [x | x <- xs, x > p]
```

4.3. List Comprehension

- Notation for sequential processing of list elements
- Analogous to set comprehension in set theory
- General form: `[func x | <gen_1>, ... , <gen_n>, <pred_1>, ..., <pred_m>]`
- Generators can depend on each other
 - ◊ E.g. `[x | n <- [1..10], x <- [1..n]]`
- Generators can depend on if then else
 - ◊ E.g. `[x | n <- [1..10], if even x then x <- [1,2] else x <- [1]]`
- **TODO: Add more handy dandy examples**

4.4. Induction Over Lists

- Prove P for all xs in $[T]$
 - ◊ **Base Case:** prove $P[xs/[]]$
 - ◊ **Step Case:** prove $\forall y :: T, ys :: [T]. P[xs/ys] \rightarrow P[xs/y : ys]$
 - * **Fix** arbitrary but non-free $y :: T, ys :: [T]$
 - * **Induction Hypothesis:** Assume $P[xs/ys]$
- Sometimes hard to pick right induction variable
 - ◊ Proof may fail depending on the variable
- **Generalisation**
 - ◊ Proof a stronger statement as a subproof
 - ◊ Required for some proofs

5. Abstraction

- **Polymorphic Type t :** A set of types
- **Parametric Polymorphism:** Function works for type t iff it works for all types contained in t
- A type w for function f is a **most general** (/principal) **type** iff for all types s for f , s is an instance of w .
- Given a function, Haskell always computes the most general type
 - ◊ If we give a type, it must be an instance of the most general type
- Type variables start with lower-case

5.1. Higher-Order Functions

- Types
 - ◊ **First Order:** Arguments are base types or constructor types
 - * `Int -> [Int]`
 - ◊ **Second Order:** Arguments are themselves functions
 - * `(Int -> Int) -> [Int]`
 - ◊ **Third Order:** Arguments are functions, whose arguments are functions
 - * `((Int -> Int) -> Int) -> [Int]`
 - ◊ **Higher-Order:** Functions of arbitrary order
- Advantages
 - + Definition is easier to understand
 - + Parts are easier to modify
 - + Parts are easier to reuse
 - + Correctness is simpler to understand and show

5.1.1. Examples

- **Map**
 - ◊ Apply function to each argument in a list
 - ◊ `map :: (a -> b) -> [a] -> [b]`
 - `map f [] = []`
 - `map f (x:xs) = f x : map f xs`
- **Folding**
 - ◊ Aggregate all elements of a list
 - ◊ **foldr**
 - * Written as `(f x_1 (f x_2 (f ... (f x_k e)))` for list x , function f and default value e
 - * When seen as a tree, the `con` is replaced by f and the empty list by e
 - * Can operate on infinite list
 - `foldr :: (a -> b -> b) -> b -> [a] -> b`
 - `foldr f e [] = e`
 - `foldr f e (x: xs) = f x (foldr f e xs)`
 - * **Recipe:** Implement some (suitable) function with folder
 - ◊ Identify the following arguments:
 - ▷ **Recursive Arguments:** The list which shrinks in each iteration
 - ▷ **Static Arguments:** The ones which do not change
 - ▷ **Dynamic Arguments:** The ones which change arbitrarily
 - ◊ Write a helper function `aux` with all recursive and then dynamic arguments

- Move the dynamic arguments to the right of the equals
 - ▷ I.e. form a lambda function
 - ▷ I.e. η -expansion
- Rewrite the helper function using `foldr` and replace `aux xs` with local variable `rec`
- Inline the helper function
- ◇ **foldl**
 - * Written as `f(f(f(f e x_1) x_2) ...) x_k` for list x , function f and default value e
 - * Runs infinitely on infinite lists
 - * `foldl :: (b -> a -> b) -> b -> [a] -> b`
 - `foldl f e [] = e`
 - `foldl f e (x: xs) = foldl f (f e x) xs`
- ◇ `foldr` and `foldl` are equivalent for associative functions

5.2. λ -Expression

- Allows in-line function definitions
- Constructed as `(\v_1 -> ... -> \v_k -> <someExpression>)`
 - ◇ Syntactic sugar `(\v_1 ... v_k -> <someExpression>)`
- Adoption of Church's λ -notation
- **η -Conversion:** `x -> f x` and `f` are equivalent
 - ◇ **η -Contraction:** From left to right
 - ◇ **η -Expansion:** From Right to left
 - ◇ Useful to simplify expression

5.3. Function as Values

- Function itself can be returned from function
- Returned function cannot be displayed, but only evaluated

5.3.1. Examples

- **Function Composition**
 - ◇ Takes two functions as arguments and returned the composite function
 - ◇ Application associates to the left
 - ◇ `(.) :: (b -> c) -> (a -> b) -> (a -> c)`
 - `(f . g) x = f (g x)`
- **Iteration**
 - ◇ Apply a function `a -> a` n times to a input x
 - ◇ `iter :: Int -> (a -> a) -> a -> a`
 - `iter 0 f x = x`
 - `iter n f x = f (iter (n - 1) f x)`
- **Difference Lists**
 - ◇ **Problem:** Appending to list is expensive
 - ◇ **Idea:** Construct list as a higher order (first) function
 - ◇ `type DList a = [a] -> [a]`
 - `empty :: DList a`
 - `empty = \xs -> xs`


```

sngl :: a -> DList a
sngl x = \xs -> x : xs

app :: DList a -> DList a -> DList a
ys 'app' zs = \xs -> ys (zs xs)

fromList :: [a] -> DList a
fromList ys = \xs -> ys ++ xs

toList :: DList a -> [a]
toList ys = ys []

```

5.4. Function Arguments

- **Partial Application**

- ◇ One applies only some but not all arguments
- ◇ A new function, still requiring some arguments, is returned
- ◇ Useful for `map`, `filter` etc.
- ◇ If $f :: t_1 \rightarrow t_2 \rightarrow \dots \rightarrow t_n \rightarrow t$ and $e_1 :: t_1, \dots, e_k :: t_k$ then the partial application has type $f e_1 \dots e_k :: t_{k+1} \rightarrow \dots \rightarrow t_n \rightarrow t$
- ◇ Partial application is consistent with the view that function takes multiple arguments
 - * But a function takes exactly one arguments
- ◇ For infix operator \oplus :
 - * $(a \oplus) \equiv \lambda x. a \oplus x$
 - * $(\oplus a) \equiv \lambda x. x \oplus a$
 - * Important to consider when operator is not commutative
 - $(a \text{ 'func' }) \neq (\text{'func' } a)$

- **Tupling**

- ◇ Wrapping multiple arguments into tuple lets us apply them as one argument
- ◇ Function is one of:
 - * **Curry Func**: Takes multiple arguments
 - * **Uncurry Func**: Takes a tuple as argument
- ◇ We want convert one representation to the other using:
 - * **Curry**: $\text{Uncurry} \rightarrow \text{curry}$

```

curry :: ((a,b) -> c) -> a -> b -> c
curry f = f' where f' x1 x2 = f (x1,x2)

```
 - * **Uncurry**: $\text{Curry} \rightarrow \text{uncurry}$

```

uncurry :: (a -> b -> c) -> (a,b) -> c
uncurry f' = f where f (x1,x2) = f' x1 x2

```

- **Uncluttering Notation**

- ◇ Right associative operator `$` for arguments
- ◇ Avoids parentheses

6. Types

- Should prevent dangerous expressions
 - ◊ Which cause a runtime error
- Classification (good/bad) of expressions is undecidable
 - ◊ Type systems are conservative and only allow what they are sure is good
- Type checker should offer:
 - ◊ quick, decidable, static analysis
 - ◊ permit generality/re-usability
 - ◊ prevent runtime-errors

6.1. Mini-Haskell

- Typing system
- Subset of Haskell
- **Syntax**
 - ◊ Programs are terms
 - ◊

$$\begin{aligned}
 t ::= & \underbrace{\mathcal{V}}_{\text{Variables}} \mid \underbrace{(\lambda x. t)}_{\text{lambda abstraction}} \mid \underbrace{(t_1 \ t_2)}_{\text{functions}} \mid \text{True} \mid \text{False} \mid \\
 & (\text{iszero } t) \mid \underbrace{\mathcal{Z}}_{\text{Integers}} \mid (t_1 + t_2) \mid (t_1 * t_2) \mid \\
 & \text{if } t_0 \text{ then } t_1 \text{ else } t_2 \mid \underbrace{(t_1, t_2)}_{\text{Pairing}} \mid (\text{fst } t) \mid (\text{snd } t)
 \end{aligned}$$

- ◊ Can easily be extended
- ◊ Add syntactic sugar: Can leave out parenthesis when not necessary
- **Typing**
 - ◊ Set of types $\tau ::=$

$$\underbrace{\mathcal{V}_\tau}_{\text{Set of Type Variables } (a,b,\dots)} \mid \text{Bool} \mid \text{Int} \mid \underbrace{(\tau, \tau)}_{\text{Pair Constructor}} \mid \underbrace{(\tau \rightarrow \tau)}_{\text{Function Constructor}}$$
 - ◊ **Typing Judgement:** $\Gamma \vdash t :: \tau$
 - * Γ : Set of bindings mappings from variables to types
 - * t : Term
 - * τ : Type
 - * “Given assignments Γ , term t is of type τ ”
 - ◊ **Rules**
 - * **Basic:**

$$\frac{}{\dots, x : \tau, \dots \vdash x :: \tau} (\text{Var}) \quad \frac{\Gamma, x : \sigma \vdash t :: \tau}{\Gamma \vdash (\lambda x. t) :: \sigma \rightarrow \tau} (\text{Abs}) \quad \frac{\Gamma \vdash t_1 :: \sigma \rightarrow \tau \quad \Gamma \vdash t_2 :: \sigma}{\Gamma \vdash (t_1 \ t_2) :: \tau} (\text{App})$$

- * **Base Types:**

$$\frac{}{\Gamma \vdash n :: \text{Int}} (\text{int}) \quad \frac{}{\Gamma \vdash \text{True} :: \text{Bool}} (\text{True}) \quad \frac{}{\Gamma \vdash \text{False} :: \text{Bool}} (\text{False})$$

- * **Operations** $\text{op} \in \{+, *\}$

$$\frac{\Gamma \vdash t :: \text{Int}}{\Gamma \vdash (\text{iszero } t) :: \text{Bool}} (\text{iszero}) \quad \frac{\Gamma \vdash t_1 :: \text{Int} \quad \Gamma \vdash t_2 :: \text{Int}}{\Gamma \vdash (t_1 \text{ op } t_2) :: \text{Int}} (\text{BinOp})$$

* **Conditional:**

$$\frac{\Gamma \vdash t_0 :: \text{Bool} \quad \Gamma \vdash t_1 :: \tau \quad \Gamma \vdash t_2 :: \tau}{\Gamma \vdash (\text{if } t_0 \text{ then } t_1 \text{ else } t_2) :: \tau} \text{ (if)}$$

* **Tuples:**

$$\frac{\Gamma \vdash t_1 :: \tau_1 \quad \Gamma \vdash t_2 :: \tau_2}{\Gamma \vdash (t_1, t_2) :: (\tau_1, \tau_2)} \text{ (Tuple)} \quad \frac{\Gamma \vdash t :: (\tau_1, \tau_2)}{\Gamma \vdash (\text{fst } t) :: \tau_1} \text{ (fst)} \quad \frac{\Gamma \vdash t :: (\tau_1, \tau_2)}{\Gamma \vdash (\text{snd } t) :: \tau_2} \text{ (snd)}$$

• **Type Inference**

- ◊ Given term t what is its type?
- ◊ Algorithms:
 1. Start with judgement $\vdash t :: \tau_0$ where τ_0 is the type variable and t is the expression whose type we want to determine
 2. Build derivation tree bottom-up by applying rules and collect constraints. Introduce fresh type variables if need
 3. Solve constraints to get possible types
- ◊ Some terms are untypeable
 - * Type inference fails to build inference tree or constraints are unsolvable

• **Type Proof**

- ◊ Given term t and type τ . Prove that $t :: \tau$

TODO: Add Type Proof section

• **Self Application**

- ◊ Apply function f to itself: $\lambda f.f f$
- ◊ Is not typeable

• **Curry-Howard Isomorphism (not examrelevant)**

- ◊ Type constructor ' \rightarrow ' corresponds to propositional logic connectivity ' \rightarrow '
- ◊ Atomic types correspond to propositional variables
- ◊ Rules correspond to those minimal propositional logic

6.2. Type Classes

- Defines
 - ◊ Set of types
 - ◊ Set of allowed functions on these types
- Allow restricted for of type generalisation
- **Monomorphic:** Restricted to a single type (base type)
- **Polymorphic:** Restricted by the type set (a type class)

6.2.1. Type Class

- Definition
 - ◊ **Name:** upper-case
 - ◊ **Signature:** Function names with their type
 - * Required to be implemented by instances of this type
 - ◊ **Default Definition:** Definition based on other signatures
 - * Optional
 - * Can be overwritten
 - ◊ `class Eq a where -- Class Name`
`(==) :: a -> a -> Bool -- Signature`

```
(/=) :: a -> a -> Bool -- Signature
```

```
x /= y = not (x == y) -- Default definition
```

- ◊ To indicate that a certain type t is of type class `Eq` we write `Eq t => t`

- **Instance**

- ◊ Application of a type class to a certain type
- ◊ Elements of a class are instances
- ◊ Interprets signature functions
 - * Requires defining all signatures and optionally, overwrite default definitions
- ◊ Done using keyword `instance`
- ◊ `instance Eq Bool where`

```
True == True    = True
False == False  = True
_ == _          = False
```
- ◊ Can be recursive
 - * If t is of type `Eq` then so is `[Eq]`
 - * I.e. membership depends on membership of other type
 - * `instance Eq t => Eq [t] where`

```
[]      == []      = True
(x:xs) == (y:ys) = x == y && xs == ys
_      == _      = False
```

6.2.2. Derived Classes and Class Hierarchies

- Type classes can build on top of other type classes
- If a belongs to the child type, it must also belong to the parent type
- All functions of the parent type are inherited and some new ones (may be) added
- `class Eq a => Ord a where...`
- Arbitrarily nested classes can be created

6.3. Overloading

- Execution of parametric polymorphic functions independent of type of arguments
- Classes implement *ad hoc* polymorphism
- Selection of function definition is either
 - ◊ At compile time if types are known
 - ◊ else, at runtime

TODO: I am not sure what this all means

7. Algebraic Data Types

- Declare new data types suitable for the object being modeled
- Algebraic means it is the smallest set
- + Less error prone

7.1. Data Types

- **Enumeration Types**

- ◊ Set of possible types
 - * Each element is a *type constructor*
- ◊ Initiated by keyword `data`
- ◊ Constructors must have unique names
- ◊ First letter of each constructor must be upper-case
- ◊ `data TypeName = Const1 | Const2 | Const3`
- ◊ Function can use this type for pattern matching
 - * `func :: TypeName -> SomeOtherType`
- ◊ Type class can have type variables as arguments
 - * For polymorphism
 - * `data TypeName a = ...`

- **Product Type**

- ◊ Consists of a type name and a set of “attributes”
 - * Attribute must be a certain type
 - ◊ Giving an alias using `type` adds a layer of abstraction
- ◊ `data TypeName = Name Attr1 Attr2`
 - * `type Attr1 = Sometype`
 - * `TypeName` and `Name` are often the same
- ◊ Constructor is a function `Name :: Attr1 -> Attr2 -> TypeName`
- ◊ Functions can use this type for pattern matching
 - * `func :: TypeName -> SomeOtherType`
 - `func (Name Attr1 Attr2) = ...`
- ◊ Could use tuples instead of product types
 - * `data TypeName = (Attr1, Attr2)`
 - Makes arguments ambiguous
 - + Allows application of polymorphic functions like `fst`, `zip...`
 - + Shorter definition

- **Enumeration and Product Types**

- ◊ Enumeration and product types can be combined
- ◊ `data TypeName = Name1 Attr1 | Name2 Attr1 Attr2`
- ◊ Functions can use this type for pattern matching
 - * `func :: TypeName -> SomeOtherType`
 - `func (Name1 Attr1) = ...`
 - `func (Name2 Attr1 Attr2) = ...`

7.2. Integration with Classes

- Default function are not applicable to our custom data types
- Have to be explicitly created

- ◊ `data TypeName = Name1 Attr1 | Name2 Attr1 Attr2`
`instance TypeClass TypeName where`
`...`
- In some cases class instances can be automatically derived
 - ◊ `data TypeName = Name1 Attr1 | Name2 Attr1 Attr2`
`deriving(TypeClass1, TypeClass2, TypeClass3)`

7.3. Recursive Types

- Defined using recursive data types
 - ◊ `data Expr = Lit Int | Add Expr Expr`
- Are evaluated recursively
 - ◊ `eval :: Expr -> Int`
`eval (Lit n) = n`
`eval (Add a b) = (eval a) + (eval b)`
- **Example:** Trees
 - ◊ Are a prime example
 - ◊ Can describe many data structures
 - ◊ `data Tree t = Leaf | Node t (Tree t) (Tree t)`
`deriving (Eq, Ord, Show)`

7.4. Algebraic Types and Type Classes

- Algebraic types are *first class* citizens
 - ◊ Fully compatible with polymorphism and type classes
- Standard types are algebraic data types defined in the prelude
- + Make program simpler to read and understand
- + Allow reusability

7.5. Correctness

- **Natural Number**
 - ◊ `data Nat = Zero | Succ Nat deriving (Eq, Ord, Show)`
 - ◊ Isomorphic to $\{Zero, Succ\ Zero, Succ\ (Succ\ Zero), \dots\}$
 - ◊ Build step by step
 - ◊ Allows structural induction proofs
- **Lists**
 - ◊ `data L t = Nil | Cons t (L t)`
 - ◊ Elements in $L\ t$ are build in steps
 - * $\{Nil\}$
 - * $\{Cons\ a\ Nil \in L\ t \mid a \in t\}$
 - * $\{Cons\ b\ (Cons\ a\ Nil) \in L\ t \mid a, b \in t\}$
 - * \vdots
 - ◊ $l \in L\ t$ iff l appears in some of the construction step
 - ◊ Rule

$$\frac{\Gamma \vdash P[xs/Nil] \quad \Gamma, P[xs/ys] \vdash P[xs/Cons\ y\ ys]}{\Gamma \vdash \forall xs \in L\ t. P} \text{ (IND on List)}^{y,ys \text{ not free in } \Gamma, P}$$

- **Trees**

- ◇ `data Tree t = Leaf | Node t (Tree t) (Tree t)`
- ◇ Elements in *Tree t* are build in steps
 - * {Leaf}
 - * {Node *a* Leaf Leaf ∈ *Tree t* | *a* ∈ *t*}
 - * ⋮
 - * Trees in step *i* are of form Node *a l r* where *a* ∈ *t*, and *l* and *r* were constructed in the previous step
- ◇ *s* ∈ *Tree t* iff *s* appears in some of the construction step
- ◇ Rule

$$\frac{\Gamma \vdash P[x/\text{Leaf}] \quad \Gamma, P[x/l], P[x/r] \vdash P[x/\text{Node } a \ l \ r]}{\Gamma \vdash \forall x \in \text{Tree } t. P} \text{ (IND on Tree)}^{a,l,r \text{ not free in } \Gamma, P}$$

- **General Idea**

- ◇ Adopt induction to the structure of the algebraic data type
- ◇ Proof non-recursively step 0
- ◇ Proof recursively how to get from step *i* − 1 to *i*

8. Lazy Evaluation

- Only evaluate arguments when needed
- Substitute arguments without argument evaluation
- Some expressions are never evaluated
 - ◊ Can save arbitrary amount of work
- **Duplicate Evaluation:**
 - ◊ One argument may be used multiple times
 - ◊ Haskell avoids duplicate evaluation of the same arguments
 - ◊ **Sharing:** Pointer graph of arguments indicated if an argument was already executed
 - * If it was, we can directly take the result
- Arguments are evaluated only when needed and at most once
- **Pattern Matching**
 - ◊ Arguments evaluate as far as needed to determine pattern match
 - ◊ Start matching the top most pattern and on failure go to the next
- **Guards**
 - ◊ Evaluate only what is required to check if guard is true
 - ◊ Start matching the top most guard and on failure go to the next
- **Local Definitions**
 - ◊ `where` and `let` are lazily evaluated
- **Functions**
 - ◊ Outermost operator is first evaluated
 - * Top-down evaluation in a syntax tree
 - ◊ If on same level, evaluate from left to right or according to operator precedence
- **Recipe:** Evaluate `t1 t2` lazily
 - ◊ Evaluate `t1`
 - ◊ The argument `t2` is substituted in `t1` without being evaluated
 - ◊ No evaluation inside lambda abstractions
 - * I.e. in an abstraction $(\lambda t \rightarrow f\ t)$, (where `f` is some arbitrary term), then `f t` is not evaluated
- **Recipe:** Evaluate `t1 t2` eagerly
 - ◊ Evaluate `t1`
 - ◊ `t2` is evaluated prior to substitution in `t1`
 - ◊ Evaluation is carried out inside lambda abstractions

8.1. Application

- **Data-Driven Programming**
 - ◊ Data can be generate on demand
 - * Improved runtime complexity
 - ◊ Due to lazy evaluation, only required data is constructed
- **Infinite Data**
 - ◊ Finite representation of infinite data
 - * E.g. `from n = n : ones (n+1)` generates an infinite list
 - ◊ We can calculate with infinite data in finite time
 - * E.g. `head from 1`
 - ◊ I.e. we describe an infinite stream and compute with arbitrarily large finite prefixes of it

8.2. Correctness

- Complicated analysis of correctness and complexity
- Type like `[Int]` include finite and infinite lists
- Proof by induction is sound only for finite lists
 - ◊ We always assume finite lists for this course

9. Case Study

9.1. Overview Interpreter

- Has three basic steps:
- **Read**
 - ◊ **Input:** Text
 - ◊ **Phases:**
 - * **Lexical Analysis**
 - Convert source code to tokens
 - ▷ I.e. tell for each groups of symbols what they are
 - **Tokens:** Identifier (variables), arithmetic symbols, assignment symbol, numbers, etc.
 - White-spaces and comments are removed
 - * **Parsing**
 - Build abstract syntax tree
 - Syntax is specified by a given grammar
 - ▷ I.e. a data type in Haskell
 - * **Outer Phases**
 - Depending on the applications, further phases may come now
 - Things like type conversion, type checking, dependency analysis, etc.
 - ◊ **Output:** Abstract Syntax Tree
 - ◊ Lexical analysis and parsing is required for all systems
- **Evaluate**
 - ◊ **Input:** Abstract Syntax Tree
 - ◊ **Semantic Interpretation**
 - ◊ **Output:** Abstract Syntax Tree
- **Print**
 - ◊ **Input:** Abstract Syntax Tree
 - ◊ **Pretty Print Output**
 - ◊ **Output:** Text

9.2. Overview Parser

- Parser is a function
- **Input:** String
- **Output:** Element of type `a`
 - ◊ Typically `a` is some data type
- A parser may not necessarily parse the whole input
 - ◊ **Combinatory Parsing**
 - ◊ There is a remainder
 - ◊ `res`, `rem`
 - ◊ Remainder may be parsed by a different parser
- A parser may try to produce different results for the same input
 - ◊ Store (`res_i`, `rem_i`) in a list
 - ◊ If `rem_i = ""` the parse is complete
 - ◊ `data Parser a = Prs (String -> [(a, String)])`
- **Application**
 - ◊ `parse :: Parser a -> String -> [(a, String)]`
 - ◊ `parse (Prs p) inp = p inp`

- **Result of (first) Complete Parse**

```

◇ completeParse :: Parser a -> String -> a
completeParse p inp
| result == [] = error "Parse unsuccessful"
| otherwise    = head results
where results  = [res | (res, "") <- parse p inp]

```

- **Primitive Parsers**

```

◇ Server as a basic building block

```

```

◇ Failure:

```

```

* Fails trivially
* [] signifies a unsuccessful parse
* failure :: Parser a
  failure = Prs (\inp -> [])
* Ex.
  $ parse failure "3+5"
  [] :: [(a, String)]

```

```

◇ Return:

```

```

* Succeeds trivially
* Without progress
* return :: a -> Parser a
  return x = Prs (\inp -> [(x, inp)])
* Ex.
  $ parse (return "foo") "3+5"
  [("foo", "3+5")] :: [(Char, String)]

```

```

◇ Item:

```

```

* Succeeds trivially
* With progress
* item :: Parser Char
  item = Prs (\inpt -> case inp of
                        "" -> []
                        (x:xs) -> [(x, xs)])
* Ex.
  $ parse item "3+5"
  [('3', "+5")] :: [(Char, String)]

```

```

◇ Sat:

```

```

* Parse single char with property p
* sat :: (Char -> Bool) -> Parser Char
  sat p = Prs (\inp -> case inp of
                        "" -> []
                        (x:xs) -> if p x then [(x,xs)] else [])
* Alternatively
  sat :: (Char -> Bool) -> Parser Char
  sat p = item >>= \x -> if p x then return x else failure
* Ex. isDigit
  $ parse (sat (\x -> '0' <= x && x <= '9')) "3+5"
  [('3', "+5")] :: [(Char, String)]
* Ex. isArithOp
  $ parse (sat (\x -> x == '+' || x == '-')) "3+5"

```

```

    [] :: [(Char, String)]
  ◇ Char:
    * char :: Char -> Parser Char
    char x = sat (==x)
  ◇ String:
    * string :: String -> Parser String
    string "" = return ""
    string (x:xs) = char x >> string xs >> return (x:xs)
  ◇ Many:
    * 0 or more repetitions of p
    * many :: Parser a -> Parser [a]
    many p = many1 p ||| return []
  ◇ Many1:
    * 1 or more repetitions of p
    * many1 :: Parser a -> Parser [a]
    many1 p = p >>= \t -> many p >>= \ts -> return (t:ts)
  ◇ numPos:
    * numPos :: Parser Int
    numPos = do ts <- many1 (sat isDigit)
    return (read ts)
  ◇ numNeg
    * numNeg :: Parser Int
    numNeg = do char '-'
    t <- numPos
    return (-t)
  ◇ num
    * num :: Parser Int
    num = numPos ||| numNeg
    * $ parse num "123"
    [(123, ""), (12, "3"), (1, "23")]
    * $ parse num "-123"
    [(-123, ""), (-12, "3"), (-1, "23")]
  • Combining Parsers
    ◇ Mutual Selection: Apply both parser and concatenate result
    * (|||) :: Parser a -> Parser a -> Parser a
    p ||| q = Prs (\s -> Parser p s ++ parser q s)
    * Ex
    $ parse (return '!' ||| sat isDigit) "3+5"
    [('!', "3+5"), ('3', "+5")]
    ◇ Alternative Selection: Apply second parser only if first fail
    * (+++) :: Parser a -> Parser a -> Parser a
    p +++ q = Prs (\s -> case parser p s of
      [] -> parser q s
      res -> res)
    * Ex
    $ parse (return '!' +++ sat isDigit) "3+5"
    [('!', "3+5")]
    ◇ Sequencing: Apply second parser on remainder of first parser. Return result and
    remainder of second parser

```

```

* Result of first parser is lost
* (>>) :: Parser a -> Parser b -> Parser b
  p >> q = Prs (\s -> [(u, s'') | (t, s') <- parse p s,
                        (u, s'') <- parse q s'])

* Ex
  $ parse (sat isDigit >> sat (== '+')) "3+5"
  [('+', "5")]
◇ Sequencing 2: Apply second parser on result of first parser. Return combined result
and remainder of second parser
* Second parser is a parser generator
* (>>=) :: Parser a -> (a -> Parser b) -> Parser b
  p >>= g = Prs (\s -> [(u, s'') | (t, s') <- parser p s
                        (u, s'') <- parser (g t) s'])
* Can improve readability by using syntactic sugar
  ○ do t1 <- p1
    t2 <- p2
    ...
    tn <- pn
    return (f t1 t2 ... tn)
  for
    p1 >>= \t1 ->
    p2 >>= \t2 ->
    ...
    pn >>= \tn ->
    return (f t1 t2 ... tn)
  ○ Parser must be an instance of Monad
* Ex
  $ parse (sat isDigit >>=
    \t -> sat isDigit >>=
    \u -> return (t:u:[])) "31+5"
  [("31", "+5")]
  $ parse (sat isDigit >>=
    \t -> sat isDigit >>=
    \u -> return (t:u:[])) "3+5"
  []

```

9.3. Arithmetic Interpretation

- **Read**
 - ◇ **Grammar:** $\text{Expr} ::= \text{Int} \mid \text{Expr } '+' \text{ Expr} \mid \text{Expr } '-' \text{ Expr}$
 - * Resp. data $\text{Expr } n \text{ Lit Int} \mid \text{Add Expr Expr} \mid \text{Sub Expr Expr}$
 - ◇ **Lexical Analysis:** Recognize integers, '+', '-', parentheses and white space
 - ◇ **Parsing:** Convert to abstract syntax tree
- **Evaluation**
 - ◇ $\text{eval} :: \text{Expr} \rightarrow \text{Int}$
 - $\text{eval } (\text{Lit } n) = n$
 - $\text{eval } (\text{Add } e1 \ e2) = (\text{eval } e1) + (\text{eval } e2)$
 - $\text{eval } (\text{Sub } e1 \ e2) = (\text{eval } e1) - (\text{eval } e2)$
- **Print**

- ◊ Instance of type class show
- ◊ instance Show Expr where
 - show (Lit n) = show n
 - show (Add e1 e2) = "(" ++ show e1 ++ "+" ++ show e2 ++ ")"
 - show (Sub e1 e2) = "(" ++ show e1 ++ "-" ++ show e2 ++ ")"

- **Parser**

- ◊ Given grammar is ambiguous
 - * Provide user a way to get rid of ambiguity
 - * Expr ::= Int | Expr '+' Expr | Expr '-' Expr | '(' Expr ')'
- ◊ Given grammar is left-recursive
 - * Parsing Expr requires to first parse Expr
 - * We can get an infinitely non-terminating recursion
 - * Atom ::= Int | '(' Expr ')'
 - Expr ::= Atom | Atom '+' Expr | Atom '-' Expr/
- ◊ Parser
 - * data Expr = Lit Int | Add Expr Expr | Sub Expr Expr
 - deriving (Show, Eq)

```
atom lit ||| pexpr
expr = atom ||| add ||| sub
```

```
lit = do x <- num
      return (Lit x)
```

```
pexpr = do string "("
           e <- expr
           string ")"
           return e
```

```
add = do a <- atom
        string "+"
        e <- expr
        return (Add a e)
```

```
sub = do a <- atom
        string "-"
        e <- expr
        return (Sub a e)
```

- ◊ Evaluator
 - * str2expr :: String -> Expr
 - str2expr s = completeParse expr s
 - eval :: Expr -> Int
 - eval (Lit n) = n
 - eval (Add x y) = eval x + eval y
 - eval (Sub x y) = eval x - eval y
 - calculate :: String -> Int
 - calculate = eval . str2expr

TODO: Example 2

Part II.

Formal Methods

10. Introduction

- **Transitional SE**
 - ◊ Documentation is incomplete
 - ◊ Testing is good, but
 - They are insufficient
 - Detect concurrency issues is e.g. very difficult
 - Impossible to cover all instances
- **Formal Methods:** Mathematical approaches to software and system development which support the rigorous specification, design, and verification of computer systems
 - ◊ Programs, programming languages, designs etc. are mathematical objects and can be treated by mathematical methods
 - ◊ Used for
 - * Proving program properties
 - * Formalizing language semantics
 - * Proving language properties
 - ◊ **Steps:**
 - * **Specification:**
 - **System Design:** What does the system look like?
 - **Requirements:** What should the system do?
 - **Assumptions:** What do we assume?
 - ▷ E.g. an attacker cannot break a encryption
 - Described in mathematical notation
 - * **Verification:**
 - **Validate Specifications:** Do the specifications make sense?
 - **Proof:** Requirements are fulfilled under the specifications and requirements
 - ▷ Often simple but tedious
 - Done using formal logic
 - ▷ **Deduction:** Proof system
 - ▷ **Algorithmic:** State space exploration or model checking
 - ◊ **State Space Exploration:** Enumerate all possible states
 - * Done very efficiently
 - * Check for deadlocks
 - Problem space may be very large
 - Limit to important properties
 - Gives weaker correctness guarantees than proofs
 - ◊ Pro/cons
 - + Strong guarantees
 - + Proof for all possible constellations
 - + Unambiguous documentation
 - Writing (correct) specifications is hard
 - Many properties are undecidable
 - Tools are limited
 - Give often false positive or false negative
 - FM specialist required
 - FM application is expensive
 - * FM complements testing
 - We need tests for
 - ▷ Validate specifications

- ▷ Test properties not proven
 - ▷ Detect errors in environment
 - FM aids tests
 - ▷ Derive test cases and test data from specifications
 - ▷ Increase test coverage
 - ▷ Replaces tests
- **Used For**
 - ◇ Verification of design
 - ◇ Analysis of safety-critical software
 - ◇ Detection of security vulnerabilities
 - ◇ Enforce usage of API and/or protocols
 - ◇ Analysis of security protocols
 - ◇ Verification of system implementations
 - ◇ Design of programming languages
 - ◇ Implementation of programming languages
 - ◇ Reasoning about programs

10.1. IMP

- Has boolean and arithmetic expressions
- Expressions have no side effects
- All variables range over integers
- All variables are initialized
- Does not include
 - ◊ Heap allocation and coiners
 - ◊ Variable declaration
 - ◊ Procedures
 - ◊ Concurrency
- Is very extensible
- **Syntax**
 - ◊ **Characters:**
 - * Letter = 'A' | ... | 'Z' | 'a' | ... | 'z'
 - Digit = '0' | '1' | ... | '9'
 - ◊ **Tokens:**
 - * Ident = Letter { Letter | Digit }*
 - Numeral = Digit | Numeral Digit
 - Var = Ident
 - ◊ **Arithmetic Expressions:**
 - * Aexp = '(' Aexp Or Aexp ')'
 - | Var
 - | Numeral
 - Op = '+' | '-' | '*'
 - ◊ **Boolean Expressions:**
 - * Bexp = '(' Bexp 'or' Bexp ')'
 - | '(' Bexp 'and' Bexp ')'
 - | 'not' Bexp
 - | Aexp Rop Aexp
 - Rop = '=' | '#' | '<' | '<=' | '>' | '>='
 - ◊ **Statement:**
 - * Stm = 'skip'
 - | Var ':=' Aexp
 - | '(' Stam ';' Stm ')'
 - | 'if' Bexp 'then' Stm 'else' 'stm' 'end'
 - | 'while' Bexp 'do' Stm 'end'
 - * Parentheses are omitted if possible
 - ◊ **Abbreviations:**
 - * “if *b* then *s* end” for “if *b* then *s* else skip end”
 - * “true” for “1 = 1”
 - * “false” for “0 = 1”
- **Variables**
 - ◊ **Program Variables:**
 - * Are concrete variables in a program
 - * Written in typewriter font
 - ◊ **Meta Variables:**
 - * Stand for arbitrary program variables

- * Convention:
 - **n**: for numerals (**Numeral**)
 - **x, y, z**: for variables (**Var**)
 - **e, e', e₁, e₂**: for arithmetic expressions (**Aexp**)
 - **b, b', b₁, b₂**: for boolean expressions (**Bexp**)
 - **s, s', s₁, s₂**: for statements (**Stm**)
 - **σ**: for states
- * Meta variables stand for arbitrary program variables
- * Written in math font
- ◇ **Syntactic Equality** \equiv :
 - * $x \equiv y$ (meta variables) may be true
 - I.e. both denote the same program variable
 - * $x \equiv y$ (program variables) is always false
 - But two program variables may have the same value $x = y$
- **Semantics**
 - ◇ **States**
 - * An expression depends on the value bound to the variables that occur in it
 - * **State** : $\text{Var} \rightarrow \text{Val}$
 - Assigns each variable a value
 - Total function
 - * **Sigma State** σ_{zero} : All variables have the value 0
 - * **Updating States** $\sigma[y \mapsto v]$: Assign v to y in the state σ
 - $$(\sigma[y \mapsto v])(x) = \begin{cases} v & \text{if } x \equiv y \\ \sigma(x) & \text{otherwise} \end{cases}$$
 - * **Equality** of states σ_1, σ_2 if they are equal as functions $\sigma_1 = \sigma_2 \iff \forall x. (\sigma_1(x) = \sigma_2(x))$
 - ◇ **Semantic Functions** map elements of syntactic categories to elements of semantic categories
 - *
 - * **Syntactic Category**: E.g. **Numeral**
 - Some ascii symbol
 - * **Semantic Category**: E.g. \mathbb{Z}
 - Actual value
 - ◇ **Numerals**: Syntactic Category **Numeral**
 - * $\mathcal{N} : \text{Numeral} \rightarrow \text{Val}$
 - * Maps numeral n to integer value $\mathcal{N}[[n]]$
 - Convention to use double brackets
 - Same as with single bracket

$$\begin{array}{ll}
 \mathcal{N}[[0]] = 0 & \mathcal{N}[[n0]] = \mathcal{N}[[n]] \times 10 + 0 \\
 \mathcal{N}[[1]] = 1 & \mathcal{N}[[n1]] = \mathcal{N}[[n]] \times 10 + 1 \\
 \dots & \dots \\
 \mathcal{N}[[9]] = 9 & \mathcal{N}[[n9]] = \mathcal{N}[[n]] \times 10 + 9
 \end{array}$$

- ◇ **Arithmetic Expressions**: Syntactic Category **Aexp**
 - * $\mathcal{A} : \text{Aexp} \rightarrow \text{State} \rightarrow \text{Val}$

- * Maps arithmetic expression e and a state σ to a value $\mathcal{A}[[e]]\sigma$
- *

$$\mathcal{A}[[x]]\sigma = \sigma(x)$$

$$\mathcal{A}[[n]]\sigma = \mathcal{N}[[n]]$$

$$\mathcal{A}[[e_1 \text{ op } e_2]]\sigma = \mathcal{A}[[e_1]]\sigma \overline{\text{op}} \mathcal{A}[[e_2]]\sigma \quad , \text{ where } \text{op} \in \text{Op}$$

- $\overline{\text{op}}$ is the operation $\text{Val} \times \text{Val} \rightarrow \text{Val}$ corresponding to op
- E.g. $\text{op} = '+'$ and $\overline{\text{op}}$ = mathematical addition
- ◊ **Arithmetic Operators:** Syntactic Category **Op**
- ◊ **Boolean Expressions:** Syntactic Category **Bexp**
- * $\mathcal{B} : \text{Bexp} \rightarrow \text{State} \rightarrow \text{Bool} = \{tt, ff\}$
- * Maps boolean expression b and state σ to a truth value $\mathcal{B}[[b]]\sigma$
- *

$$\mathcal{B}[[e_1 \text{ op } e_2]]\sigma = \begin{cases} tt & \text{if } \mathcal{A}[[e_1]]\sigma \overline{\text{op}} \mathcal{A}[[e_2]]\sigma \\ ff & \text{otherwise} \end{cases} \quad , \text{ where } \text{op} \in \text{Rop}$$

- $\overline{\text{op}}$ is the operation $\text{Val} \times \text{Val} \rightarrow \text{Val}$ corresponding to op
- *

$$\mathcal{B}[[e_1 \text{ or } e_2]]\sigma = \begin{cases} tt & \text{if } \mathcal{B}[[e_1]]\sigma = tt \text{ or } \mathcal{B}[[e_2]]\sigma = tt \\ ff & \text{otherwise} \end{cases}$$

$$\mathcal{B}[[e_1 \text{ and } e_2]]\sigma = \begin{cases} tt & \text{if } \mathcal{B}[[e_1]]\sigma = tt \text{ and } \mathcal{B}[[e_2]]\sigma = tt \\ ff & \text{otherwise} \end{cases}$$

$$\mathcal{B}[[\text{not } e]]\sigma = \begin{cases} tt & \text{if } \mathcal{B}[[e]]\sigma = ff \\ ff & \text{otherwise} \end{cases}$$

- ◊ **Relational Operators:** Syntactic Category **Rop**
- ◊ **Statements:** Syntactic Category **Stm**

10.2. Properties

- \mathcal{A}, \mathcal{B} are defined recursively
- Base elements are defined directly
- Composite elements are defined inductively in terms of immediate constituents
- Definition suggests proof by structural induction
- **Structural Induction over Programs**
- ◊

10.3. Free Variables

- Free Variables
 - ◊ All variables occurring in an expression
 - ◊ The naming may be confusing since we do not mean “free” in terms of “bound or free” but rather if there were replaced by a concrete value
 - ◊ **Arithmetic Expressions:**

*

$$FV(e_1 \text{ op } e_2) = FV(e_1) \cup FV(e_2)$$

$$FV(n) = \emptyset$$

$$FV(x) = \{x\}$$

◇ **Boolean Expressions:**

*

$$FV(e_1 \text{ op } e_2) = FV(e_1) \cup FV(e_2)$$

$$FV(\text{not } b) = FV(b)$$

$$FV(b_1 \text{ or } b_2) = FV(b_1) \cup FV(b_2)$$

$$FV(b_1 \text{ and } b_2) = FV(b_1) \cup FV(b_2)$$

◇ **Statements:**

*

$$FV(\text{skip}) = \emptyset$$

$$FV(x := e) = \{x\} \cup FV(e)$$

$$FV(s_1; s_2) = FV(s_1) \cup FV(s_2)$$

$$FV(\text{if } b \text{ then } s_1 \text{ else } s_2 \text{ end}) = FV(b) \cup FV(s_1) \cup FV(s_2)$$

$$FV(\text{while } b \text{ do } s \text{ end}) = FV(b) \cup FV(s)$$

• **Substitution**

◇ $_{[x \mapsto e]}$

* Replace free variable x by e in some expression

◇ **Arithmetic Expressions:**

*

$$(e_1 \text{ op } e_2)[x \mapsto e] \equiv (e_1[x \mapsto e] \text{ op } e_2[x \mapsto e])$$

$$n[x \mapsto e] \equiv n$$

$$y[x \mapsto e] \equiv \begin{cases} e & \text{if } x \equiv y \\ y & \text{otherwise} \end{cases}$$

◇ **Boolean Expressions:**

*

$$(e_1 \text{ op } e_2)[x \mapsto e] \equiv (e_1[x \mapsto e] \text{ op } e_2[x \mapsto e])$$

$$(\text{not } b)[x \mapsto e] \equiv \text{not } (b[x \mapsto e])$$

$$(b_1 \text{ or } b_2)[x \mapsto e] \equiv (b_1[x \mapsto e] \text{ or } b_2[x \mapsto e])$$

$$(b_1 \text{ and } b_2)[x \mapsto e] \equiv (b_1[x \mapsto e] \text{ and } b_2[x \mapsto e])$$

TODO: Move lemma to right location

◇ Lemma $\mathcal{B}[[b[x \mapsto e]]]\sigma \iff \mathcal{B}[[b]]\sigma[x \mapsto \mathcal{A}[[e]]\sigma]$

11. Operational Semantics

- Describes execution on an abstract machine
- Describes how an effect is achieved
- Describes how the state is modified during the execution of a statement
- Useful for proofs about language design and implementations

11.1. Big-Step Semantics

- Describes how the overall result of the execution are obtained
- **Natural Semantics (NS):** The system we use
 - ◊ **Configuration:**
 - * Two types
 - * **Normal Configuration** $\langle s, \sigma \rangle$: Statement s is to be executed in state σ
 - * **Terminal Configuration** σ : Final state
 - ◊ **Transition System:** Tuple (Γ, T, \rightarrow)
 - * **Γ :** Set of configurations
 - $\Gamma = \{\langle s, \sigma \rangle \mid s \in \text{Stm}, \sigma \in \text{State}\} \cup \text{State}$
 - * **T :** Set of terminal configurations
 - $T = \text{State} \subseteq \Gamma$
 - * **\rightarrow :** Transition relation
 - $\rightarrow \subseteq \{\langle s, \sigma \rangle \mid s \in \text{Stm}, \sigma \in \text{State}\} \times \text{State} \subseteq \Gamma \times \Gamma$
 - Described how execution takes place
 - $\langle s, \sigma \rangle \rightarrow \sigma'$
 - ◊ **Inference Rules:**
 - * **Rule Schemas:** Contain meta-variables
 - * **Rule Instance:** Replacing all meta-variables with syntactic elements
 - Only rule instances can be applied
 - * Meta-variables are written using underline
 - * **Rules**
 - **Skip**
 - ▷ Does not modify the state
 - ▷ $\frac{}{\langle \text{skip}, \underline{\sigma} \rangle \rightarrow \underline{\sigma}}$ (SKIP_{NS})
 - **Assignment**
 - ▷ Assigns some value to a variable
 - ▷ $\frac{}{\langle \underline{x} := \underline{e}, \underline{\sigma} \rangle \rightarrow \underline{\sigma}[\underline{x} \mapsto \mathcal{A}[\underline{e}]]\underline{\sigma}}$ (ASS_{NS})
 - **Sequential composition**
 - ▷ Execute the first statement in the initial state, then the second statement in the intermediate state, resulting to some new final state
 - ▷ $\frac{\langle \underline{s}, \underline{\sigma} \rangle \rightarrow \underline{\sigma'} \quad \langle \underline{s'}, \underline{\sigma'} \rangle \rightarrow \underline{\sigma''}}{\langle \underline{s}; \underline{s'}, \underline{\sigma} \rangle \rightarrow \underline{\sigma''}}$ (SEQ_{NS})
 - **If**
 - ▷ If the conditional is true, execute the first statement, else the second
 - ▷ if $\mathcal{B}[\underline{b}]\underline{\sigma} = \text{tt}$: $\frac{\langle \underline{s}, \underline{\sigma} \rangle \rightarrow \underline{\sigma'}}{\langle \text{if } \underline{b} \text{ then } \underline{s} \text{ else } \underline{s'} \text{ end}, \underline{\sigma} \rangle \rightarrow \underline{\sigma'}}$ (IFT_{NS})
 - ▷ if $\mathcal{B}[\underline{b}]\underline{\sigma} = \text{ff}$: $\frac{\langle \underline{s'}, \underline{\sigma} \rangle \rightarrow \underline{\sigma'}}{\langle \text{if } \underline{b} \text{ then } \underline{s} \text{ else } \underline{s'} \text{ end}, \underline{\sigma} \rangle \rightarrow \underline{\sigma'}}$ (IFF_{NS})
 - **While**

- ▷ If the condition hold, execute the body once, leading in a new state
 - ▷ if $\mathcal{B}[[b]]\underline{\sigma} = \text{tt}$: $\frac{\langle \underline{s}, \underline{\sigma} \rangle \rightarrow \underline{\sigma'} \quad \langle \text{while } \underline{b} \text{ do } \underline{s} \text{ end}, \underline{\sigma'} \rangle \rightarrow \underline{\sigma''}}{\langle \text{while } \underline{b} \text{ to } \underline{s} \text{ end}, \underline{\sigma} \rangle \rightarrow \underline{\sigma''}} \text{ (WHT}_{\text{NS}})$
 - ▷ If the condition does not hold, the state is not modified
 - ▷ if $\mathcal{B}[[b]]\underline{\sigma} = \text{ff}$: $\frac{}{\langle \text{while } \underline{b} \text{ to } \underline{s} \text{ end}, \underline{\sigma} \rangle \rightarrow \underline{\sigma}} \text{ (WHF}_{\text{NS}})$
- * **Derivation Tree T :**
 - Combination of rule instances
 - **Root** of T is $\text{root}(T)$
 - **Leaves** are axiom rule instances
 - **Internal nodes** are conclusion rule instances, having the premises are immediate children
 - **Side condition** of all instances must be satisfied
 - $\vdash \langle s, \sigma \rangle \rightarrow \sigma' \iff \exists T. \text{root}(T) \equiv \langle s, \sigma \rangle \rightarrow \sigma'$
 - ▷ I.e. if there exists a valid tree with $\langle s, \sigma \rangle \rightarrow \sigma'$ in its root
- ◇ **Termination:**
 - * Execution of statement s in σ :
 - **Termination Successful:** Iff there exists a state σ' such that $\vdash \langle s, \sigma \rangle \rightarrow \sigma'$
 - **Termination Fails:** Iff there is not state σ' such that $\vdash \langle s, \sigma \rangle \rightarrow \sigma'$
- **Properties**
 - ◇ **Semantic Equivalence**
 - * **Semantically equivalent** are two statements s_1, s_2 iff $\forall \sigma, \sigma'. (\vdash \langle s_1, \sigma \rangle \rightarrow \sigma' \iff \vdash \langle s_2, \sigma \rangle \rightarrow \sigma')$
 - **Notation:** $s_1 \simeq s_2$
 - * Loop unrolling is semantically equivalent in IMP
 - $\forall b, s. (\text{while } b \text{ do } s \text{ end} \simeq \text{if } b \text{ then } s; \text{while } b \text{ do } s \text{ end end})$
 - Does not hold for imperative languages
 - **Proof Idea:**
 - ▷ Show statement in both directions
 - ▷ For each direction, use structural induction
 - ◇ **Deterministic Semantics**
 - * **Lemma:** Big-step semantics of IMP is deterministic
 - $\forall s, \sigma, \sigma', \sigma''. (\vdash \langle s, \sigma \rangle \rightarrow \sigma' \wedge \vdash \langle s, \sigma \rangle \rightarrow \sigma'' \implies \sigma' = \sigma'')$
 - * **Proof Idea:**
 - Structural induction fails if the state does not change
 - ▷ I.e. be have no proper sub-statements
 - Use induction on the shape of derivation tree
 - ▷ To prove property $P(T)$ for all derivation trees T , prove that $P(T)$ holds for an arbitrary derivation tree T under the assumption that $P(T')$ holds for all sub-trees T' of T
 - ▷ $T' \sqsubset T$
 - ▷ Often we do a case distinction on the rule applied at the root of the tree T
 - **IMP Extension** TODO: IMP Extension
 - ◇
 - **Limitation**
 - ◇ Properties of non-terminating programs cannot be expressed
 - ◇ Non distinction between aborting and non-termination
 - ◇ Non-determinism suppresses non-termination
 - ◇ Parallelism cannot be modeled
 - ◇ Definition of semantic equivalence is coarse

11.2. Small-Step Semantics

- Describes how the individual steps of the computation take place
- Allows to express the order of individual steps
- **Structural Operational Semantics (SOS)**: The system we use
 - ◊ **Configuration**:
 - * Same as for NS
 - * Use γ as meta-variables
 - ◊ **Transition System**:
 - * **Γ** : Set of configurations
 - $\Gamma = \{\langle s, \sigma \rangle \mid s \in \text{Stm}, \sigma \in \text{State}\} \cup \text{State}$
 - Same as for NS
 - **Stuck** is non-terminal configuration $\langle s, \sigma \rangle$ if $\nexists \gamma$ such that $\langle s, \sigma \rangle \rightarrow_1 \gamma$
 - ▷ Terminal configurations are never stuck
 - * **T** : Set of terminal configurations
 - $T = \text{State} \subseteq \Gamma$
 - Same as for NS
 - * **\rightarrow_1** : Transition relation
 - $\rightarrow_1 \subseteq \{\langle s, \sigma \rangle \mid s \in \text{Stm}, \sigma \in \text{State}\} \times \Gamma$
 - $\langle s, \sigma \rangle \rightarrow_1 \gamma$ describes the **first step** of executing s in σ
 - γ can have to forms
 - $\gamma = \langle s', \sigma' \rangle$: Execution is **not complete** and we get the configuration $\langle s', \sigma' \rangle$
 - $\gamma = \sigma'$: Execution has **terminate** and the final state is σ'
 - **k-step Execution**: $\gamma \rightarrow_1^k \gamma'$
 - ▷ I.e. there \exists execution from γ to γ' in exactly k steps
 - ▷ Defined inductively over k
 - ▷ $\gamma \rightarrow_1^* \gamma'$ means $\exists k. \gamma \rightarrow_1^k \gamma'$
 - I.e. there is some finite execution
 - ◊ **Inference Rules**:
 - * **Rules**
 - **Skip**
 - ▷ Same as for NS
 - ▷ $\frac{}{\langle \text{skip}, \sigma \rangle \rightarrow_1 \sigma}$ (SKIP_{SOS})
 - ▷ Same as for NS
 - **Assignment**
 - ▷ Same as for NS
 - ▷ $\frac{}{\langle x := e, \sigma \rangle \rightarrow_1 \sigma[x \mapsto \mathcal{A}[[e]]\sigma]}$ (ASS_{SOS})
 - **Sequential composition**
 - ▷ First step of executing the composition is executing the first step of the first statement
 - ▷ If the first statement is done after one step
 - ▷ $\frac{\langle s, \sigma \rangle \rightarrow_1 \sigma'}{\langle s; s', \sigma \rangle \rightarrow_1 \langle s', \sigma' \rangle}$ (SEQ1_{SOS})
 - ▷ If the first statement is not done after one step
 - ▷ $\frac{\langle s, \sigma \rangle \rightarrow_1 \langle s'', \sigma' \rangle}{\langle s; s', \sigma \rangle \rightarrow_1 \langle s''; s', \sigma' \rangle}$ (SEQ2_{SOS})
 - **If**
 - ▷ The first step of executing an if statement is determine the boolean value of the condition

- ▷ if $\mathcal{B}[[b]]\underline{\sigma} = \text{tt}$: $\frac{}{\langle \text{if } b \text{ then } \underline{s} \text{ else } \underline{s'} \text{ end}, \underline{\sigma} \rangle \rightarrow_1 \langle \underline{s}, \underline{\sigma} \rangle}$ (IFT_{SOS})
 - ▷ if $\mathcal{B}[[b]]\underline{\sigma} = \text{ff}$: $\frac{}{\langle \text{if } b \text{ then } \underline{s} \text{ else } \underline{s'} \text{ end}, \underline{\sigma} \rangle \rightarrow_1 \langle \underline{s'}, \underline{\sigma} \rangle}$ (IFT_{SOS})
 - **While**
 - ▷ The first step is to unroll the loop
 - ▷ $\frac{}{\langle \text{while } b \text{ to } \underline{s} \text{ end}, \underline{\sigma} \rangle \rightarrow_1 \langle \text{if } b \text{ then } \underline{s}; \text{while } b \text{ do } \underline{s} \text{ end} \text{ else skip end}, \underline{\sigma} \rangle}$ (WH)
 - * **Derivation Sequence**
 - Sequence of transitions which cannot be extended with further transitions
 - Non-empty
 - Finite or infinite
 - Sequence of configuration $\gamma_0, \gamma_1, \dots$ for which
 - ▷ $\gamma_i \rightarrow_1^1 \gamma_{i+1}$ for each $0 \leq i$ such that $i+1$ is in the range of sequence
 - ▷ If the derivation sequence is finite, then the last configuration is either a terminal or a stuck configuration
 - **Length**: Number of transitions
 - * **Derivation Tree T** :
 - Justify a single step in a derivation sequence
 - Combination of rule instances
 - $\vdash \langle s, \sigma \rangle \rightarrow_1 \sigma' \iff \exists T. \text{root}(T) \equiv \langle s, \sigma \rangle \rightarrow_1 \sigma'$
- ◇ **Termination**:
 - * Execution of statement s in σ :
 - **Terminates**: Iff there exists a finite derivation sequence starting with $\langle s, \sigma \rangle$
 - **Runs Forever**: Iff there exists a infinite derivation sequence starting with $\langle s, \sigma \rangle$
- **Properties**
 - ◇ Proofs over a multi-step execution $\gamma \rightarrow_1^k \gamma'$ are done using strong induction on the number of steps k
 - * Proof the 0-step execution
 - * Proof all other steps using strong mathematical induction
 - Define $P(k)$
 - Prove $P(k)$ for arbitrary k with IH. $\forall k' < k. P(k')$
 - ◇ Semantic Equivalence
 - * **Semantically Equivalent** are two statements s_1, s_2 iff $\forall \sigma$ both:
 - for all stuck or terminal configurations γ we have $\langle s_1, \sigma \rangle \rightarrow_1^* \gamma \iff \langle s_2, \sigma \rangle \rightarrow_1^* \gamma$
 - ▷ The length may be different
 - ▷ The intermediate configurations may be different
 - there is an infinite derivation sequence starting in $\langle s_1, \sigma \rangle$ iff there is one starting in $\langle s_2, \sigma \rangle$
 - **Notation**: $s_1 \simeq s_2$
 - ◇ **Determinism**
 - * **Lemma**: Small-step semantics of IMP is deterministic
 - $\forall s, \sigma, \gamma, \gamma'. \vdash \langle s, \sigma \rangle \rightarrow_1 \gamma \wedge \vdash \langle s, \sigma \rangle \rightarrow_1 \gamma' \implies \gamma = \gamma'$
 - * **Corollary**: There is exactly one derivation sequence starting in a configuration $\langle s, \sigma \rangle$
 - * **Proof Idea**:
 - Induction on the spae of the derivation tree for the transition $\langle s, \sigma \rangle \rightarrow_1 \gamma$
- **IMP Extension** TODO: Imp Extension
 - ◇

11.3. Equivalence

- **Theorem:** For every statement s in IMP, $\vdash \langle s, \sigma \rangle \rightarrow \sigma' \iff \langle s, \sigma \rangle \rightarrow_1^* \sigma'$
 - ◊ If a statement terminates successfully in one semantic, then it also does so in the other, and the final state is equivalent
 - ◊ The termination fails to terminate in the big-step semantics iff it gets stuck or runs forever in the small-step semantic
- **Proof Idea:**
 - ◊ \Rightarrow : Induction in the shape of the derivation tree for $\langle s, \sigma \rangle \rightarrow \sigma'$
 - ◊ \Leftarrow : Induction on the number of steps k

12. Axiomatic Semantics

- Expresses specific properties of the effect of executing a program
- Some aspects of the computation may be ignored
- Useful for program verification
- **Partial Correctness:** Expresses that if a program terminates then there will be a certain relationship between the initial and the final state
- **Total Correctness:** Expresses that a program will terminate and there will be a certain relationship between the initial and the final state
 - ◊ Total Correctness = Partial Correctness + Termination
- Proofs are too detailed when using operational semantics
- **Hoare Triples:** The system we use
 - ◊ $\{P\}s\{Q\}$
 - * **P:** Precondition (Assertion)
 - * **Q:** Postcondition (Assertion)
 - * **s:** Statement
 - ◊ If P evaluates to true in an initial state σ , and if the execution of s from σ terminates in an state σ' then Q will evaluate to true in σ'
 - * Describes partial correctness
 - ◊ **Local Variables**
 - * Can be used to save a value in the initial state so that it can be referenced later
 - * Occur only in assertions
 - * Are never assigned to and are not used by the program
 - ◊ **Assertions**
 - * Consists of boolean expression with local variables (optional)
 - Can be extended with other expressions like quantifiers, new operators etc.
 - * Pre- and postcondition are assertions
 - * We use some convenience notations like \wedge for **and** etc.
 - ◊ **Derivation System**
 - * **Rules**
 - **Skip**

$$\frac{}{\{P\}\text{skip}\{P\}} \text{ (SKIP}_{\text{Ax}})$$
 - **Assignment**

$$\frac{}{\{P[x \mapsto e]\underline{x} := e\}\{P\}} \text{ (ASS}_{\text{Ax}})$$
 - **Sequential Composition**

$$\frac{\{P\}\underline{s}\{Q\} \quad \{Q\}\underline{s'}\{R\}}{\{P\}\underline{s};\underline{s'}\{R\}} \text{ (SEQ}_{\text{Ax}})$$
 - **Conditional Statement**

$$\frac{\{b \wedge P\}\underline{s}\{Q\} \quad \{\neg b \wedge P\}\underline{s'}\{Q\}}{\{P\}\text{if } b \text{ then } \underline{s} \text{ else } \underline{s'} \text{ end}\{Q\}} \text{ (IF}_{\text{Ax}})$$
 - **Loop**

$$\frac{\{b \wedge P\}\underline{s}\{P\}}{\{P\}\text{while } b \text{ do } \underline{s} \text{ end}\{\neg b \wedge P\}} \text{ (WH}_{\text{Ax}})$$
 - ▷ The assertion P is the loop invariant
 - **Consequence**

$$\frac{\{P'\}\underline{s}\{Q'\}}{\{P\}\underline{s}\{Q\}} \text{ (CONS}_{\text{Ax}}) \text{ if } P \models P' \text{ and } Q' \models Q$$
 - **Semantic Entailment** $\models: P \models Q \iff \forall \sigma, \mathcal{B}[[P]]\sigma = \text{tt} \implies \mathcal{B}[[Q]]\sigma =$

- tt
 - ▷ Strengthen precondition
 - ▷ Weaken postcondition
- * **Derivation Tree**
 - As we are used to
 - $\vdash \{P\}s\{Q\} \iff \exists T. \text{root}(T) \equiv \{P\}s\{Q\}$
- * **Proof**
 - Two main methods
 - ▷ **Proof Trees:**
 - Write as derivation trees
 - Tend to get very long
 - Start from the bottom (/end)
 - ▷ **Proof Outlines:**
 - Write proof vertically
 - Not a proof since there is no unique interpretation
 - But most of the time it is ok since we want to show that there exists a derivation tree
 - Loop-invariant is determined by looking how the value changes in consecutive iterations
 - ▷ Could use a table with iteration $0, 1, 2, i, N - 1$ on the x -axis and the variables we care about on the y -axis
 - ▷ Loop invariant is often very similar to the post condition we have
- **Properties**
 - ◊ Properties are typically proven by induction on the shape of derivation tree
 - * Structural induction does often not work due to the rule of consequence
 - ◊ **Semantic Equivalence**
 - * **Semantically equivalent** are two statements s_1, s_2 if $\forall P, Q, \vdash \{P\}s_1\{Q\} \iff \vdash \{P\}s_2\{Q\}$
- **Total Correctness (Termination)**
 - ◊ **Total Correctness:** If P evaluates to true in the initial state σ then the execution of s from σ terminates and Q will evaluate to true in the final statement
 - ◊ **Notation:** $\{P\}s\{\Downarrow Q\}$
 - ◊ **Loop Variant:**
 - * Expression that evaluates to a value in a well-founded set before each iteration
 - Normally we use \mathbb{N}
 - * Each loop iteration must decrease the value of the invariant
 - * Loop has to terminate once the minimal value of the well-founded set is reached
 - * Used to prove termination
 - ◊ This is a separate axiomatic semantic and is not mixed with the previous one
 - ◊ **Rules**
 - * **Loop**

$$\frac{\{\underline{b} \wedge \underline{P} \wedge \underline{e} = Z\}s\{\Downarrow \underline{P} \wedge \underline{e} < Z\}}{\{\underline{P}\}\text{while } \underline{b} \text{ do } \underline{s} \text{ end}\{\Downarrow \neg \underline{b} \wedge \underline{P}\}} \text{ (WHTOT}_{\text{Ax}}) \text{ if } \underline{b} \wedge \underline{P} \models 0 \leq \underline{e} \text{ and } Z \notin \underline{P}$$
 - All other rules are equivalent to before except that we add \Downarrow to the postcondition
 - ◊ In proof schemas asserts are often pre- and postcondition. Therefore, we do not write an arrow there. For asserts which are only postcondition, we write an arrow

12.1. Soundness and Completeness

- **Soundness:** If a property can be prove then it does indeed hold

- ◊ $\vdash \{P\}s\{Q\} \implies \models \{P\}s\{Q\}$
- **Completeness:** If a property does hold then it can be proved
 - ◊ $\models \{P\}s\{Q\} \implies \vdash \{P\}s\{Q\}$
- Hard to create an axiomatic semantic which is sound and complete
- Soundness and completeness can be proved with respect to an operational semantics
 - ◊ $\{P\}s\{Q\}$ is valid, written as $\models \{P\}s\{Q\}$ iff:

$$\forall \sigma, \sigma'. \mathcal{B}[[P]]\sigma = \text{tt} \wedge \vdash \langle s, \sigma \rangle \rightarrow \sigma' \implies \mathcal{B}[[Q]]\sigma' = \text{tt}$$
 - ◊ I.e. $\models \{P\}s\{Q\}$ is true if, whenever we start execution of s from a state where P holds, if the execution terminates, then Q will hold in the final state
- **Theorem:** For all partial correctness triplets $\{P\}s\{Q\}$ of IMP we have $\vdash \{P\}s\{Q\} \iff \models \{P\}s\{Q\}$
 - ◊ **Proof Idea:**
 - * \implies : Induction on the shape of the derivation tree for $\{P\}s\{Q\}$
 - * \impliedby : Induction but using some weakest precondition stuff

13. Model Checking

- With operational/axiomatic semantics:
 - ◊ Hard to specify properties of sequences of states
 - ◊ Hard to proof interleaving of concurrent systems
 - ◊ Hard to prove programs with infinite derivation sequences
- **Modelling:** Automated technique that, given a finite-state model of a system and a formal property systematically check whether this property holds for (a given state in) that model
- Abstraction of the real world
- Enumerates all possible states of a system
- Mainly used to analyse system designs
 - ◊ And not implementations
- **Explicit State Model Checking:** Represent states explicitly through concrete values
 - ◊ Our focus
- **Symbolic Model Checking:** Represent state through (boolean) formulas
- **Model Checking Process**
 - ◊ **Modelling Phase**
 - * Model the system under consideration using the description language of the model checker
 - * Formalize the properties to be checked
 - ◊ **Running Phase**
 - * Run the model checker to check the validity of the property in the system model
 - ◊ **Analysis Phase**
 - * If property the property is violated, analyse the counter example
 - * If we run out of memory we have to reduce the model
- **Modeling Concurrent Systems**
 - ◊ Systems are modelled as finite transition systems
 - ◊ Systems are modelled as communication sequential processes
 - ◊ Processes can communicate via
 - * Shared variables
 - * Synchronous message passing
 - * Asynchronous message passing

13.1. Promela:

Model checking language we use

- Input language of the Spin model checker
- Main objects are processes, channels and variables
- C-like
- **Syntax:**
 - ◊ Constant declaration
 - * `#define N 5`
 - * `mytype = {ack, req};`
 - ◊ Variable declaration
 - * `byte a, b = 5, c;`
 - * `int d[3], e[4] = 3;`
 - * Initialized to zero-equivalent values
 - * Are either local to a process or global
 - ◊ Structure declaration

- * `typedef verctor {int x; int y};`
- ◇ Channel declaration
 - * `chan c1 = [2] of {mytype, bit, chan};`
 - * `chan c2 = [0] of {int};`
 - * `chan c3;`
 - * `c1` can store up to two messages and messages sent via `c1` consists of three parts
 - * `c2` models rendez-vous communication as it has no buffer
 - * `c3` is uninitialized and must be assigned an initialized channel before usage
 - * Are either local to a process or global
- ◇ Process declaration
 - * `proctype myProc(int p) {...}`
 - * Body contains of a sequence of variable declarations, channel declarations and statements
- ◇ Activate process
 - * `active [N] proctype myProc(...) {...}`
 - * Start N instances of `myProc` in the initial state
 - * The `init` process is started in the initial state

◇ **Types**

	Type	Value range
	bit or bool	$0 \dots 1$
* Primitive types	byte	$0 \dots 255$
	short	$-2^{15} \dots 2^{15} - 1$
	int	$-2^{31} \dots 2^{31} - 1$
* User-defined types		
○ Arrays:	<code>int name[4]</code>	
○ Structures		
○ Type of symbolic contents:	<code>mtype</code>	
* Channel type:	<code>chan</code>	

• **State Space:**

◇ **Sequential Programs**

- * $\#states = \#program\ locations \times \prod_{variable\ x} |\underbrace{\text{dom}(x)}_{\#possible\ values\ of\ x}|$
- * Exponential growth of states in number of variables
- * State space explosion

◇ **Concurrent Programs**

- * Upper bound for $\#$ states of $P \equiv P_1 \parallel \dots \parallel P_N$
- * $\#states\ of\ P_1 \times \dots \times \#states\ of\ P_N = \prod_{i=1}^N (\#program\ locations_i \times \prod_{variable\ x_i} |\text{dom}(x_i)|)$
- * Exponential growth of states in number of processes
- * State space explosion

◇ **Promela Model**

- * Number of states of a system with N processes and K channels is bounded by

$$\prod_{i=1}^N (\#program\ locations_i \times \prod_{variable\ x_i} |\text{dom}(x_i)|) \times \prod_{j=1}^K |\underbrace{\text{dom}(c_j)}_{\#possible\ messages\ of\ channel\ c}| \underbrace{\text{cap}(c_j)}_{\text{capacity/buffer size of channel } c}$$

- * Exponential growth of states in number of channels and the capacity of channels
- * State space explosion

- **State Transitions:**
 - ◊ Statement can be **executable** or **blocked**
 - * Send is blocked if channel is full
 - * **s1;s2** is blocked if **s1** is blocked
 - * **timeout** is executable if all other statements are blocked
 - ◊ Transitions is made in three steps
 - * Determine all executable statements of all active processes
 - If there are none, transition system gets stuck
 - * Choose non-deterministically one of the executable statements
 - * Change the state according to the chosen statement
- **Expressions**
 - ◊ Variables, constants and literals
 - ◊ Structure and array accesses
 - ◊ Unary and binary expression with operators
 - * + - * / % > >= < <= == != ! & || && | ~ >> << ^ ++ --
 - ◊ Function applications
 - * **len()** **empty()** **nempty()** **nfull()** **full()** **run** **eval()** **enable()** **pcvalue()**
 - ◊ Conditional expressions (**E1 -> E2 : E3**)
- **Statements**
 - ◊ **skip**
 - * Does not change the state
 - * Always executable
 - ◊ **timeout**
 - * Does not change the state
 - * Executable if all other statements in the system are blocked
 - ◊ **assert(E)**
 - * Aborts execution if expression E evaluates to zero and otherwise equivalent to **skip**
 - * Always executable
 - ◊ **Assignment**
 - * **x = E** assigns the value of E to variable **x**
 - * **a[n] = E** assigns the value of E to array element **a[n]**
 - * Always executable
 - ◊ **Sequential composition**
 - * **s1;s2** is executable if **s1** is executable
 - ◊ **Expression statement**
 - * Evaluates expression E
 - * Executable if E evaluates to a value different from zero
 - * E must not change state
 - ◊ **Selection**
 - * **if**
 - :: **s1**
 - :: ...
 - :: **s=**
 - fi**
 - * Executable if at least one of its options is executable
 - * Chooses an option non-deterministically and executes it
 - * Optional statement **else** is executed if non of the other options is
 - ◊ **Repetition**

- * **do**
 - :: **s1**
 - :: ...
 - :: **sn**
- od**
- * Executable if at least one of its options is executable
- * Chooses repeatedly an option non-deterministically and executed it
- * Terminates when a **break** or **goto** is executed
- ◇ **Atomic**
 - * Basic statements are executed atomically
 - Includes **skip**, **timeout**, **assert**, assignment, expression statement
 - * **atomic{s}** executes **s** atomically
 - * Executable if the first statement of **s** is executable
 - * If any other statement within **s** blocks once the execution of **s** has started, atomicity is lost
- **Macros**
 - ◇ Does not contain procedures
 - * Can most of the time be achieved with macros
 - ◇ String replacement as in C
- **Channels**
 - ◇ Declare **chan ch = [d] of {t1, ..., tn}**
 - ◇ Buffer up to *d* messages
 - * **d > 0**: FIFO buffer channel
 - * **d = 0**: Rendez-vous unbuffered channel
 - ◇ Each message is a tuple whose elements are of type **t1, ..., tn**
 - ◇ **Buffered Channel:**
 - * **Send Message**
 - **ch ! e1, ..., en**
 - Type of **ei** must match type **ti** of channel declaration
 - Executable iff buffer is not full
 - * **Receive Message**
 - **ch ? a1, ..., an**
 - **ai** is a variable or constant of type **ti**
 - Executable iff buffer is not empty and oldest message in the buffer matches the constants **ai**
 - Variables **ai** are assigned values of the message
 - ◇ **Unbuffered Channel:**
 - * Models synchronous communication
 - * **Send Message**
 - **ch ! e1, ..., en**
 - Executable if there is a receive operation that can be executed simultaneously
 - * **Receive Message**
 - **ch ? a1, ..., an**
 - Executable if there is a send operation that can be executed simultaneously

13.2. Linear Temporal Logic (LTL)

- Many interesting properties relate several states
- **Transition System**
 - ◇ Slightly different from what we are used to

- ◇ Tuple $(\Gamma, \sigma_I, \rightarrow)$
 - * **Γ** : Finite set of configurations
 - Different is that now it is finite
 - * **σ_I** : Internal configuration
 - $\sigma_I \in \Gamma$
 - Different is that we only consider the initial configuration
 - Terminal configuration can be modelled by introducing a special **sink state** which cannot be left again
 - * \rightarrow : transition relation
 - $\rightarrow \subseteq \Gamma \times \Gamma$
- ◇ **Promela Model**
 - * Configurations are just states
 - We do not need statement since this is appointed by the location counter
 - * The initial configuration is the initial state
 - Init process is active
 - Everything is initialized to zero-equivalent
 - * Transition relation is defined by OS statements
 - * Promela model has a finite number of states
 - Still very large, but finite
- **Computations**
 - ◇ S^ω is a infinite sequence of elements of the set S
 - * $s_{[i]}$ is the i -th element in this sequence
 - * Opposed to S^* which is a finite sequence
 - ◇ **Computation**: Infinite sequence $\gamma \in \Gamma^\omega$ of states for which:
 - * $\gamma_{[0]} = \sigma_I$
 - * $\gamma_{[i]} \rightarrow \gamma_{[i+1]}, i \geq 0$
 - ◇ $\mathcal{C}(TS)$ is the set of all computations of a transition system TS
- **Linear-Time Properties (LT-Properties)**
 - ◇ Limits the permitted computations of a transition system
 - ◇ $P \subseteq \Gamma^\omega$
 - ◇ $TS \models P \iff \mathcal{C}(TS) \subseteq P$
 - * All computations of TS belong to the set P
 - ◇ LT-properties express properties of computations
 - * Non-termination is handled by infinite sequences
 - * Non-determinism is handled by considering each computation separately
 - ◇ Try to simplify it more
 - ◇ **Atomic Propositions (AP)**: Set of properties we care about
 - * Called atomic since they contain no logical connectives
 - ◇ **Labeling Function**: Maps configurations to sets of atomic propositions from AP
 - * $L : \Gamma \rightarrow \mathcal{P}(AP)$
 - * \mathcal{P} is the powerset. Once configuration can be part of multiple APs
 - * **Abstract State**: $L(\sigma)$ labeled state
 - ◇ We consider AP and L as part of the system
 - * We have a 5-tuple instead of tripple
 - ◇ **Trace**
 - * Abstraction of a computation
 - * Infinite sequence of abstract states
 - $\mathcal{P}(AP)^\omega$
 - * $t \in \mathcal{P}(AP)^\omega$ is a trace of transition system TS if $t = L(\gamma_{[0]})L_{\gamma_{[1]}} \dots$ and γ is a

- computation of TS
- * $\mathcal{T}(\text{TS})$ set of all traces of transition system TS
- ◇ **Safety Properties**
 - * I.e. something bad is never allowed to happen
 - And once it happened, it cannot be fixed
 - * LT-property P is a safety property if for all infinite sequences $t \in \mathcal{P}(\text{AP})^\omega$: if $t \notin P$, then there is a finite prefix \hat{t} of t such that every infinite sequence t' with prefix \hat{t} , $t' \notin P$
 - * **Bad Prefix \hat{t}** : Finite sequence which already violates the property
 - Even if the violation only happens after the sequence
 - * Safety properties are violated in finite time
 - Even if the sequence is infinite
 - Can be tested
- ◇ **Liveness Properties**
 - * I.e. something good will happen eventually
 - * LT-property P is a liveness property if all finite sequences $\hat{t} \in \mathcal{P}(\text{AP})^*$ are a prefix of an infinite sequence $t \in P$
 - Every finite prefix can be extended to an infinite sequence which is in P
 - * Liveness properties are violated in infinite time
 - Cannot be tested
- **Linear Temporal Logic (LTL)**
 - ◇ Logic which makes it easy to reason about LT-properties
 - ◇ Fully blown logic
 - + Whether or not a trace of a finite transition system satisfies an LTL formula is decidable
 - ◇ Reasons about traces and not single states
 - ◇ **Syntax:**
 - * $\phi = p \mid \neg\phi \mid \phi \wedge \phi \mid \underbrace{\phi \text{U} \phi}_{\text{until}} \mid \underbrace{\bigcirc \phi}_{\text{next}}$
 - Where p is a proposition from a chosen set of atomic propositions $\text{AT} \neq \emptyset$
 - ◇ **Semantics:**
 - * Trace $t \in \mathcal{P}(\text{AP})^\omega$ satisfies LTL formula ϕ : $t \models \phi$
 - * $t_{(\geq i)}$ is the suffix of t starting at t_i
 - *

$$\begin{array}{ll}
 t \models p & \text{iff } p \in t_{[0]} \\
 t \models \neg\phi & \text{iff not } t \models \phi \\
 t \models \phi \wedge \psi & \text{iff } t \models \phi \text{ and } t \models \psi \\
 t \models \phi \text{U} \psi & \text{iff } \exists k \geq 0, t_{(\geq k)} \models \psi \text{ and } t_{(\geq j)} \models \phi \forall j, 0 \leq j < k \\
 t \models \bigcirc \phi & \text{iff } t_{(\geq 1)} \models \phi
 \end{array}$$

- ◇ **Derived Operators:**
 - * true, false, \vee , \implies , \iff are defined as usual
 - * **Eventually:** $\Diamond\phi \equiv (\text{true} \text{U} \phi)$
 - * **Always from now:** $\Box\phi \equiv \neg\Diamond\neg\phi$
 - * **Precedence:** Unary over binary
 - * **Specification Patterns:**
 - **Strong Invariant:** $\Box\psi$
 - ▷ ψ always holds

- ▷ Safety property
 - **Monotone Invariant:** $\Box(\psi \implies \Box\psi)$
 - ▷ Once ψ is true, then ψ is always true
 - ▷ Safety property
 - **Establishing an invariant:** $\Diamond\Box\psi$
 - ▷ Eventually ψ will always hold
 - ▷ Liveness property
 - **Responsiveness:** $\Box(\psi \implies \Diamond\phi)$
 - ▷ Every time that ψ holds, ϕ will eventually hold
 - ▷ Liveness property
 - **Fairness:** $\Box\Diamond\psi$
 - ▷ ψ holds infinitely often
 - ▷ Liveness property
- ◇ **Model Checking**
 - * Given a finite transition system TS and a LTL formula ϕ , decide whether $t \models \phi$ for all $t \in \mathcal{T}(\text{TS})$
 - I.e. $\mathcal{T}(\text{TS}) \subseteq P(\phi)$
 - * Hard because traces are in general infinite
 - * **Checking Safety Properties:**
 - Violation is observed in an finite prefix
 - **Idea:**
 - ▷ Characterize all finite prefixes of the traces of the transition system using a finite automata
 - In TS labels are on the states where there are on the transitions for the FA
 - FA is Tuple $(Q, \Sigma, \delta, Q_0, F)$
 - Q : finite set of states
 - Σ : finite alphabet
 - δ : transition relation
 - $\delta \subseteq Q \times \Sigma \times Q$
 - $Q_0 \subseteq Q$: initial state
 - $F \subseteq Q$: accepting states
 - Given transition system $TS = (\Gamma, \sigma_I, \rightarrow)$ we define NFA $\mathcal{F} \mathcal{A}_{\text{TS}}$ characterizing all finite prefixes $\mathcal{T}_{\text{fin}}(\text{TS})$ of the traces of TS
 - $\mathcal{F} \mathcal{A}_{\text{TS}} = (Q, \Sigma, \delta, Q_0, F)$
 - $Q = \Gamma \cup \{\sigma_0\}, \sigma_0 \notin \Gamma$
 - $\Sigma = \mathcal{P}(\text{AP})$
 - $\delta = \{(\sigma, p, \sigma') \mid \sigma \rightarrow \sigma' \text{ and } p = L(\sigma')\} \cup \{(\sigma_0, p, \sigma_I) \mid p = L(\sigma_I)\}$
 - $Q_0 = \{\sigma_0\}$
 - $F = Q$
 - ▷ Check whether any of them violates the safety property
 - Manual checking possible for simple FA
 - Automatic checking not possible
 - **Regular Safe Properties:**
 - ▷ Restriction
 - ▷ Safety property is regular if its bad prefixes are described by a regular language over the alphabet $\mathcal{P}(\text{AP})$
 - ▷ Every invariant over AP is a regular safety property
 - ▷ **Checking Regular Safety Properties:**

- Describe finite prefixes $\mathcal{T}_{\text{fin}}(\text{TS})$ by finite automata $\mathcal{F} \mathcal{A}_{\text{TS}}$
- Describe bad prefixes of regular safety property P by finite automata $\mathcal{F} \mathcal{A}_{\overline{P}}$
- Construct finite automata for product of $\mathcal{F} \mathcal{A}_{\text{TS}}$ and $\mathcal{F} \mathcal{A}_{\overline{P}}$
 - Product corresponds to the intersection of both FA **TODO: describe construction**
- Check if resulting automaton has any reachable accepting states
 - If not, property P is never violated in traces of TS
 - If yes, the property P is violated
 - Counterexample is any accepted word by the automata
- So far we can not check non-regular safety properties and liveness properties
- * **ω -Regular Languages**
 - Denote languages of infinite words
 - Expression G has the form $G = E_1 F_1^\omega + \dots + E_n F_n^\omega$ ($1 \leq n$)
 - ▷ E_i and F_i are regular expression
 - ▷ $+$ means or
 - **Büchi Automata (NBA)**
 - ▷ Very similar to FA
 - ▷ Accept infinite words
 - ▷ Accepted language agrees with the class of ω -regular languages
 - ▷ Non-deterministic
 - ▷ Tuple $(Q, \Sigma, \delta, Q_0, F)$
 - Q : finite set of states
 - Σ : finite alphabet
 - δ : transition relation
 - $\delta \subseteq Q \times \Sigma \times Q$
 - $Q_0 \subseteq Q$: initial state
 - $F \subseteq Q$: accepting states
 - ▷ Accept word if it passes infinitely often through an accepting state
 - **Checking:**
 - ▷ Describe traces $\mathcal{T}(\text{TS})$ by NBA $\mathcal{B} \mathcal{A}_{\text{TS}}$
 - ▷ For an LTL formula ϕ , construct NBA $\mathcal{B} \mathcal{A}_{\neg\phi}$ that accepts the traces (i.e. the bad traces) characterized by $\neg\phi$
 - ▷ Construct NBA for products of $\mathcal{B} \mathcal{A}_{\text{TS}}$ and $\mathcal{B} \mathcal{A}_{\neg\phi}$
 - ▷ Check whether the language accepted by product NBA is empty
 - If language is non-empty, property ϕ is violated
 - Each word in the language is a counterexample
- * **Complexity**
 - For a finite transition system TS and an LTL formula ϕ the model checking problem $\text{TS} \models \phi$ is solvable in $\mathcal{O}(|\text{TS}| \times 2^{|\phi|})$
 - ▷ $|\text{TS}|$: size of the transition system
 - Grows exponentially in the number of variables, processes and channels
 - ▷ $|\phi|$: size of ϕ
 - Grows exponentially due to the construction of the $\mathcal{B} \mathcal{A}_{\neg\phi}$

Part III.

Appendix

14. Prelude

- `curry :: ((a, b) -> c) -> a -> b -> c`
 - ◊ Converts uncurried function to curried function
- `uncurry :: (a -> b -> c) -> (a, b) -> c`
 - ◊ Converts curried function to function on tuple
- `fromEnum :: a -> Int`
 - ◊ Gives ascii value of a char
- `toEnum :: Int -> a`
 - ◊ Gives character of a certain ascii value
- `abs :: Num => a -> a`
 - ◊ ABS value of number
- `signum :: Num => a -> a`
 - ◊ Returns -1, 0 or 1
- `foldMap :: Monoid m => (a -> m) -> t a -> m`
 - ◊ Map each element of the passed list to a monoid (array of one element) and apply the function on it
 - ◊ Example:
 - * `foldMap (replicate 3) [1,2,3] = [1,1,1,2,2,2,3,3,3]`
- `foldr :: (a -> b -> b) -> b -> t a -> b`
- `foldl :: (b -> a -> b) -> b -> t a -> b`
- `elem :: Eq a => a -> t a -> Bool`
 - ◊ Does element occur in list
- `maximum :: Ord a => t a -> a`
 - ◊ Largest element of non-empty list
- `minimum :: Ord a => t a -> a`
 - ◊ Least element of non-empty list
- `sum :: Num a => t a -> a`
 - ◊ Sum of list
- `product :: Num a => t a -> a`
 - ◊ Product of list
- `(.) :: (b -> c) -> (a -> b) -> a -> c`
 - ◊ Function composition
- `flip :: (a -> b -> c) -> b -> a -> c`
 - ◊ Takes function with two arguments and applies the arguments in switched order
- `($)`
 - ◊ Useful to omit parentheses
 - ◊ Example: `f $ g $ h x = f (g (h x))`
- `until :: (a -> Bool) -> (a -> a) -> a -> a`
 - ◊ Yields the result of applying the function until the condition hold
- `map :: (a -> b) -> [a] -> [b]`
- `(++) :: [a] -> [a] -> [a]`
- `filter :: (a -> Bool) -> [a] -> [a]`
- `head :: [a] -> a`
 - ◊ First element of the list
- `last :: [a] -> a`
 - ◊ Last element of the list
- `tail :: [a] -> [a]`
 - ◊ All except the first element of the list

- `init :: [a] -> [a]`
 - ◊ All expect the last
- `(!!) :: [a] -> Int -> a`
 - ◊ Returns the n -th element of a list
- `null :: Foldable t => t a -> Bool`
 - ◊ Test whether list is empty
- `length :: Foldable t => t a -> Int`
 - ◊ Length of list
- `reverse :: [a] -> [a]`
 - ◊ Reverses given list
 - ◊ Only works for finite list
- `and :: Foldable t => t Bool -> Bool`
 - ◊ Return true iff all elements in the list are true
- `or :: Foldable t => t Bool -> Bool`
 - ◊ Return true iff at least one element of the list is true
- `any :: Foldable t => (a -> Bool) -> t a -> Bool`
 - ◊ Check if any element of the list satisfies the predict
- `all :: Foldable t => (a -> Bool) -> t a -> Bool`
 - ◊ Check if all element of the list satisfies the predict
- `concat :: foldable t => t [a] -> [a]`
 - ◊ The concatenation of all the elements of a container of lists
 - ◊ Example: `concat [[1,2,3],[4,5],[6],[]] = [1,2,3,4,5,6]`
- `concatMap :: Foldable t => (a -> [b]) -> t a -> [b]`
 - ◊ Example: `concatMap (take 3) [[1..],[10..],[100..]] = [1,2,3,10,11,12,100,101,102]`
- `scanl :: (b -> a -> b) -> b -> [a] -> [b]`
 - ◊ Similar to `foldl` but gives intermediate results
 - ◊ Example: `scanl (+) 0 [1..4] = [0,1,3,6,10]`
 - ◊ Example: `scanl (-) 100 [1..4] = [100,99,97,94,90]`
- `scanr :: (a -> b -> b) -> b -> [a] -> [b]`
 - ◊ Similar to `foldl` but gives intermediate results
 - ◊ Example: `scanl (+) 0 [1..4] = [10,9,7,4,0]`
 - ◊ Example: `scanl (-) 100 [1..4] = [98,-97,99,-96,100]`
- `iterate :: (a -> a) -> a -> [a]`
 - ◊ Infinitely often apply the function to the value
 - ◊ Example: `iterate (+3) 42 = [42,45,48,51,54,...]`
- `repeat :: a -> [a]`
 - ◊ Repeat the value in an infinite list
 - ◊ Example: `repeat 0 = [0,0,0,...]`
- `replicate :: Int -> a -> [a]`
 - ◊ Create list containing x n times
 - ◊ Example: `replicate 4 True = [True, True, True, True]`
- `cycle :: [a] -> [a]`
 - ◊ Create infinite list from given list
 - ◊ Example: `cycle [1,2] = [1,2,1,2,1,2,...]`
- `take :: Int -> [a] -> [a]`
 - ◊ Returns prefix of length n or xs if n is larger than its size
 - ◊ Example: `take 3 "test" = "tes"`
- `drop :: Int -> [a] -> [a]`
 - ◊ Returns suffix after the first n elements or `[]` if n is larger than length of list

- ◊ Example: `drop 3 "test" = "t"`
- `takeWhile :: (a -> Bool) -> [a] -> [a]`
 - ◊ Returns longest prefix of list that all satisfy the predicate
 - ◊ Example: `takeWhile (<3) [1..5] = [1,2]`
- `dropWhile :: (a -> Bool) -> [a] -> [a]`
 - ◊ Returns suffix after applying `takeWhile`
 - ◊ Example: `dropWhile (<3) [1..5] = [3,4,5]`
- `span :: (a -> Bool) -> [a] -> ([a], [a])`
 - ◊ Tuple of `takeWhile` and `dropWhile`
 - ◊ Example: `span (<3) [1..5] = ([1,2], [3,4,5])`
- `splitAt :: Int -> [a] -> ([a], [a])`
 - ◊ Split list at n (first element is n long)
 - ◊ Example: `splitAt 3 "Test" = ("Tes", "t")`
- `zip :: [a] -> [b] -> [(a, b)]`
 - ◊ Combines two list into tuple
 - ◊ Final length is length of the shorter list
- `zip3 :: [a] -> [b] -> [c] -> [(a, b, c)]`
- `zipWith :: (a -> b -> c) -> [a] -> [b] -> [c]`
 - ◊ Example: `zipWith (+) [1,2,3] [4,5,6] = [5,7,9]`
 - ◊ `zipWith3` also exists
- `unzip :: (a, b) -> [a] -> [b]`
- `unzip3 :: (a, b, c) -> [a] -> [b] -> [c]`
- `show :: a -> String`
 - ◊ Convert anything to string
- `read :: Read a => String -> a`
 - ◊ Convert string to anything
 - ◊ Often we need to give the type
 - ◊ Example: `read "123" :: Int = 123`

15. Data.List

- `intersperse :: a -> [a] -> [a]`
 - ◊ Example: `intersperse ', ', "abcdef" = "a,b,c,d,e,f"`
- `transpose :: [[a]] -> [[a]]`
 - ◊ Can be useful in conjunction with infinite list
- `subsequences :: [a] -> [[a]]`
 - ◊ Powerset of given set (/list)
 - ◊ Example: `subsequences "abc" = ["", "a", "b", "c", "ab", "ac", "cd", "abc"]`
- `permutations :: [a] -> [[a]]`
 - ◊ Example: `permutations "abc" = ["abc", "bac", "cba", "cab", "acb"]`
- `group :: Eq a => [a] -> [[a]]`
 - ◊ Split list into sublist where each element contains only the same element
 - ◊ Example: `group "Mississippi" = ["M", "i", "ss", "i", "ss", "i", "pp", "i"]`
- `isPrefixOf :: Eq a => [a] -> [a] -> Bool`
- `isSuffixOf :: Eq a => [a] -> [a] -> Bool`
- `isInfixOf :: Eq a => [a] -> [a] -> Bool`
- `isSubsequenceOf :: Eq a => [a] -> [a] -> Bool`
 - ◊ If all elements of the first list are present in the second
- `nub :: Eq a => [a] -> [a]`
 - ◊ Convert list into set by removing duplicates
- `(\\) :: Eq a => [a] -> [a] -> [a]`
 - ◊ Set difference
- `union :: Eq a => [a] -> [a] -> [a]`
- `intersect :: Eq a => [a] -> [a] -> [a]`
- `sort :: Ord a => [a] -> [a]`