

Handling Uncertainty in a Stochastic Wind Farm Simulator

Jack Kennedy

Kevin Wilson, Daniel Henderson

June 29, 2020

SQuaRES

Newcastle University

Outline

Motivation

Code Uncertainty (Emulation)

Parameter Uncertainty in Computer Models

Athena Application


Motivation

Introduction

- Physical experiments with offshore wind farms at best impractical; possibly deadly
- Computer models predict the future when physical experimentation infeasible
- The output of a computer model $f(\cdot)$ depends on the (unknown) inputs \mathbf{x}
- In a wind farm context, novel designs may be implemented \implies relevant data may not be available
- Perhaps only feasible solution is to **elicit** \mathbf{x}

Athena Simulator

- Inputs (\mathbf{x}): Component hazard parameters; maintenance strategy; wind farm topology (and more!)
- Key Outputs: Availability time series; Average availability (\bar{A})



Uncertainties in computer modelling

- Input uncertainty $\pi(\mathbf{x}) \implies$ output uncertainty $\pi(f(\mathbf{x}))$
- Model is wrong (perhaps it is useful) \implies model discrepancy
- Model might be stochastic \implies output uncertainty EVEN IF inputs known
- Observation error: will typically observe $z = f(\mathbf{x}) + \varepsilon$
- If model complex, obtaining $f(\mathbf{x})$ for single \mathbf{x} could take minutes, hours, weeks ...


Uncertainties in computer modelling

- Input uncertainty $\pi(\mathbf{x}) \implies$ output uncertainty $\pi(f(\mathbf{x}))$
- Model is wrong (perhaps it is useful) \implies model discrepancy
- Model might be stochastic \implies output uncertainty EVEN IF inputs known
- Observation error: will typically observe $z = f(\mathbf{x}) + \varepsilon$
- If model complex, obtaining $f(\mathbf{x})$ for single \mathbf{x} could take minutes, hours, weeks ...

Subjectivism is going to solve all these problems!
Although we all know subjectivism is the best anyway :-)

Process for handling key uncertainties

Model complex \implies not clear which x_i are most important in $f(\mathbf{x})$



Could replace $\pi(\mathbf{x})$ with a posterior $\pi(\mathbf{x}|\mathbf{z})$ IF relevant data available

Code Uncertainty (Emulation)

- Suppose computer simulation is expensive to evaluate, possibly stochastic
- Although I have code to find $f(\mathbf{x})$, pragmatically $f(\mathbf{x})$ unknown
- Able to obtain a handful of runs $y_i = f(\mathbf{x}_i)$, $i = 1 \dots, n$
- Hopefully $f(\mathbf{x})$ ($E(f(\mathbf{x}))$) is “close” to $f(\mathbf{x}')$ ($E(f(\mathbf{x}'))$) when \mathbf{x} “close” to \mathbf{x}'


Bayesian solution takes f a priori to be a Gaussian Process

$$f(\cdot) \sim \mathcal{GP} \{m(\cdot), C(\cdot, \cdot) + \lambda^2(\cdot)\}$$


$$f(\cdot) \sim \mathcal{GP} \{m(\cdot), C(\cdot, \cdot) + \lambda^2(\cdot)\}$$

- $\lambda = 0$ when $f(\cdot)$ deterministic
- $m(\mathbf{x}) = \mathbf{h}(\mathbf{x})^T \beta$: captures global variation in f
- $C(\mathbf{x}, \mathbf{x}') = \sigma^2 \exp \{ -(\mathbf{x} - \mathbf{x}')^T D^{-1} (\mathbf{x} - \mathbf{x}') \}$: local variation, epistemic uncertainty, differentiability
- $\log \lambda^2(\cdot) \sim \mathcal{GP} \{ m_\lambda(\cdot), C_\lambda(\cdot, \cdot) + \omega^2 \}$: aleatory uncertainty (noise)
- Emulator is the posterior predictive: $f(\mathbf{x}) | \mathbf{y} \sim \mathcal{N}(M(\mathbf{x}), V(\mathbf{x}))$


Deterministic Example




Deterministic Example




Deterministic Example



Stochastic Example



Stochastic Example



Stochastic Example

- Many complex stochastic simulators have high noise with low signal
- HetGPs require a lot of “information” to separate signal from noise
- Stochastic simulation is of increasing use to people who aren't statisticians
- Highly topical example: variants of stochastic SIR being used so that humanity survives a massive pandemic
- A few different approaches to signal/noise problem Baker et al. [2020]

Parameter Uncertainty in Computer Models

Parameter Uncertainty

- $f(\cdot)$ effectively “unknown”, but I have emulator
- \mathbf{x} (parameters of f) also unknown for many complex projects
- E.g. in Athena
 - Generator WT = Nobody Knows
 - An Expert might say:
The time at which a typical generator begins degrading $\sim \text{Gamma}(2, 4)$
- Formulate expert opinion as prior density $\pi(\mathbf{x})$
- **How does uncertainty in \mathbf{x} induce uncertainty in $f(\mathbf{x})$?**

Scenario Analysis



Figure 1: “what if” predictions of a coastal town given different plans for energy generation

“Scenarios” are evaluations of $f(\mathbf{x}^{(i)})$ $i = 1, 2, 3, 4$.

How does this take into account $\pi(\mathbf{x})$?

Spoiler alert: it doesn't!

Saltelli and Annoni [2010] explain other dubious practices e.g. OAT

Probabilistic Sensitivity Analysis (Means)

Consider a complex (deterministic) function $Y = f(X)$; $X \sim \pi(x)$

$f(X)$ has a unique ANOVA decomposition

$$f(X) = f_0 + \sum_i f_i(X_i) + \sum_{i < j} f_{ij}(X_{ij}) + \cdots + f_{1\dots K}(X)$$

$$f_i(x_i) = \mathbb{E}_{X_{-i}|i} \{Y | X_i = x_i\} - f_0$$

Probabilistic Sensitivity Analysis (Means)

Consider a complex (deterministic) function $Y = f(X)$; $X \sim \pi(x)$

$f(X)$ has a unique ANOVA decomposition

$$f(X) = f_0 + \sum_i f_i(X_i) + \sum_{i < j} f_{ij}(X_{ij}) + \cdots + f_{1\dots K}(X)$$

$$f_i(x_i) = E_{X_{-i}|i} \{Y | X_i = x_i\} - f_0$$

$$f_{ij}(x_{ij}) = E_{X_{-ij}|ij} \{Y | X_{ij} = x_{ij}\} - f_i(x_i) - f_j(x_j) - f_0$$

Probabilistic Sensitivity Analysis (Means)

Consider a complex (deterministic) function $Y = f(X)$; $X \sim \pi(\mathbf{x})$

$f(X)$ has a unique ANOVA decomposition

$$f(X) = f_0 + \sum_i f_i(X_i) + \sum_{i < j} f_{ij}(X_{ij}) + \cdots + f_{1\dots K}(X)$$

$$f_i(x_i) = E_{X_{-i}|i} \{Y | X_i = x_i\} - f_0$$

$$f_{ij}(x_{ij}) = E_{X_{-ij}|ij} \{Y | X_{ij} = x_{ij}\} - f_i(x_i) - f_j(x_j) - f_0$$

Certain choices of $\pi(\mathbf{x}) \implies$ tractable approximation [Oakley and O'Hagan, 2004]

Probabilistic Sensitivity Analysis (Variances)

- Means “decompose” shape of f
- Want to decompose variance of f : assume f deterministic

$$S_i = \frac{\text{Var}_{X_i} \{f_i(X_i)\}}{\text{Var}(Y)}$$

$$S_{T_i} = \frac{\text{Var}(Y) - \text{Var}_{X_{-i}} \{E(Y|X_{-i})\}}{\text{Var}(Y)}$$

$$S_{T_1} = S_1 + S_{12} + S_{13} + S_{123} \text{ for example}$$

Certain choices of $\pi(x) \implies$ tractable approximation [Oakley and O'Hagan, 2004]

Probabilistic Sensitivity Analysis (Variances)

Marrel et al. [2012] propose adjustment of PSA to accommodate stochastic models
Consider a complex stochastic function $Y = f(X, X_\epsilon)$

$$\text{Var}(Y) = \text{E} \{ Y_d(X) \} + \text{Var} \{ Y_m(X) \}$$

$$S_i = \frac{\text{Var}_{X_{-i}} \{ Y_m(X_i) \}}{\text{Var}(Y)}$$

$$S_{T_\epsilon} = \frac{\text{E} \{ Y_d(X) \}}{\text{Var}(Y)}$$

S_{T_ϵ} is “uncontrollable” uncertainty in simulations (c.f. $1 - R^2$)

Athena Application

Emulator of Athena Model

- Varied 6 inputs using Latin Hypercube design to construct emulator
- We aim to model an offshore wind farm with 200 turbines

Parameter	Lower	Upper
Learning Rate	1.5	10
Cable Failure Rate	0.01	1
Cable Repair Rate	0.15	10
Gearbox WT	0.1	1.5
Freq. Conv. WT	0.1	1.5
Generator WT	0.1	1.5

WT = time to wear out/wear out time

Emulator of Athena Model

- $\bar{A} \in (0, 1) \implies$ emulate $\text{probit}(\bar{A})$
- In fact, used multilevel emulator

$$\text{probit}(\bar{A}_{200}(x)) = \rho E \{ \text{probit}(\bar{A}_{20}(x)) \} + \delta(x) + \varepsilon(x)$$

- Useful when simulator is “very” expensive and cheap approximations are available
- See [previous talk](#) for more details

Emulator of Athena Model




Figure 2: Quick graphical representation of stochastic multilevel emulator.







Stochastic PSA with Athena (Variances)

- 6 inputs $X_i^* \sim \mathcal{N}(0, 0.65^2)$
- Want to use more realistic prior in future (expert's “coarse” opinion)
- With emulator computation takes ~ 2 hours (one run Athena ~ 30 mins!)

Param	Learning Rate	Cable Failure Rate	Cable Repair Rate	Gearbox WT	Generator WT	Freq. Conv. WT	S_{T_ϵ}
\hat{S}_i	0.005	0.080	0.113	0.082	0.274	0.252	0.142

Interactions amongst controllable variables account for $\approx 5\%$ variation

Stochastic PSA with Athena (Expectations)




Sensitivity to the Decision

- I can choose to implement a tried & tested component (d_1) or implement a novel technology (d_2)
- I know a lot about the tried & tested component $\implies \pi_1$ “tight”
- I know relatively little about the novel component $\implies \pi_2$ diffuse
- Suppose I need $\bar{A} > A_{\text{crit}} = 0.8$ (say)
- The choice of component depends on the decision criterion

$$P(\bar{A} > 0.8)$$

Sensitivity to the Decision

Clearly d_2 is best although the particular outcome is more uncertain!
Variance is not always the best description of uncertainty



Sensitivity to the Decision

In fact, the S_i from before have a decision theoretic justification

$$EVPI = E_{x_i} \left[\max_{d \in \mathcal{D}} E_{\mathbf{x}_{-i}|i} [U\{d, f(\mathbf{x})\}] \right] - U^*$$

$$U^* = \max_{d \in \mathcal{D}} E_{\mathbf{x}} [U(d, f(\mathbf{x}))]$$

$U(d, f(\mathbf{x})) = -(d - f(\mathbf{x}))^2 \implies$ recover PSA (variance) and $d^* = E(f(\mathbf{x})|\mathbf{y})$

i.e. best guess of $f(\mathbf{x})$ is its posterior expectation

If I want to improve guess of $Y = f(\mathbf{x})$ I need to “learn” x_i with max S_i

Another one of Oakley [2009]’s brainy ideas

Conclusions

- Emulator reduced computation time from absolutely ages to under a week (most of this was training emulators)
- Athena seems to be approximately additive in mean response and quite smooth
- When I get round to it I will be doing PSA on the variance too
- **My uncertainty** in turbine performance (especially generator) is driving majority of **my uncertainty** in wind farm performance
- \implies In elicitation, spend most time/resources on this (because has largest \hat{S}_i)

Further Work

- Over the next year(ish) plan to perform a series of elicitations to quantify expert uncertainty w.r.t. an actual problem (using Athena)
- i.e. get $\tilde{\pi}(\mathbf{x})$ then use PSA to guide elicitation of $\pi(\mathbf{x})$
- Might even throw some decision analysis in there if I have the time

Thanks!

References

- Evan Baker, Pierre Barbillon, Arindam Fadikar, Robert B. Gramacy, Radu Herbei, David Higdon, Jiangeng Huang, Leah R. Johnson, Pulong Ma, Anirban Mondal, Bianica Pires, Jerome Sacks, and Vadim Sokolov. Stochastic Simulators: An Overview with Opportunities, 2020.
- Amandine Marrel, Bertrand Iooss, Sébastien Da Veiga, and Mathieu Ribatet. Global sensitivity analysis of stochastic computer models with joint metamodels. *Statistics and Computing*, 22(3):833–847, 2012.
- Jeremy E Oakley. Decision-theoretic sensitivity analysis for complex computer models. *Technometrics*, 51(2):121–129, 2009.

- Jeremy E. Oakley and Anthony O'Hagan. Probabilistic sensitivity analysis of complex models: a bayesian approach. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 66(3):751–769, 2004. doi: 10.1111/j.1467-9868.2004.05304.x.
- Andrea Saltelli and Paola Annoni. How to avoid a perfunctory sensitivity analysis. *Environmental Modelling & Software*, 25(12):1508–1517, 2010.