



Model		PT4E010S200
Camera		
Image Sensor	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor	
Horizontal Resolution	1080P	
S/N Ratio	>50db	
PTZ		
Horizontal Rotation Speed	45°/S	
Horizontal Rotation Range	360°	
Tilt Rotation Speed	30°/S	
Tilt Rotation Range	93°	
Auto Flip	Support	
Ratio Speed	Support	
360° Scan	Support	
A-B Scan	Support	
Preset Points	220	
Guard Tours	3 groups	
Guard Points	Max.16 points	
Lens		
Focus Length	5mm-50mm	
Focus Control	10X Optical Zoom	
Night Vision		
Infrared LED	042x6PCS	
IR Range	60 m	
Auto Control IR LED	PWM	
Network		
Network protocol	TCP/IP , TTP , NTP , IGMP , DHCP , UDP , SMTP , RTP , RTSP , ARP , DDNS , DNS , PPPoE , P2P	
ONVIF	Support	
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA	
General		
Weatherproof	IP66	
Operating Temperature	Indoor: 0°~ +40° Outdoor: -20°~ +60°	
Operating Humidity	<90% Non Condensing	
Heater & Blower	Auto temperature control	
Power	DC12V 2A/3A	
Lightning Protection	Transient voltage 6000V	
Dimension	29.5x28x17(cm)	
Weight	4.2Kgs	