



Model NO.	WIFI2004PG1SE200
Package	
NVR	1x NVR2004PGW
Camera	4x LBH30SE200W
WIFI Range	No Obstacles 400m Max
Hard Disk	1x1TB Seagate Hard Disk ST1000VM002
Mouse	1xUSB 2.0 Mouse
Adaptor	1xDC12V2A for WIFI NVR, 8xDC12V0.5A for WIFI IP Camera
Weight	4.6kg/SET
Camera Model	
LBH30SE200W	
Image Sensor	IMX323
Main processor	HI3518EV200
Resolution	1080P
Effective Pixels	1985(H)*1105(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Lens	
Focus Length	3.6mm
Focus Control	Fixed
Lens Type	Fixed
Pixels	3M Pixels
Night Vision	
Infrared LED	14μ x 18PCS (42μ x 2PCS Optional)
Infrared Distance	25M(30M with 42μ x 2PCS LEDS)
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,S MTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
WIFI	Support
Video Delay	0.3S (Within the Lan)
Main Stream	1920*1080@1-15fps(default resolution:1920*1080/frame rate:15fps/bit rate:2Mbps)
Sub Stream	720*480@1-15fps(default frame rate:15fps/bit rate:0.5Mbps)
IE Brower	IE8-11, Google Chrome, Firefox
Smart Phone	iPhone, iPad, Android, Android Pad
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/JPEG/AVI

Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control),Defog Mode
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
WDR	NO
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French,
	Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands
General	
Housing	Metal , IP66
Bracket	YES
IR Cut Filter	YES
Operation Temperature	-10°C ~ +50°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 500mA
Dimension	157(W) x 70(H) x 66(D)mm
Weight	650g
Model	NVR2004PGW
System	
Main Processor	ARM Cortex A9 Processor(HI3520D)
Operating System	Embedded LINUX
Video	
Input	9 Channel(4xWIFI IP Camera + 5xONVIF Wired IP Camera), Support 1920×1080, 1280×960, 1280×720 ect...
Output	1 VGA, 1 HDMI
Alarm	
Sensor Input	NO
Output	NO
Motion Detection	9 Channel
Email Alarm	Support
Display	
VGA	Resolution: 1920×1080/1280×1024/1280×720
HDMI	Resolution: 1080P(1920×1080) 720P:(1280×720)
Display Split	9 channel / 8 channel / 4 Channel / 1Channel
Digital Zoom	YES
OSD	Camera title, Time, Video loss, Recording, Motion Detection
Recording	
Video Compression	H.264
Resolution	1080P(1920×1080) / 960P(1280×960) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	PAL :1080P@9x25fps, 960P@9x25fps, 720P@9x25fpss, D1@9x25fps
Record Mode	NTSC:1080P@9x30fps, 960P@9x30fps, 720P@9x30fps, D1@9x30fps Manual\Timer\Motion Detection

Playback & Backup	
Local Sync Playback	Support 4 Channel Mode
Remote Sync Playback	YES
Search Mode	ALL, Channel, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play
Backup Mode	USB Device/Network
Network	
Interface	4xRJ45(1xWAN + 3xLAN) 10M/100M Adaptive Ethernet Interface
Network Functions	HTTP, IPv4, TCP/IP, DNS,DHCP,NTP,PPPOE,FTP,SMTP, DDNS, Upnp
WIFI	Support
Onvif Version	Support Onvif 2.4
Web Browser	IE8-11, Google Chrome(IE Tab), Firefox(IE Tab)
CMS Software	Support Windows 7/ Windows 8 /Window 10
Cloud Support(P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android PAD
Hard Disk Driver	
Interface Type	1 SATA Interface
Capacity	2.5" / 3.5" SATA up to 6TB
General	
	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa
Language	
	German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian,Nederlands,Greek
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC12V/2A
Working Environment	-10~55°C/10~90%
Dimension(W×D×H)	219*217*40(mm)
Weight	2.0KG (without HDD)