

Lecture 03

Concurrent Programming in Java

Conditional synchronization, native library, and implementation of elementary synchronization mechanisms

Object-Oriented Concurrent Programming, 2019-2020

v2.3, 02-10-2019

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Miguel Oliveira e Silva
DETI, Universidade de Aveiro

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Conditional synchronization

Conditional synchronization

Basic synchronization mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and conditional synchronization with Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomic

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- In the communication between different threads sometimes it is necessary to ensure a certain condition before executing a given code (for example, a thread for printing documents could be scheduled to wait for a non-empty queue);
- This communication requirement is called **conditional synchronization**, and its implementation can be done in two ways;
- It could *actively* be waiting for the condition:

```
while (!condition)
    Thread.yield();
```

- However, if the wait is long, the processor will be actively working on anything relevant (instead of doing useful work elsewhere);

Conditional synchronization (2)

- Alternatively, a cooperative mechanism could be used, in which some threads voluntarily wait (without CPU consumption), and threads that might change the condition explicitly notify such modifications, possibly awakening the former;
- This mechanism is called **condition variables**;
- In Java, this behavior is implemented by methods defined in the `Object` class: `wait`, `notify`, and `notifyAll`.

```
package java.lang;

public class Object {
    public void notify();
    public void notifyAll();
    public void wait() throws InterruptedException;
    public void wait(long timeout) throws InterruptedException;
    public void wait(long timeout, int nanos)
        throws InterruptedException;
    ...
}
```

Conditional synchronization

Basic synchronization mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and conditional synchronization with Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Conditional synchronization

Basic synchronization mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and conditional synchronization with Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- There is a very close relationship between `synchronized` regions and condition variables;
- A conditional wait (`wait`) **has** to be done inside a `synchronized` block (or function) of the **same** object (otherwise, a race condition might occur).
- Although condition variables are based on a cooperative wait/notify mechanism, the mechanism allows waiting threads to be awoken without an explicit notification (*spurious wakeups*);

Conditional synchronization (4)

- Thus a correct use of this mechanism **requires** that the invocation of service `wait` is inside a cycle checking the waiting condition:

```
while (!condition)
    wait();
```

- This requirement also eases the reuse of the same condition variable for several conditions;
- In this case, however: (1) either it is necessary to use the `notifyAll` service (which is the safest and simpler option); (2) or use `notify`, and whenever the wrong thread is awoken, re-notify other possibly waiting threads:

```
while (!condition) {
    wait();
    if (!condition)
        notify();
}
```

Conditional synchronization

Basic synchronization mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and conditional synchronization with Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Conditional synchronization: the problem of checked exceptions

- One of the practical problems posed by native Java's conditional synchronization interface, is the requirement to explicitly deal with `InterruptedException` exceptions;
- If in theory this group of exceptions (named *checked*) seems to make sense, in practice it has shown to be a real menace to program quality (arising several correctness and robustness problems);
- In fact, program developers usually **do not know** what to do to handle exceptions (or, simply, don't want to "waste time" on that, delaying that problem to a later time) leaving empty `catch` blocks (or only with a log registry, which is logically the same thing);
- The possibility to declare within the method's signature the list of exceptions it may launch (an obligation when uncaught checked exceptions are involved), is also a very questionable alternative because, not only may require a lot of bookkeeping code, but also it may break algorithmic abstraction (which, let us not forget, is the essence of the methods);

Conditional synchronization: the problem of checked exceptions

- All these problems can be avoided by implementing waiting methods in which such exceptions are transformed into a proper *unchecked exception*. Such as:
ThreadInterruptedException (such as the one defined in `pt.ua.concurrent` library);
- We can also create a new class to be used in place of the `Object` class where we abstract all this functionality:

```
public class SimplableObject {  
    protected SimplableObject() { super(); }  
  
    public void await() {  
        try { wait(); }  
        catch (InterruptedException e) {  
            throw new ThreadInterruptedException(e);  
        }  
    }  
    ...  
}
```

- The problem with this option is that it is only applicable to classes that do not need to extend other classes. That is, classes that extend it directly or indirectly.

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers


Fork/join executor

Other useful classes

Basic synchronization mechanisms

Semaphores

- A semaphore is a special shared non-negative integer variable, to which the following operations are applicable:
 - acquire (lock, wait, P, decrement, down)
 - release (unlock, signal, V, increment, up)
- The acquire operation ensures a non-negative result, thus it may block until such outcome is possible.
- In general, a maximum counter value is attached to a semaphore (maximum number of concurrent accesses to the resource).
- A semaphore is said to be *binary* if this value is one.
- We can establish a typing relation between different semaphore types:



Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

```
public class Semaphore {  
    /** Creates an unbounded semaphore */  
    public Semaphore();  
  
    /** Creates an unbounded semaphore with  
     * counter initialized to initialCount.  
     * <P><B>requires </B>: {@code initialCount >= 0}  
    */  
    public Semaphore(int initialCount);  
  
    /** Decrements counter (waits if counter equals zero) */  
    public synchronized void acquire();  
  
    /** Increments counter */  
    public synchronized void release();  
}
```

Semaphores: Interface (2)

```
public class BoundedSemaphore extends Semaphore {
    /** Creates a semaphore with maxCount upper limit.
     *  <P><B>requires </B>: {@code maxCount > 0}
     */
    public BoundedSemaphore(int maxCount);

    /** Creates a semaphore with maxCount upper limit
     *  and counter initialized to initialCount.
     *  <P><B>requires </B>: {@code maxCount > 0}
     *  <P><B>requires </B>: {@code initialCount >= 0 &&
     *                        initialCount <= maxCount}
     */
    public BoundedSemaphore(int maxCount, int initialCount);
}

public class BinarySemaphore extends BoundedSemaphore {
    /** Creates a binary semaphore */
    public BinarySemaphore();

    /** Creates a binary semaphore initialized to initialCount.
     *  <P><B>requires </B>: {@code initialCount >= 0 &&
     *                        initialCount <= maxCount}
     */
    public BinarySemaphore(int initialCount);
}
```

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- Synchronization mechanism that gives a single thread the exclusive access to a shared resource.
- It is characterized for having (at least) the following operations:
 - `lock`
 - `unlock`
- Unlike a binary semaphore, it is also characterized by having lock ownership. Thus, an `unlock` operation can only be executed by the owner thread (i.e. the current lock thread).
- A mutex could be defined to be recursive (i.e. the mutex owner thread might perform recursive locks).

```
public class Mutex {  
    /** Creates a non-recursive Mutex */  
    public Mutex();  
  
    /** Creates a Mutex */  
    public Mutex(boolean recursive);  
  
    /** Locks mutex.  
     * <P><B>requires </B>: {@code !lockIsMine()} || recursive()  
     * <P><B>ensures </B>: {@code lockIsMine()}  
     */  
    public synchronized void lock();  
  
    /** Unlocks mutex.  
     * <P><B>requires </B>: {@code lockIsMine()}  
     */  
    public synchronized void unlock();  
  
    /** Is mutex locked by current thread? */  
    public synchronized boolean lockIsMine();  
  
    /** Is mutex recursive? */  
    public synchronized boolean recursive();  
}
```

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- Synchronization mechanism used to safely pass indicative information on the state of the shared resource.
- Is characterized by the following operations:
 - `await (wait)`
 - `signal (notify)`
 - `broadcast (notifyAll)`
- A change in the state attached to a condition variable, should be followed by the execution of a `signal` or `broadcast` operation.
- An exclusive access to the resource that does not finds the required (waiting) state should be followed by the execution of an `await` operation that atomically waits and releases the resource (otherwise a race condition could occur).

Condition variables: Interface

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

```
public class CVMutex {
    /** Creates a condition variable attached to mutex mtx
     * <P><B>requires </B>: {@code mtx != null}
     */
    CVMutex(Mutex mtx);

    /** Mutex attached to condition variable */
    public final Mutex mtx;

    /** Waits signaling.
     * <P><B>requires </B>: {@code mtx.lockIsMine() &&
     *                       mtx.lockCount() == 1}
     */
    public synchronized void await();

    /** Signal one waiting thread */
    public synchronized void signal();

    /** Signal all waiting thread */
    public synchronized void broadcast();
}
```


- Synchronization mechanism that gives exclusive access to a single *writer* (a thread executing a method that might change the resource state) at each time, but allows the concurrent execution to multiple readers (threads execution side-effect free query methods).
- Is characterized by the following operations:
 - `lockReader`
 - `unlockReader`
 - `lockWriter`
 - `unlockWriter`

Readers-writer exclusion: Interface

```
public class RWEx {
    public enum Priority {WRITER, READERS};
    /** Creates a non-recursive RWEx */
    public RWEx(Priority priority);
    /** Is current lock mine? */
    public synchronized boolean lockIsMine();
    /** Is current lock mine as a reader? */
    public synchronized boolean readerLockIsMine();
    /** Is current lock mine as a writer? */
    public synchronized boolean writerLockIsMine();
    /** Locks RWEx as a reader.
     * <P><B>requires </B>: {@code !lockIsMine()}
     * <P><B>ensures </B>: {@code readerLockIsMine()} */
    public synchronized void lockReader();
    /** Locks RWEx as a writer.
     * <P><B>requires </B>: {@code !lockIsMine()}
     * <P><B>ensures </B>: {@code writerLockIsMine()} */
    public synchronized void lockWriter();
    /** Unlocks reader RWEx lock.
     * <P><B>requires </B>: {@code readerLockIsMine()}
     * <P><B>ensures </B>: {@code !lockIsMine()} */
    public synchronized void unlockReader();
    /** Unlocks writer RWEx lock.
     * <P><B>requires </B>: {@code writerLockIsMine()}
     * <P><B>ensures </B>: {@code !lockIsMine()} */
    public synchronized void unlockWriter();
}
```

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Mutual exclusion with Semaphores

- The condition variable mechanism is a programming pattern that can easily be applied to any use of condition synchronization.
- On the other hand, although semaphores are not equivalent to a conditional variable, they are a basic synchronization mechanism implemented for all types of concurrent systems (UNIX processes, for instance, have semaphores, but not condition variables).
- Mutual exclusion is easily implemented with a single binary semaphore.

```
Semaphore mtx = new BinarySemaphore (1);  
  
// lock:  
mtx.acquire ();  
  
// unlock:  
mtx.release ();
```

Conditional synchronization with Semaphores

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- Semaphores can also be applied to implement general condition variables. Lets see how.
- The first thing to be noted is that a condition variable is required to be attached with a mutual exclusion mechanism. Hence, an exclusion binary semaphore is also required.
- The second characteristic of condition variables is that a group of threads may be required to wait for proper signaling. Hence, an integer waiting counter is also necessary.
- Finally, this mechanism requires an atomic behavior joining signaling and mutex acquisition.
- Considering all these requirements, a general solution is the following:

Conditional synchronization with Semaphores

Mutex code:

```
// variables:
Mutex mtx = new Mutex();

MutexCV cvar = mtx.newCV();

// wait:
mtx.lock();
while (!condition)
    cvar.wait();

...
mtx.unlock();

// broadcast:
mtx.lock();
...
cvar.broadcast();

mtx.unlock();
```

Semaphore code:

```
// variables:
Semaphore mtx =
    new BinarySemaphore(1);
int waitingCounter = 0;
Semaphore waitingCondition =
    new Semaphore(0);

// wait:
mtx.acquire();
while (!condition)
{
    waitingCounter++;
    mtx.release();
    waitingCondition.acquire();
    mtx.acquire();
}

...
mtx.release();

// broadcast:
mtx.acquire();
...
while(waitingCounter > 0)
{
    waitingCondition.release();
    waitingCounter--;
}

mtx.release();
```

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Concurrency Library: Lock

- The `Java` native library contains classes that allow the use of explicit locks: `Lock` (and `ReentrantLock`) interfaces;
- These classes surpass some limitations of the `synchronized` blocks:
 - Do not require in association to a structured block;
 - Allow interruption (method `lockInterruptibly`);
 - Provide `tryLock` service;
 - There are different implementations (adapted to each use).
- Usage pattern:

```
lock.lock();  
try {  
    // action  
}  
finally {  
    lock.unlock();  
}
```

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- Interface:

```
package java.util.concurrent.locks;

interface Lock {
    void lock();
    void lockInterruptibly()
        throws InterruptedException;
    Condition newCondition();
    boolean tryLock();
    boolean tryLock(long time, TimeUnit unit)
        throws InterruptedException;
    void unlock();
}
```

- (See also `ReentrantLock`)

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Concurrency Library: Condition

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- Interface:

```
package java.util.concurrent.locks;

interface Condition {
    void await() throws InterruptedException;
    void awaitUninterruptibly();
    boolean await(long time, TimeUnit unit)
        throws InterruptedException;
    long awaitNanos(long nanosTimeout)
        throws InterruptedException;
    boolean awaitUntil(Date deadline)
        throws InterruptedException;
    void signal();
    void signalAll();
}
```

- Allows more than one condition variable in each object.

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Concurrency Library: Tasks

- A concurrent program organizes itself around the execution of *threads*;
- The creation and execution of threads is clearly based on the message passing communication model, but in which the communicating active entities do so by the `Runnable` interface;
- In this model, the asynchronous execution of method is desired, in which `Thread` class binds a method (`run`) to a thread;
- This direct one-to-one connection between tasks and threads may, sometimes, create problems:
 - The **overhead** involved in the creation/destruction of threads;
 - Resource **consumption**, *memory* in particular;
 - **Scalability**: there is a practical limit to the number of threads that may coexist.
- Concurrency abstractions based on the separation between “task” and “thread” provides a controllable solution to these limitations.

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Concurrency Library: Executor

- A scalable alternative that avoids these problems is the usage of a task library;
- The package `java.util.concurrent` provides such a group of functionalities.
- The topmost abstraction defined in this package toward such a goal is the `Executor`:

```
package java.util.concurrent;

public interface Executor {
    void execute(Runnable task);
}
```

- This abstraction is a direct replacement of the thread's `start` method (or `run` method of `Runnable` class).

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- “Under” this interface different thread control schemes can be built:
- Sequential:

```
public class SeqExecutor implements Executor {  
    public void execute(Runnable task) {  
        task.run();  
    }  
}
```

- One task per *thread*:

```
public class ThreadExecutor implements Executor {  
    public void execute(Runnable task) {  
        new Thread(task).start();  
    }  
}
```

- Or any other.

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Concurrency Library: Thread-pools

- The `java.util.concurrent` library provide a rich set of `Executor` modules that covers the more common needs.
- `Executors` class provides static methods that give a simple instantiation:

```
package java.util.concurrent;

public class Executors {
    static ExecutorService newSingleThreadExecutor();
    static ExecutorService newFixedThreadPool(int nThreads);
    static ExecutorService newCachedThreadPool();
    static ScheduledExecutorService newScheduledThreadPool(int corePoolSize);
    ...
}
```

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures
Barriers

Fork/join executor

Other useful classes

- `newSingleThreadExecutor`
 - Creates a single thread that is reused by the submitted tasks (stored internally in an unbounded queue).
- `newFixedThreadPool`
 - Creates a fixed predefined number of threads that are reused by the submitted tasks.
- `newCachedThreadPool`
 - Automatically increases or reduces the number of threads that are reused by the submitted (the number is adapted by the number of submitted tasks).
- `newScheduledThreadPool`
 - Allows the execution of tasks with a pre-defined time schedule. We can launch tasks to be performed after a time delay, or launch tasks to be performed periodically (like timers). This type of thread-pool replaces with many advantages the `Timer` class.

Conditional synchronization

Basic synchronization mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and conditional synchronization with Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- The abstraction `ExecutorService` allows the management of the `Executor` lifecycle:

```
package java.util.concurrent;

public interface ExecutorService extends Executor {
    boolean isShutdown();
    boolean isTerminated();
    void shutdown();
    <T> Future<T> submit(Callable<T> task);
    Future<?> submit(Runnable task);
    <T> Future<T> submit(Runnable task, T result);
    ...
}
```

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

```
package java.util.concurrent;

public interface Future<V> {
    boolean cancel(boolean mayInterruptIfRunning);
    V get();
    boolean isCancelled();
    boolean isDone();
    ...
}
```

```
package java.util.concurrent;

public interface Callable<V> {
    V call();
}
```

- (Later on we will see this type of interfaces in more detail.)

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Concurrency Library: Atomics

- Non-blocking transaction like shared data structures.
- These modules allow a lock-free (i.e. with non-blocking behavior) handling of shared variables.
- **Package:** `java.util.concurrent.atomic`
- `AtomicInteger`, `AtomicLong`, `AtomicBoolean`, `AtomicIntegerArray`, `AtomicLongArray`, `AtomicReference`, `AtomicReferenceArray`.
- These modules represent a better and safer alternative to volatile variables.

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Concurrency Library: Concurrent data structures

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- `java.util.concurrent.BlockingQueue`
- A shared queue in which its normal semantics might be ensured by blocking (add/remove element from a full/empty queue).
- Selected interface:

```
void put(E e)
E take()
```

- Existing implementations: `ArrayBlockingQueue`, `LinkedBlockingQueue`, `PriorityBlockingQueue`, `LinkedBlockingDeque`, `SynchronousQueue`, `DelayQueue`

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- `java.util.concurrent.ConcurrentLinkedQueue`
- Shared lock-free queue.
- Defensive approach to queue operations, issuing immediately a failure if an operation is not possible
- Selected interface:

```
boolean add(E e)
E peek()
E poll()
Iterator<E> iterator()
```

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- `java.util.concurrent.ConcurrentHashMap`
- Shared (mostly) lock-free associative array.
- Defensive approach, issuing immediately a failure if an operation is not possible
- Class `ConcurrentHashMap<K, V>` selected interface:

```
V get(Object key)
V put(K key, V value)           // might be a race condition
V putIfAbsent(K key, V value)  // safe
boolean containsKey(Object key)
boolean replace(K key, V oldValue, V newValue)
Enumeration<K> keys()
```

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures


Barriers

Fork/join executor

Other useful classes

Concurrency Library: Barriers

- Synchronizing the execution of multiple threads to a single point:



Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Barriers (2)

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

- Class

`java.util.concurrent.atomic.CountDownLatch`

- Selected interface:

```
CountDownLatch(int count)
void await()
boolean await(long timeout, TimeUnit unit)
void countDown()
long getCount()
```

- Service `await` waits for `getCount` invocations of `countDown` method.

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Concurrency Library: Fork/join executor

- Optimized executor for fork/join parallel execution (new in Java 7).
- Create the pool:

```
ForkJoinPool forkJoinPool = new ForkJoinPool();
```

- Execute with `invoke` or `invokeAll`
- Possible to define `ForkJoinTask` (`RecursiveAction`, `RecursiveTask`)

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Fork/join executor: example

```
import static java.lang.System.*;
import java.util.concurrent.ForkJoinPool;
import java.util.concurrent.RecursiveAction;

public class Fibonacci {
    public static void main(String[] args) {
        int n = Integer.parseInt(args[0]); // error checking missing!
        FibonacciTask fn = new FibonacciTask(n);
        ForkJoinPool forkJoinPool = new ForkJoinPool();
        forkJoinPool.invoke(fn);
        out.println("f(" + n + ") = " + fn.result());
    }

    static class FibonacciTask extends RecursiveAction {
        final int n;
        int result = 1;
        FibonacciTask(int n) {
            this.n = n;
        }
        int result() {
            return result;
        }
        protected void compute() {
            if (n > 2) {
                FibonacciTask t1 = new FibonacciTask(n-1);
                FibonacciTask t2 = new FibonacciTask(n-2);
                invokeAll(t1, t2);
                result = t1.result + t2.result;
            }
        }
    }
}
```

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Conditional
synchronization

Basic synchronization
mechanisms

Semaphores

Mutual exclusion (Mutex)

Condition variables

Readers-writer exclusion

Mutual exclusion and
conditional
synchronization with
Semaphores

Concurrency Library

Lock

Condition

Tasks

Executor

Thread-pools

Atomics

Concurrent data structures

Barriers

Fork/join executor

Other useful classes

Concurrency Library: Other useful classes

- `ThreadLocal`: variable in which each threads register its own data (a kind of thread local variable accessible through the same object);
- `ReadWriteLock` (to be presented later on);
- ***Synchronizers***: `Semaphore`, `FairSemaphore`, `Exchanger`, ...
- ...
- None of these classes uses Design by Contract!
- A library is being developed (since 2010) that solve this serious flaw:

<http://sweet.ua.pt/mos/pt.ua.concurrent/index.xhtml>