

Introduction to R Graphing

Jeff Oliver

2026-02-12

This brief tutorial will demonstrate how to create a basic plot in R from a text file of data. This introduction provides an entry point for those unfamiliar with R (or a refresher for those who are rusty). We will start with a very minimal piece of code and work our way up to code that automates the creation of 12 different PDF files, each with a different X-Y scatterplot.

Learning objectives

1. Gain familiarity with R
2. Read data from a file
3. Visualize data in a graph
4. Understand the principle of control flow

In this tutorial, we will be using the ‘gapminder’ dataset, available here: <http://tinyurl.com/gapminder-five-year-csv> (right-click or Ctrl-click on link and Save As...). Make sure to save it somewhere you can remember (like your Desktop), as we will need to move it later.

Setup

First we need to setup our development environment. Open RStudio and create a new project via:

- File > New Project...
- Select ‘New Directory’
- For the Project Type select ‘New Project’
- For Directory name, call it something like “r-graphing” (without the quotes)
- For the subdirectory, select somewhere you will remember (like “My Documents” or “Desktop”)

We need to create two folders: ‘data’ will store the data we will be analyzing, and ‘output’ will store the results of our analyses. In the RStudio console:

```
dir.create(path = "data")
dir.create(path = "output")
```

Finally, move the file you downloaded (gapminder-FiveYearData.csv) into the data folder you just created. This is best accomplished *outside* of RStudio, using your computer's file management system.

Your first plot

Plot the points!

```
# Read in data
all_gapminder <- read.csv(file = "data/gapminder-FiveYearData.csv",
                          stringsAsFactors = TRUE)
```

When reading data into R, it is always a good idea to make sure you read in the data correctly. There are a number of ways to investigate your data, but three common methods are:

- `head` shows us the first 6 rows in a data frame.
- `str` (structure) provides some information about the data stored in the data frame.
- `summary` provides even more information about the data, including some summary statistics for numerical data.

```
# Investigate data
head(all_gapminder)
```

	country	year	pop	continent	lifeExp	gdpPercap
1	Afghanistan	1952	8425333	Asia	28.801	779.4453
2	Afghanistan	1957	9240934	Asia	30.332	820.8530
3	Afghanistan	1962	10267083	Asia	31.997	853.1007
4	Afghanistan	1967	11537966	Asia	34.020	836.1971
5	Afghanistan	1972	13079460	Asia	36.088	739.9811
6	Afghanistan	1977	14880372	Asia	38.438	786.1134

```
str(all_gapminder)
```

```
'data.frame': 1704 obs. of 6 variables:
 $ country : Factor w/ 142 levels "Afghanistan",...: 1 1 1 1 1 1 1 1 1 1 ...
 $ year : int 1952 1957 1962 1967 1972 1977 1982 1987 1992 1997 ...
 $ pop : num 8425333 9240934 10267083 11537966 13079460 ...
 $ continent: Factor w/ 5 levels "Africa","Americas",...: 3 3 3 3 3 3 3 3 3 3 ...
 $ lifeExp : num 28.8 30.3 32 34 36.1 ...
 $ gdpPercap: num 779 821 853 836 740 ...
```

```
summary(all_gapminder)
```


country	year	pop	continent
Afghanistan: 12	Min. :1952	Min. :6.001e+04	Africa :624
Albania : 12	1st Qu.:1966	1st Qu.:2.794e+06	Americas:300
Algeria : 12	Median :1980	Median :7.024e+06	Asia :396
Angola : 12	Mean :1980	Mean :2.960e+07	Europe :360
Argentina : 12	3rd Qu.:1993	3rd Qu.:1.959e+07	Oceania : 24
Australia : 12	Max. :2007	Max. :1.319e+09	
(Other) :1632			
lifeExp	gdpPercap		
Min. :23.60	Min. : 241.2		
1st Qu.:48.20	1st Qu.: 1202.1		
Median :60.71	Median : 3531.8		
Mean :59.47	Mean : 7215.3		
3rd Qu.:70.85	3rd Qu.: 9325.5		
Max. :82.60	Max. :113523.1		

Because we are only interested in graphing data from 2002, we just pull out those data.

```
# Subset data, retaining only those data from 2002
gapminder <- all_gapminder[all_gapminder$year == 2002, ]
```

Last but not least, we use the `plot` function to draw the plot.

```
# Plot points
plot(x = gapminder$gdpPercap,
     y = gapminder$lifeExp)
```



Make it pretty

Before we get to the next step we need to start using scripts, rather than typing directly into the console. This is the ideal way to save your work. You can create a new script in RStudio via File > New File > R Script (or the shortcut Ctrl+Shift+N / Cmd+Shift+N). Name the script something like “r-graphing.R” (without the quotes) - you will have to add the .R extension when you name the file. At the start of *every* script you write, you should provide at least this basic information:

- A brief description of what the script does
- Your name
- Contact information
- Date

Fix those axes titles

Our original graph was a good start, but those axis labels are pretty unseemly. We can fix those up by setting values in the `plot` function call. Namely, we will be passing values to the `main`, `xlab` (x-axis label), and `ylab` (y-axis label) parameters.

```


# Graphing Life Expectancy vs. GDP
# Jeffrey C. Oliver
# jcoliver@email.arizona.edu
# 2016-11-15

# Read in data
all_gapminder <- read.csv(file = "data/gapminder-FiveYearData.csv",
                           stringsAsFactors = TRUE)

# Subset data
gapminder <- all_gapminder[all_gapminder$year == 2002, ]

plot(x = gapminder$gdpPercap,
     y = gapminder$lifeExp,
     main = "Life expectancy v. GDP",
     xlab = "GDP Per capita",
     ylab = "Life expectancy (years)")

```



Changing scales

Log-transform data

This does not look like a linear relationship, but we can try a simple log-transformation on the GDP data to see how that looks.

```
# Graphing Life Expectancy vs. GDP
# Jeffrey C. Oliver
# jcoliver@email.arizona.edu
# 2016-11-15


# Read in data
all_gapminder <- read.csv(file = "data/gapminder-FiveYearData.csv",
                          stringsAsFactors = TRUE)

# Subset data
gapminder <- all_gapminder[all_gapminder$year == 2002, ]

# Make new vector of Log GDP
gapminder$Log10GDP <- log10(gapminder$gdpPercap)

plot(x = gapminder$Log10GDP,
     y = gapminder$lifeExp,
     main = "Life expectancy v. GDP",
     xlab = "Log(GDP Per capita)",
     ylab = "Life expectancy (years)")
```

Life expectancy v. GDP



Make it prettier

Color the points

We are not restricted to black and white colors. Here we will color points by the continent each country is located on.

```
# Graphing Life Expectancy vs. GDP
# Jeffrey C. Oliver
# jcoliver@email.arizona.edu
# 2016-11-15

# Read in data
all_gapminder <- read.csv(file = "data/gapminder-FiveYearData.csv",
                          stringsAsFactors = TRUE)

# Subset data
gapminder <- all_gapminder[all_gapminder$year == 2002, ]
```

```
# Make new vector of Log GDP
gapminder$Log10GDP <- log10(gapminder$gdpPercap)
```

Start by looking at the different values in the `gapminder$continent` vector.

```
# What are the possible values for continent?
levels(gapminder$continent)
```

```
[1] "Africa"    "Americas" "Asia"      "Europe"    "Oceania"
```

There are five possible values, so we will need five different colors. The first step is to create a new vector in the `gapminder` data frame; call it `colors` and fill it with `NA` values. Then assign colors based on the value in the `gapminder$continent` vector.


```
# Create new vector for colors
gapminder$colors <- NA

# Assign colors based on gapminder$continent
gapminder$colors[gapminder$continent == "Africa"] <- "red"
gapminder$colors[gapminder$continent == "Americas"] <- "orange"
gapminder$colors[gapminder$continent == "Asia"] <- "forestgreen"
gapminder$colors[gapminder$continent == "Europe"] <- "darkblue"
gapminder$colors[gapminder$continent == "Oceania"] <- "violet"

# Create main plot
plot(x = gapminder$Log10GDP,
     y = gapminder$lifeExp,
     main = "Life expectancy v. GDP",
     xlab = "Log(GDP Per capita)",
     ylab = "Life expectancy (years)",
     col = gapminder$colors,
     pch = 18) # A diamond symbol

# We will also need to add a legend, so we know what the colors mean.
# Here we have to be sure the order of the colors matches the order
# of the different levels of gapminder$continents.
legend("topleft",
      legend = levels(gapminder$continent),
      col = c("red", "orange", "forestgreen", "darkblue", "violet"),
      pch = 18)
```


Life expectancy v. GDP



Prevent mistakes

Abstract the code

When writing code, abstraction can be quite useful, to ensure consistency throughout your code.

```
# Graphing Life Expectancy vs. GDP
# Jeffrey C. Oliver
# jcoliver@email.arizona.edu
# 2016-11-15

# Read in data
all_gapminder <- read.csv(file = "data/gapminder-FiveYearData.csv",
                          stringsAsFactors = TRUE)

# Subset data
gapminder <- all_gapminder[all_gapminder$year == 2002, ]

# Make new vector of Log GDP
```

```

gapminder$Log10GDP <- log10(gapminder$gdpPercap)

# Store values to use for some plotting parameters
symbol <- 18
sym_size <- 1.2
continents <- levels(gapminder$continent)
continent_colors <- c("red", "orange", "forestgreen", "darkblue", "violet")

# Assign colors for each continent
gapminder$colors <- NA
gapminder$colors[gapminder$continent == continents[1]] <- continent_colors[1]
gapminder$colors[gapminder$continent == continents[2]] <- continent_colors[2]
gapminder$colors[gapminder$continent == continents[3]] <- continent_colors[3]
gapminder$colors[gapminder$continent == continents[4]] <- continent_colors[4]
gapminder$colors[gapminder$continent == continents[5]] <- continent_colors[5]


# Create main plot
plot(x = gapminder$Log10GDP,
     y = gapminder$lifeExp,
     main = "Life expectancy v. GDP",
     xlab = "Log(GDP Per capita)",
     ylab = "Life expectancy (years)",
     col = gapminder$colors,
     pch = symbol,
     cex = sym_size,
     lwd = 1.5)

# Add a legend - we don't have to worry about getting the colors
# in the right order because we are using the same vector that we used
# when assigning colors in the first place.
legend("topleft",
      legend = continents,
      col = continent_colors,
      pch = symbol)

# Add a regression line
lifeExp_lm <- lm(gapminder$lifeExp ~ gapminder$Log10GDP)
abline(reg = lifeExp_lm, lty = 2, lwd = 2)

```

Life expectancy v. GDP



Even fewer mistakes via less code o.O

More code abstraction & loops

Continuing with abstraction, we can simplify our code with control flow - here we use a `for` loop to accomplish the color assignment task.

```
# Graphing Life Expectancy vs. GDP
# Jeffrey C. Oliver
# jcoliver@email.arizona.edu
# 2016-11-15

# Read in data
all_gapminder <- read.csv(file = "data/gapminder-FiveYearData.csv",
                          stringsAsFactors = TRUE)

# Subset data
gapminder <- all_gapminder[all_gapminder$year == 2002, ]

# Make new vector of Log GDP
```

```

gapminder$Log10GDP <- log10(gapminder$gdpPercap)

# Store values to use for some plotting parameters
symbol <- 18
sym_size <- 1.2
continents <- levels(gapminder$continent)
continent_colors <- c("red", "orange", "forestgreen", "darkblue", "violet")

# Establish empty column to store colors
gapminder$colors <- NA
# Loop over continents and assign colors
for (i in 1:length(continents)) {
  gapminder$colors[gapminder$continent == continents[i]] <- continent_colors[i]
}


# Create main plot
plot(x = gapminder$Log10GDP,
     y = gapminder$lifeExp,
     main = "Life expectancy v. GDP",
     xlab = "Log(GDP Per capita)",
     ylab = "Life expectancy (years)",
     col = gapminder$colors,
     pch = symbol,
     cex = sym_size)

# Add a legend
legend("topleft",
      legend = continents,
      col = continent_colors,
      pch = symbol)

# Add a regression line
lifeExp_lm <- lm(gapminder$lifeExp ~ gapminder$Log10GDP)
abline(reg = lifeExp_lm, lty = 2, lwd = 2)

```

Life expectancy v. GDP



Saving graphical output

Redirect graphics to PDF file

To save the file, we can redirect the output to a graphics device. In this example we use a PDF writer; many other graphics devices are available for writing different file formats, including `svg`, `jpeg`, and `png`.

```
# Graphing Life Expectancy vs. GDP
# Jeffrey C. Oliver
# jcoliver@email.arizona.edu
# 2016-11-15

# Read in data
all_gapminder <- read.csv(file = "data/gapminder-FiveYearData.csv",
                          stringsAsFactors = TRUE)

# Subset data
gapminder <- all_gapminder[all_gapminder$year == 2002, ]
```

```

# Make new vector of Log GDP
gapminder$Log10GDP <- log10(gapminder$gdpPercap)

# Store values to use for some plotting parameters
symbol <- 18
sym_size <- 1.2
continents <- levels(gapminder$continent)
continent_colors <- c("red", "orange", "forestgreen", "darkblue", "violet")

# Create new vector for colors
gapminder$colors <- NA
# Loop over continents and assign colors
for (i in 1:length(continents)) {
  gapminder$colors[gapminder$continent == continents[i]] <- continent_colors[i]
}

# Open PDF device
pdf(file = "output/Life_expectancy_graph.pdf", useDingbats = FALSE)
# Create main plot
plot(x = gapminder$Log10GDP,
     y = gapminder$lifeExp,
     main = "Life expectancy v. GDP",
     xlab = "Log(GDP Per capita)",
     ylab = "Life expectancy (years)",
     col = gapminder$colors,
     pch = symbol,
     cex = sym_size)

# Add a legend
legend("topleft",
      legend = continents,
      col = continent_colors,
      pch = symbol)

# Add a regression line
lifeExp_lm <- lm(gapminder$lifeExp ~ gapminder$Log10GDP)
abline(reg = lifeExp_lm, lty = 2, lwd = 2)

# Close PDF device
dev.off()

```

Automation!

Make 12 separate PDF graphs

Finally (well, almost finally, see below), we can automate this process to create a separate PDF of the same graph for each year of data in the gapminder datasets (there are 12 years of data for each country).

```
# Graphing Life Expectancy vs. GDP
# Jeffrey C. Oliver
# jcoliver@email.arizona.edu
# 2016-11-15

# Read in data
all_gapminder <- read.csv(file = "data/gapminder-FiveYearData.csv",
                          stringsAsFactors = TRUE)

# Hold off on subsetting the data
# Make new vector of Log GDP
all_gapminder$Log10GDP <- log10(all_gapminder$gdpPercap)

# Store values to use for some plotting parameters
symbol <- 18
sym_size <- 1.2
continents <- levels(all_gapminder$continent)
continent_colors <- c("red", "orange", "forestgreen", "darkblue", "violet")

# Create new vector for colors
all_gapminder$colors <- NA
# Loop over continents and assign colors
for (i in 1:length(continents)) {
  all_gapminder$colors[all_gapminder$continent == continents[i]] <- continent_colors[i]
}

# Find the unique values in the all_gapminder$year vector
years <- unique(all_gapminder$year)

# Now loop over each of the different years to create the PDFs.
for (curr_year in years) {
  # Subset data
  gapminder_one_year <- all_gapminder[all_gapminder$year == curr_year, ]
```

```

# Open PDF device
filename <- paste0("output/Life_exp_", curr_year, "_graph.pdf")
pdf(file = filename, useDingbats = FALSE)
# Create main plot
plot(x = gapminder_one_year$Log10GDP,
     y = gapminder_one_year$lifeExp,
     main = "Life expectancy v. GDP",
     sub = curr_year,
     xlab = "Log(GDP Per capita)",
     ylab = "Life expectancy (years)",
     col = gapminder_one_year$colors,
     pch = symbol,
     cex = sym_size,
     lwd = 1.5)

# Add a legend
legend("topleft",
      legend = continents,
      col = continent_colors,
      pch = symbol)

# Add a regression line
lifeExp_lm <- lm(gapminder_one_year$lifeExp ~ gapminder_one_year$Log10GDP)
abline(reg = lifeExp_lm, lty = 2, lwd = 2)

# Close PDF device
dev.off()
}

```

Advanced topic: making it even prettier

Add transparency to points

And for advanced users, we can add some transparency to the points (skipping the step where the plot is saved to a PDF file).

```

# Graphing Life Expectancy vs. GDP
# Jeffrey C. Oliver
# jcoliver@email.arizona.edu

```



```
# 2016-11-15

# Read in data
all_gapminder <- read.csv(file = "data/gapminder-FiveYearData.csv",
                          stringsAsFactors = TRUE)

# Subset data
gapminder <- all_gapminder[all_gapminder$year == 2002, ]

# Make new vector of Log GDP
gapminder$Log10GDP <- log10(gapminder$gdpPercap)

# Store values to use for some plotting parameters
symbol <- 18
sym_size <- 1.2
continents <- levels(gapminder$continent)
continent_colors <- c("red", "orange", "forestgreen", "darkblue", "violet")
```

To add transparency, color names will not be enough - we will have to use RGB values and add an alpha (transparency) value. Start by using the `col2rgb` function to see what the red, green, and blue values are for our five colors.

```
# Investigating colors
col2rgb(continent_colors)
```

	[,1]	[,2]	[,3]	[,4]	[,5]
red	255	255	34	0	238
green	0	165	139	0	130
blue	0	0	34	139	238

In this output, we see that each column corresponds to a color in our `continents_colors` vector (first column corresponds to “red”, second column corresponds to “orange”, etc.). Each row corresponds to one of the three primary colors.

```
# Convert colors to RGB, so we can add an alpha (transparency) value
continent_rgb <- col2rgb(continent_colors)
continent_colors <- NULL
opacity <- 150
# Loop over each column (i.e. color) in continent_rgb and extract Red, Green,
# and Blue values
for (color_column in 1:ncol(continent_rgb)) {
```

```

new_color <- rgb(red = continent_rgb['red', color_column],
                green = continent_rgb['green', color_column],
                blue = continent_rgb['blue', color_column],
                alpha = opacity,
                maxColorValue = 255)
continent_colors[color_column] <- new_color
}

# Create new vector for colors
gapminder$colors <- NA
# loop over continents and assign colors
for (i in 1:length(continents)) {
  gapminder$colors[gapminder$continent == continents[i]] <- continent_colors[i]
}


# Create main plot
plot(x = gapminder$Log10GDP,
     y = gapminder$lifeExp,
     main = "Life expectancy v. GDP",
     xlab = "Log(GDP Per capita)",
     ylab = "Life expectancy (years)",
     col = gapminder$colors,
     bg = gapminder$colors,
     pch = symbol,
     cex = sym_size,
     lwd = 1.5)

# Add a legend
legend("topleft",
      legend = continents,
      col = continent_colors,
      pch = symbol)

# Add a regression line
lifeExp_lm <- lm(gapminder$lifeExp ~ gapminder$Log10GDP)
abline(reg = lifeExp_lm, lty = 2, lwd = 2)

```

Life expectancy v. GDP



Additional resources

- For advanced graphing, the ggplot2 package is *extremely* useful. A companion lesson for using ggplot2 is available at <https://jcoliver.github.io/learn-r/004-intro-ggplot.html>.
- A [PDF version](#) of this lesson