

Binary to xGrades fo xwww.falst xBinary to xHex to Bi xi2c lpc17x(2) Faceb xattribute xSJSU-De xSJOne Te xJared

localhost:5001

AppsBookmarksProfessor's PagessmicheggPrimeVideosupremeOther Bookmarks

Telemetry version 0.0.2
server connected

☒ Graph☒ Telemetry☒ Reset On Connect

Refresh Devices

/dev/cu.usbserial-A503OK3T

Disconnect

Serial Output

Serial 1 Hz

38400 baud

Write Serial Data Here ...

☒ CR

☒ NL

Send

```
Last sbrk() size : 32
Num sbrk() calls: 34

-----

You can program a PERMANENT ID of your board.
To do this, hold SW1 and SW4 and reset the board.
CPU flash altered/programmed counts: 354/476
CPU programmed flash (min/max): 68Kb - 116Kb
Last programming took 1900 ms

-----

Calling your main()

-----

Started main
I2C Interrupt
I2C Interrupt
0x60: write
I2C Interrupt
0x80: reading value
I2C Interrupt
0x80: reading value
I2C Interrupt
0xA0: done or repeatingI2C Interrupt
0x60: write
I2C Interrupt
0x80: reading value
I2C Interrupt
```

Telemetry Feedback

Telem 1 Hz

Graph 1 Hz

Table

Graph

Raw

Bucket	Variable Name	Type	Value	Set
--------	---------------	------	-------	-----