


# THE BRIGHT-STAR MASKS FOR HSC-SSP

📅 April 17, 2017   👤 coupon   💬 0 Comment   📖 Astronomy

The masks to flag objects in the HSC-SSP area can be found [here](#). The archive contains the masks and tools to flag objects potentially affected by a nearby star in the HSC-SSP footprint, as illustrated below:



(Y-band image from the [PDR1](#). The green shapes are the bright-star masks).

## Version history

### Current version:

- “Arcturus” (April 21th, 2017): identical to Canopus, with tract- and patch-based region files included.

### Previous versions:

- “Canopus” (April 2017): new masks, Gaia-dr1, Tycho-2 and SDSS, pure star sample, a few areas with lower Gaia-star density due to low scanned areas.
- “Sirius” (March 2016, S15B, S16A, PDR1): 8% of bright galaxies, size of mask over conservative below mag  $\sim 5$  for a dozen stars.

## How to use it?

### Uncompressing the archive:

Run:

```
1 | $ tar xzvf HSC-SSP_brightStarMask_VERSION.tgz
```

### Installing venice

venice is a mask utility program that reads a mask file (DS9 or fits type) and a catalogue of objects to:

- create a pixelized mask,
- find objects inside/outside a mask,
- or generate a random catalogue of objects inside/outside a mask.

The code sources are in HSC-SSP\_brightStarMask\_VERSION/venice-v.v.v/

To compile it, you first need to install the gsl and cfitsio libraries ([gsl](#), [cfitsio](#)).

Then, go to venice directory

```
1 | $ cd HSC-SSP_brightStarMask_VERSION/venice-v.v.v/
```

and run:

```
1 | $ make
```

or, if gsl and cfitsio libraries are installed in a different directory than /usr/local:

```
1 | $ make PREFIX_GSL=DIRECTORY_NAME PREFIX_CFITSIO=DIRECTORY_NAME
```

If you want to use a different compiler than gcc, type (only tested with gcc and icc):

```
1 | $ make CC=my_favorite_compiler
```

The compiled program is installed in HSC-SSP\_brightStarMask\_VERSION/venice-v.v.v/bin/

## The star catalogue

The star catalogue is in HSC-SSP\_brightStarMask\_VERSION/star. It contains the following information:

Columns: 9

Rows: 1812106

Columns

— — —

1: source\_id(Long) – source\_id

2: ra(Double)/Angle[deg] – ra

3: dec(Double)/Angle[deg] – dec

4: G\_Gaia(Double)/Magnitude[mag] – phot\_g\_mean\_mag

5: origin(String)

6: G\_Gaia\_SDSS(Double)

7: G\_Gaia\_HSC(Double)

8: extended\_HSC(Short)

9: ipsf\_FWHM(Double)

## Flagging a catalogue using venice

Run:

```
1 | $ venice \  
2 | -m reg/masks_all.reg -f all \  
3 | -cat MY_INPUT_CAT \  
4 | -xcol RA_COLUMN_NAME -ycol DEC_COLUMN_NAME \  
5 | -o MY_OUTPUT_CAT
```

Note: venice can read both fits files (default) and ascii files.

For ascii files, set: “-ifmt ascii” and “-ofmt ascii”

See gitHub [venice directory](#) for more information.

## Tract and patch version

The archives “reg/patches.tgz” “reg/tracts.tgz” contains the masks split per tract and patch for the five filters. To untar it, run:

```
1 | $ cd HSC-SSP_brightStarMask_VERSION/reg
2 | $ tar xzvf tracts.tgz
3 | $ tar xzvf patches.tgz
```

**WARNING: tracts expand into 5715 files and patches expand into 356550 files!**

The file path and names are the following:

tract: HSC-SSP\_brightStarMask\_VERSION/reg/tracts/BrightStarMask-9000-0,0-FILTER.reg

patch: HSC-SSP\_brightStarMask\_VERSION/reg/tracts/TRACT/BrightStarMask-TRACT-PATCH-FILTER.reg

Note: currently, the mask is the same for each filter, so g, r, z, and Y filter masks are symbolic links pointing to the i filter mask.

## Example: flagging objects in the tract 9376

First create a catalogue of random points for the example:

```
1 | $ venice -r -xmin 221.476 -xmax 222.967 -ymin -1.5014 -ymax 0.044
2 | -coord spher -o tract_9376.fits
3 | $ venice -m reg/tracts/BrightStarMask-9376-HSC-I.reg \
4 | -cat tract_9376.fits -xcol ra -ycol dec \
5 | -f all -flagName isOutsideMask -o tract_9376_flagged.fits
```

Options:

- -m reg/tracts/BrightStarMask-9376-HSC-I.reg: masks in region format
- -cat tract\_9376.fits: catalogue to flag
- -xcol ra -ycol dec: names of the input coordinates columns
- -f all: keep all object, 1: outside the mask, 0: inside the mask
- -flagName isOutsideMask: name of the flag column
- -o tract\_9376\_flagged.fits: the output file

