

Plotting with Pandas Series and DataFrames



Pandas uses Matplotlib to generate figures. Once a figure is generated with Pandas, all of Matplotlib's functions can be used to modify the title, labels, legend, etc. In a Jupyter notebook, all plotting calls for a given plot should be in the same cell.

Setup

Import packages:

```
> import pandas as pd  
> import matplotlib.pyplot as plt
```

Execute this at IPython prompt to display figures in new windows:

```
> %matplotlib
```

Use this in Jupyter notebooks to display static images inline:


```
> %matplotlib inline
```

Use this in Jupyter notebooks to display zoomable images inline:

```
> %matplotlib notebook
```

Parts of a Figure


An Axes object is what we think of as a "plot". It has a title and two Axis objects that define data limits. Each Axis can have a label. There can be multiple Axes objects in a Figure.



Plotting with Pandas Objects

Series

a	
b	
c	




With a Series, Pandas plots values against the index:

```
> ax = s.plot()
```

When plotting the results of complex manipulations with **groupby**, it's often useful to **stack/unstack** the resulting DataFrame to fit the one-line-per-column assumption (see Data Structures cheatsheet).

Dataframe


	X	Y	Z
a			
b			
c			



With a DataFrame, Pandas creates one line per column:

```
> ax = df.plot()
```

Labels



Use Matplotlib to override or add annotations:


```
> ax.set_xlabel('Time')  
> ax.set_ylabel('Value')  
> ax.set_title('Experiment A')
```

Pass labels if you want to override the column names and set the legend location:

```
> ax.legend(labels, loc='best')
```


Useful Arguments to plot

	X	Y
a		
b		
c		




- **subplots=True**: one subplot per column, instead of one line
- **figsize**: set figure size, in inches
- **x** and **y**: plot one column against another


Kinds of Plots




```
df.plot(kind='scatter')
```




```
df.plot(kind='bar')
```



```
df.plot(kind='hist')
```



```
df.boxplot()
```



Red Panda
Ailurus fulgens

Take your Pandas skills to the next level! Register at www.enthought.com/pandas-master-class

© 2016 Enthought, Inc., licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.
To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/>

ENTHOUGHT

Reading and Writing Data with Pandas




Methods to read data are all named **pd.read_*** where * is the file type. Series and DataFrames can be saved to disk using their **to_*** method.

Usage Patterns

- Use **pd.read_clipboard()** for one-off data extractions.
- Use the other **pd.read_*** methods in scripts for repeatable analyses.

Reading Text Files into a DataFrame

Colors highlight how different arguments map from the data file to a DataFrame.



```
# Historical_data.csv
Date, Cs, Rd
2005-01-03, 64.78, -
2005-01-04, 63.79, 201.4
2005-01-05, 64.46, 193.45
...
Data from Lab Z.
Recorded by Agent E
```

```
>>> read_table(
    'historical_data.csv',
    sep=',',
    header=1,
    skiprows=1,
    skipfooter=2,
    index_col=0,
    parse_dates=True,
    na_values=['-'])
```

Date	Cs	Rd


Other arguments:

- **names**: set or override column names
- **parse_dates**: accepts multiple argument types, see on the right
- **converters**: manually process each element in a column
- **comment**: character indicating commented line
- **chunksize**: read only a certain number of rows each time


Possible values of **parse_dates**:

- **[0, 2]**: Parse columns 0 and 2 as separate dates
 - **[[0, 2]]**: Group columns 0 and 2 and parse as single date
 - **{'Date': [0, 2]}**: Group columns 0 and 2, parse as single date in a column named Date.
- Dates are parsed *after* the **converters** have been applied.

Parsing Tables from the Web



```
>>> df_list = read_html(url)
```



Writing Data Structures to Disk

Writing data structures to disk:

```
> s_df.to_csv(filename)
> s_df.to_excel(filename)
```

Write multiple DataFrames to single Excel file:

```
> writer = pd.ExcelWriter(filename)
> df1.to_excel(writer, sheet_name='First')
> df2.to_excel(writer, sheet_name='Second')
> writer.save()
```

From and To a Database

Read, using SQLAlchemy. Supports multiple databases:

```
> from sqlalchemy import create_engine
> engine = create_engine(database_url)
> conn = engine.connect()
> df = pd.read_sql(query_str_or_table_name, conn)
```

Write:

```
> df.to_sql(table_name, conn)
```

Take your Pandas skills to the next level! Register at www.enthought.com/pandas-master-class

© 2016 Enthought, Inc., licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.
To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/>

ENTHOUGHT

Computation with Series and DataFrames



Pandas objects do not behave exactly like Numpy arrays. They follow three main rules (see on the right). Aligning objects on the index (or columns) before calculations might be the most important difference. There are built-in methods for most common statistical operations, such as **mean** or **sum**, and they apply across one-dimension at a time. To apply custom functions, use one of three methods to do tablewise (**pipe**), row or column-wise (**apply**) or elementwise (**applymap**) operations.

Rule 1: Alignment First

```
> s1 + s2
```

s1		s2	
a	1	NaN	NaN
b	2	4	6
c	NaN	5	NaN

```
> s1.add(s2, fill_value=0)
```

s1		s2	
a	1	0	1
b	2	4	6
c	0	5	5

Use **add**, **sub**, **mul**, **div**, to set fill value.

Rule 3: Reduction Operations

```
>>> df.sum() → Series
```

	X	Y
a		
b		
c		

df.sum()

X	Y

Operates across rows by default (**axis=0**, or **axis='rows'**).
Operate across columns with **axis=1** or **axis='columns'**.

Reduction functions

- count:** Number of non-null observations
- sum:** Sum of values
- mean:** Mean of values
- mad:** Mean absolute deviation
- median:** Arithmetic median of values
- min:** Minimum
- max:** Maximum
- mode:** Mode
- prod:** Product of values
- std:** Bessel-corrected sample standard deviation
- var:** Unbiased variance
- sem:** Standard error of the mean
- skew:** Sample skewness (3rd moment)
- kurt:** Sample kurtosis (4th moment)
- quantile:** Sample quantile (Value at %)
- value_counts:** Count of unique values

The 3 Rules of Binary Operations

Rule 1:

Operations between multiple Pandas objects implement auto-alignment based on index first.

Rule 2:

Mathematical operators (+ - * / exp, log, ...) apply element by element, on the values.

Rule 3:

Reduction operations (mean, std, skew, kurt, sum, prod, ...) are applied column by column by default.

Rule 2: Element-By-Element Mathematical Operations

df + 1 **df.abs()** **np.log(df)**

	X	Y
a	-2	-2
b	-2	-2
c	-2	-2

	X	Y
a	-1	-1
b	-1	-1
c	-1	-1

	X	Y
a	1	1
b	1	1
c	1	1

	X	Y
a	0	0
b	0	0
c	0	0

Apply a Function to Each Value

Apply a function to each value in a Series or DataFrame

s.apply(value_to_value) → Series

df.applymap(value_to_value) → DataFrame

Apply a Function to Each Series

Apply **series_to_*** function to every column by default (across rows):

df.apply(series_to_series) → DataFrame

df.apply(series_to_value) → Series

To apply the function to every row (across columns), set **axis=1**:

df.apply(series_to_series, axis=1)

Apply a Function to a DataFrame

Apply a function that receives a DataFrame and returns a DataFrame, a Series, or a single value:

df.pipe(df_to_df) → DataFrame

df.pipe(df_to_series) → Series

df.pipe(df_to_value) → Value

What Happens with Missing Values?

Missing values are represented by **NaN** (not a number) or **NaT** (not a time).

- They propagate in operations across Pandas objects (**1 + NaN → NaN**).
- They are ignored in a "sensible" way in computations, they equal 0 in **sum**, they're ignored in **mean**, etc.
- They stay **NaN** with mathematical operations (**np.log(NaN) → NaN**).

Take your Pandas skills to the next level! Register at www.enthought.com/pandas-master-class

© 2016 Enthought, Inc., licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.
To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/>

Split / Apply / Combine with DataFrames



1. Split the data based on some criteria.
2. Apply a function to each group to aggregate, transform, or filter.
3. Combine the results.

The apply and combine steps are typically done together in Pandas.

Split: Group By

Group by a single column:


```
> g = df.groupby(col_name)
```

Grouping with list of column names creates DataFrame with MultiIndex. (see "Reshaping DataFrames and Pivot Tables" cheatsheet):

```
> g = df.groupby(list_col_names)
```

Pass a function to group based on the index:

```
> g = df.groupby(function)
```



Apply/Combine: General Tool: apply

More general than **agg**, **transform**, and **filter**. Can aggregate, transform or filter. The resulting dimensions can change, for example:

```
> g.apply(lambda x: x.describe())
```


Apply/Combine: Transformation

The shape and the index do not change.

```
> g.transform(df_to_df)
```

Example, normalization:


```
> def normalize(grp):  
    return (grp - grp.mean()) / grp.var()  
> g.transform(normalize)
```



Apply/Combine: Filtering


Returns a group only if condition is true.

```
> g.filter(lambda x: len(x)>1)
```




Other Groupby-Like Operations: Window Functions

- **resample**, **rolling**, and **ewm** (exponential weighted function) methods behave like GroupBy objects. They keep track of which row is in which "group". Results must be aggregated with **sum**, **mean**, **count**, etc. (see Aggregation).
- **resample** is often used before **rolling**, **expanding**, and **ewm** when using a DateTime index.



Split/Apply/Combine



Split

- Groupby
- Window Functions

Apply

- Apply
- Group-specific transformations
- Aggregation
- Group-specific Filtering

Combine

Split: What's a GroupBy Object?

It keeps track of which rows are part of which group.

> **g.groups** → Dictionary, where keys are group names, and values are indices of rows in a given group.

It is iterable:

```
> for group, sub_df in g:  
    ...
```

Apply/Combine: Aggregation

Perform computations on each group. The shape changes; the categories in the grouping columns become the index. Can use built-in aggregation methods: **mean**, **sum**, **size**, **count**, **std**, **var**, **sem**, **describe**, **first**, **last**, **nth**, **min**, **max**, for example:

```
> g.mean()
```

... or aggregate using custom function:


```
> g.agg(series_to_value)
```

... or aggregate with multiple functions at once:

```
> g.agg([s_to_v1, s_to_v2])
```

... or use different functions on different columns.

```
> g.agg({'Y': s_to_v1, 'Z': s_to_v2})
```



Take your Pandas skills to the next level! Register at www.enthought.com/pandas-master-class

© 2016 Enthought, Inc., licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/>

ENTHOUGHT

Manipulating Dates and Times



Use a Datetime index for easy time-based indexing and slicing, as well as for powerful resampling and data alignment.

Pandas makes a distinction between timestamps, called **Datetime** objects, and time spans, called **Period** objects.

Converting Objects to Time Objects

Convert different types, for example strings, lists, or arrays to Datetime with:

```
> pd.to_datetime(value)
```

Convert timestamps to time spans: set period "duration" with frequency offset (see below).

```
> date_obj.to_period(freq=freq_offset)
```

Creating Ranges of Timestamps

```
> pd.date_range(start=None, end=None,
                periods=None, freq=offset,
                tz='Europe/London')
```

Specify either a start or end date, or both. Set number of "steps" with **periods**. Set "step size" with **freq**; see "Frequency offsets" for acceptable values. Specify time zones with **tz**.

Frequency Offsets

Used by **date_range**, **period_range** and **resample**:

- | | |
|--------------------------|-----------------------|
| • B: Business day | • A: Year end |
| • D: Calendar day | • AS: Year start |
| • W: Weekly | • H: Hourly |
| • M: Month end | • T, min: Minutely |
| • MS: Month start | • S: Secondly |
| • BM: Business month end | • L, ms: Milliseconds |
| • Q: Quarter end | • U, us: Microseconds |
| | • N: Nanoseconds |

For more:

Lookup "Pandas Offset Aliases" or check out **pandas.tseries.offsets**, and **pandas.tseries.holiday** modules.

Vectorized String Operations

Pandas implements vectorized string operations named after Python's string methods. Access them through the **str** attribute of string Series

Some String Methods

```
> s.str.lower()      > s.str.strip()
> s.str.isupper()    > s.str.normalize()
> s.str.len()        and more...
```


Index by character position:

```
> s.str[0]
```

True if regular expression pattern or string in Series:

```
> s.str.contains(str_or_pattern)
```

Timestamps vs Periods



Save Yourself Some Pain: Use ISO 8601 Format

When entering dates, to be consistent and to lower the risk of error or confusion, use ISO format YYYY-MM-DD:

```
>>> pd.to_datetime('12/01/2000') # 1st December
Timestamp('2000-12-01 00:00:00')
>>> pd.to_datetime('13/01/2000') # 13th January!
Timestamp('2000-01-13 00:00:00')
>>> pd.to_datetime('2000-01-13') # 13th January
Timestamp('2000-01-13 00:00:00')
```

Creating Ranges or Periods

```
> pd.period_range(start=None, end=None,
                  periods=None, freq=offset)
```

Resampling

```
> s_df.resample(freq_offset).mean()
```

resample returns a groupby-like object that must be aggregated with **mean**, **sum**, **std**, **apply**, etc. (See also the Split-Apply-Combine cheat sheet.)

Splitting and Replacing

split returns a Series of lists:

```
> s.str.split()
```

Access an element of each list with **get**:

```
> s.str.split(char).str.get(1)
```

Return a DataFrame instead of a list:

```
> s.str.split(expand=True)
```

Find and replace with string or regular expressions:

```
> s.str.replace(str_or_regex, new)
> s.str.extract(regex)
> s.str.findall(regex)
```

Take your Pandas skills to the next level! Register at www.enthought.com/pandas-master-class

© 2016 Enthought, Inc., licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/>

Pandas Data Structures: Series and DataFrames



A Series, **s**, maps an index to values. It is:

- Like an ordered dictionary
- A Numpy array with row labels and a name

A DataFrame, **df**, maps index and column labels to values. It is:

- Like a dictionary of Series (columns) sharing the same index
- A 2D Numpy array with row and column labels

s_df applies to both Series and DataFrames.

Assume that manipulations of Pandas object return copies.

Creating Series and DataFrames

Series

```
> pd.Series(values, index=index,
            name=name)
```

```
> pd.Series({'idx1': val1, 'idx2': val2})
```

Where **values**, **index**, and **name** are sequences or arrays.

Series		
Values		
n1	'Cary'	0
n2	'Lynn'	1
n3	'Sam'	2
Index		Integer location

DataFrame

	Age	Gender	Columns
'Cary'	32	M	
'Lynn'	18	F	
'Sam'	26	M	
Index	Values		

DataFrame

```
> pd.DataFrame(values, index=index,
               columns=col_names)
```

```
> pd.DataFrame({'col1': series1_or_seq,
               'col2': series2_or_seq})
```

Where **values** is a sequence of sequences or a 2D array

Manipulating Series and DataFrames

Manipulating Columns

```
df.rename(columns={old_name: new_name})
```

Renames column

```
df.drop(name_or_names, axis='columns')
```

Drops column name

Manipulating Index

```
s_df.reindex(new_index)
```

Conform to new index

```
s_df.drop(labels_to_drop)
```

Drops index labels

```
s_df.rename(index={old_label: new_label})
```

Renames index labels

```
s_df.reset_index()
```

Drops index, replaces with **Range** index

```
s_df.sort_index()
```

Sorts index labels

```
df.set_index(column_name_or_names)
```

Manipulating Values

All row values and the index will follow:

```
df.sort_values(col_name, ascending=True)
```

```
df.sort_values(['X', 'Y'], ascending=[False, True])
```

Important Attributes and Methods

s_df.index Array-like row labels

df.columns Array-like column labels

s_df.values Numpy array, data

s_df.shape (n_rows, m_cols)

s.dtype, df.dtypes Type of **Series**, of each column

len(s_df) Number of rows

s_df.head() and **s_df.tail()** First/last rows

s.unique() Series of unique values

s_df.describe() Summary stats

df.info() Memory usage

Indexing and Slicing

Use these attributes on Series and DataFrames for indexing, slicing, and assignments:

s_df.loc[] Refers only to the index labels

s_df.iloc[] Refers only to the integer location, similar to lists or Numpy arrays

s_df.xs(key, level) Select rows with label **key** in level **level** of an object with MultiIndex.

Masking and Boolean Indexing

Create masks with, for example, comparisons

```
mask = df['X'] < 0
```

Or **isin**, for membership mask

```
mask = df['X'].isin(list_valid_values)
```

Use masks for indexing (must use **loc**)

```
df.loc[mask] = 0
```

Combine multiple masks with bitwise operators (and (&), or (|), xor (^), not (~)) and group them with parentheses:

```
mask = (df['X'] < 0) & (df['Y'] == 0)
```

Common Indexing and Slicing Patterns

rows and **cols** can be values, lists, Series or masks.

s_df.loc[rows]	Some rows (all columns in a DataFrame)
df.loc[:, cols_list]	All rows, some columns
df.loc[rows, cols]	Subset of rows and columns
s_df.loc[mask]	Boolean mask of rows (all columns)
df.loc[mask, cols]	Boolean mask of rows, some columns

Using [] on Series and DataFrames

On Series, [] refers to the index labels, or to a slice

s['a']	Value
s[:2]	Series, first 2 rows

On DataFrames, [] refers to columns labels:

df['X']	Series
df[['X', 'Y']]	DataFrame
df['new_or_old_col'] = series_or_array	

EXCEPT! with a slice or mask.

df[:2]	DataFrame, first 2 rows
df[mask]	DataFrame, rows where mask is True

NEVER CHAIN BRACKETS!

✗ **> df[mask]['X'] = 1**
SettingWithCopyWarning

✓ **> df.loc[mask, 'X'] = 1**

THOUGHT

Take your Pandas skills to the next level! Register at www.enthought.com/pandas-master-class

© 2016 Enthought, Inc., licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.
To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/>

Combining DataFrames




Tools for combining Series and DataFrames together, with SQL-type joins and concatenation. Use join if merging on indices, otherwise use merge.

Merge on Column Values

```
> pd.merge(left, right, how='inner', on='id')
```

Ignores index, unless `on=None`. See value of `how` below.
 Use `on` if merging on same column in both DataFrames, otherwise use `left_on`, `right_on`.

Merge Types: The `how` Keyword



Concatenating DataFrames

```
> pd.concat(df_list)
```

"Stacks" DataFrames on top of each other.
 Set `ignore_index=True`, to replace index with `RangeIndex`.
 Note: Faster than repeated `df.append(other_df)`.

Join on Index

```
> df.join(other)
```

Merge DataFrames on index. Set `on=keys` to join on index of `df` and on `keys` of `other`. Join uses `pd.merge` under the covers.

Cleaning Data with Missing Values

Pandas represents missing values as **NaN** (Not a Number). It comes from Numpy and is of type `float64`. Pandas has many methods to find and replace missing values.

Find Missing Values

```
> s_df.isnull() or > pd.isnull(obj)
> s_df.notnull() or > pd.notnull(obj)
```

Replacing Missing Values

```
s_df.loc[s_df.isnull()] = 0
```

Use mask to replace NaN

```
s_df.interpolate(method='linear')
```

Interpolate using different methods

```
s_df.fillna(method='ffill')
```

Fill forward (last valid value)

```
s_df.fillna(method='bfill')
```

Or backward (next valid value)

```
s_df.dropna(how='any')
```

Drop rows if any value is NaN

```
s_df.dropna(how='all')
```

Drop rows if all values are NaN

```
s_df.dropna(how='all', axis=1)
```

Drop across columns instead of rows

ENTHOUGHT

Take your Pandas skills to the next level! Register at www.enthought.com/pandas-master-class

© 2016 Enthought, Inc., licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.
To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/>

Reshaping Dataframes and Pivot Tables



Tools for reshaping **DataFrames** from the *wide* to the *long* format and back. The *long* format can be *tidy*, which means that "each variable is a column, each observation is a row". Tidy data is easier to filter, aggregate, transform, sort, and pivot. Reshaping operations often produce multi-level indices or columns, which can be sliced and indexed.

1 Hadley Wickham (2014) "Tidy Data", <http://dx.doi.org/10.38637/jss.v059.i10>

MultiIndex: A Multi-Level Hierarchical Index

Often created as a result of:

```
> df.groupby(list_of_columns)
> df.set_index(list_of_columns)
```

Contiguous labels are *displayed* together but apply to each row. The concept is similar to multi-level columns.

A **MultiIndex** allows indexing and slicing one or multiple levels at once. Using the *Long* example from the right:

```
long.loc[1900]      All 1900 rows
long.loc[(1900, 'March')]  value 2
long.xs('March', level='Month')  All March rows
```

Simpler than using boolean indexing, for example:

```
> long[long.Month == 'March']
```

Long to Wide Format and Back with **stack()** and **unstack()**

Pivot **column** level to index, i.e. "stacking the columns" (wide to long):
`> df.stack()`

Pivot **index** level to columns, "unstack the columns" (long to wide):
`> df.unstack()`

If multiple indices or column levels, use level number or name to **stack/unstack**:

```
> df.unstack(0) or > df.unstack('Year')
```

A common use case for unstacking, plotting group data vs index after groupby:

```
> (df.groupby(['A', 'B'])['relevant'].mean()
   .unstack().plot())
```

Wide				Long		
Year	Jan.	Feb.	Mar.	Year	Month	Value
1900	1	7	2	1900	Jan.	1
					Feb.	7
					Mar.	2
2000	4	3	9	2000	Jan.	4
					Feb.	3
					Mar.	9

Pivot Tables

```
> pd.pivot_table(df,
  index=cols, (keys to group by for index)
  columns=cols2, (keys to group by for columns)
  values=cols3, (columns to aggregate)
  aggfunc='mean') (what to do with repeated values)
```

Omitting index, columns, or values will use all remaining columns of df. You can "pivot" a table manually using **groupby**, **stack** and **unstack**.

Index				Columns		
0	Recently updated	Number of stations	Continent code	Continent code	AN	EU
1	FALSE	1	EU	Recently updated		
2	FALSE	1	EU	FALSE	1	3
3	FALSE	1	EU	TRUE	2	1
4	TRUE	1	EU			
5	FALSE	1	AN			
6	TRUE	1	AN			
7	TRUE	1	AN			

```
pd.pivot_table(df,
  index="Recently updated",
  columns="continent code",
  values="Number of Stations",
  aggfunc=np.sum)
```

From Wide to Long with **melt**

Specify which columns are identifiers (**id_vars**, values will be repeated for each row) and which are "measured variables" (**value_vars**, will become values in *variable* column. All remaining columns by default).

```
pd.melt(df, id_vars=id_cols, value_vars=value_columns)
```

```
pd.melt(team, id_vars=['Color'],
  value_vars=['A', 'B', 'C'],
  var_name='Team', value_name='Score')
```

Team

	Color	A	B	C
0	Red	1	3	4
1	Blue	2	-	6

Melt

	Color	Team	Score
0	Red	A	1
1	Blue	A	2
2	Red	B	3
3	Blue	B	-
4	Red	C	4
5	Blue	C	5

df.pivot() vs pd.pivot_table

df.pivot() Does not deal with repeated values in index. It's a declarative form of **stack** and **unstack**.

pd.pivot_table() Use if you have repeated values in index (specify **aggfunc** argument).



Red Panda
Ailurus fulgens

Take your Pandas skills to the next level! Register at www.enthought.com/pandas-master-class

© 2016 Enthought, Inc., licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/>

THE
G
U
O
H
T
N
E