
Table of Contents

Project 2 Analysis	1
Usefull Constants	1
Given Data	1
Import Collected Data	1
Convert Data	2
Call a Helper function for each Deliverable	4

Project 2 Analysis

This script is the main controller for the SR30 analysis in Project 2 of ME140. It should import data, and call the component functions for each of the individual parts of the project.

Authors: Jean-Christophe Perrin, Beck Goodloe, Richard Randall, Jason Trinidad

Created: 2018-04-11 Edited: 2018-04-11

```
clear all;  
clc;
```

Usefull Constants

These are mostly conversion factors so that we can convert from imperial units collected into metric.

```
const.insqToMsq = 0.00064516; % [m^2/in^2]  
const.lbfToN = 4.44822; % [N/lbf]  
const.R = 287; % [kJ/kg/k] Gas cosntant of air  
const.KCdiff = 273; % [  
const.kPaToPa = 1e3; % [Pa/kPa]
```

Given Data

The following values were supplied to us in the original project specifications and should not be changed.

```
given.pitotEffectiveArea = 6.4*const.insqToMsq; % [m^2]  
given.jetAHeating = 42.8e6; % [J/kg/K]  
given.A = [27.3, 6.4, 9.0, 7.2, 4.7, 3.87]'.*const.insqToMsq; % [m^2]
```

Import Collected Data

Our collected data is in an excel file named `Data_proj2`. Here we import that data into a vector for use in our MatLab script. The excel file should never be modified by our script.

```
fname = 'Data_proj2.xlsx';  
sname = 'CollectedData';  
range = 'A3:M11';  
%[NUM, TXT, RAW] = xlsread(fname, sname, range); % basic reading
```

```
stateData = readtable(fname, 'Sheet', sname, 'Range', range);
```

Convert Data

Before we start to do calculations on this data, let's convert it to the basic units that we will use throughout the course of our analysis. That means converting all temperature values into Kelvin and all pressure values into Pascals.

```
stateData(:, 2:6) = stateData(:, 2:6) + const.KCdiff; % convert T to [K]
stateData(:, 7:11) = stateData(:, 7:11) * const.kPaToPa + 1; % convert P to [Pa]
stateData.Properties.VariableUnits = {'', 'K', 'K', 'K', 'K', 'K', ...
    'Pa', 'Pa', 'Pa', 'Pa', 'Pa', 'kg/s', 'N'};
summary(stateData);
```

Variables:

RPM: 8×1 double

Values:

Min	0
Median	0
Max	0

T2: 8×1 double

Units: K

Values:

Min	273
Median	273
Max	273

T3: 8×1 double

Units: K

Values:

Min	273
Median	273
Max	273

T4: 8×1 double

Units: K

Values:

Min	273
Median	273
Max	273

T5: 8×1 double

Units: K

Values:

Min 273

Median 273

Max 273

T8: 8×1 double

Units: K

Values:

Min 273

Median 273

Max 273

P2: 8×1 double

Units: Pa

Values:

Min 1

Median 1

Max 1

P3: 8×1 double

Units: Pa

Values:

Min 1

Median 1

Max 1

P4: 8×1 double

Units: Pa

Values:

Min 1

Median 1

Max 1

P5: 8×1 double

Units: Pa

Values:

Min 1

Median 1

Max 1

P8: 8×1 double

Units: Pa

Values:

<i>Min</i>	<i>1</i>
<i>Median</i>	<i>1</i>
<i>Max</i>	<i>1</i>

Fuel: 8×1 double

Units: kg/s

Values:

<i>Min</i>	<i>0</i>
<i>Median</i>	<i>0</i>
<i>Max</i>	<i>0</i>

Thrust: 8×1 double

Units: N

Values:

<i>Min</i>	<i>0</i>
<i>Median</i>	<i>0</i>
<i>Max</i>	<i>0</i>

Call a Helper function for each Deliverable

Each function should take in the current table of calculated data and then add to it the component values that it calculates.

```
stateData = deliverable2(stateData, given, const);  
stateData = deliverable3(stateData, given, const);  
stateData = deliverable4(stateData, given, const);
```

Columns 1 through 9

<i>'RPM'</i>	<i>'T2'</i>	<i>'T3'</i>	<i>'T4'</i>	<i>'T5'</i>	<i>'T8'</i>	<i>'P2'</i>	<i>'P3'</i>
<i>'P4'</i>							

Columns 10 through 13

<i>'P5'</i>	<i>'P8'</i>	<i>'Fuel'</i>	<i>'Thrust'</i>
-------------	-------------	---------------	-----------------

Hello, world! 1

Hello, world! 2

Hello, world! 3

Published with MATLAB® R2017b