

# Delusions of Grandeur (NetSec) Blog

<div><div>Tuesday, September 24, 2013</div><div><h2>CSAW CTF Quals: Cryptography 300 Onlythisprogram</h2><p>For this challenge, we are given the onlythisprogram.tar.gz file. We extracted the files and in that file was the onlythisprogram.py script and an output file with 9 fileX.enc files. Looking through the python code, this line is of interest:</p><pre>args.outfile.write(chr(ord(keydata[counter % len(keydata)]) ^ ord(byte)))</pre><p>This line shows that the operation of interest is an XOR operation. <b>Here</b> is a reading on that vulnerability:</p><p>The first thing that I thought might have been it was crib dragging, exactly like it showed in the reading. Still brainstorming, however, I guessed that it probably wasn't just text files, but the ENC files were the encrypted files.</p><p>Okay, still looking at the same line we have above, the modulus is happening with the length of the keydata. Further above, you see this:</p><pre>while (args.secretkey.tell() &lt; blocksize):</pre><p>Blocksize is set to 256 at the top so you know that the secretkey file is a 256 byte key that is used over and over again until the files are done being encrypted.</p><p>Great! Now it's time to build the decryption script.</p><p>I want the script to take the bytes from two files and then XOR them together and output that to an outfile. This is pretty much a straight Ctrl+C, Ctrl+V from the CSAW provided python file! #EPIC!</p><p>So, if each fileX.enc represented a file, then they would probably have headers that we know are at the beginning. <b>This</b> is the library that I used for the file headers.</p><p>So now you need to understand what cribbing does. Here's an example. If you have encrypted byte AE and encrypted byte BE, both of which use the same key (K), you can XOR AE and BE together. What that does is it gets rid of the key and gives you A ^ B, where A and B are the original bytes. At that point, if you XOR that with the original byte A, you will get the original byte of B.</p><p>So for this particular challenge, if we suspect that the file1 is supposed to be a DOC file, for example, we can assume the original byte in that position should be the header byte of a DOC file. If the bytes returned is not gibberish, then we know that one of file1 or whatever file we XOR'd it against to be a DOC file. Here's the code for this function:</p><pre>header=open('header','w+') header.write('\xFF\xD8\xff\xE0\x00\x10\x4A\x46\x49\x46\x00') header.seek(0)  ...  while 1:     byte1, byte2 = args.infile1.read(1), args.infile2.read(1)     if not byte1 or not byte2:         break     temp.write(chr(ord(byte1) ^ ord(byte2)))  temp.flush() temp.seek(0)  while 1:     byte1, byte2 = args.infile1.read(1), temp.read(1)     if not byte1 or not byte2:         break     args.outfile.write(chr(ord(byte1) ^ ord(byte2)))</pre><p>I did this with file0 and ran it against the other files until something gave me another header set that was in the website that I showed you. File0 was not a doc file, as most other files gave me gibberish in return, but one of the files was. I then took that file and ran the same operation against all the other files and was able to find all the file types.</p><p>file0 - MID, MIDI file1, 3 - JFIF, JPE, JPEG, JPG file2 - PNG file4 - GZ, TGZ file5 - BMP, DIB file6 - GIF file7 - DOC, DOT, PPS, PPT, XLA, XLS, WIZ file8 - PDF, FDF</p><p>The longest header available to us is the JPG file type. After that, I was able to use trailer bytes to find out with certainty 4 more bytes. At this point, I was a little stumped so I downloaded a lot of files matching the file types I needed. Eventually, I realized that BMP files (at least in the ones I downloaded) had several large blocks of FF bytes. (Read using Hex Editor - I used HxD)</p><p>So using a byte of FF for the original message, I ran that against file5. Hopefully, I would get a large chunk of the secretkey.dat file. Maybe even the whole thing! Here's the code to do that:</p><pre>while 1:     byte1, byte2 = args.infile1.read(1), '\xff'     if not byte1 or not byte2:         break     args.outfile.write(chr(ord(byte1) ^ ord(byte2)))</pre><p>I named this file buzzbmp and went through every 256 byte block until I found one that matched up with my first 11 byte block. I copy and pasted that using HxD to a new secret.dat file and ran the original onlythisprogram.py script with the following code commented out:</p><pre>#args.secretkey.truncate()</pre><pre>#while (args.secretkey.tell() &lt; blocksize):</pre></div></div>	<div><div>Blog Archive</div><div><div><div>► 2015 (7)</div><div>► 2014 (18)</div><div>▼ 2013 (32)</div><div><div>► December (2)</div><div>► October (5)</div><div>▼ September (20)</div><div>CSAW CTF Quals: Recon All</div><div>CSAW CTF Quals: Reversing 150 - bikinibonanza</div><div>CSAW CTF Quals: Web 400 - Widgets</div><div>CSAW CTF Quals: Misc 50 50 100 200</div><div>CSAW CTF Quals: Reversing 500 Noobs First Firmware...</div><div>CSAW CTF Quals: Reversing 400 Keygenme32</div><div>CSAW CTF Quals: Cryptography 300 Onlythisprogram</div><div>CSAW CTF Quals: Reversing 100 DotNetReversing.exe</div><div>CSAW CTF Quals: Exploitation 400_1</div><div>CSAW CTF Quals - Web 300: herpderper.apk</div><div>CSAW CTF Quals: Reversing 500 Impossible.nds</div><div>CSAW CTF Quals: Trivias</div><div>CSAW CTF Quals: Exploitation 300</div><div>CSAW CTF Quals: Exploitation 200</div><div>CSAW CTF Quals: Reversing 200 csaw2013reversing2</div><div>CSAW CTF Quals: Cryptography 100 Cswapad</div><div>CSAW CTF Quals: Web 200</div><div>CSAW CTF Quals: Web 100</div><div>CSAW CTF Quals: Misc 300</div><div>CSAW CTF Quals: Reversing 100 csaw2013reversing1</div></div></div><div><div>► April (1)</div><div>► February (4)</div><div>► 2012 (58)</div></div></div></div>
---	--

```
#while (args.secretkey.tell() < blocksize):
# maybe remove the next line for release since it makes it more obvious the key only generates
#     sys.stdout.write('.')
#     args.secretkey.write(os.urandom(1))
```

The file to decrypt I used was the PDF file, file8. After several iterations of error checking for correct and incorrect bytes, a decrypted PDF file that had a few errors. However, I had enough correct bytes in that secret.dat test file that a lot of strings were intact. I had about two bytes that were off. Here is that secret.dat file:

```
Offset(h) 00 01 02 03 04 05 06 07 08 09 0A 0B 0C 0D 0E 0F
00000000 40 50 3A C8 2D 69 F7 D3 02 3A F4 AC 67 DE 4D 3B @P:È-i÷Ó.:ô-gfBM;
00000010 81 44 3E 4D ED E1 D5 43 74 56 A8 D2 9F A0 23 29 .D>MíáŒCtV"ŒŸ #)
00000020 12 6D 0B CE A4 0F C7 F6 BE 9F F7 C6 6D 74 DC BA .m.î».Çø%Ÿ÷ËmtŮ°
00000030 D2 D4 0E A3 D5 29 0C 31 F1 08 53 2E B1 0C 79 6A ŒŒ.ŒŒ).îñ.S.±.yĵ
00000040 29 BC E1 E4 B3 BB 40 BF 69 77 7D 21 55 EA 80 45 )!ááá"»@ziw)!UëEE
00000050 7E 43 03 60 93 B4 98 B3 26 8E 35 A1 6C CC 6E D4 ~C.````"~¿Z5;lîñŒ
00000060 CA 8F 10 EE 61 29 7F AB 88 24 08 B5 30 23 A6 1B Ê..îa).«`$.µ0#|.
00000070 C8 9C 10 A0 18 1E AC 9E 62 A1 B6 6A 48 46 9C 60 Êæ. ...-žb;ŸjHFæ`
00000080 85 87 CB 63 A8 7F 2B D6 30 53 1D 65 7C AC 22 0D ...+Ëc".+ŒŒS.e|~".
00000090 3A 41 E1 64 DC F7 78 E3 F8 DE 04 43 9C 6E EC 5A :AádŮ÷xääøP.CœîZ
000000A0 D4 A6 D1 7F A9 6C DF 63 DF D5 71 2E C1 D6 5E 55 Œ;Ñ.ŒlâcBŒq.ĂŒŮU
000000B0 5F 8E 70 4B B8 53 F2 8D F7 16 2B 3A B9 A1 8A 8B _žpK,Sô.÷.+:;Ÿ;
000000C0 9B E0 3E E7 FC 68 CB 8D 9A 95 45 00 E4 A4 EC 15 >â>çûhË.š•E.â=î.
000000D0 F4 1E 80 83 E4 36 81 7A 45 12 00 6C 5A A4 D3 0B ô.Ěfa6.zE..lZ×Œ.
000000E0 8B 89 B9 91 39 F7 E2 B7 98 59 39 B3 86 4D 5D AF <Ÿ" '9÷ă~"Y9"+M]~
000000F0 58 9E 30 EF CD 2B BC 0C 9F DC E6 C6 9E 71 AA E8 Xž0îî+4.YŮæEžq*è
```

#### Incorrect Secret.dat File

To narrow those down and correct them, I went through the file looking for intact strings. I was able to narrow down the incorrect bytes and, because I knew what a few of the strings should have looked like, I was able to correct the incorrect bytes and build the correct key! Manually. #CRYPTOOOO

```
Offset(h) 00 01 02 03 04 05 06 07 08 09 0A 0B 0C 0D 0E 0F
00000000 40 50 3A C8 2D 69 F7 D3 02 3A F4 AC 67 DE 4D 3B @P:È-i÷Ó.:ô-gfBM;
00000010 81 44 3E 4D ED E1 D5 43 74 56 A8 D2 9F A0 23 29 .D>MíáŒCtV"ŒŸ #)
00000020 12 6D 0B CE A4 0F C7 F6 BE 9F F7 C6 6D 74 DC BA .m.î».Çø%Ÿ÷ËmtŮ°
00000030 D2 D4 0E A3 D5 29 0C 31 F1 08 53 2E B1 0C 79 6A ŒŒ.ŒŒ).îñ.S.±.yĵ
00000040 29 BC E1 E4 B3 BB 40 BF 69 77 7D 21 55 EA 80 45 )!ááá"»@ziw)!UëEE
00000050 7E 43 03 60 93 B4 98 B3 26 8E 35 A1 6C CC 6E D4 ~C.````"~¿Z5;lîñŒ
00000060 CA 8F 10 EE 61 29 7F AB 88 24 08 B5 30 23 A6 1B Ê..îa).«`$.µ0#|.
00000070 C8 9C 10 A0 18 1E AC 9E 62 A1 B6 6A 48 46 9C 60 Êæ. ...-žb;ŸjHFæ`
00000080 85 87 CB 63 A8 7F 2B D6 30 53 1D 65 7C AC 22 0D ...+Ëc".+ŒŒS.e|~".
00000090 3A 41 E1 64 DC F7 78 E3 F8 DE 04 43 9C 6E EC 5A :AádŮ÷xääøP.CœîZ
000000A0 D4 A6 D1 7F A9 6C DF 63 DF D5 71 2E C1 D6 5E 55 Œ;Ñ.ŒlâcBŒq.ĂŒŮU
000000B0 5F 8E 70 4B B8 53 F2 8D F7 16 2B 3A B9 A1 75 74 _žpK,Sô.÷.+:;Ÿ;ut
000000C0 9B E0 3E E7 FC 68 CB 8D 9A 95 45 00 E4 A4 EC 15 >â>çûhË.š•E.â=î.
000000D0 F4 1E 80 83 E4 36 81 7A 45 12 00 6C 5A A4 D3 0B ô.Ěfa6.zE..lZ×Œ.
000000E0 8B 89 B9 91 39 F7 E2 B7 98 59 39 B3 86 4D 5D AF <Ÿ" '9÷ă~"Y9"+M]~
000000F0 58 9E 30 EF CD 2B BC 0C 9F DC E6 C6 9E 71 AA E8 Xž0îî+4.YŮæEžq*è
```

#### Correct Secret.dat File :

I decrypted every file and then extracted everything from file4.gz. File4 contained the key, which we opened up in Notepad++. It says in ASCII block text, "For some reason psifertex really likes Aglets (??? - Not sure about this word really.) In this case it's necessary because the file size should not be a huge giveaway. Though I suppose images would have worked too. Anyway, the key: BuildYourOwnCryptoSoOthersHaveJobSecurity"

And there's your key! Here's all the code that I used to build my secret.dat files. It's a bit messy with the commenting though!

```
import sys
import argparse

parser = argparse.ArgumentParser(description="n.a")
parser.add_argument('--infile1', metavar='i1', nargs='?', type=argparse.FileType('rb'), help=':
parser.add_argument('--infile2', metavar='i2', nargs='?', type=argparse.FileType('rb'), help=':
parser.add_argument('--outfile', metavar='o', nargs='?', type=argparse.FileType('w+'), help='o

# outfile a+ option opens file for both append and read. New file created for read/write if no

args = parser.parse_args()
temp = open('temp', 'w+')
temp.truncate()
header=open('header','w+')
header.write('\xFF\xD8\xff\xE0\x00\x10\x4A\x46\x49\x46\x00')
header.seek(0)
key=open('key', 'w+')
key.write('\x40\x50\x3A\xC8\x2D\x69\xF7\xD3\x02\x3A\xF4\xAC')
key.seek(0)

#fuzz.open('fuzz', 'w+')
#fuzz.write('\xff'*256)

#while 1:
#     byte1, byte2 = args.infile1.read(1), args.infile2.read(1)
#     if not byte1 or not byte2:
#         break
#     temp.write(chr(ord(byte1) ^ ord(byte2)))

#temp.flush()
#temp.seek(0)

while 1:
    byte1, byte2 = args.infile1.read(1), '\xff'
    if not byte1 or not byte2:
        break
    args.outfile.write(chr(ord(byte1) ^ ord(byte2)))

sys.stderr.write('Done.\n')
```

-----



Please comment down below if you have an comments or questions for me! Thanks for reading!

--dotKasper

Posted by **Delusions Grandeur** at **2:00 PM**  
Labels: **CSAW QUALS 2013**

No comments:

Post a Comment

Enter your comment...

Comment as: Select profile... ▾

Publish

Preview

Newer Post

Home

Older Post

Ads