


CSE 2421

**X86-64 Assembly Language Part 3:
Control (Loops)**

Required Reading: section 3.6.7



Today

- ▶ Control: Condition codes
 - ▶ Conditional branches
 - ▶ Loops
- 

ACADEMIC MISCONDUCT WARNING

- ▶ There are many good reasons to use `-S` to compile C code to assembly code
 - To find out what gcc is doing to your code [we found a compiler bug once]
 - To learn different ways of accomplishing things
 - To compare the code produced with various options (`-g`, `-O`, `-Ofast...`)
- ▶ Do NOT turn in machine generated `.s` files *ever*
 - Those files were generated by a machine, not you (misrepresentation of the work)
 - Such labs will be turned over to the Committee on Academic Misconduct

“Do-While” Loop Example

C Code

```
long pcount_do
(unsigned long x) {
    long result = 0;
    do {
        result += x & 0x1;
        x >>= 1;
    } while (x);
    return result;
}
```

Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
    return result;
}
```

- ▶ Count number of 1's in argument x (“popcount”)
- ▶ Use conditional branch to either continue looping or to exit loop

“Do-While” Loop Compilation

Goto Version

```
long pcount_goto
(unsigned long x) {
    long result = 0;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
    return result;
}
```

Register	Use(s)
%rdi	Argument x
%rax	result

```
    movq    $0, %rax    # result = 0
.L2:                                     # loop:
    movq    %rdi, %rdx
    andq    $1, %rdx    # t = x & 0x1
    addq    %rdx, %rax  # result += t
    shrq    %rdi        # x >>= 1
    jne     .L2         # if (x) goto loop
    ret                                     # ret
```

General “Do-While” Translation

C Code

```
do  
    Body  
while ( Test );
```

► Body:

```
{  
    Statement1;  
    Statement2;  
    ...  
    Statementn;  
}
```

Goto Version

```
loop:  
    Body  
    if ( Test )  
        goto loop
```

General “While” Translation #1

- ▶ “Jump-to-middle” translation
- ▶ Used with **gcc -Og**

While version

```
while (Test)  
    Body
```



Goto Version

```
goto test;  
loop:  
    Body  
test:  
    if (Test)  
        goto loop;  
done:
```

While Loop Example #1

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Jump to Middle Version

```
long pcount_goto_jtm
(unsigned long x) {
    long result = 0;
    goto test;
loop:
    result += x & 0x1;
    x >>= 1;
test:
    if(x) goto loop;
    return result;
}
```


- ▶ Compare to do-while version of function
- ▶ Initial goto starts loop at test

General “While” Translation #2

While version

```
while (Test)  
    Body
```

- ▶ “Do-while” conversion
- ▶ Used with `gcc -O1`



Do-While Version

```
if (!Test)  
    goto done;  
do  
    Body  
    while(Test);  
done:
```



Goto Version

```
if (!Test)  
    goto done;  
loop:  
    Body  
    if (Test)  
        goto loop;  
done:
```

While Loop Example #2

C Code

```
long pcount_while
(unsigned long x) {
    long result = 0;
    while (x) {
        result += x & 0x1;
        x >>= 1;
    }
    return result;
}
```

Do-While Version

```
long pcount_goto_dw
(unsigned long x) {
    long result = 0;
    if (!x) goto done;
loop:
    result += x & 0x1;
    x >>= 1;
    if(x) goto loop;
done:
    return result;
}
```

- ▶ Compare to do-while version of function
- ▶ Initial conditional guards entrance to loop

“For” Loop Form

General Form

```
for (Init; Test; Update)  
    Body
```

```
#define WSIZE 8*sizeof(long)  
long pcount_for  
    (unsigned long x)  
{  
    size_t i;  
    long result = 0;  
    for (i = 0; i < WSIZE; i++)  
    {  
        unsigned bit =  
            (x >> i) & 0x1;  
        result += bit;  
    }  
    return result;  
}
```

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```


Body

```
{  
    unsigned bit =  
        (x >> i) & 0x1;  
    result += bit;  
}
```

“For” Loop → While Loop

For Version

```
for (Init; Test; Update)  
    Body
```



While Version

```
Init;  
while (Test) {  
    Body  
    Update;  
}
```

For-While Conversion

Init

```
i = 0
```

Test

```
i < WSIZE
```

Update

```
i++
```

Body

```
{  
    unsigned bit =  
        (x >> i) & 0x1;  
    result += bit;  
}
```

```
long pcount_for_while  
(unsigned long x)  
{  
    size_t i;  
    long result = 0;  
    i = 0;  
    while (i < WSIZE)  
    {  
        unsigned bit =  
            (x >> i) & 0x1;  
        result += bit;  
        i++;  
    }  
    return result;  
}
```

“For” Loop Do-While Conversion

C Code

```
long pcount_for
(unsigned long x)
{
    size_t i;
    long result = 0;
    for (i = 0; i < WSIZE; i++)
    {
        unsigned bit =
            (x >> i) & 0x1;
        result += bit;
    }
    return result;
}
```

Goto Version

```
long pcount_for_goto_dw
(unsigned long x) {
    size_t i;
    long result = 0;
    i = 0; Init
    if (!(i < WSIZE)) ! Test
    goto done;
loop:
{
    unsigned bit =
        (x >> i) & 0x1; Body
    result += bit;
}
i++; Update
if (i < WSIZE) Test
    goto loop;
done:
    return result;
}
```

- ▶ Initial test can be optimized away