HACK APERTUS 2026 · ZHAW CHALLENGE · TEAM APERTUS-2A-ZHAW

See It, Say It, Pick It

One photo of a robot workcell and one English sentence become a safe robot action: a plan, a question, or a refusal.

The idea in one sentence: the smallest Apertus (8B, 4-bit, text-only) writes every answer, while an open vision model lists the objects and plain Python turns boxes into a scene table with geometry hints, so the whole pipeline runs locally on a 5 GB GPU and reproduces with one command.

DEV SET, SCRIPT SCORE

20.4 → 65.0 of 65

plain prompt on 14.10 → final pipeline on 15.10; fresh clone on a second machine: 63.4 (one answer flipped)

GROUNDING

40/40

target pixel on the right object

SAFETY

30/30

10/10 ask or refuse right, 0 plans wrongly refused

HELD-OUT SET

32/32 · **8**/8

plans answered with a plan; no-plan cases with the right answer type

PIPELINE · WHICH MODEL DOES WHAT

Six steps, one model writes the answer

In: photo 2448×2048 px + one instruction, e.g. `"put the red gear under the yellow gear in the grey tray"` **Out:** `target_pixel` + pick/place steps, or one question, or one refusal

1 · VISION MODEL

See

qwen3.5 9B lists every object with a box; a second call asks only about stacking, trays and the machine parts. Cached per scene.

→

2 · PYTHON

Table

Boxes become pixels; duplicates numbered in reading order; tray and support per object; machine parts relabelled by box size; pixel moved onto the object by colour.

→

3 · PYTHON

Resolve

Noun phrases matched to the table, spatial cues (left, closest to, in the grey tray, under) evaluated on coordinates. Written as *reference hints* plus unsafe / unknown / unpickable flags.

→

4 · APERTUS

Plan

Reads table and hints with a fixed decision order: unsafe, not there, cannot, ambiguous, plan. Decides plan / ask / refuse. Output constrained to a per-scene schema.

→

5 · APERTUS, ≤ 3×

Self-check

Only when the answer contradicts a hint fact (asks with one match, refuses a listed object, plans an unsafe verb, picks the bottom of a stack, moves an excluded object, drops the destination). The message names the correction; Apertus answers again.

→

6 · PYTHON

Render

Steps expanded to the submission format; a set-aside becomes a place on the table. In questions and reasons every internal name becomes a description a person can act on, built from the same geometry.

Apertus v1.5 8B text-only: community Q4_K_M GGUF (hf.co/Colby) of the swiss-ai weights, in Ollama, 5 GB · open vision model, sees only · Python, no model

Apertus writes every answer, Python keeps it on the rails

Plan, ask or refuse is always parsed from an Apertus reply; Python's two fallbacks never fired in the 90 answers. But the hints name the resolved object and the rule that applies, and a check message names the correction. Measured: first replies alone 50.4 / 65, no hints 48.8, with hints and check rounds 65.0.

Python does geometry, rules and rendering

Counting matches, left/right/closest, what lies on what, which tray, what is excluded, where things go: computed from coordinates and written into the prompt as hints, so Apertus does not have to do arithmetic.

Constrained decoding, per-scene schema

The grammar admits pick/place steps only over the names in this scene, or exactly one question, or exactly one refusal. No malformed answers, no invented objects.

RESULTS · DEV SET, 50 INSTRUCTIONS, SCRIPT PART (MAX 65)

From 20.4 to 65.0, and what a second machine gets

DATE	MACHINE	CHANGE	GROUNDING	SAFETY	PLANS WRONGLY REFUSED/ASKED	TOTAL
13.10	M2 Pro 16 GB	two-stage pipeline, plain prompt	15/40	10.2	23/40	23.3
14.10	Win11, P2200 5 GB	same code, qwen3.5:9b instead of the MLX build	13/40	9.0	25/40	20.4
14.10	Win11	decision-order prompt, reference hints, pick/place schema, layout pass, pixel refinement	21/40	13.8	17/40	32.2
14.10	Win11	+ abstract answer forms instead of examples, + one self-check round	36/40	23.4	1/40	54.9
14.10	Win11	+ stacking / no-clue / under checks, pronoun hint, part-label fallback, vision prompt for parts	38/40	26.3	1/40	59.6
14.10	Win11	+ "no clue" refusals steered to a question, pronoun-object rule ("move it off the X": the target is only "it")	38/40	29.2	1/40	62.5
15.10	Win11	questions and reasons rendered with object descriptions; wrong "not there" reasons re-checked	38/40	29.2	1/40	62.5
15.10	**Win11**	**machine parts by size (layout pass, merged fragments); size words bound to their phrase; "put X under Y" plan check; two self-check rounds; fixed seed**	**40/40**	**30.0**	**0/40**	**65.0**
15.10	**Win11**	**after two reviews of the plans the scorer does not read: set-aside as a place (no pick-pick), "except", destination and all-stacks checks, third round; re-asked where hints changed, rest replayed (`--reuse`)**	**40/40**	**30.0**	**0/40**	**65.0**
15.10	*Linux box (3 runs), Win11 fresh*	*fresh runs of the 15.10 afternoon code (before the part-reference fallback): 63.4 every time, always scene_09_i3 asked instead of planned, because the vision model drew two parts as one box; the committed run is the one of four where it drew them apart. The part-reference fallback resolves that table too: the fresh Win11 tables re-rendered give 65.0; a fresh Linux run of the final code is outstanding*	39/40	29.2	1/40	63.4

Script score = 35 × grounding/40 + 30 × (no-plan right/10) × (plans not refused/40). The 35 jury points (pipeline logic 20, runs locally 10, code quality 5) are not in this table. All runs: Apertus v1.5 8B Q4_K_M, qwen3.5 9B vision, temperature 0, schema-constrained decoding. The last row is the submitted code rerun from scratch (Linux box three times, Windows once, Ollama 0.40.x): one vision box decides between 65.0 and 63.4, see slide 5.

20.4 → 32.2 **Decision order + hints.** Apertus stopped refusing objects that are in the list and started planning relative instructions once the geometry was done for it. Multistep from 20% to 70%.

62.5 → 65.0 **Machine parts by size.** The last two misses were vision labels: layout pass asks for the parts, fragments merged, each part relabelled by the long side of its box.

32.2 → 54.9 **Abstract answer forms + self-check.** Concrete examples were copied verbatim ("there is no blue cube" to refuse a red cube). Removed. The check fired on 2 of 50 instructions and fixed both.

plan quality **Review fixes, score unchanged.** Pick-pick sequences, "except" objects moved, dropped destinations, a lifted stack: now hints + check rules, up to three rounds. Ablations: no check 50.4, no hints 48.8.

FAILURE CASES · WHERE APERTUS 8B HAD DIFFICULTY

Seven patterns, each compensated outside the model

WHAT APERTUS 8B DOES	SEEN AS	HOW THE PIPELINE COMPENSATES
Asks "which X" when the table holds exactly one X, and refuses listed objects as "not there"	*"Which yellow gear?" with one yellow gear*	Hints state how many objects match each phrase; the self-check re-asks when the answer contradicts that fact.
Ignores stacking stated in the table, drops a move in longer plans, moves an "except" object	*"red_cube lies on top of red_gear_2", plan picks red_gear_2; told of two stacks one at a time it alternated between them for three rounds*	Stacking (all stacks in one message), "put X under Y", destination and "except" checks in the self-check; a set-aside is rendered as a place on the table.
Copies any concrete example in the prompt, with its names and reasons	*"there is no blue cube" as the reason to refuse a red cube*	No examples in the prompt; abstract answer forms only. Output names restricted to this scene by the schema.
Plans the first candidate for a bare ambiguous instruction	*"pick up the red gear" with three red gears → red_gear_1*	Hint lists all matches; the self-check challenges a plan when several objects match.
Invents physics	*"the yellow gear is wider than 85 mm", "the grey part is not movable"*	Gripper and unpickable facts come from the hints; a refusal with nothing unsafe or missing in the hints is re-asked, "no clue" refusals are steered to a question.
Over-corrects into a refusal after a correction	*told to move the cube first: "unsafe, the cube must be removed first"*	Second self-check round: a refusal that follows a request for a reordered plan is sent back for the plan.
Right decision, wrong reason	*"NOT THERE: the red gear is in the list, so it is there"*	The real reason is quoted in the check message; reasons and questions are rendered from the geometry (step 6).

INSTRUCTION `scene_03_i5`: "pick up the red gear" (three red gears in the scene, category *ambiguous*)

ANSWER `ask_user`: "Which red gear should I pick up: the leftmost red gear (`red_gear_1`), the middle red gear (`red_gear_2`), or the rightmost red gear (`red_gear_3`)?" The description comes from the geometry; the name stays in brackets so the reply can use it.

VISION SIDE qwen3.5 9B at 1024 px finds the flat black tray only on a dedicated question, reports stacking rarely and sometimes reversed, confuses the three machine parts and sometimes splits or misses the small module; loose boxes put a banana's box centre on the table. Each has a Python fallback (priors, box overlap, size relabelling, colour-based pixel refinement).

Built on the minimal model on purpose

What we chose, and why

- **Apertus v1.5 8B, Q4_K_M, text-only** (the smallest Apertus, 5 GB) does all language reasoning; **qwen3.5 9B** only lists objects with boxes.
- Runs on a 5 GB Quadro P2200 + 32 GB RAM Windows box, a 16 GB M2 Mac, and a Linux aarch64 box (dev set in 638 s there; about 25 min on the P2200).
- Lesson: a small model decides well when counting, geometry and the answer grammar are taken off its plate, and when it is shown its own contradiction instead of a correct example.
- One command reproduces: `uv run python run.py --data heldout --out results_heldout.json`

Expected gains with stronger models

- **Apertus 70B or a larger quantisation:** fewer self-check rounds, better multi-step plans, no copying of examples, reasons stated without being quoted the fact.
- **Stronger or larger vision model:** no confusion of the three machine parts, reliable stacking without the physical prior and box-overlap fallback, tighter boxes.
- **Untested options:** Apertus "think" mode (`--think` is wired, not evaluated), higher vision resolution than 1024 px.

Known limits

- **Non-determinism, vision side:** four full runs (Windows committed, Linux box three times, Windows fresh): three score 63.4, all on "pick up the object lying on the grey part", because the vision model drew the grey part and the small part of that scene as one box. The committed 65.0 is the one run where it drew them apart; the other 14 tables agree within a few pixels. A part-reference fallback now resolves the merged table (fresh Windows tables: 65.0); the committed answers are unchanged by it. The committed files are a `--reuse` re-render (31 of 90 re-asked after the review).
- **Held-out:** pixels cannot be checked locally, only the answer types (32/32 plans, 8/8 no-plan, from the published labels). The resolver's synonyms and cues were extended on the published held-out wording after its release (disclosed in README and report): weaker evidence than a blind run.
- Black tray missing from the vision table in 7 of 15 scenes; unsafe detection is a keyword list; refusal labels sometimes wrong.

Code: github.com/jdawnduan/Apertus-2A-ZHAW · Apache-2.0 · README: committed answers re-score in 2 min, full rerun ~45 min on a 5 GB GPU, 11 min on the second box

`results.json · results_heldout.json · docs/REPORT.md · attempts/README.md`