

EXERCISE 1: BUILD A CONTACT FORM (LEVEL 1, ~25 MIN)

Pure HTML, no JavaScript yet. The goal: get comfortable with form structure.

EXERCISE 2: THE "GREET ME" PAGE (LEVEL 1, ~30 MIN)

Build the lecture example from scratch.

Step 5: Investigate. Open DevTools > Console. Then:

1. Comment out `event.preventDefault();` (add `//` in front). Save. Refresh. Type a name. Click Greet me. What happens? Why?
It refreshed because `event.preventDefault()` prevents the browser from refreshing.
2. Restore `event.preventDefault();`. Now change `greeting.textContent` to `greeting.innerHTML` and the message to `<strong>Hello, ${name}!</strong>`. Save, refresh, try it. What changed?
It showed all of the text. `<strong>Hello, Jacqueline!</strong>`
3. With `.innerHTML` still in place, try entering `<em>injected</em>` as your name. What does the page show?
It shows: Hello, *injected*! (This is exactly why `.innerHTML` is risky for user input.) Switch back to `.textContent` and try the same input -- now it shows the literal text including the angle brackets. Yes, it shows: Hello, `<em>injected</em>`!

EXERCISE 3: A 2-QUESTION SURVEY (LEVEL 2, ~35 MIN)

Collect inputs and show a summary on submit.

1. Grabs the form, the two inputs, and the summary div.
2. Listens for the form's `submit` event.
3. Calls `event.preventDefault()`.
4. Reads `.value` from each input.
5. Updates the summary div with text like "Your favorite color is blue and you've been coding for 1 year(s)."

EXERCISE 4: "AI, BUILD ME AN INTERACTIVE THING" (LEVEL 2, ~30 MIN)

Practice the accept/reject/modify workflow on JavaScript code.

Line	What It Does	Decision (Accept / Reject / Modify)	Why
<pre>const form = document.getElementById('numberForm'); // Get the form element by its ID const input = document.getElementById('numberInput'); // Get the input field by its ID const result = document.getElementById('result');</pre>	Finds the, the numberForm, numberInput, and result by ID	Accept	Because I understand it, but querySelector also worked.
<pre>form.addEventListener('submit', function(event) { // Add an event listener for form submission event.preventDefault();</pre>	Listens for submit, Stops page reload on submit	Accept	AI used submit for the form, it's correct.
<pre>result.textContent = "Your number doubled is: " + doubled;</pre>	It displays text content	Accept	Used textContent, no errors in console, innerText worked, innerHTML also worked too; no errors in console but XSS is an issue for innerHTML

Step 4: Apply your decisions. Run the page. Does it still work? Yes they both worked without errors.

EXERCISE 5: BUILD YOUR OWN (LEVEL 3, ~30 MIN)

Pick ONE small interactive idea and build it. Use AI to scaffold if you want, but read every line.

