Apache Isis™ CheatSheet

Apache Isis Annotations

@DomainService @DomainServiceLayout

@DomainObject @DomainObjectLayout

@ViewModel, @ViewModelLayout

@Property, @PropertyLayout

@Collection, @CollectionLayout

@Action , @ActionLayout

@Parameter, @ParameterLayout

@Title, @MemberOrder, @MemberGroupLayout

@HomePage, @MinLength, @Programmatic

Xxx.layout.xml instead of @XxxLayout

JDO (DataNucleus) Annotations

@PersistenceCapable, @DatastoreIdentity

@Inheritance, @Discriminator; @Version

@Queries, @Query;

@Uniques, @Unique; @Indices, @Index

@Persistent, @NotPersistent

@Column, @PrimaryKey,@Join, @Element

http://www.datanucleus.org/products/datanucleus/jdo/annotations.html

Other Annotations

@javax.enterprise.context.RequestScoped

@javax.inject.Inject

@javax.annotation.PostConstruct

@javax.annotation.PreDestroy

@javax.validation.constraints. Digits

@javax.xml.bind.annotation.XmRootElement etc.

@com.google.common.eventbus.Subscribe @org.axonframework.eventhandling.annotation.EventHandler

Methods: Class

title(), iconName(), cssClass()
hidden, disabled(IdentifierType), validate()

Methods: Properties

getName(), setName(); modifyName(), clearName()
hideName(); disableName(); validateName()
autoCompleteName(), choicesName()

Methods: Collections

getOrders(); {addTo/removeFrom}Orders()
hideOrders(); disableOrders();
validate{AddTo/RemoveFrom}Orders

Methods: Actions

placeOrder(X x, Y y, Z z) hidePlaceOrder(); disablePlaceOrder() validate{0|1|2}PlaceOrder(X|Y|Z); validatePlaceOrder(X x, Y y, Z z) autoComplete{0|1|2}PlaceOrder(X,Y) choices{0|1|2}PlaceOrder(X,Y) (n-1 args) default{0}PlaceOrder()

RepositoryService

allMatches(Query) & QueryDefault(...), persist(), remove(), instantiate()

MessageService

informUser(), warnUser(), raiseError()

Error & Exception Handling

RecoverableException, NonRecoverableExeption

(some other) Applib Services (API, fwk implements)

FactoryService, TitleService, DomainObjectContainer,
ClockService, ConfigurationService, BookmarkService,
JaxbService, EventBusService, BackgroundService
EmailService, MetaModelService,
IsisJdoSupport, WrapperFactory TranslationService,
CommandContext, ActionInvocationContext
QueryResultsCache, Scratchpad,

request
scoped

(some) Applib Services (SPI, Isis addons impl.)

AuditingService3 (isis-module-audit); CommandService & BackgroundCommandService (isis-module-command); Security services (isis-module-settings)
SessionLoggingService (isis-module-sessionlogger),

Applib Services (SPI, no impl., app must provide)

 $Fixture Scripts, \ User Profile Service, \ User Registration Service$

Other Add-ons (http://www.isisaddons.org)

isis-module-xxx: docx; excel; settings; stringinterpolator; isis-wicket-xxx: excel; fullcalendar2; gmap3

Mixins (fwk implements)

clearHints(), downloadLayout(), id & version properties

Value Types

8 primitive types + wrappers; BigDecimal, BigInteger; java.util.Date, java.sql.{Date|Time|Timestamp}; enums; JODA dates; org.apache.isis.value.*

Applib Utility Classes

ObjectContracts, Enums; TranslatableString

Config Files

WEB-INF/isis.properties, WEB-INF/shiro.ini