



14m 5s (Submitted)

Q1 of 5



State TRUE or FALSE

A NOT NULL constraint can be applied both as a column level or table level constraint.

☐ TRUE

☒ FALSE ✓

Explanation :

A NOT NULL constraint can be applied as a column level constraint.



Q2 of 5



Choose the statement/s that is/are incorrect with respect to the UNIQUE key constraint



14m 5s (Submitted)

Q2 of 5



Choose the statement/s that is/are incorrect with respect to the UNIQUE key constraint



The value of the column must be unique across the whole table.



The column can have many NULL values because PostgreSQL treats each NULL value to be unique.



The value of the column must not be unique across the whole table. ✓



The column can have only one NULL value because PostgreSQL treats repeated NULL value to be duplicate. ✓



14m 5s (Submitted)

Q3 of 5



The datatype Text supports

- ☐ Limited variable length
- ☐ Fixed variable length
- ☐ Blank padded
- ☒ Unlimited variable length ✓

Explanation :

Text datatype is used to store characters of unlimited length



14m 5s (Submitted)

Q4 of 5



```
CREATE TABLE table_name  
(col_name datatype [column constraint])  
[INHERITS (existing_table_name)]
```

Select that well suits Inherits

- ☐ create a table
- ☒ creates a tables with given column and inherits columns from existing tables

- ☐ creates the table with columns from existing tables
- ☐ creates a table with the column given

Explanation :

Postgresql allows inheriting one table to another

Q5 of 5



```
CREATE TABLE employees
(employee_id NUMERIC PRIMARY KEY,
name VARCHAR(20) NOT NULL,
manager_id NUMERIC REFERENCES
employees
ON DELETE SET NULL ON UPDATE SET NULL)
```

What will be the output if the *employee_id* is removed.

-  ☐ The manager_id will be removed
- ☒ The manager_id will be set to NULL ✓ 
- ☐ The output will not be affected.
- ☐ Will give an error

Explanation :

SET key will update the column with specific



9m 52s (Submitted)

Q1 of 3



Which command is used to change the name of an existing column?

- ☒ ALTER TABLE ✓
- ☐ UPDATE TABLE
- ☐ ALTER COLUMN
- ☐ NONE OF THE ABOVE



Explanation :

ALTER is used to alter the definition of the table

Q2 of 3



Which of the following is false with ALTER command.



9m 52s (Submitted)

Q2 of 3



Which of the following is false with ALTER command.

- ☐ Adding constraint is possible
- ☐ Drop constraint is possible
- ☒ Modifying constraint is possible ✓
- ☐ None of the above



Explanation :

Modifying constraints is not possible with alter command



9m 52s (Submitted)

Q3 of 3



Choose the correct syntax to rename the column

☒ ALTER TABLE table_name RENAME
COLUMN column_name TO
new_column_name; ✓

☐ ALTER TABLE table_name ALTER
COLUMN column_name TO
new_column_name;

☐ ALTER TABLE table_name ALTER
COLUMN column_name,
new_column_name;

☐ ALTER TABLE table_name RENAME
COLUMN column_name,
new_column_name;

Q1 of 3



The _____ can be used with DROP TABLE syntax to avoid errors if tables do not exist.

- ☐ cascade
- ☒ if exists ✓
- ☐ restrict
- ☐ none of the above

Explanation :

if exists will work only on the existing tables



Q2 of 3



_____ removes the dependent object while dropping the table.

☒ cascade ✓

☐ if exists

☐ exists

☐ restrict

Explanation :

Cascade removes the dependency

Q3 of 3



Identify the correct syntax to drop employee table from database

- ☐ DROP employee
- ☒ DROP TABLE employee ✓
- ☐ DROP FROM employee
- ☐ DROP employee FROM test

Explanation :
Refer Syntax

Q1 of 3



Which of the following syntax is used to insert a null value for the column "passport" in employee table?

- ☐ insert into
employee(employee_id,passport)
values (101,'null');
- ☐ insert into employee values(101,'');
- ☐ insert into employee values (101);
- ☒ insert into employee values(101,null);

Explanation :

Refer syntax to insert values



Q2 of 3



Which of the following SQL statement is suitable for INSERT command?



INSERT INTO tablename

values(value1, value2); ✓



INSERT INTO table values(value1, value2);



INSERT INTO public.tablename

VALUES(value1, value2); ✓



INSERT INTO

databasename.tablename VALUES (val1, val2);

Explanation :



Explanation :

Refer Syntax

Q3 of 3



INSERTION of data from one table to another table is possible ?

☒ TRUE ✓

☐ FALSE

Explanation :

Insertion from one table to another is possible



Q1 of 3



To update more than one column, use:

☐ UPDATE table_name SET col_name = value1 and col_name1 = value2 WHERE condition;

☐ UPDATE table_name SET col_name = value1 && col_name1 = value2 WHERE condition;

☒ UPDATE table_name SET col_name = value1, col_name = value2 WHERE condition; ✓

☐ UPDATE table_name SET col_name= value1 & col_name = value2 WHERE condition;

Explanation :

Refer update syntax



Q2 of 3



Which of the following statements is TRUE to modify the last name of the employee using UPDATE statement

- ☐ UPDATE employee SET LastName = 'Thomas' INTO LastName = 'Michel'
- ☒ UPDATE Users SET LastName = 'Michel' WHERE LastName = 'Thomas' ✓
- ☐ MODIFY employee SET LastName = 'Michel' WHERE LastName = 'Thomas'
- ☐ MODIFY Users SET LastName = 'Michel' WHERE LastName = 'Thomas'

Explanation :

Use Set and Where clause

Q3 of 3



_____ is the keyword used in update statement

☐ WHERE

☐ LIKE

☒ SET ✓

☐ SELECT

Explanation :

SET is used with UPDATE



14m 54s (Submitted)

Q1 of 3



Which of the following query will be used to delete employees who are not earning any commission?



DELETE FROM employees WHERE
commission_pct is NULL ✓



DELETE FROM employees WHERE
commission_pct = NULL



DELETE FROM employees WHERE
commission_pct LIKE 'NULL'



DELETE FROM employees WHERE
commission_pct = 0

Explanation :

DELETE WITH WHERE clause is used



14m 54s (Submitted)

DELETE WITH WHERE clause is used

Q2 of 3



Which of the following is the correct usage of the DELETE statement?

- ☐ DELETE * FROM tablename;
- ☒ DELETE FROM tablename; ✓
- ☐ DELETE TABLE tablename;
- ☐ DELETE FROM TABLE tablename;

Explanation :

Refer Syntax



14m 54s (Submitted)

Q3 of 3



Which of the following statement is correct to delete a employee "john" from employee table.

- ☐ DROP FROM employee WHERE
employeename = "john"
- ☐ DROP employeename = "john" FROM
employee
- ☒ DELETE FROM employee WHERE
employeename = "john" ✓
- ☐ DELETE employeename = "john" FROM
employee

Explanation :

DELETE with WHERE clause is used



Q1 of 4



Consider the following query: select distinct first_name from clients. The following clients are in this table: Aamir Rao, Aamir Malhotra, Ankur Gopal. The query will return how many rows:

☐ 1☐ 2☒ 3 ✓☐ it depends**Explanation :**

Distinct Is used to remove duplicate values, as there are no duplicates in the given statement



19m 38s (Submitted)

Q2 of 4



Choose the correct SELECT statement to find the salary of employee between 60000 and 80000

☐ SELECT * FROM employees WHERE salary NOT BETWEEN 60000 AND 80000;

☒ SELECT * FROM employees WHERE salary BETWEEN 60000 AND 80000;



☐ SELECT * FROM employees WHERE salary IN (60000, 80000);

☐ SELECT * FROM employees WHERE salary IN (60000, 80000);



19m 38s (Submitted)

Q3 of 4



Which of the following is TRUE for SELECT statements



SELECT * FROM department WHERE
dept_id NOT IN (10,11); ✓



SELECT * FROM department WHERE
dept_id IS (10,11)



SELECT * FROM department WHERE
dept_id IN (10,11) ✓



SELECT * FROM department WHERE
dept_id NOT IS (10,11)



19m 38s (Submitted)

Explanation :

Refer Syntax

Q4 of 4



____ condition is used to check the values in list

☐ DISTINCT

☐ LIKE

☒ IN ✓

☐ BETWEEN

Explanation :

IN is used to check the values in list of values



14m 52s (Submitted)

Q1 of 3



If no order is specified in the ORDER BY clause, then Postgres sorts the data in _____ order

- ☐ descending
- ☒ ascending ✓
- ☐ compiler error
- ☐ non of the above

Explanation :

ORDER BY clause stores value in ascending order by default



14m 52s (Submitted)

Q2 of 3



What is the output if both ASC and DESC are used in the query with ORDER BY

```
SELECT trainer_id, stream_id FROM  
trainer_details ORDER BY stream_id DESC,  
trainer_id ASC;
```

- ☐ The above query works only on stream_id
- ☐ The above query works only on trainer_id
- ☒ The above query works on both stream_id and trainer_id ✓
- ☐ The above query throws an error as ORDER BY cannot use ASC, DESC at once



in stream_id

Q3 of 3



SELECT * FROM employee LIMIT 3 OFFSET 2;
What is the result of the above statement?

- ☐ picks up three records
- ☒ picks up three records starting from the second position ✓
- ☐ picks up second and third record
- ☐ throws an error



9m 51s (Submitted)

Q1 of 3



Which of the following operator can be used to reduce the number of records in the output?

- ☐ offset
- ☐ remove
- ☒ limit ✓
- ☐ none of the above

Explanation :

Limit will restrict no of rows to display



9m 51s (Submitted)

- ☐ SELECT * FROM Persons WHERE first_name ='a';
- ☒ SELECT * FROM Persons WHERE first_name LIKE 'a%'; ✓
- ☐ SELECT * FROM Persons WHERE first_name LIKE '%a';

Q3 of 3



State TRUE or FALSE

The BETWEEN operator used for giving a range of values also include boundaries.

- ☒ TRUE ✓
- ☐ FALSE



GROUP BY clause - Quiz 1



Q1 of 3



What is the output of the following query?

```
SELECT department_id,job_id,sum(salary)
FROM employees GROUP BY department_id;
```

- ☒ ERROR: column "employees.job_id" must appear in the GROUP BY clause or be used in an aggregate function SQL

state: 42803 Character: 23 ✓

- ☐ Output is shown

Explanation :

Columns selected should be used for Grouping or Aggregate function. As job_id is not used so it throws error



☐ TRUNC

☐ MOD

☒ POSITION(substr in string) ✓

☐ TO_CHAR(numeric,string)

Explanation :

Position is the character manipulating function



Q3 of 3



An aggregate function can be used without a GROUP BY clause.

☒ TRUE ✓

☐ FALSE



State TRUE OR FALSE.

HAVING clause can be used instead of WHERE clause to filter records.

☐ TRUE

☒ FALSE ✓

Explanation :

Having clause is used for Grouping



Q2 of 2



The having clause is often used in combination with _____

☐ ORDER BY

☒ GROUP BY ✓



14m 36s (Submitted)

Q1 of 4



What does UNION operator does in a query?

- ☐ Bring common data from the listed tables.
- ☐ Bring data which is not common from the listed tables
- ☒ Bring all data from the listed tables. ✓
- ☐ Bring all distinct from the listed tables





14m 36s (Submitted)

The column list in the SELECT statements should match in number and datatype.

☒ TRUE ✓

☐ FALSE

Explanation :

The column list in the SELECT statements should match in number and datatype.



Q3 of 4



Where can the ORDER BY clause used in case when SET operators are used?

☐ In each of the queries being combined

☐ In the first query only

☒ At the very end of the compound query ✓



ORDER BY clause is used at the end of the query component

Q4 of 4



To return the records that are present in first table but not in the second, which operator is used?

☐ UNION

☒ EXCEPT ✓

☐ INTERSECT

☐ MINUS



Inner Join Equi Join Quiz



4m 53s (Submitted)

Q1 of 1



Understanding the primary key and foreign key relationship is not important to join on the correct columns



TRUE



FALSE ✓

Explanation :

Understanding the primary key and foreign key relationship is important to join on the correct columns





 9m 46s (Submitted)

Q1 of 2



State TRUE OR FALSE

You can drop OUTER keyword and just say LEFT JOIN or RIGHT JOIN or FULL JOIN.

☒ TRUE ✓

☐ FALSE

Explanation :

You can use LEFT JOIN or RIGHT JOIN or FULL JOIN.





Q2 of 2



Which of the following statement is TRUE about FULL OUTER JOIN created on two tables

- ☐ Retrieves all the unmatched rows of Table1
- ☐ Retrieves all the unmatched rows of Table2
- ☐ Retrieves only matched rows of table1 and Table2
- ☒ Retrieves both matched and unmatched rows of Table1 and Table2 ✓

- ☐ All of above
- ☒ Both Option 1 and Option 2 ✓

Explanation :

Self join is used with inner join and outer join

Q2 of 2



Self join uses _____ relation ship

- ☒ Unary ✓
- ☐ binary
- ☐ ternary
- ☐ None of the above



CROSS JOIN - Quiz 1



☐ TRUE

☒ FALSE ✓

Explanation :

A cartesian product cannot be obtained between two tables by giving a join condition

Q2 of 2



Cross join is also known as



☐ Left Join

☐ Right Join

☐ Full Join

☒ Cartesian Products ✓





Q1 of 2



Which of the following are valid subquery types?

- ☐ Single Row Subquery
- ☐ Multiple Row Subquery
- ☐ Correlated Subquery
- ☒ All are valid ✓

Explanation :

Sub Query has Corelated and non corelated types with single row and multi row subquery



Sub Query has Corelated and non corelated types with single row and multi row subquery

Q2 of 2



A subquery can itself include one or more subqueries. The subqueries that can be nested in a statement can be _____

☐ Limited

☐ 256

☐ 1024

☒ any ✓

Explanation :

No restriction for nesting query

Q1 of 2



A _____ subquery is one that depends on a value of the outer query.

- ☐ nested
- ☒ correlated ✓
- ☐ materialized
- ☐ both option 2 and option 3



Q2 of 2



In independent subqueries, the inner query executes _____ times

☐ 0

☐ n

☐ 3

☒ 1 ✓

← EXISTS operator - Quiz 1



4m 54s (Submitted)

Q1 of 1



State TRUE OR FALSE

An EXISTS operator returns either a boolean value TRUE or FALSE depending upon the number of records returned by the inner query

☒ TRUE ✓

☐ FALSE



Views - Quiz 1



response time.



All of the above ✓

Explanation :

Refer definition of views

Q2 of 2



To restrict the modifications to a simple view through WHERE clause _____ is used.



WITH READ ONLY



RECURSIVE



NOT ALLOWED



WITH CHECK OPTION ✓



Q1 of 2



State TRUE OR FALSE

An Index can be created on multiple columns

☒ TRUE ✓

☐ FALSE



9m 49s (Submitted)

Explanation :

An Index can be created on multiple columns

Q2 of 2



A unique index is created on the columns having _____ or _____ constraints

☐ UNIQUE

☐ NOT NULL

☐ PRIMARY KEY

☒ Option 1 & Option 3 ✓

Q1 of 2



State TRUE or FALSE

Sequences objects can be used as an optional way to generate unique numeric values in a table.

☒ TRUE ✓

☐ FALSE

☒ TRUE ✓

☐ FALSE

Q2 of 2



The _____ clause specifies that the object should restart from the minimum value when its maximum value is exceeded

☐ Restart

☐ Min_Max

☒ Cycle ✓

☐ None of the above

Result: CLEARED

Overall Percentage: 100% (10/10)

Final Assessment

Assessment

Section Score: 10/10

 Correct |  Incorrect |  Unattempted

Q1 of 10

The sequence of the column in a GROUP BY clause has no effect in the ordering of the output.

- ☒ True
☐ False

Q2 of 10

Which of the following keyword is used to add a new column to an existing table?

- ☐ MODIFY COLUMN
☐ ALTER COLUMN
☒ ADD COLUMN



CREATE TABLE course (course_id int, course_name varchar(20), dept_id int, dept_name varchar(20), FOREIGN KEY(dept_id) REFERENCES department). Which of the following is used to delete the entries in the referenced table when the record is deleted in the course table.

- ☐ delete
- ☒ on delete cascade
- ☐ on set null
- ☐ all of the above

Q4 of 10

Which of the following is not true regarding single row functions?

- ☐ They return one result per row
- ☐ They expect one or more user arguments
- ☐ They act on each row returned in the query
- ☒ They cannot be nested

Q5 of 10

Which of the following statements is used to remove the privileges from "John" in the employee table

- ☐ Remove update on employee from John
- ☒ Revoke update on employee from John
- ☐ Paste update on employee from John
- ☐ Grant update on employee from John

Q6 of 10

What is the purpose of the index in PostgreSQL?

- ☐ To store backup
- ☐ To enforce integrity
- ☐ To encrypt sensitive data
- ☒ To optimize data retrieval

- ☐ To enforce integrity
- ☐ To encrypt sensitive data
- ☒ To optimize data retrieval

Q7 of 10

What is the key difference between the INNER JOIN and LEFT JOIN in PostgreSQL.

- ☒ LEFT JOIN returns all the rows from left table along with the matching values from right table.
- ☐ INNER JOIN returns the rows that have no matching in the other table
- ☐ LEFT JOIN returns only matching rows from both tables
- ☐ INNER JOIN returns all rows from both tables

Q8 of 10



Which of the following is supported by CURF operator in

Q8 of 10

Which of the following is supported by CUBE operator in PostgreSQL.

- ☐ To generate random numbers for analysis
- ☐ To calculate the average of all values in a column
- ☒ To produce all possible combinations of grouping sets
- ☐ To filter rows based on a specified condition

Q9 of 10

Which among the following is true about sub queries.

- ☒ Sub queries can be written on either side of comparison operator
- ☐ Parenthesis is not mandatory for sub queries
- ☐ Single row sub queries can use multi row operators but vice versa is not possible

Q9 of 10

Which among the following is true about sub queries.

- ☒ Sub queries can be written on either side of comparison operator
- ☐ Parenthesis is not mandatory for sub queries
- ☐ Single row sub queries can use multi row operators but vice versa is not possible
- ☐ All of the above



Q10 of 10

Which of the following options will reset the auto-incremented sequence?

- ☐ DELETE FROM
- ☒ TRUNCATE TABLE
- ☐ DROP TABLE
- ☐ All the above mentioned

