

Practical 01

Aim: To study and execute DDL Commands in RDBMS.

Theory:

DATA DEFINITION LANGUAGE (DDL):

A Data Definition Language (DDL) statement is used to define the database structure or schema.

The Data Definition Language (DDL) is used to create and destroy databases and database objects.

These commands will primarily be used by database administrators during the setup and removal phases of a database project.

Let's take a look at the structure and usage of four basic DDL commands:

1. CREATE
2. ALTER
3. DROP
4. RENAME
5. TRUNCATE

1. CREATE TABLE:

To make a new database, table, index, or stored query. A create statement in SQL creates an object

inside of a relational database management system (RDBMS).

Syntax,

```
CREATE TABLE <table_name>
(
Column_name1 data_type ([size]),
Column_name2 data_type ([size]),
.
.
.
Column_name-n data_type ([size])
);
```

```
SQL> create table emp1(id number,ename varchar2(15), eadd varchar2(25));
Table created.
```

```
SQL> create table studentdb(rno number, name varchar2(15));
Table created.
```

2. ALTER TABLE:

To modify an existing database object. Alter the structure of the database.

To add a column in a table

ALTER TABLE table_name ADD column_name datatype;

```
SQL> alter table studentdb add address varchar2(25);  
Table altered.
```

```
SQL> desc studentdb;  
Name                               Null?      Type  
-----  
RNO                                NUMBER  
NAME                               VARCHAR2(15)  
ADDRESS                            VARCHAR2(25)
```

To delete a column in a table

ALTER TABLE table_name DROP column column_name;

```
SQL> alter table studentdb drop column address;  
Table altered.
```

To modify a column in a table

ALTER TABLE table_name MODIFY (column_name datatype(size));

```
SQL> alter table studentdb modify (name varchar2(20));  
Table altered.
```

```
SQL> desc studentdb;  
Name                               Null?      Type  
-----  
RNO                                NUMBER  
NAME                               VARCHAR2(20)
```

3. RENAMING TABLE:

It is used to modify the name of the existing database object.

Syntax:

Rename <oldtable> to <new table>;

EXAMPLE:

rename Employee to Employee 1;

```
SQL> rename studentdb to studentdbs;  
Table renamed.
```

4. TRUNCATE TABLE:

Remove all records from a table, including all spaces allocated for the records are removed.

Syntax,

TRUNCATE TABLE table_name;

```
SQL> truncate table studentdb;
Table truncated.
```

```
SQL> desc studentdb;
Name                               Null?    Type
-----
RNO                                NUMBER
NAME                               VARCHAR2(20)
```

3. DROP TABLE:

Delete Objects from the Database.

Syntax,

DROP TABLE table_name;

```
SQL> drop table studentdb;
Table dropped.
```

```
SQL> desc studentdb;
ERROR:
ORA-04043: object studentdb does not exist
```

DESCRIBE TABLE

This is used to view the structure of the table.

Syntax:

DESC <TABLE NAME>;

Example:

desc employee;

Write down all Queries to be executed in practical slot related to DDL Commands with screenshot of output.

RESULT:

Thus executed the DDL commands in RDBMS.