

5CCS2FC2: Foundations of Computing II

Optimisation and Approximation

Week 9


Dr Christopher Hampson

Department of Informatics

King's College London

Warm-up : The Eight Queens

- Position **eight Queens** (8 x ♔) on the board so that no Queen is threatened.
(no two Queens can appear in the same row, column, or diagonal)




Objectives for Today

- To be able to explain **local search**, and where it might fail,
 - **Global** vs **Local** maxima / minima,
- To be able to explain what it means for a problem to be **approximable** or **unapproximable**
- To be able to apply the **2-OPT algorithm** for the TSP

Local Search

Local Search

- **State Space** collection of all possible **solutions** and **non-solutions**
(e.g. all possible ways of placing eights / four queens on a chessboard)




- **Successor Function** All the '**locally**' **accessible** states
(e.g. all configurations that differ by one vertical move)

Local Search

- **Heuristic Function** Assigns a 'score' to each state in the state space

$h : \text{search space} \rightarrow \text{possible score}$



Heuristic

$$h(x) = 4$$

(e.g. the number of pairs currently in conflict)

Local Search


Hill-climbing Local Search

- Step 1)** Guess an initial configuration,
- Step 2)** Evaluate the heuristic function of the successor states,
- Step 3)** Move to a successor state with a better heuristic 'score'.
- Step 4)** Repeat until no further improvement to the score are possible.

(the Greedy SAT algorithm from last week employed Hill-climbing)

Local Search

- **Potential Pitfalls:** The Hill-climbing search may get '**stuck**' in a local maximum/minimum!

8	3	3	3	3	2	3		3
7	3	3	4	2		4	2	4
6	2		3	3	5	4	2	3
5	3	2	4		4	4	3	2
4	3	3	4	3	4		2	3
3	3	5	3	2	4	3	2	
2	4	3		2	2	3	3	3
1		3	3	2	2	3	2	3
	A	B	C	D	E	F	G	H

(there is only one conflict – (D5,G8) – but no local improvements!)


Local Search

- The happens with The Eight Queens about **86% of the time!**
(...so only successful 14% of the time!)
- However each paths are typically **quite short**,
(takes about 3 moves on average to get stuck!)
- Can quickly **stop** and **re-search** from a random configuration,
- I was able to get **577 successes** out of **4160 runs** in <20 seconds

Global and Local Optima

- Global and Local Maxima

- Global Maximum** $h(x^*) \geq h(x)$ for all $x \in X$
(x^* is attains the greatest value *anywhere*)
- Local Maximum** $h(x^*) \geq h(x)$ for all 'neighbouring' $x \in X$



(similarly, we may define global and local minima)

Optimisation Problems

Decision vs Optimisation Problems

Decision Problems

Decide whether a solution *exists* or not.

VS

Optimisation Problems

Identify the *best* / *optimal* solution.

- Some problems make sense only as **Decision Problems**
 - **Examples:** The SAT problem, the Hamiltonian cycle problem, the Clique problem, the Graph Isomorphism problem,
(typically problems where the answer is yes/no)
- Others are more natural to consider as **Optimisation Problems**
 - **Examples:** The Travelling Salesman Problem, Vertex-cover problem, the Knapsack problem, *etc.*

Decision vs Optimisation Problems


- We can **parameterize** any optimisation problem into a decision problem:

Vertex Cover *Optimisation* Problem

Input) A graph (V, E) ,

Output) A vertex cover with the fewest nodes.


check if optimal
solution is smaller
than k



Vertex Cover *Decision* Problem

Input) A graph (V, E) and parameter k ,

Output) Is there a vertex cover with fewer than k nodes?



decrease k
and repeat

Optimisation by Local Search

- **A Search Space for Vertex Cover**

- **State Space** All possible subsets of vertices,

$$\mathcal{P}(V) = \{U : U \subseteq V\}$$

(i.e., the powerset of V)

- **Successor Relation** All sets that differ by a single vertex

$$X \longleftrightarrow Y \quad \text{iff} \quad |(X - Y) \cup (Y - X)| = 1$$

(for all $X, Y \subseteq V$)



- **Heuristic Function** The number of edges that are not covered.

$$h(X) = |\{(u, v) \in E : u \notin X \text{ and } v \notin X\}|$$

(for all $X \subseteq V$)



Optimisation by Local Search

- Example:





Optimisation by Local Search

- Example:





Optimisation by Local Search

- Example:





Optimisation by Local Search

- Example:





Optimisation by Local Search

- Example:



Optimisation by Local Search

- Example:



Approximate Algorithms

Approximate Algorithms

- The Approximation Ratio

$$R = \max \left(\frac{C}{C^*}, \frac{C^*}{C} \right)$$

(if $C < C^*$ then $R = C^*/C$, otherwise $R = C/C^*$)

- C is the cost of the **approximate solution**
- C^* is the cost of the **optimal solution**

- **R -approximable problems** There is an **approximate algorithm** such that **every instance** of the problem has an approximation ratio $\leq R$.

(the algorithm never returns a solution worse than R times the optimal)

Approximate Algorithms

- The Travelling Salesman (Optimisation) Problem (TSP):

Input) A complete weighted graph (V, d) ,

$(d(x, y)$ is the distance between two points $x, y \in V$)

Output) The *shortest* Hamiltonian cycle, visiting all nodes.

Theorem TSP is NP-complete.

But can find a ‘good’ approximation for TSP?

The 2-OPT approximation algorithm for TSP


- The 2-OPT swap move:

Step 1) Given a cycle, choose two *non-adjacent* edges in the cycle:

(x, y) and (u, v)

(where $x, y, u,$ and v are all distinct)

Step 2) Compare the *weight* of (x, y) and (u, v) with the weight (x, v) and (u, y) .



The 2-OPT approximation algorithm for TSP

- The 2-OPT swap move (cont.):

Step 3) Replace the two edges (x, y) and (u, v) with (x, v) and (u, y) whenever,

$$\underbrace{d(x, v) + d(u, y)}_{\text{after swap}} < \underbrace{d(x, y) + d(u, v)}_{\text{before swap}}$$

The new path visits all nodes in a shorter distance!


The 2-OPT approximation algorithm for TSP

Input: A complete weighted graph $G = (V, d)$.

- Step 1)** Construct a **minimum spanning tree** of the complete weighted graph.
(using *Prim's Algorithm*, for example)
- Step 2)** Use the **preorder traversal** of the spanning tree as an initial cycle.
- Step 3)** Apply the **2-OPT swap move** for each pair of non-adjacent edges.
- Step 4)** **Repeat** until no more optimisations are possible.


The 2-OPT approximation algorithm for TSP

- Example:




The 2-OPT approximation algorithm for TSP

- Example:




The 2-OPT approximation algorithm for TSP

- Example:




The 2-OPT approximation algorithm for TSP

- Example:




The 2-OPT approximation algorithm for TSP

- Example:




The 2-OPT approximation algorithm for TSP

- Example:




The 2-OPT approximation algorithm for TSP

- Example:



The 2-OPT approximation algorithm for TSP

- Example:



The 2-OPT approximation algorithm for TSP

- In this instance our **approximate algorithm** was able to find the optimal path!

length_of (optimal path) \approx 14.71

- In general, for other instances, we may may get stuck in a **local optimum**.
- But how close to the **global optimum** does our approximate algorithm get, when we get stuck?

What is the Approximation Ratio in the *worst* case?

The 2-OPT approximation algorithm for TSP

Theorem The cycle found is no worse than **twice** the optimal length!

Proof: **Step 1)** Let H and H^* denote the following cycles

H = Local optimal found by 2-OPT algorithm

H^* = Global optimal Hamiltonian cycle,

(we want to show that $\text{length_of}(H) \leq 2 \times \text{length_of}(H^*)$)

Step 2) Remove one edge from H^* to create a path T ,

$$\text{length_of}(T) \leq \text{length_of}(H^*)$$

(note that T is a (trivial) spanning tree!)

The 2-OPT approximation algorithm for TSP

Step 3) Let T_0 denote the following **minimum spanning tree** computed as the first step of the 2-OPT algorithm,

$$T_0 = \text{Minimum spanning tree}$$

It then follows that

$$\text{length_of}(T_0) \leq \text{length_of}(T)$$

(since a *minimum spanning tree* is shorter than another spanning tree!)

Step 4) The length of the **pre-order traversal** is at most twice the length of the spanning tree,

$$\text{length_of}(W) \leq 2 \times \text{length_of}(T_0)$$

(we walk the length of each edge *twice*—first on the left, then on the right)

The 2-OPT approximation algorithm for TSP

Step 5) Every application of the 2-OPT swap decreases the length of the cycle, so

$$\text{length_of}(\mathbf{H}) \leq \text{length_of}(\mathbf{W})$$

where \mathbf{H} is the local minimum return by the 2-OPT algorithm.

Step 6) Therefore

$$\begin{aligned}\text{length_of}(\mathbf{H}) &\leq \text{length_of}(\mathbf{W}) \\ &\leq 2 \times \text{length_of}(\mathbf{T}_0) \\ &\leq 2 \times \text{length_of}(\mathbf{T}) \\ &\leq 2 \times \text{length_of}(\mathbf{H}^*)\end{aligned}$$


Q.E.D

Unapproximable Instances of TSP

- **Caution!** In the above example, we assumed that our weighted graph was **'reasonable'**.
- We assumed that it satisfied the **triangle inequality**

$$d(x, y) + d(y, z) \geq d(x, z)$$

(for all nodes $x, y, z \in V$)



- If we drop this requirement then there is **no approximate algorithm** for TSP.

Unapproximable Instances of TSP

Theorem If d does not satisfy the **triangle inequality** then TSP is **unapproximable**.

Proof:

Step 1) Suppose that there is a **polynomial time** approximate algorithm for TSP whose approximation ratio is R .

(so all approximate solutions are no worse than R times the optimal)

Step 2) Consider an instance of the **Hamiltonian Cycle** problem $G = (V, E)$ and let $n = |V|$ denote the number of vertices in G .


We will convert the graph G into an instance of TSP and use the approximate algorithm to find a solution for the Hamiltonian Cycle problem

Unapproximable Instances of TSP

Step 3) Construct a complete weighted graph (V, d) by setting

$$d(x, y) = \begin{cases} 1 & \text{if } (x, y) \in E \\ nR + 1 & \text{if } (x, y) \notin E \end{cases}$$

(the edges from the original graph are short)



Unapproximable Instances of TSP

Step 4) Let H be the cycle returned by the approximate algorithm.

We will show that

$$\text{length_of}(H) \leq nR \iff G \text{ has a Hamiltonian cycle}$$

Left-to-Right) Suppose that H is a 'short' TSP cycle

$$\text{length_of}(H) \leq nR$$

Then H must use only 'short edges'!

('short edges' = length 1)

Therefore H is a Hamiltonian cycle in G !

Unapproximable Instances of TSP

Right-to-Left) Suppose that G has a Hamiltonian cycle.

Then there is a TSP path H^* that uses only 'short' edges.

$$\text{length_of}(H^*) = \underbrace{1 + 1 + \dots + 1}_{n \text{ nodes}} = n$$

$(H^*$ must be *optimal* as no shorter paths can visit all n nodes)

Since our proposed approximate algorithm has an **approximation ratio** of R , we must have that

$$\text{length_of}(H) \leq R \times \text{length_of}(H^*) = nR$$

Therefore H is 'short' TSP cycle!

Unapproximable Instances of TSP

Step 5) This equivalence is a key to **efficiently deciding** whether G has a Hamiltonian cycle.

A Polynomial Time Algorithm for TSP (?)

- Convert G into a TSP graph,
- Use polynomial-time approximate algorithm to find H ,
- If $\text{length_of}(H) \leq nR$ then return **TRUE**,
- Else return **FALSE**

Conclusion) Either we have just proved that $P = NP$... or ...

There is no polynomial-time approximate algorithm for TSP.

Q.E.D

Summary of TSP


- Summary

- If your graph is 'reasonable' then TSP is 2-approximable,
(‘reasonable’ = satisfies the triangle inequality)
- Otherwise the graph is unapproximable.

Routing to minimise *distance* is approximable...

... Routing to minimise *duration* is not!

Summary of TSP




<https://xkcd.com/399/>

End of Slides!



Feedback

- Let me know how you found today's lecture?



<https://goo.gl/forms/wHsWHGU9qWskEm8x2>

Teaching Excellence Awards 2018

- Teaching Excellence Awards 2018

Home | Study | Learning & teaching | Funding and Awards | Teaching Excellence Awards

TEACHING EXCELLENCE AWARDS

EDUCATION STRATEGY

CENTRE FOR TECHNOLOGY ENHANCED LEARNING

FUNDING AND AWARDS

- Teaching Innovation & Enhancement Fund
- National Teaching Fellowship Scheme
- Teaching Excellence Awards** ➡
- How to Nominate
- Teaching Excellence Award Winners
- What you said in 2017
- Supervisory Excellence Awards

KINGS ONLINE

KING'S ACADEMY OF EDUCATORS

KING'S LEARNING INSTITUTE

RESOURCES AND SUPPORT

TEACHING EXCELLENCE AWARDS

Teaching Excellence Awards 2018

Who will you nominate?

Here at King's we value those people who are making your experience the best it can be and we know that you do too.

The **Teaching Excellence Awards** are your chance to nominate that person who has been your shining star. You can nominate lecturers, tutors, teaching support, graduate teaching assistants (GTAs), professional service staff, researchers or your personal tutor - anyone who has supported you in and outside of the classroom. It could be the amazing lectures they give, the support they have given you or it could be someone who has shown you a whole new way of learning.

All you need to do is let us know why you think they should win!

Congratulations to all those who won an award last year:

FOLLOW US

Twitter: @KCL_TEA

HOW TO NOMINATE

Education

breed

PREVIOUS

'She
and

<https://goo.gl/QRKsH>