

```

        </participantRole>
    </participant>
    <entryRelationship typeCode="REFR">
        <act classCode="ACT" moodCode="EVN">
            <templateId root="2.16.840.1.113883.10.20.1.19" />
            . . .

        </act>
    </entryRelationship>
</act>

```

### 3.72 Postprocedure Diagnosis (V3)

[act: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.51:2015-08-01 (open)]

**Table 404: Postprocedure Diagnosis (V3) Contexts**

Contained By:	Contains:
<a href="#">Health Concern Act (V2)</a> (optional) <a href="#">Risk Concern Act (V2)</a> (optional) <a href="#">Postprocedure Diagnosis Section (V3)</a> (optional)	<a href="#">Problem Observation (V3)</a> (required)

This template represents the diagnosis or diagnoses discovered or confirmed during the procedure. They may be the same as preprocedure diagnoses or indications.

**Table 405: Postprocedure Diagnosis (V3) Constraints Overview**

XPath	Card.	Verb	Data Type	CONF#	Value
act (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.4.51:2015-08-01)					
@classCode	1..1	SHALL		<a href="#">1198-8756</a>	ACT
@moodCode	1..1	SHALL		<a href="#">1198-8757</a>	EVN
templateId	1..1	SHALL		<a href="#">1198-16766</a>	
@root	1..1	SHALL		<a href="#">1198-16767</a>	2.16.840.1.113883.10.20.22.4.51
@extension	1..1	SHALL		<a href="#">1198-32539</a>	2015-08-01
code	1..1	SHALL		<a href="#">1198-19151</a>	
@code	1..1	SHALL		<a href="#">1198-19152</a>	59769-0
@codeSystem	1..1	SHALL		<a href="#">1198-32166</a>	urn:oid:2.16.840.1.113883.6.1 (LOINC) = 2.16.840.1.113883.6.1
entryRelationship	1..*	SHALL		<a href="#">1198-8759</a>	
@typeCode	1..1	SHALL		<a href="#">1198-8760</a>	urn:oid:2.16.840.1.113883.5.1002 (HL7ActRelationshipType) = SUBJ
observation	1..1	SHALL		<a href="#">1198-15583</a>	<a href="#">Problem Observation (V3) (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.4.4:2015-08-01)</a>

1. **SHALL** contain exactly one [1..1] **@classCode**="ACT" (CONF:1198-8756).
2. **SHALL** contain exactly one [1..1] **@moodCode**="EVN" (CONF:1198-8757).
3. **SHALL** contain exactly one [1..1] **templateId** (CONF:1198-16766) such that it
  - a. **SHALL** contain exactly one [1..1] **@root**="2.16.840.1.113883.10.20.22.4.51" (CONF:1198-16767).
  - b. **SHALL** contain exactly one [1..1] **@extension**="2015-08-01" (CONF:1198-32539).
4. **SHALL** contain exactly one [1..1] **code** (CONF:1198-19151).
  - a. This code **SHALL** contain exactly one [1..1] **@code**="59769-0" Postprocedure diagnosis (CONF:1198-19152).
  - b. This code **SHALL** contain exactly one [1..1] **@codeSystem**="2.16.840.1.113883.6.1" (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1) (CONF:1198-32166).
5. **SHALL** contain at least one [1..\*] **entryRelationship** (CONF:1198-8759) such that it
  - a. **SHALL** contain exactly one [1..1] **@typeCode**="SUBJ" Has subject (CodeSystem: HL7ActRelationshipType urn:oid:2.16.840.1.113883.5.1002 **STATIC**) (CONF:1198-8760).

- b. **SHALL** contain exactly one [1..1] [Problem Observation \(V3\)](#) (identifier: urn:hl7ii:2.16.840.1.113883.10.20.22.4.4:2015-08-01) (CONF:1198-15583).

**Figure 192: Postprocedure Diagnosis (V3) Example**

```
<section>
  <templateId root="2.16.840.1.113883.10.20.22.2.36" extension="2015-08-01" />
  <code code="59769-0" codeSystem="2.16.840.1.113883.6.1" codeSystemName="LOINC"
displayName="POSTPROCEDURE DIAGNOSIS" />
  <title>Postprocedure Diagnosis</title>
  <text>
    ...
  </text>
  <entry>
    <act moodCode="EVN" classCode="ACT">
      <templateId root="2.16.840.1.113883.10.20.22.4.51" extension="2015-08-01" />
      <!-- ** Postprocedure Diagnosis ** -->

      ...

    </act>
  </entry>
</section>
```

### 3.73 Precondition for Substance Administration (V2)

[criterion: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.25:2014-06-09  
(open) ]

**Table 406: Precondition for Substance Administration (V2) Contexts**

Contained By:	Contains:
<a href="#">Medication Activity (V2)</a> (optional) <a href="#">Planned Medication Activity (V2)</a> (optional) <a href="#">Planned Immunization Activity</a> (optional) <a href="#">Immunization Activity (V3)</a> (optional)	

A criterion for administration can be used to record that the medication is to be administered only when the associated criteria are met.