### Figure 217: Series Act Example

```
<act classCode="ACT" moodCode="EVN">
    <templateId root="2.16.840.1.113883.10.20.22.4.63"/>
    <id root="1.2.840.113619.2.62.994044785528.20060823223142485051"/>
    <code code="113015" codeSystem="1.2.840.10008.2.16.4"</pre>
          codeSystemName="DCM" displayName="Series">
        <qualifier>
            <name code="121139" codeSystem="1.2.840.10008.2.16.4"</pre>
                  codeSystemName="DCM" displayName="Modality"/>
            <value code="CR" codeSystem="1.2.840.10008.2.16.4" codeSystemName="DCM"</pre>
                   displayName="Computed Radiography"/>
        </qualifier>
    </code>
    <!-- **** SOP Instance UID *** -->
    <entryRelationship typeCode="COMP">
        <observation classCode="DGIMG" moodCode="EVN">
            <templateId root="2.16.840.1.113883.10.20.6.2.8"/>
        </observation>
    </entryRelationship>
</act>
```

## 3.98 Service Delivery Location

[participantRole: identifier urn:oid:2.16.840.1.113883.10.20.22.4.32 (open)]

Table 474: Service Delivery Location Contexts

Contained By:	Contains:
Procedure Activity Act (V2) (optional)	
Procedure Activity Procedure (V2) (optional)	
Procedure Activity Observation (V2) (optional)	
Planned Encounter (V2) (optional)	
Encounter Activity (V3) (optional)	

This clinical statement represents the location of a service event where an act, observation or procedure took place.

Table 475: Service Delivery Location Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value	
participantRole (identifier: urn:oid:2.16.840.1.113883.10.20.22.4.32)						
@classCode	11	SHALL		81-7758	urn:oid:2.16.840.1.113883.5.1 11 (HL7RoleCode) = SDLOC	
templateId	11	SHALL		81-7635		
@root	11	SHALL		81-10524	2.16.840.1.113883.10.20.22.4 .32	
code	11	SHALL		81-16850	urn:oid:2.16.840.1.113883.1.1 1.20275 (HealthcareServiceLocation)	
addr	0*	SHOULD		81-7760		
telecom	0*	SHOULD		81-7761		
playingEntity	01	MAY		81-7762		
@classCode	11	SHALL		81-7763	urn:oid:2.16.840.1.113883.5.4 1 (HL7EntityClass) = PLC	
name	01	MAY		81-16037		

- 1. **SHALL** contain exactly one [1..1] **@classCode=**"SDLOC" (CodeSystem: HL7RoleCode urn:oid:2.16.840.1.113883.5.111 STATIC) (CONF:81-7758).
- 2. SHALL contain exactly one [1..1] templateId (CONF:81-7635) such that it
  - a. **SHALL** contain exactly one [1..1] **@root="**2.16.840.1.113883.10.20.22.4.32" (CONF:81-10524).
- 3. **SHALL** contain exactly one [1..1] **code**, which **SHALL** be selected from ValueSet HealthcareServiceLocation urn:oid:2.16.840.1.113883.1.11.20275 DYNAMIC (CONF:81-16850).
- 4. **SHOULD** contain zero or more [0..\*] **addr** (CONF:81-7760).
- 5. **SHOULD** contain zero or more [0..\*] **telecom** (CONF:81-7761).
- 6. **MAY** contain zero or one [0..1] **playingEntity** (CONF:81-7762).
  - a. The playingEntity, if present, **SHALL** contain exactly one [1..1] **@classCode="PLC"** (CodeSystem: HL7EntityClass urn:oid:2.16.840.1.113883.5.41 STATIC) (CONF:81-7763).
  - b. The playingEntity, if present, MAY contain zero or one [0..1] name (CONF:81-16037).

#### Table 476: HealthcareServiceLocation

Value Set: HealthcareServiceLocation urn:oid:2.16.840.1.113883.1.11.20275

(Clinical Focus: Concepts representing locations and settings where healthcare services are provided. This includes non- (or atypical) patient care locations where emergency services may be provided. The values are derived from the NHSN Healthcare Facility Patient Care Location code system.),(Data Element Scope: Location),(Inclusion Criteria: All codes in code system),(Exclusion Criteria: Codes that do not represent an actual location where health care services can be delivered, IE: Float, or a location aggregation.)

This value set was imported on 6/24/2019 with a version of 20190424.

Value Set Source:

https://vsac.nlm.nih.gov/valueset/2.16.840.1.113883.1.11.20275/expansion

Code	Code System	Code System OID	Print Name
1005-8	HSLOC	urn:oid:2.16.840.1.113883.6.25	Cardiac Catheterization Room/Suite
1007-4	HSLOC	urn:oid:2.16.840.1.113883.6.25	Endoscopy Suite
1008-2	HSLOC	urn:oid:2.16.840.1.113883.6.25	Radiology
1009-0	HSLOC	urn:oid:2.16.840.1.113883.6.25	Pulmonary Function Testing
1010-8	HSLOC	urn:oid:2.16.840.1.113883.6.25	General Laboratory
1011-6	HSLOC	urn:oid:2.16.840.1.113883.6.25	Clinical Chemistry Laboratory
1012-4	HSLOC	urn:oid:2.16.840.1.113883.6.25	Hematology Laboratory
1013-2	HSLOC	urn:oid:2.16.840.1.113883.6.25	Histology-Surgical Pathology Laboratory
1014-0	HSLOC	urn:oid:2.16.840.1.113883.6.25	Microbiology Laboratory
1015-7	HSLOC	urn:oid:2.16.840.1.113883.6.25	Serology Laboratory
	<u>.</u>		

## Figure 218: Service Delivery Location Example

# 3.99 Severity Observation (V2)

[observation: identifier urn:hl7ii:2.16.840.1.113883.10.20.22.4.8:2014-06-09 (open)]

Table 477: Severity Observation (V2) Contexts

Contained By:	Contains:
Reaction Observation (V2) (optional)	
Allergy - Intolerance Observation (V2) (optional)	
<u>Substance or Device Allergy - Intolerance Observation</u> (V2) (optional)	

This clinical statement represents the gravity of the reaction. The Severity Observation characterizes the Reaction Observation. A person may manifest many symptoms in a reaction to a single substance, and each reaction to the substance can be represented. However, each reaction observation can have only one severity observation associated with it. For example, someone may have a rash reaction observation as well as an itching reaction observation, but each can have only one level of severity. Note the severity observation is no longer recommended for use with the Allergy and Intolerance Observation. The Criticality Observation is preferred for characterizing the Allergy and Intolerance.