2.55 Procedure Disposition Section

[section: identifier urn:oid:2.16.840.1.113883.10.20.18.2.12 (open)]

Table 182: Procedure Disposition Section Contexts

Contained By:	Contains:
Procedure Note (V3) (optional)	
Operative Note (V3) (optional)	

The Procedure Disposition Section records the status and condition of the patient at the completion of the procedure or surgery. It often also states where the patient was transferred to for the next level of care.

Table 183: Procedure Disposition Section Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value			
section (identifier: urn:oid:2.16.840.1.113883.10.20.18.2.12)								
templateId	11	SHALL		81-8070				
@root	11	SHALL	UID	81-10466	2.16.840.1.113883.10.20.18.2 .12			
code	11	SHALL		81-15413				
@code	11	SHALL		81-15414	59775-7			
@codeSystem	11	SHALL		81-26490	urn:oid:2.16.840.1.113883.6.1 (LOINC) = 2.16.840.1.113883.6.1			
title	11	SHALL		81-8072				
text	11	SHALL		81-8073				

- 1. **SHALL** contain exactly one [1..1] **templateId** (CONF:81-8070) such that it
 - a. **SHALL** contain exactly one [1..1] @root="2.16.840.1.113883.10.20.18.2.12" (CONF:81-10466).
- 2. **SHALL** contain exactly one [1..1] **code** (CONF:81-15413).
 - a. This code **SHALL** contain exactly one [1..1] @code="59775-7" Procedure Disposition (CONF:81-15414).
 - b. This code **SHALL** contain exactly one [1..1] @codeSystem="2.16.840.1.113883.6.1" (CodeSystem: LOINC urn:oid:2.16.840.1.113883.6.1) (CONF:81-26490).
- 3. **SHALL** contain exactly one [1..1] **title** (CONF:81-8072).
- 4. **SHALL** contain exactly one [1..1] **text** (CONF:81-8073).

Figure 108: Procedure Disposition Section Example

```
<section>
     <templateId root="2.16.840.1.113883.10.20.18.2.12"/>
     <code code="59775-7" codeSystem="2.16.840.1.113883.6.1"
          codeSystemName="LOINC"
          displayName="PROCEDURE DISPOSITION"/>
          <title>PROCEDURE DISPOSITION</title>
          <text>The patient was taken to the Endoscopy Recovery Unit in stable condition.</text>
</section>
```

2.56 Procedure Estimated Blood Loss Section

[section: identifier urn:oid:2.16.840.1.113883.10.20.18.2.9 (open)]

Table 184: Procedure Estimated Blood Loss Section Contexts

Contained By:	Contains:
Procedure Note (V3) (optional)	
Operative Note (V3) (required)	

The Procedure Estimated Blood Loss Section may be a subsection of another section such as the Procedure Description Section. The Procedure Estimated Blood Loss Section records the approximate amount of blood that the patient lost during the procedure or surgery. It may be an accurate quantitative amount, e.g., 250 milliliters, or it may be descriptive, e.g., "minimal" or "none".

Table 185: Procedure Estimated Blood Loss Section Constraints Overview

XPath	Card.	Verb	Data Type	CONF#	Value			
section (identifier: urn:oid:2.16.840.1.113883.10.20.18.2.9)								
templateId	11	SHALL		81-8074				
@root	11	SHALL	UID	81-10467	2.16.840.1.113883.10.20.18.2 .9			
code	11	SHALL		81-15415				
@code	11	SHALL		81-15416	59770-8			
@codeSystem	11	SHALL		81-26491	urn:oid:2.16.840.1.113883.6.1 (LOINC) = 2.16.840.1.113883.6.1			
title	11	SHALL		81-8076				
text	11	SHALL		81-8077				

- 1. **SHALL** contain exactly one [1..1] **templateId** (CONF:81-8074) such that it
 - a. **SHALL** contain exactly one [1..1] @root="2.16.840.1.113883.10.20.18.2.9" (CONF:81-10467).
- 2. **SHALL** contain exactly one [1..1] **code** (CONF:81-15415).